

# globus ftp control Reference Manual

## 2.10

Generated by Doxygen 1.2.18

Tue Aug 11 22:48:59 2009

## Contents

1	<a href="#">Globus GSIFTP Control Connection API</a>	1
2	<a href="#">globus ftp control Data Structure Index</a>	1
3	<a href="#">globus ftp control File Index</a>	2
4	<a href="#">globus ftp control Page Index</a>	2
5	<a href="#">globus ftp control Data Structure Documentation</a>	2
6	<a href="#">globus ftp control File Documentation</a>	4
7	<a href="#">globus ftp control Page Documentation</a>	37

## 1 Globus GSIFTP Control Connection API

The `globusftp_control` library provides low-level services needed to implement FTP client and servers. The API provided is protocol specific. See the GASS Transfer library for a protocol-independent transfer interface.

This data transfer portion of this API provides support for the standard data methods described in [FTP Specification](#) as well as extensions as known reference! for parallel, striped, and partial data transfer.

Any program that uses the GSIFTP Control Library must include `globusftp_control.h`.

## 2 globus ftp control Data Structure Index

### 2.1 globus ftp control Data Structures

Here are the data structures with brief descriptions:

<a href="#">globus.ftp_control_auth_info_s</a> (Authentication Values)	2
<a href="#">globus.ftp_control_dcau_subject_s</a> (Control dcau subject authentication type)	2
<a href="#">globus.ftp_control_dcau_u</a> (Control dcau union)	3
<a href="#">globus.ftp_control_layout_u</a> (Control striping attribute union)	3
<a href="#">globus.ftp_control_parallelism_u</a> (Control parallelism attribute structure)	3
<a href="#">globus.ftp_control_round_robin_s</a> (Control striping round robin attribute structure)	3
<a href="#">globus.ftp_control_tcpbuffer_automatic_s</a> (Automatically set the TCP buffer/window size)	3
<a href="#">globus.ftp_control_tcpbuffer_default_t</a> (Don't change the TCP buffer/window size from the system default)	3
<a href="#">globus.ftp_control_tcpbuffer_fixed_t</a> (Set the TCP buffer/window size to a fixed value)	4

[globus.ftp.control.tcpbuffer.t](#) (Control tcpbuffer attribute structure) 4

## 3 globus ftp control File Index

### 3.1 globus ftp control File List

Here is a list of all documented files with brief descriptions:

<a href="#">globus.ftp.control.c</a> (FTP Control API Activation/Deactivation and Global State)	4
<a href="#">globus.ftp.control.h</a> (GSIFTP Control Connection API (Data structures and types))	5
<a href="#">globus.ftp.control.client.c</a> (Client-side FTP Control API)	14
<a href="#">globus.ftp.control.data.c</a> (FTP Data Connection Configuration and Management)	21
<a href="#">globus.ftp.control.layout.c</a>	32
<a href="#">globus.ftp.control.server.c</a> (FTP Server-side Control Connection Management)	32

## 4 globus ftp control Page Index

### 4.1 globus ftp control Related Pages

Here is a list of all related documentation pages:

GridFTP: Protocol Extensions to FTP for the Grid	37
--	----

## 5 globus ftp control Data Structure Documentation

### 5.1 globusftp\_control\_auth\_info\_s Struct Reference

Authentication Values.

#### 5.1.1 Detailed Description

Authentication Values.

This structure is populated and passed back to the user via [globusftp\\_control\\_auth\\_callback\\_t\(\)](#). It contains the information needed to decide if a client may use the server.

### 5.2 globusftp\_control\_dcau\_subject\_s Struct Reference

control dcau subject authentication type

#### 5.2.1 Detailed Description

control dcau subject authentication type

## 5.3 globusftp\_control\_dcau.u Union Reference

control dcau union

### 5.3.1 Detailed Description

control dcau union

## 5.4 globusftp\_control\_layout.u Union Reference

control striping attribute union

### 5.4.1 Detailed Description

control striping attribute union

## 5.5 globusftp\_control\_parallelism.u Union Reference

control parallelism attribute structure

### 5.5.1 Detailed Description

control parallelism attribute structure

## 5.6 globusftp\_control\_round\_robin.s Struct Reference

control striping round robin attribute structure

### 5.6.1 Detailed Description

control striping round robin attribute structure

## 5.7 globusftp\_control\_tcpbuffer\_automatic.s Struct Reference

Automatically set the TCP buffer/window size.

### 5.7.1 Detailed Description

Automatically set the TCP buffer/window size.

## 5.8 globusftp\_control\_tcpbuffer\_default.t Struct Reference

Don't change the TCP buffer/window size from the system default.

### 5.8.1 Detailed Description

Don't change the TCP buffer/window size from the system default.

## 5.9 globusftp\_control\_tcpbuffer\_xed\_t Struct Reference

Set the TCP buffer/window size to a xed value.

### 5.9.1 Detailed Description

Set the TCP buffer/window size to a xed value.

## 5.10 globusftp\_control\_tcpbuffer\_t Union Reference

control tcpbuffer attribute structure

### 5.10.1 Detailed Description

control tcpbuffer attribute structure

## 6 globus ftp control File Documentation

### 6.1 globusftp\_control.c File Reference

FTP Control API Activation/Deactivation and Global State.

Variables

```
int globusi\_ftp\_controldebuglevel = 0
```

### 6.1.1 Detailed Description

FTP Control API Activation/Deactivation and Global State.

### 6.1.2 Variable Documentation

#### 6.1.2.1 globusmodule\_descriptor\_t globus.i\_ftp\_control\_module

Initial value:

```
{
    "globus_ftp_control",
    globus_i_ftp_control_activate,
    globus_i_ftp_control_deactivate,
    GLOBUS_NULL,
    GLOBUS_NULL,
    &local_version
}
```

6.1.2.2 int globus\_i\_ftp\_control\_debug\_level = 0

Debugging level.

1 thru 3 enable debug output for control channel 4 thru 6 enable debug output for control and data channel

## 6.2 globusftp\_control.h File Reference

GSIFTP Control Connection API (Data structures and types).

### Data Structures

struct [globusftp\\_control\\_dcau\\_subjects](#)

control dcau subject authentication type

struct [globusftp\\_control\\_round\\_robin\\_s](#)

control striping round robin attribute structure

union [globusftp\\_control\\_dcau\\_u](#)

control dcau union

union [globusftp\\_control\\_layout\\_u](#)

control striping attribute union

union [globusftp\\_control\\_parallelism\\_u](#)

control parallelism attribute structure

struct [globusftp\\_control\\_tcpbuffer\\_default\\_t](#)

Don't change the TCP buffer/window size from the system default.

struct [globusftp\\_control\\_tcpbuffer\\_xed\\_t](#)

Set the TCP buffer/window size to a xed value.

struct [globusftp\\_control\\_tcpbuffer\\_automatics](#)

Automatically set the TCP buffer/window size.

union [globusftp\\_control\\_tcpbuffer\\_t](#)

control tcpbuffer attribute structure

struct [globusftp\\_control\\_auth\\_info\\_s](#)

Authentication Values.

### Defines

#define [GLOBUS\\_FTP\\_CONTROL\\_MODULE](#) (&globus\_i\_ftp\_control\_module)

## Typedefs

```
typedef enum globusftp_control_type_e globusftp_control_type_t
typedef enum globusftp_control_mode_e globusftp_control_mode_t
typedef enum globusftp_control_dcau_mode_e globusftp_control_dcau_mode_t
typedef globusftp_control_dcau_subjects globusftp_control_dcau_subject_t
typedef enum globusftp_control_stripping_mode_e globusftp_control_stripping_mode_t
typedef globusftp_control_round_robin_s globusftp_control_round_robin_t
typedef globusftp_control_dcau_u globusftp_control_dcau_t
typedef globusftp_control_layout_u globusftp_control_layout_t
typedef enum globusftp_control_structree globusftp_control_structree_t
typedef enum globusftp_control_parallelism_mode_e globusftp_control_parallelism_mode_t
typedef globusftp_control_parallelism_u globusftp_control_parallelism_t
typedef enum globusftp_control_tcpbuffer_mode_e globusftp_control_tcpbuffer_mode_t
typedef globusftp_control_tcpbuffer_automatics globusftp_control_tcpbuffer_automatic_t
typedef globusftp_control_tcpbuffer_t globusftp_control_tcpbuffer_t
typedef globusftp_control_auth_info_s globusftp_control_auth_info_t
typedef void( globusftp_control_response_callback_t )(void callbackarg, struct globusftp_control_handles
    handle, globusobject_t error, globusftp_control_response_t ftp_response)
typedef void( globusftp_control_callback_t )(void callbackarg, struct globusftp_control_handles handle,
    globusobject_t error)
typedef void( globusftp_control_command_callback_t )(void callbackarg, struct globusftp_control_handles
    handle, globusobject_t error, union globusftp_control_command_u command)
typedef void( globusftp_control_auth_callback_t )(void callbackarg, struct globusftp_control_handles
    handle, globusobject_t error, globusftp_control_auth_info_t auth_result)
typedef unsigned long globusftp_control_auth_requirements_t
typedef void( globusftp_control_data_callback_t )(void callbackarg, globusftp_control_handle_t handle,
    globusobject_t error, globusbyte_t buffer, globussize_t length, globusoff_t offset, globusbool_t eof)
typedef void( globusftp_control_server_callback_t )(void callbackarg, struct globusftp_control_servers
    serverhandle, globusobject_t error)
```

## Enumerations

```
enum globusftp_control_type_e
enum globusftp_control_mode_e
enum globusftp_control_dcau_mode_e
enum globusftp_control_stripping_mode_e
enum globusftp_control_protection_t
enum globusftp_control_delay_passive_t
enum globusftp_control_structree
enum globusftp_control_parallelism_mode_e
enum globusftp_control_tcpbuffer_mode_e f GLOBUS.FTP.CONTROL.TCPBUFFERDEFAULT,
GLOBUS.FTP.CONTROL.TCPBUFFERFIXED, GLOBUS.FTP.CONTROL.TCPBUFFERAUTOMATIC
g
```

## Functions

```

globusresult_t globusftp_control_local_layout (globusftp_control_handle_t handle, globusftp_control-
layout_t layout, globussize_t datasize)
globusresult_t globusftp_control_dataset_interface (globusftp_control_handle_t handle, const char
interfaceaddr)
globusresult_t globusftp_control_createdatainfo (globusftp_control_handle_t handle, globusftp_control-
datawrite_info_t datainfo, globusbyte_t buffer, globussize_t length, globusoff_t offset, globusbool_t eof,
globusftp_control_datacallback_t callback, void callbackarg)
globusresult_t globusftp_control_releasedatainfo (globusftp_control_handle_t handle, globusftp_control-
datawrite_info_t datainfo)
globusresult_t globusftp_control_datawrite_stripe (globusftp_control_handle_t handle, globusbyte_t buffer,
globussize_t length, globusoff_t offset, globusbool_t eof, int stripindx, globusftp_control_datacallback_t
callback, void callbackarg)
globusresult_t globusX_ftp_control_datawrite_stripe (globusftp_control_handle_t handle, globusbyte-
t buffer, globussize_t length, globusoff_t offset, globusbool_t eof, int stripindx, globusftp_control_data-
write_info_t datainfo)

```

### 6.2.1 Detailed Description

GSIFTP Control Connection API (Data structures and types).

### 6.2.2 De ne Documentation

#### 6.2.2.1 #de ne GLOBUSFTP\_CONTROL\_MODULE (&globus\_i\_ftp\_control\_module)

Module descriptor.

The Globus FTP Control library uses the standard module activation and deactivation API to initialize it's state. Before any GSIFTP functions are called, the module must be activated

```
globus_module_activate(GLOBUS_GSIFTP_CONTROL_MODULE);
```

This function returns GLOBUS\_SUCCESS if the GSIFTP library was successfully initialized. This may be called multiple times.

To deactivate the GSIFTP library, the following must be called

```
globus_module_deactivate(GLOBUS_GSIFTP_CONTROL_MODULE);
```

### 6.2.3 Typedef Documentation

#### 6.2.3.1 typedef enum globusftp\_control\_type\_e globusftp\_control\_type\_t control structure types.

The enumeration values match the character value of the argument to TYPE.

#### 6.2.3.2 typedef enum globusftp\_control\_mode\_e globusftp\_control\_mode\_t control structure mode



6.2.3.3 typedef enum [globusftp\\_control\\_dcau\\_mode\\_e](#) globusftp\_control\_dcau\_mode\_t  
control dcau types

6.2.3.4 typedef struct [globusftp\\_control\\_dcau\\_subject\\_s](#) globusftp\_control\_dcau\_subject\_t  
control dcau subject authentication type

6.2.3.5 typedef enum [globusftp\\_control\\_striping\\_mode\\_e](#) globusftp\_control\_striping\_mode\_t  
control striping Types

6.2.3.6 typedef struct [globusftp\\_control\\_round\\_robin\\_s](#) globusftp\_control\_round\_robin\_t  
control striping round robin attribute structure

6.2.3.7 typedef union [globusftp\\_control\\_dcau\\_u](#) globusftp\_control\_dcau\_t  
control dcau union

6.2.3.8 typedef union [globusftp\\_control\\_layout\\_u](#) globusftp\_control\_layout\_t  
control striping attribute union

6.2.3.9 typedef enum [globusftp\\_control\\_structure\\_e](#) globusftp\_control\_structure\_t  
control structure structure

6.2.3.10 typedef enum [globusftp\\_control\\_parallelism\\_mode\\_e](#) globusftp\_control\_parallelism\_mode\_t  
control parallelism Types

6.2.3.11 typedef union [globusftp\\_control\\_parallelism\\_u](#) globusftp\_control\_parallelism\_t  
control parallelism attribute structure

6.2.3.12 typedef enum [globusftp\\_control\\_tcpbuffer\\_mode\\_e](#) globusftp\_control\_tcpbuffer\_mode\_t  
TCP Buffer Setting Modes.

6.2.3.13 typedef struct [globusftp\\_control\\_tcpbuffer\\_automatic\\_s](#) globusftp\_control\_tcpbuffer\_automatic\_t  
Automatically set the TCP buffer/window size.

6.2.3.14 typedef union globusftp\_control\_tcpbuffer\_t globusftp\_control\_tcpbuffer\_t  
control tcpbuffer attribute structure

### 6.2.3.15 typedef struct globusftp\_control\_auth\_info\_s globusftp\_control\_auth\_info\_t

Authentication Values.

This structure is populated and passed back to the user via `globusftp_control_auth_callback()`. It contains the information needed to decide if a client may use the server.

### 6.2.3.16 typedef void( globusftp\_control\_responsecallback\_t)( void callback\_arg, struct globusftp\_control\_handle\_s handle, globusobject\_t error, globusftp\_control\_responset ftp\_response)

Asynchronous operation completion callback.

This callback is called whenever a reply to command is received on the FTP control channel. It allows the user to handle the received reply or alternatively handle any errors that occurred during the interaction with the FTP server. This function will be called multiple times in the case when intermediate responses (1yz) are received.

Parameters:

- callback\_arg User supplied argument to the callback function
- handle A pointer to the GSIFTP control handle. Used to identify which control connection the operation was applied to.
- error Pointer to a globus error object containing information about any errors that occurred processing the operation
- ftp\_response Pointer to a response structure containing the FTP response to the command.

### 6.2.3.17 typedef void( globusftp\_control\_callback\_t)( void callback\_arg, struct globusftp\_control\_handle\_s handle, globusobject\_t error)

Asynchronous control callback.

This callback is used as a generic control operation callback.

Parameters:

- callback\_arg User supplied argument to the callback function
- handle A pointer to the GSIFTP control handle. Used to identify which control connection the operation was applied to.
- error Pointer to a globus error object containing information about any errors that occurred processing the operation

### 6.2.3.18 typedef void( globusftp\_control\_commandcallback\_t)( void callback\_arg, struct globusftp\_control\_handle\_s handle, globusobject\_t error, union globusftp\_control\_command\_u command)

Server command callback.

When a command from a client is received on the control channel a user callback with this signature is called.

Parameters:

- callback\_arg The user argument passed to the callback function.
- handle The control handle that the command was issued on.
- error Indicates if a command was successful read or or if a failure occurred. This object will be freed once this callback returns. If the user wishes to have a copy of the error that persists past the life of this callback, they must make a copy using `globusobjectcopy()`, and free it with `globusobjectfree()`.

**command** The command structure indicates what type of command the client issued. Based on the 'type' further information can be extracted. This command structure will be freed once this callback returns. If the user wishes to have a copy of the error that persists past the life of this callback, they must make a copy using [globusftp\\_control\\_commandcopy\(\)](#), and free it with [globusftp\\_control\\_commandfree\(\)](#).

6.2.3.19 `typedef void( globusftp_control_auth_callback_t)( void callback_arg, struct globusftp_control_handle_s handle, globusobject_t error, globusftp\_control\_auth\_info\_t auth_result)`

Server authentication complete callback.

A function with this signature is registered by calling [globusftp\\_control\\_accept\(\)](#). It is called when the authentication protocol has completed. Based on the **auth\_result**, the server implementor should determine authorization and then send the appropriate response using [globusftp\\_control\\_sendresponse\(\)](#) indicating to the client whether authorization was successful or not.

Parameters:

**handle** This structure is populated when the callback is called and represents a control connection to the client.

**auth\_result** A `globusftp_control_auth_result_t` containing the values the client sent for gss authentication, user name, password and account. If any of the values were not sent by the client they will be NULL. Based on that information the user can decide if the client will be authorized for use of the server.

**callback\_arg** The user argument passed to the callback.

6.2.3.20 `typedef unsigned long globusftp_control_auth_requirements_t`

Authentication requirements.

The value of this should be a bitwise or of

```
GLOBUS_FTP_CONTROL_AUTH_NONE
GLOBUS_FTP_CONTROL_AUTH_GSSAPI
GLOBUS_FTP_CONTROL_AUTH_USER
GLOBUS_FTP_CONTROL_AUTH_PASS
GLOBUS_FTP_CONTROL_AUTH_ACCT
```

6.2.3.21 `typedef void( globusftp_control_data_callback_t)( void callback_arg, struct globusftp_control_handle_t handle, globusobject_t error, globus_byte_t buffer, globus_size_t length, globus_off_t offset, globus_bool_t eof)`

Asynchronous data transmission operation callback.

This callback is called in functions that send or receive data on the data channel(s).

In the case of a write, this function is invoked when the entire data buffer is sent. Depending on the data transfer properties set by the [globusftp\\_control\\_local\\_\(\)](#) functions, the data may actually be split into multiple buffers and sent to multiple data nodes.

In the case of a read, this function will return a single extent of the data. The order of the data returned is not defined in an extended block mode data transfer. It is up to the user of the API to re-construct the file order.

Parameters:

**callback\_arg** User supplied argument to the callback function

**handle** A pointer to the GSIFTP control handle. Used to identify which control connection the operation was applied to.

error Pointer to a globus error object containing information about any errors that occurred processing the operation

buffer The user buffer passed as a parameter to [globusftp\\_control\\_dataread\(\)](#) or [globusftp\\_control\\_datawrite\(\)](#).

length The amount of data in the buffer. In the case of an incoming data channel, this may be less than the buffer size.

offset The file offset of the data which is contained in the buffer.

eof This is set to GLOBUS\_TRUE then all of the data associated with the transfer has arrived on the data connections associated with this handle. If multiple data callbacks are registered with this handle, there is no guaranteed order of the EOF callback with respect to other data callbacks. If multiple callbacks are registered when EOF is reached on the data connections, at least one callback function will be called with eof set to GLOBUS\_TRUE.

6.2.3.22 typedef void( globusftp\_control\_server\_callback\_t)( void callback\_arg, struct globusftp\_control\_server\_s server\_handle, globusobject\_t error)

Server callback.

A functions with this signature can be used as general callbacks for the GSIFTP server API.

Parameters:

serverhandle The server handle associated with callback.

result Indicates if the operation completed successfully or if a failure occurred.

callback\_arg The user argument passed to the callback function.

## 6.2.4 Enumeration Type Documentation

### 6.2.4.1 enum globusftp\_control\_type\_e

control structure types.

The enumeration values match the character value of the argument to TYPE.

### 6.2.4.2 enum globusftp\_control\_mode\_e

control structure mode

### 6.2.4.3 enum globusftp\_control\_dcau\_mode\_e

control dcau types

### 6.2.4.4 enum globusftp\_control\_striping\_mode\_e

control striping Types

### 6.2.4.5 enum globusftp\_control\_protection\_t

control protection levels

### 6.2.4.6 enum globusftp\_control\_delay\_passivet

delayed passive flags

## 6.2.4.7 enum globusftp\_control\_structure\_e

control structure structure

## 6.2.4.8 enum globusftp\_control\_parallelism\_mode\_e

control parallelism Types

## 6.2.4.9 enum globusftp\_control\_tcpbuffer\_mode\_e

TCP Buffer Setting Modes.

Enumeration values:

    GLOBUS\_FTP\_CONTROL\_TCPBUFFER\_DEFAULT Don't change the TCP buffer/window size from the system default.

    GLOBUS\_FTP\_CONTROL\_TCPBUFFER\_FIXED Set the TCP buffer/window size to a fixed value.

    GLOBUS\_FTP\_CONTROL\_TCPBUFFER\_AUTOMATIC Automatically set the TCP buffer/window size.

## 6.2.5 Function Documentation

6.2.5.1 globusresult\_t globusftp\_control\_local\_layout (globusftp\_control\_handle\_t handle, globusftp\_control\_layout\_t layout, globus\_size\_t data\_size)

Update the handle with the layout and the size of the data sent over the data channel.

This function is deprecated. The interface will be changed to [globusXftp\\_control\\_local\\_layout\(\)](#)

Parameters:

    handle A pointer to the FTP control handle into which to insert the layout information.

    layout A variable containing the layout information

    data\_size The size of the data that is going to be sent. This may be needed to interpret the layout information.

6.2.5.2 globusresult\_t globusftp\_control\_data\_set\_interface (globusftp\_control\_handle\_t handle, const char interface\_addr)

Create an outgoing FTP data connection.

This function sets the interface that will be used to send and receive information along the data channel.

Parameters:

    handle A pointer to a FTP control handle which is configured to create an outgoing data connection.

    interface\_addr

6.2.5.3 globusresult\_t globusftp\_control\_create\_data\_info (globusftp\_control\_handle\_t handle, globusftp\_control\_data\_write\_info\_t data\_info, globus\_byte\_t buffer, globus\_size\_t length, globus\_off\_t offset, globus\_bool\_t eof, globusftp\_control\_data\_callback\_t callback, void callback\_arg)

Create a globusftp\_control\_datawrite\_info\_t structure.

This function populates a globusftp\_control\_datacallback\_t structure with valid information. This structure provides the user a way to register several data writes with a single callback. This is quite useful to the writer of enqueue functions. It allows a single call to [globusftp\\_control\\_datawrite\(\)](#) to be broken up into many writes, potentially on different stripes, and for a single callback to be called when all are finished.

## Parameters:

- handle A pointer to a FTP control handle. The handle contains information about the current state of the control and data connections.
- datainfo The globusftp\_controldatawrite\_info\_t structure to be released.
- buffer The pointer to the user buffer that will be passed to the callback argument when there are zero references to datainfo. This is intended to be the start of all the data the user intends to write using globusftp\_control\_datawrite\_stripe(), but it does not have to be.
- length The length of the memory segment pointed to by the argument buffer.
- offset The file offset of the data segment specified.
- eof This should be set to true if the user plans on registering eof on the data structure.
- callback The user function to be called when all references to datainfo are released. This occurs after all data registered for write from globusftp\_controldatawrite\_stripe have occurred and the user calls globusftp\_control\_releasedatainfo(). The callback is passed all of the arguments passed to this function with the exception of datainfo.
- callbackarg User supplied argument to the callback function

#### 6.2.5.4 globusresult\_t globusftp\_control\_releasedatainfo (globusftp\_control\_handle\_t handle, globusftp\_control\_datawrite\_info\_t datainfo)

Release a datainfo structure.

This function releases all memory and references created when a call to globusftp\_control\_createdatainfo() was made. For every call to globusftp\_control\_createdatainfo() a call to this function must be made.

## Parameters:

- handle A pointer to a FTP control handle. The handle contains information about the current state of the control and data connections.
- datainfo The globusftp\_controldatawrite\_info\_t structure to be released.

#### 6.2.5.5 globusresult\_t globusftp\_control\_datawrite\_stripe (globusftp\_control\_handle\_t handle, globus\_byte\_t buffer, globus\_size\_t length, globus\_off\_t offset, globus\_bool\_t eof, int stripe\_idx, globusftp\_control\_data\_callback\_t callback, void callbackarg)

Write FTP data to a particular stripe.

This function allows the user to write to a specified stripe. The stripe index relates to the order passed into local spor(). This function differs from globusftp\_control\_datawrite() in that no enqueue function is needed since the user specifies the stripe on which data is written. In order to use this function the user must have a valid pointer to a globusftp\_controldatawrite\_info\_t structure. The datainfo structure can be obtained by a call to globusftp\_control\_createdatainfo(). Many calls to this function can be made, but only a single user callback occurs per creation of a globusftp\_controldatawrite\_info\_t structure.

## Parameters:

- handle A pointer to a FTP control handle. The handle contains information about the current state of the control and data connections.
- buffer a pointer to the data the user wishes to send along the FTP data channels.
- length the length of the data pointer to by the parameter buffer.
- offset the offset into the file of the data.
- eof A boolean stating that this will be the last chunk of data registered on the given stripe. In order to properly send an eof message the user must register an eof on every stripe.

`stripe_ndx` The index of the stripe on which the data will be sent. The index of each stripe is determined by the call to `localspas` or `localspor`.

`callback` The function to be called once the data has been sent

`callbackarg` User supplied argument to the callback function

6.2.5.6 `globusresult_t globus_X_ftp_control_data_write_stripe (globusftp_control_handle_t handle, globus_byte_t buffer, globus_size_t length, globus_off_t offset, globus_bool_t eof, int stripe_ndx, globusftp_control_data_write_info_t datainfo)`

Write data on a specific stripe from an enqueue callback function only.

This function allows the user to register the write of ftp data on a specific stripe. This function can only be called from an enqueue function callback. This function should be used only by the implementor of an enqueue function. It should be viewed as unstable and used only by advanced users. This is the only function in the library that the enqueue function implementor is allowed from the enqueue callback.

Parameters:

`handle` A pointer to a FTP control handle. The handle contains information about the current state of the control and data connections.

`buffer` a pointer to the data the user wishes to send along the FTP data channels.

`length` the length of the data pointer to by the parameter `buffer`.

`offset` the offset into the file of the data.

`eof` a boolean stating that this is the last buffer to be registered. When using the version of this function the user does not need to register an eof on each stripe, the control library will take care of that internally.

`stripe_ndx` The index of the stripe on which the data will be sent. The index of each stripe is determined by the call to `localspas` or `localspor`.

`datainfo` An opaque structure that is passed into the enqueue function and contains reference count and state information. The same `datainfo` pointer that is passed into the enqueue function must be used for this parameter.

## 6.3 globusftp\_control\_client.c File Reference

Client-side FTP Control API.

Functions

```
globusresult_t globusftp_control_handle_init (globusftp_control_handle_t handle)
globusresult_t globusftp_control_handle_destroy (globusftp_control_handle_t handle)
globusresult_t globusftp_control_connect (globusftp_control_handle_t handle, char host, unsigned short port, globusftp_control_response_callback_t callback, void callbackarg)
globusresult_t globusftp_control_response_destroy (globusftp_control_response_t response)
globusresult_t globusftp_control_response_copy (globusftp_control_response_t src, globusftp_control_response_t dest)
globusresult_t globusftp_control_authenticate (globusftp_control_handle_t handle, globusftp_control_auth_info_t authinfo, globus_bool_t use_auth, globusftp_control_response_callback_t callback, void callbackarg)
globusresult_t globusftp_control_send_command (globusftp_control_handle_t handle, const char cmdspec, globusftp_control_response_callback_t callback, void callbackarg, ...)
globusresult_t globusftp_control_abort (globusftp_control_handle_t handle, globusftp_control_response_callback_t callback, void callbackarg)
```

```

globusresult_t globusftp_control_quit (globusftp_control_handle_t handle, globusftp_control_response_callback_t callback, void callbackarg)
globusresult_t globusftp_control_force_close (globusftp_control_handle_t handle, globusftp_control_response_callback_t callback, void callbackarg)
globusresult_t globusftp_control_auth_info_init (globusftp_control_auth_info_t authinfo, gsscredid_t credential_handle, globus_bool_t encrypt, char user, char password, char account, char subject)
int globusftp_control_auth_info_compare (globusftp_control_auth_info_t authinfo_1, globusftp_control_auth_info_t authinfo_2)

```

### 6.3.1 Detailed Description

Client-side FTP Control API.

### 6.3.2 Function Documentation

#### 6.3.2.1 globusresult\_t globusftp\_control\_handle\_init (globusftp\_control\_handle\_t handle)

Initialize a globus ftp handle.

This function will set up (i.e. initialize all mutexes and variables) a globus ftp handle. It will also enter the handle in a list used by the module activation/deactivation functions.

Parameters:

handle The handle to initialize.

Returns:

GLOBUS\_SUCCESS  
error object

#### 6.3.2.2 globusresult\_t globusftp\_control\_handle\_destroy (globusftp\_control\_handle\_t handle)

Destroy a globus ftp handle.

This function will free up all dynamically allocated memory associated with a given globus ftp handle. It will also remove the handle from a list used by the module activation/deactivation functions. This function should only be called after a call to either `globusftp_control_force_close` or `globusftp_control_quit`.

Parameters:

handle The handle to destroy.

Returns:

success  
invalid handle  
handle is still in connected state

#### 6.3.2.3 globusresult\_t globusftp\_control\_connect (globusftp\_control\_handle\_t handle, char host, unsigned short port, globusftp\_control\_response\_callback\_t callback, void callbackarg)

Create a new control connection to an FTP server.

This function is used to initiate an FTP control connection. It creates the socket to the FTP server. When the connection is made to the server, and the server's identification string is received, the callback function will be invoked.



**Parameters:**

handle A pointer to a initialized FTP control handle. This handle will be used for all subsequent FTP control operations.

host The hostname of the FTP server.

port The TCP port number of the FTP server.

callback A function to be called once the connection to the server is established, and a response has been read.

callback.arg Parameter to the callback function.

**Returns:**

success  
 Null handle  
 Null host  
 Illegal port number  
 Null callback  
 Cannot resolve hostname  
 Cannot create socket

**Callback errors:**

success  
 connection refused  
 protocol error  
 eof

**Expected callback response values:**

120 Service ready in nnn minutes.  
 220 Service ready for new user.  
 421 Service not available, closing control connection.  
 500 Syntax error, command unrecognized.

**Note:**

The server may send other responses.

#### 6.3.2.4 globusresult\_t globusftp\_control\_responsetdestroy (globusftp\_control\_responset response)

Helper function which frees the memory associated with a response structure.

This is a helper function which frees the memory associated with a response structure.

**Parameters:**

response This parameter indicates the response structure to destroy

**Returns:**

Error object  
 GLOBUS\_SUCCESS

#### 6.3.2.5 globusresult\_t globusftp\_control\_responsecopy (globusftp\_control\_responset src, globusftp\_control\_responset dest)

Helper function which copies one response structure to another.

This is a helper function which copies one response structure to another.

**Parameters:**

src This parameter indicates the response structure to copy

dest This parameter specifies the target response structure

Returns:

Error object  
GLOBUS\_SUCCESS

6.3.2.6 globusresult\_t globusftp\_control\_authenticate (globusftp\_control\_handle\_t handle, globusftp\_control\_auth\_info\_t auth\_info, globus\_bool\_t use\_auth, globusftp\_control\_responsecallback\_t callback, void callback\_arg)

Authenticate the user to the FTP server.

This will perform the authentication handshake with the FTP server. depending on which parameters are non-NULL, the authentication may involve GSSAPI credentials, a username, a password, and an account name.

Note:

Do we want to add attribute arguments for:

specifying type of delegation  
gsswrap control messages for integrity or confidentiality

Parameters:

handle A pointer to a unauthenticated GSIFTP control handle. In the case of GSS authentication the GSS security context is stored in this structure.

auth\_info This structure is used to pass the following information:

user The user's name for login purposes. If this string is "anonymous", "ftp", GLOBUS\_NULL or ":globus-mapping:" then the password argument is optional. If this string is GLOBUS\_NULL or ":globus-mapping:" and gss\_auth is true then the user's login is looked by the FTP server host.  
password The password for the above user argument. If the user argument is "anonymous" or "ftp" or if gss\_auth is true this string may be GLOBUS\_NULL.  
account This parameter is optional. If not used it should be set to GLOBUS\_NULL. It might be needed by rewall.  
auth\_gssapi\_subject The GSSAPI subject name of the server you are connecting to. If this is GLOBUS\_NULL, and the gss\_auth parameter is set to GLOBUS\_TRUE, then the name will default to the host name.

Parameters:

use\_auth If set to GLOBUS\_TRUE the above argument indicates that GSS authentication should be used, otherwise cleartext user/password authentication is used.

callback The function to be called once the authentication process is complete or when an error occurs.

callback\_arg User supplied argument to the callback function

Returns:

success  
Null handle  
Invalid handle  
Handle already authenticated

Callback errors:

success  
authentication failed  
protocol error  
eof

Expected callback response values:

- 230 User logged in, proceed.
- 232 User logged in, authorized by security data exchange.
- 234 Security data exchange complete.
- 331 User name okay, need password.
- 332 Need account for login.
- 336 Username okay, need password. Challenge is "...."
- 431 Need some unavailable resource to process security.
- 500 Syntax error, command unrecognized.
- 530 Not logged in.

Note:

The server may send other responses.

6.3.2.7 `globusresult_t globusftp_control_sendcommand (globusftp_control_handle_t handle, const char cmdspec, globusftp\_control\_responsecallback\_t callback, void callbackarg, ...)`

Send an FTP protocol command to the FTP server and register a response handler.

This function is used to send an FTP command, and register a handler to receive the FTP reply (or replies, if an intermediate one is sent). When the control channel is gss authenticated, the message and the reply will be automatically gss wrapped/unwrapped.

Parameters:

- `handle` A pointer to a GSIFTP control handle. The command described by the `cmdspec` is issued to the server over the control channel associated with this handle.
- `cmdspec` A printf-style format string containing the text of the command to send to the server. The optional parameters to the format string are passed after the `callback` in the function invocation.
- `callback` The function to be called once the authentication process is complete or when an error occurs.
- `callbackarg` User supplied argument to the callback function
- ... Parameters which will be substituted into the % escapes in the `cmdspec` string.

Returns:

- Success
- Null handle
- Command already in progress

Callback errors:

- success
- protocol error
- eof

Expected callback response values:

Any defined in RFC 959, 2228, 2389, draft-ietf-ftpext-mlst-10, or [protocol extensions](#) document.

6.3.2.8 `globusresult_t globusftp_control_abort (globusftp_control_handle_t handle, globusftp\_control\_responsecallback\_t callback, void callbackarg)`

Send an ABORT to the FTP server and register a response handler.

This function is used to send the ABORT message to the FTP server. The ABORT message is sent out-of-band, and terminates any current data transfer in progress.

As a result of the ABORT, the data channels used by this control channel will be closed. The data command callback will be issued with either a completion reply, or a transfer aborted reply. The ABORT callback will also be invoked, with the server's response to the abort command.

Any attempts to register buffers for read or write after an ABORT has been sent will fail with a "no transfer in progress" error.

**Parameters:**

handle A pointer to a GSIFTP control handle. The ABORT command is issued to the server over the control channel associated with this handle.

callback The function to be called once the authentication process is complete or when an error occurs.

callback.arg User supplied argument to the callback function

**Returns:**

Success  
Null handle  
No transfer in progress

**Callback errors:**

success  
protocol error  
eof

**Expected callback response values:**

226 Abort successful.  
500 Syntax error, command unrecognized.

**Note:**

The server may send other responses.

6.3.2.9 globusresult\_t globusftp\_control\_quit (globusftp\_control\_handle\_t handle, [globusftp\\_control\\_responsecallback\\_t](#) callback, void callback.arg)

Send a QUIT message to the FTP server and register a response handler.

This function is used to close the control channel to the FTP server. There should be no transfer commands in progress when this is called. Once the nal response callback passed to this function is invoked, the control handle can no longer be used for any gsiftp control operations.

**Note:**

Need to further define behavior for when a QUIT happens during a transfer or command is in progress.

**Note:**

Since this function waits until all other callbacks are completed before calling it's own callback it may not be called in a blocking fashion from another callback.

**Parameters:**

handle A pointer to a GSIFTP control handle. The quit message is issued to the server over the control channel associated with this handle.

callback The function to be called once the authentication process is complete or when an error occurs.

callback.arg User supplied argument to the callback function

## Returns:

- Success
- Null handle
- Command in progress

## Callback errors:

- success
- protocol error
- eof

## Expected callback response values:

- 221 Service closing control connection.
- 500 Syntax error, command unrecognized.

## Note:

The server may send other responses.

6.3.2.10 `globusresult_t globusftp_control_force_close (globusftp_control_handle_t handle, globusftp\_control\_responsecallback\_t callback, void callback_arg)`

Force a close of the control connection without waiting for outstanding commands to complete and without sending QUIT.

This function is used to close the control channel to the FTP server. Once the final response callback passed to this function is invoked, the control handle can no longer be used for any gsiftp control operations.

## Note:

Since this function waits until all other callbacks are completed before calling it's own callback it may not be called in a blocking fashion from another callback.

## Parameters:

`handle` A pointer to a GSIFTP control handle. The quit message is issued to the server over the control channel associated with this handle.

`callback` The function to be called once the authentication process is complete or when an error occurs.

`callback_arg` User supplied argument to the callback function

## Returns:

- Success
- Null handle

## Callback errors:

- success
- failure

## Expected callback response values:

- GLOBUS\_NULL

6.3.2.11 `globusresult_t globusftp_control_auth_info_init (globusftp\_control\_auth\_info\_t auth_info, gss_cred_id_t credential_handle, globus_bool_t encrypt, char user, char password, char account, char subject)`

Helper function which initializes a authentication information structure.

This is helper function initializes a authentication information structure with the values contained in the second to fifth arguments, which may be GLOBUS\_NULL. No memory is allocated in this function.

**Parameters:**

auth\_info The authentication structure to initialize.

credentialhandle The credential to use for authentication. This may be GSSO.CREDENTIAL to use the user's default credential.

encrypt Boolean whether or not to encrypt the control channel for this handle.

user The user name

passwordThe password for the user name

account The account for the user name/password

subject The gss api subject name

**Returns:**

Error object  
GLOBUS.SUCCESS

6.3.2.12 int globusftp\_control\_auth\_info\_compare (globusftp\_control\_auth\_info\_t auth\_info\_1, globusftp\_control\_auth\_info\_t auth\_info\_2)

Helper function which compares two authentication information structures.

This is helper function compares two authentication information structures and return zero if the two structures are deemed equal and a non-zero value otherwise.

**Parameters:**

auth\_info\_1 The first authentication structure

auth\_info\_2 The second authentication structure

**Returns:**

0 if the structures are equal  
!0 if the structures differ or an error occurred

## 6.4 globusftp\_control\_data.c File Reference

FTP Data Connection Configuration and Management.

**Functions**

```

globusresult_t globusftp_control_data_connectread(globusftp_control_handle_t handle, globusftp_control_data_connect_callback_t callback, void userarg)
globusresult_t globusftp_control_data_set_interface(globusftp_control_handle_t handle, const char interfaceaddr)
globusresult_t globusftp_control_data_connectwrite(globusftp_control_handle_t handle, globusftp_control_data_connect_callback_t callback, void userarg)
globusresult_t globusftp_control_data_add_channels(globusftp_control_handle_t handle, unsigned int num_channels, unsigned int stripe)
globusresult_t globusftp_control_data_send_eof(globusftp_control_handle_t handle, int count[], int array_size, globus_bool_t eof_message, globusftp_control_callback_t cb, void userarg)
globusresult_t globusftp_control_data_remove_channels(globusftp_control_handle_t handle, unsigned int num_channels, unsigned int stripe)
globusresult_t globusftp_control_data_query_channels(globusftp_control_handle_t handle, unsigned int num_channels, unsigned int stripe)

```

```

globusresultt globusftp_control_data_get_total_data_channels(globusftp_control_handle_t handle, unsigned
int num_channels, unsigned int stripidx)
globusresultt globusftp_control_local_send_eof(globusftp_control_handle_t handle, globusbool_t send_eof)
globusresultt globusftp_control_local_parallelism(globusftp_control_handle_t handle, globusftp_control-
parallelism_t parallelism)
globusresultt globusftp_control_local_pasv(globusftp_control_handle_t handle, globusftp_control_host-
port_t address)
globusresultt globusftp_control_local_spas(globusftp_control_handle_t handle, globusftp_control_host-
port_t addresses[], unsigned int num_addresses)
globusresultt globusftp_control_local_port(globusftp_control_handle_t handle, globusftp_control_host-
port_t address)
globusresultt globusftp_control_local_spor(globusftp_control_handle_t handle, globusftp_control_host-
port_t addresses[], unsigned int num_addresses)
globusresultt globusftp_control_local_type(globusftp_control_handle_t handle, globusftp_control_type-
t type, int form_code)
globusresultt globusftp_control_local_mode(globusftp_control_handle_t handle, globusftp_control_mode_t
mode)
globusresultt globusftp_control_local_tcp_buffer(globusftp_control_handle_t handle, globusftp_control-
tcp_buffer_t tcp_buffer)
globusresultt globusftp_control_local_dcau(globusftp_control_handle_t handle, const globusftp_control-
dcau_t dcau, gss_cred_id_t delegated_credential_handle)
globusresultt globusftp_control_local_pbsz(globusftp_control_handle_t handle, unsigned long bufsize)
globusresultt globusftp_control_get_pbsz(globusftp_control_handle_t handle, unsigned long bufsize)
globusresultt globusftp_control_local_stru(globusftp_control_handle_t handle, globusftp_control-
structure_t structure)
globusresultt globusftp_control_data_write(globusftp_control_handle_t handle, globusbyte_t buffer,
globussize_t length, globusoff_t offset, globusbool_t eof, globusftp_control_data_callback_t callback, void
callbackarg)
globusresultt globusftp_control_data_read(globusftp_control_handle_t handle, globusbyte_t buffer,
globussize_t max_length, globusftp_control_data_callback_t callback, void callbackarg)
globusresultt globusftp_control_local_layout(globusftp_control_handle_t handle, globusftp_control-
layout_t layout, globussize_t datasize)
globusresultt globusftp_control_createdatainfo(globusftp_control_handle_t handle, globusftp_control-
datawrite_info_t datainfo, globusbyte_t buffer, globussize_t length, globusoff_t offset, globusbool_t eof,
globusftp_control_data_callback_t callback, void callbackarg)
globusresultt globusftp_control_releasedatainfo(globusftp_control_handle_t handle, globusftp_control-
datawrite_info_t datainfo)
globusresultt globusftp_control_data_write_stripe(globusftp_control_handle_t handle, globusbyte_t buffer,
globussize_t length, globusoff_t offset, globusbool_t eof, int stripidx, globusftp_control_data_callback_t
callback, void callbackarg)
globusresultt globusX_ftp_control_data_write_stripe(globusftp_control_handle_t handle, globusbyte-
t buffer, globussize_t length, globusoff_t offset, globusbool_t eof, int stripidx, globusftp_control_data-
write_info_t datainfo)
globusresultt globusftp_control_data_force_close(globusftp_control_handle_t control_handle, globusftp-
control_callback_t close_callback_func, void closearg)

```

#### 6.4.1 Detailed Description

FTP Data Connection Configuration and Management.

### 6.4.2 De ne Documentation

#### 6.4.2.1 #de ne GlobusFTPControlSetMagic(dhandle)

Value:

```
{
    strcpy(dc_handle->magic, GLOBUS_FTP_CONTROL_DATA_MAGIC);
}
```

#### 6.4.2.2 #de ne GlobusFTPControlDataTestMagic(dhandle)

Value:

```
{
    globus_assert(dc_handle != GLOBUS_NULL &&
        strcmp(dc_handle->magic, GLOBUS_FTP_CONTROL_DATA_MAGIC) == 0);
}
```

#### 6.4.2.3 #de ne DATA\_CONN\_MALLOC(data\_conn, stripe, cb, ua)

Value:

```
{
    data_conn = (globus_ftp_data_connection_t *)
        globus_malloc(
            sizeof(globus_ftp_data_connection_t));
    data_conn->whos_my_daddy = stripe;
    data_conn->offset = 0;
    data_conn->callback = cb;
    data_conn->user_arg = ua;
    data_conn->bytes_ready = 0;
    data_conn->eod = GLOBUS_FALSE;
    data_conn->close = GLOBUS_FALSE;
    data_conn->free_me = GLOBUS_FALSE;
    data_conn->reusing = GLOBUS_FALSE;
}
```

#### 6.4.2.4 #de ne CALLBACK\_INFO\_MALLOC(ci, dh, th, s, dc)

Value:

```
{
    ci = (globus_l_ftp_data_callback_info_t *)
        globus_malloc(sizeof(globus_l_ftp_data_callback_info_t));
    ci->stripe = s;
    ci->dc_handle = dh;
    ci->transfer_handle = th;
    ci->data_conn = dc;
}
```



## 6.4.2.5 #define TABLE\_ENTRY\_MALLOC(t\_e, buf, len, off, \_eof, cb, cba, dc\_h)

Value:

```
{
    t_e = (globus_ftp_handle_table_entry_t *)
        globus_malloc(sizeof(globus_ftp_handle_table_entry_t));
    t_e->buffer = buf;
    t_e->length = len;
    t_e->offset = off;
    t_e->error = GLOBUS_NULL;
    t_e->callback = cb;
    t_e->callback_arg = cba;
    t_e->direction = dc_h->transfer_handle->direction;
    t_e->dc_handle = dc_h;
    t_e->transfer_handle = dc_h->transfer_handle;
    t_e->type = dc_h->type;
    t_e->error = GLOBUS_NULL;
    t_e->whos_my_daddy = GLOBUS_NULL;
    t_e->ascii_buffer = GLOBUS_NULL;
    t_e->eof = _eof;
}
```

## 6.4.3 Function Documentation

## 6.4.3.1 globusresult\_t globusftp\_control\_data\_connectread (globusftp\_control\_handle\_t handle, globusftp\_control\_data\_connectcallback\_t callback, void user\_arg)

Create an incoming FTP data connection.

This function will register a `globusftp_control_data_connectread` callback. Further accepts/connects are done by registering a new accept/connect in the current accept/connect callback. A call to [globusftp\\_control\\_data\\_connectlocalpasv\(\)](#) or [globusftp\\_control\\_data\\_connectlocalport\(\)](#) needs to precede this calling this function. This function may be followed by a `globusftp_control_data_read`.

Parameters:

- handle A pointer to a FTP control handle which is configured to create an incoming data connection.
- callback This callback is called when the connection occurs. This parameter may be NULL.
- user\_arg The user argument passed to the connect callback.

## 6.4.3.2 globusresult\_t globusftp\_control\_data\_setinterface (globusftp\_control\_handle\_t handle, const char interface\_addr)

Create an outgoing FTP data connection.

This function sets the interface that will be used to send and receive information along the data channel.

Parameters:

- handle A pointer to a FTP control handle which is configured to create an outgoing data connection.
- interface\_addr

## 6.4.3.3 globusresult\_t globusftp\_control\_data\_connectwrite (globusftp\_control\_handle\_t handle, globusftp\_control\_data\_connectcallback\_t callback, void user\_arg)

Create an outgoing FTP data connection.

This function will register a `globusftp_control_data_write` callback. Further accepts/connects are done by registering a new accept/connect in the current accept/connect callback. A call to `globusftp_control_data_write` needs to precede this calling this function. This function may be followed by a `globusftp_control_data_write`.

Parameters:

- `handle` A pointer to a FTP control handle which is configured to create an outgoing data connection.
- `callback` This callback is called when the connection occurs. This parameter may be NULL.
- `user_arg` The user argument passed to the connect callback.

6.4.3.4 `globusresult_t globusftp_control_data_add_channels (globusftp_control_handle_t handle, unsigned int num_channels, unsigned int stripe_ndx)`

Opens additional data channels (connections) to the host identified by the stripe parameter.

Parameters:

- `handle` A pointer to a FTP control handle. This handle is used to determine the host corresponding to the stripe number and to store information about any channels added by this function.
- `num_channels` The number of additional channels to add.
- `stripe_ndx` A integer identifying the stripe to add channels too. In the case of non-striped transfer this parameter will be ignored.

6.4.3.5 `globusresult_t globusftp_control_data_send_eof (globusftp_control_handle_t handle, int count[], int array_size, globus_bool_t eof_message, globusftp_control_callback_t cb, void user_arg)`

Sends an eof message to each stripe along an open data connection.

Parameters:

- `handle` A pointer to a FTP control handle. This handle contains the the state for a connection.
- `count []` This array of integers should contain an integer that will be added to the current parallel data connection count on each stripe. The order of the integers corresponds to each stripe in the same order as what was returned from `localport()`.

An eof message must be sent to all receiving hosts in a transfer. The message contains the total number of data connections used by each stripe. Many stripes may be sending to a single receiver but only one eof message may be sent. The count parameter allows the user to pass in the total number of data connections used by all other hosts. The local values are added to the passed in values and then sent to the receiver.

Parameters:

- `array_size` The number of elements in `count[]`.
- `eof_message`
- `cb` The function to be called when the eof message has been called.
- `user_arg` A user pointer that is threaded through to the user callback.

6.4.3.6 `globusresult_t globus_ftp_control_data_remove_channels (globusftp_control_handle_t handle, unsigned int num_channels, unsigned int stripe_ndx)`

Removes data channels (connections) to the host identified by the stripe parameter.

Parameters:

`handle` A pointer to a FTP control handle. This handle is used to determine the host corresponding to the stripe number and to update information about any channels removed by this function.

`num_channels` The number of channels to remove.

`stripe_ndx` A integer identifying the stripe to remove channels from. In the case of non-striped transfer this parameter will be ignored.

6.4.3.7 `globusresult_t globus_ftp_control_data_query_channels (globusftp_control_handle_t handle, unsigned int num_channels, unsigned int stripe_ndx)`

Returns the number of currently open channels for the host identified by the stripe parameter.

This number may be less than the level of parallelism specified in `parallelism`, due to the possibility that some channels have not yet connected.

Parameters:

`handle` A pointer to a FTP control handle. This handle is used to determine the host corresponding to "stripe" and number of channels corresponding to that host.

`num_channels`

`stripe_ndx` A integer identifying the stripe for which to return the number of channels. In the case of non-striped transfer this parameter should be zero.

6.4.3.8 `globusresult_t globus_ftp_control_data_get_total_data_channels (globusftp_control_handle_t handle, unsigned int num_channels, unsigned int stripe_ndx)`

Returns the total number of data channels used so far in the current transfer on the given stripe.

Parameters:

`handle` A pointer to a FTP control handle. This handle is used to determine the host corresponding to "stripe" and number of channels corresponding to that host.

`num_channels`

`stripe_ndx` A integer identifying the stripe for which to return the number of channels. In the case of non-striped transfer this parameter should be zero.

6.4.3.9 `globusresult_t globus_ftp_control_local_send_eof (globusftp_control_handle_t handle, globus_bool_t send_eof)`

Determines if the library will automatically send an EOF message in extended block mode, or if the user will have to explicitly do it by calling `globus_ftp_control_data_send_eof()`.

Parameters:

`handle` The ftp handle you wish to set the `send_eof` attribute on.

`send_eof` A boolean representing whether or not to automatically send an EOF message.

6.4.3.10 `globus_result_t globus_ftp_control_local_parallelism (globus_ftp_control_handle_t handle, globus_ftp_control_parallelism_t parallelism)`

Set the parallelism information in a FTP control handle.

Parameters:

handle A pointer to the FTP control handle for which the parallelism information is to be updated  
parallelism A structure containing parallelism information

6.4.3.11 `globus_result_t globus_ftp_control_local_pasv (globusftp_control_handle_t handle, globus_ftp_control_host_port_t address)`

Create a local listening socket, bind it and return the address the socket is listening to.

If there is a existing data connection it is closed.

Parameters:

handle A pointer to a FTP control handle. Information about the listening socket is stored in the handle.  
address The host IP address and port is returned through this parameter.

6.4.3.12 `globus_result_t globus_ftp_control_local_spas (globusftp_control_handle_t handle, globus_ftp_control_host_port_t addresses, unsigned int num_addresses)`

Create num\_addresses local listening sockets, bind them and return the addresses the sockets are listening to.

If there is a existing data connection it is closed.

Parameters:

handle A pointer to a FTP control handle. Information about the listening sockets is stored in the handle.  
addresses The host IP addresses and ports are returned through this parameter.  
num\_addresses The number of listening sockets to create

6.4.3.13 `globus_result_t globus_ftp_control_local_port (globus_ftp_control_handle_t handle, globus_ftp_control_host_port_t address)`

Insert the host/port information returned by a PASV on the remote host into the local FTP control handle.

(close any outstanding data con)

Parameters:

handle A pointer to the FTP control handle into which to insert the host/port information  
address The host IP address and port

6.4.3.14 `globus_result_t globus_ftp_control_local_spor (globus_ftp_control_handle_t handle, globus_ftp_control_host_port_t addresses, unsigned int num_addresses)`

Insert the host/port addresses returned by a SPAS on the remote host into the local FTP control handle.

If there are any outstanding data connections at this point, they are closed.

Parameters:

handle A pointer to the FTP control handle into which to insert the host/port addresses  
addresses The host IP addresses and port numbers  
num\_addresses The number of addresses

6.4.3.15 globusresult\_t globusftp\_control\_local\_type (globusftp\_control\_handle\_t handle, globusftp\_control\_type\_t type, int form\_code)

Update the FTP control handle with the given type information.

Parameters:

handle A pointer to the FTP control handle to be updated

type The type of the data connection. Possible values are: ASCII, EBCDIC, IMAGE and LOCAL. Currently only ASCII and IMAGE types are supported.

form\_code The logical byte size parameter for the LOCAL type.

6.4.3.16 globusresult\_t globusftp\_control\_local\_mode (globusftp\_control\_handle\_t handle, globusftp\_control\_mode\_t mode)

Update the FTP control handle with the given mode information.

Parameters:

handle A pointer to the FTP control handle to be updated

mode Specifies the mode of the data connection. Possible modes are STREAM, BLOCK, EXTENDED BLOCK and COMPRESSED. Out of these only STREAM and EXTENDED BLOCK are supported in this implementation. Also, EXTENDED BLOCK is only supported in combination with the IMAGE type.

6.4.3.17 globusresult\_t globusftp\_control\_local\_tcp\_buffer (globusftp\_control\_handle\_t handle, globusftp\_control\_tcpbuffer\_t tcp\_buffer)

Update the FTP control handle with the given socket buffer information.

Parameters:

handle A pointer to the FTP control handle to be updated

tcp\_buffer A pointer to the socket buffer.

6.4.3.18 globusresult\_t globusftp\_control\_local\_dcau (globusftp\_control\_handle\_t handle, const globusftp\_control\_dcau\_t dcau, gsscred\_id\_t delegated\_credential\_handle)

Update the FTP control handle with the given data channel authentication information.

If authentication is set to GLOBUSFTP\_CONTROL\_DCAU\_NONE, then protection will also be disabled for this control handle.

Parameters:

handle A pointer to the FTP control handle to be updated

dcau A parameter specifying the data channel authentication mode. Possible values are No Authentication, Self Authentication and Subject-name authentication.

delegated\_credential\_handle

6.4.3.19 `globusresult_t globus.ftp_control_local_pbsz (globusftp_control_handle_t handle, unsigned long bufsize)`

Update the FTP control handle with the given protection buffer size information.

This function sets protection buffer size to be used by this handle. This value is used to determine how much data will be sent in each packet during a protected data transfer.

Parameters:

handle A pointer to the FTP control handle to be updated

bufsize A parameter specifying the protection buffer size value.

6.4.3.20 `globusresult_t globus.ftp_control_get_pbsz (globusftp_control_handle_t handle, unsigned long bufsize)`

Query the FTP control handle for the protection buffer size information.

This function queries the handle to determine the protection buffer size which is used by this handle. This value is used to determine how much data will be sent in each packet during a protected data transfer.

Parameters:

handle A pointer to the FTP control handle to be updated

bufsize A pointer to a parameter to store the value of the protection buffer size.

6.4.3.21 `globusresult_t globus.ftp_control_local_stru (globusftp_control_handle_t handle, globus.ftp\_control\_structure\_t structure)`

Updates the handle with information on the structure of the data being sent on the data channel.

This function updates the handle with the provided structure information. At this point the only structure type that is supported is the `le` type.

Parameters:

handle A pointer to a FTP control handle. The handle contains information about the current state of the control and data connections.

structure This parameter is used to pass the structure information. Possible values are `le`, `record` and `page`. Only the `le` type is supported

6.4.3.22 `globusresult_t globus.ftp_control_data_write (globusftp_control_handle_t handle, globus_byte_t buffer, globus_size_t length, globus_off_t offset, globus_bool_t eof, globus.ftp\_control\_data\_callback\_t callback, void callback_arg)`

Writes data from the supplied buffer to data connection(s).

This function writes contained in the buffer to the data channel(s).

Parameters:

handle A pointer to a FTP control handle. The handle contains information about the current state of the control and data connections.

buffer A user supplied buffer from which data will be written to the data connection(s)

length The length of the data contained in the buffer.

offset The offset in the `le` at which the data in the buffer starts

eof Indicates that the buffer is that last part of a file. In the striped case this will cause a EOF block to be sent to every data node involved in the transfer.

callback The function to be called once the data has been sent

callback.arg User supplied argument to the callback function

6.4.3.23 globusresult\_t globusftp\_control\_data\_read (globusftp\_control\_handle\_t handle, globus\_byte\_t buffer, globus\_size\_t max\_length, [globusftp\\_control\\_data\\_callback\\_t](#) callback, void callback.arg)

Reads data from data connection(s) and put them in the supplied buffer.

This function takes the given buffer and will try to read data from the data connection(s).

Parameters:

handle A pointer to a FTP control handle. The handle contains information about the current state of the control and data connections.

buffer A user supplied buffer into which data from the data connection(s) will be written

max\_length The maximum length of the data that can be written to the buffer

callback The function to be called once the data has been read

callback.arg User supplied argument to the callback function

6.4.3.24 globusresult\_t globusftp\_control\_local\_layout (globusftp\_control\_handle\_t handle, [globusftp\\_control\\_layout\\_t](#) layout, globus\_size\_t data\_size)

Update the handle with the layout and the size of the data sent over the data channel.

This function is deprecated. The interface will be changed to [globusXftp\\_control\\_local\\_layout\(\)](#)

Parameters:

handle A pointer to the FTP control handle into which to insert the layout information.

layout A variable containing the layout information

data\_size The size of the data that is going to be sent. This may be needed to interpret the layout information.

6.4.3.25 globusresult\_t globusftp\_control\_create\_data\_info (globusftp\_control\_handle\_t handle, globusftp\_control\_data\_write\_info\_t data\_info, globus\_byte\_t buffer, globus\_size\_t length, globus\_off\_t offset, globus\_bool\_t eof, [globusftp\\_control\\_data\\_callback\\_t](#) callback, void callback.arg)

Create a [globusftp\\_control\\_data\\_write\\_info\\_t](#) structure.

This function populates a [globusftp\\_control\\_data\\_callback\\_t](#) structure with valid information. This structure provides the user a way to register several data writes with a single callback. This is quite useful to the writer of enqueue functions. It allows a single call to [globusftp\\_control\\_data\\_write\(\)](#) to be broken up into many writes, potentially on different stripes, and for a single callback to be called when all are finished.

Parameters:

handle A pointer to a FTP control handle. The handle contains information about the current state of the control and data connections.

data\_info The [globusftp\\_control\\_data\\_write\\_info\\_t](#) structure to be released.

buffer The pointer to the user buffer that will be passed to the callback argument when there are zero references to data\_info. This is intended to be the start of all the data the user intends to write [using globusftp\\_control\\_data\\_write\\_stripe\(\)](#) but it does not have to be.

length The length of the memory segment pointed to by the argument buffer.

offset The file offset of the data segment specified.

eof This should be set to true if the user plans on registering eof on the data structure.

callback The user function to be called when all references to data are released. This occurs after all data registered for write from globusftp\_control\_datawrite\_stripe have occurred and the user calls globusftp\_control\_releasedatainfo(). The callback is passed all of the arguments passed to this function with the exception of datainfo.

callback.arg User supplied argument to the callback function

6.4.3.26 globusresult\_t globusftp\_control\_releasedatainfo (globusftp\_control\_handle\_t handle, globusftp\_control\_datawrite\_info\_t datainfo)

Release a datainfo structure.

This function releases all memory and references created when a globusftp\_control\_createdatainfo() was made. For every call to globusftp\_control\_createdatainfo() a call to this function must be made.

Parameters:

handle A pointer to a FTP control handle. The handle contains information about the current state of the control and data connections.

datainfo The globusftp\_control\_datawrite\_info\_t structure to be released.

6.4.3.27 globusresult\_t globusftp\_control\_data\_write\_stripe (globusftp\_control\_handle\_t handle, globus\_byte\_t buffer, globus\_size\_t length, globus\_off\_t offset, globus\_bool\_t eof, int stripe.ndx, globusftp\_control\_data\_callback\_t callback, void callback.arg)

Write FTP data to a particular stripe.

This function allows the user to write to a specified stripe. The stripe index relates to the order passed into localspor(). This function differs from globusftp\_control\_datawrite() in that no enqueue function is needed since the user specifies the stripe on which data is written. In order to use this function the user must have a valid pointer to a globusftp\_control\_datawrite\_info\_t structure. The datainfo structure can be obtained by a call to globusftp\_control\_createdatainfo(). Many calls to this function can be made, but only a single user callback occurs per creation of a globusftp\_control\_datawrite\_info\_t structure.

Parameters:

handle A pointer to a FTP control handle. The handle contains information about the current state of the control and data connections.

buffer a pointer to the data the user wishes to send along the FTP data channels.

length the length of the data pointer to by the parameter buffer.

offset the offset into the file of the data.

eof A boolean stating that this will be the last chunk of data registered on the given stripe. In order to properly send an eof message the user must register an eof on every stripe.

stripe.ndx The index of the stripe on which the data will be sent. The index of each stripe is determined by the call to localspas or localspor.

callback The function to be called once the data has been sent

callback.arg User supplied argument to the callback function



6.4.3.28 `globusresult_t globus_X_ftp_control_data_write_stripe (globusftp_control_handle_t handle, globus_byte_t buffer, globus_size_t length, globus_off_t offset, globus_bool_t eof, int stripe_ndx, globusftp_control_data_write_info_t data_info)`

Write data on a specific stripe from an enqueue callback function only.

This function allows the user to register the write of ftp data on a specific stripe. This function can only be called from an enqueue function callback. This function should be used only by the implementor of an enqueue function. It should be viewed as unstable and used only by advanced users. This is the only function in the library that the enqueue function implementor is allowed from the enqueue callback.

Parameters:

`handle` A pointer to a FTP control handle. The handle contains information about the current state of the control and data connections.

`buffer` a pointer to the data the user wishes to send along the FTP data channels.

`length` the length of the data pointer to by the parameter `buffer`.

`offset` the offset into the file of the data.

`eof` a boolean stating that this is the last buffer to be registered. When using the version of this function the user does not need to register an eof on each stripe, the control library will take care of that internally.

`stripe_ndx` The index of the stripe on which the data will be sent. The index of each stripe is determined by the call to `localspas` or `localspor`.

`data_info` An opaque structure that is passed into the enqueue function and contains reference count and state information. The same `data_info` pointer that is passed into the enqueue function must be used for this parameter.

6.4.3.29 `globusresult_t globusftp_control_data_force_close (globusftp_control_handle_t control_handle, globusftp_control_callback_t closecallbackfunc, void closearg)`

Forces an immediate close of all data connections.

Parameters:

`control_handle` The `globusftp_controlhandle` that is have its data connections closed.

`closecallbackfunc` A user function that will be called when the data connections are closed.

`closearg` The user argument that will be threaded through to `closecallbackfunc`.

## 6.5 globusftp\_control\_layout.c File Reference

### 6.5.1 Detailed Description

## 6.6 globusftp\_control\_server.c File Reference

FTP Server-side Control Connection Management.

Functions

`globusresult_t globusftp_control_serverhandleinit (globusftp_control_server_t handle)`

`globusresult_t globusftp_control_serverhandledestroy (globusftp_control_server_t handle)`

`globusresult_t globusftp_control_serverlisten (globusftp_control_server_t serverhandle, unsigned short port, globusftp_control_servercallback_t callback, void callbackarg)`

```

globusresultt globusftp_control_commandinit (globusftp_control_commandt command, char raw_
command, globusftp_control_auth_info_t auth_info)
globusresultt globusftp_control_commanddestroy(globusftp_control_commandt command)
globusresultt globusftp_control_commandcopy (globusftp_control_commandt dest, globusftp_control_
commandt src)
globusresultt globusftp_control_serverstop(globusftp_control_server_t listener, globusftp_control_server_
callbackt callback, void callbackarg)
globusresultt globusftp_control_serveraccept (globusftp_control_server_t listener, globusftp_control_
handlet handle, globusftp_control_callbackt callback, void callbackarg)
globusresultt globusftp_control_serverauthenticate (globusftp_control_handlet handle, globusftp_
control_auth_requirements_t auth_requirements, globusftp_control_auth_callbackt callback, void callback_
arg)
globusresultt globusftp_control_read_commands(globusftp_control_handlet handle, globusftp_control_
command_callbackt callback, void callbackarg)
globusresultt globusftp_control_send_response(globusftp_control_handlet handle, const char respspec,
globusftp_control_callbackt callback, void callbackarg,...)

```

### 6.6.1 Detailed Description

FTP Server-side Control Connection Management.

### 6.6.2 Function Documentation

#### 6.6.2.1 globusresult\_t globusftp\_control\_server\_handle\_init (globusftp\_control\_server\_t handle)

Initialize a globus ftp server handle.

This function will set up (i.e. initialize all mutexes and variables) a globus ftp server handle. It will also enter the handle in a list used by the module activation/deactivation functions.

Parameters:

handle The handle to initialize.

Returns:

GLOBUS\_SUCCESS  
invalid handle

#### 6.6.2.2 globusresult\_t globusftp\_control\_server\_handle\_destroy (globusftp\_control\_server\_t handle)

Destroy a globus ftp server handle.

This function will free up all dynamically allocated memory associated with a given globus ftp server handle. It will also remove the handle from a list used by the module activation/deactivation functions. This function should only be called after a call to globusftp\_control\_serverstop.

Parameters:

handle The handle to destroy.

Returns:

success  
invalid handle  
handle is still in listening state

6.6.2.3 globusresult\_t globusftp\_control\_server\_listen (globusftp\_control\_server\_t serverhandle, unsigned short port, [globusftp\\_control\\_server\\_callback\\_t](#) callback, void callback.arg)

Start listening on a given port for FTP client connections.

This function starts the listening on port for connections from ftp clients. When a connection request is made callback is called and passed callback.arg. Upon return from this function the serverhandle structure is initialized.

Parameters:

serverhandle A pointer to a initialized server handle.

port A pointer to the port to listen on. If the initial value is zero it will be set to the default value.

callback The callback function called when connection requests are made.

callback.arg The user argument passed to the callback function when connection requests are made.

Note:

I'm not providing any mechanism for making sure that this function is only called once. Is this needed?

6.6.2.4 globusresult\_t globusftp\_control\_command\_init (globusftp\_control\_command\_t command, char raw\_command, [globusftp\\_control\\_auth\\_info\\_t](#) auth\_info)

Initialize a command structure.

This function initializes a command structure based on a null terminated string representing one line of input from the client. The command structure is used as a convience to determine what command the client issued. This function parses a command string sent by a client and populates the command argument appropriately. In the GSSAPI case it will also decode and unwrap the command before parsing it.

Parameters:

command A pointer to the command structure to be initialized

raw\_command A null terminated line of client input. Should contain one command.

auth\_info Authentication information needed for unwrapping a command

6.6.2.5 globusresult\_t globusftp\_control\_command\_destroy (globusftp\_control\_command\_t command)

Destroy a command structure.

This function frees up the memory allocated to the command argument.

Parameters:

command The command structure whose associated memory is to be freed

6.6.2.6 globusresult\_t globusftp\_control\_command\_copy (globusftp\_control\_command\_t dest, globusftp\_control\_command\_t src)

Creates a copy of a command structure.

This function should be called when the user needs to make a copy of a command structure.

Parameters:

dest The area of memory that the command structure is copied to.

src The command structure to be copied.

6.6.2.7 globusresult\_t globusftp\_control\_server\_stop (globusftp\_control\_server\_t listener, [globusftp\\_control\\_server\\_callback\\_t](#) callback, void callback\_arg)

Stop the GSIFTP server from listening for client connections.

This function stops listening on the given listener object for client connections. All existing client connections are left open.

Parameters:

- listener the globusftp\_control\_server\_t object that should no longer listen for connections.
- callback The user callback that will be called when the server structure is no longer listening.
- callback\_arg The user argument that is passed into callback.

6.6.2.8 globusresult\_t globusftp\_control\_server\_accept (globusftp\_control\_server\_t listener, globusftp\_control\_handle\_t handle, [globusftp\\_control\\_callback\\_t](#) callback, void callback\_arg)

Accept a client connection request.

This function is called to accept a connection request from a client.

When the listen callback is called (see [globusftp\\_control\\_server\\_listen](#)) a client has requested a connection. This function must be called to accept that user connection request. Once the connection is established or if a error occurs, the callback function is called.

Parameters:

- listener The server object that received the connection request.
- handle The control connection object. This structure will be populated and passed to the callback when the client is authorized. This structure represents the control connection between the server and client. It will be used to read commands from the client and send responses to the client.]
- callback The function called when the client connection has been accepted.
- callback\_arg The user argument passed to the callback.

Note:

This functions assumes the the server and control handles have been initialized prior to calling this function.

6.6.2.9 globusresult\_t globusftp\_control\_server\_authenticate (globusftp\_control\_handle\_t handle, [globusftp\\_control\\_auth\\_requirements\\_t](#) auth\_requirements, [globusftp\\_control\\_auth\\_callback\\_t](#) callback, void callback\_arg)

Authenticate a client connection.

This function is called to authenticate a connection from a client.

After a client connection has been accepted (using the [globusftp\\_control\\_server\\_accept](#) call), this function should be called to authenticate the client. The caller of this function may specify certain authentication requirements using the auth\_requirements parameter.

Parameters:

- handle The control connection object. This structure will be populated and passed to the callback when the client is authorized. This structure represents the control connection between the server and client. It will be used to read commands from the client and send responses to the client.]
- auth\_requirements This structure represents the authentication requirements that the user has for a given connection. For example GSIFTP user name, password, and account.

callback The function called when the client authentication has been accepted or rejected.

callback.arg The user argument passed to the callback.

**Note:**

It is up to the user of this function to send the reply to the last command of the authentication sequence.

This functions assumes the the server and control handles have been initialized prior to calling this function.

6.6.2.10 globusresult\_t globusftp\_control\_read\_commands (globusftp\_control\_handle\_t handle, [globusftp\\_control\\_command\\_callback\\_t](#) callback, void callback.arg)

Begin reading GSIFTP commands on a given control connection.

This function begins reading control commands on a [globusftp\\_control\\_handle\\_t](#). When a command is read the callback function is called.

**Parameters:**

handle The control connection handle that commands will be read from. Prior to calling this the function [globusftp\\_control\\_handle\\_t](#) must be populated via a call to [globusftp\\_control\\_accept\(\)](#).

callback The user callback that will be called when commands are read.

callback.arg The user argument passed to the callback.

6.6.2.11 globusresult\_t globusftp\_control\_send\_response (globusftp\_control\_handle\_t handle, const char respspec, [globusftp\\_control\\_callback\\_t](#) callback, void callback.arg, ...)

Send a response to the GSIFTP client.

This function sends a GSIFTP formatted response to the client. When a command callback is received the user calls this function to respond to the clients request.

**Parameters:**

handle The control connection to send the response across.

respspec A formatted string representing the users response.

callback The user callback that will be called when the response has been sent.

callback.arg The user argument passed to the callback.

### 6.6.3 Variable Documentation

6.6.3.1 const char globus\_i\_ftp\_server\_220\_reply

Initial value:

"220 Service ready for new user.\r\n"

6.6.3.2 const char globus\_i\_ftp\_server\_235\_reply

Initial value:

"235 GSSAPI Authentication succeeded\r\n"

## 6.6.3.3 const char globus.i\_ftp\_server\_331\_reply

Initial value:

`"331 User name okay, need password.\r\n"`

## 6.6.3.4 const char globus.i\_ftp\_server\_332\_reply

Initial value:

`"332 Need account for login.\r\n"`

## 6.6.3.5 const char globus.i\_ftp\_server\_334\_reply

Initial value:

`"334 Using authentication type GSSAPI; ADAT must follow.\r\n"`

## 7 globus ftp control Page Documentation

### 7.1 GridFTP: Protocol Extensions to FTP for the Grid

#### 7.1.1 Introduction

This section defines extensions to the FTP specification STD 9, RFC [959: TRANSFER PROTOCOL \(FTP\)](#) (October 1985). These extensions provide striped data transfer, parallel data transfer, extended data transfer, data buffer size configuration, and data channel authentication.

The following new commands are introduced in this specification:

- [Striped Passive \(SPAS\)](#)
- [Striped Data Port \(SPOR\)](#)
- [Extended Retrieve \(ERET\)](#)
- [Extended Store \(ESTO\)](#)
- [Set Data Buffer Size \(SBUF\)](#)
- [Data Channel Authentication Mode \(DCAU\)](#)

A new transfer mode [extended-block mode](#) is introduced for parallel and striped data transfers. Also, a set of extensions [options to RETR](#) are added to control striped data layout and parallelism.

The following new feature names are to be included in the FTP server's response to FEAT if it implements the following sets of functionality:

#### PARALLEL

The server supports the SPOR, SPAS, the RETR options mentioned above, and extended block mode.

#### ESTO

The server implements the ESTO command as described in this document.

#### ERET

The server implements the ERET command as described in this document.

**SBUF**

The server implements the SBUF command as described in this document.

**DCAU**

The server implements the DCAU command as described in this document, including the requirement that data channels are authenticated by default. [RFC 2228](#) authentication is used to establish the control channel.

**7.1.2 Terminology****Parallel transfer**

From a single data server, splitting the data for transfer over multiple data connections.

**Striped transfer**

Distributing a file's data over multiple independent data nodes, and transferring over multiple data connections.

**Data Node**

In a striped data transfer, a data node is one of the stripe destinations returned in the SPAS command, or one of the stripe destinations sent in the SPOR command.

**DTP**

The data transfer process establishes and manages the data connection. The DTP can be passive or active.

**PI**

The protocol interpreter. The user and server sides of the protocol have distinct roles implemented in a user-PI and a server-PI.

**7.1.3 FTP Standards Used**

RFC 959, [FILE TRANSFER PROTOCOL \(FTP\)](#), J. Postel, R. Reynolds (October 1985)

– Commands used by GridFTP

USER  
PASS  
ACCT  
CWD  
CDUP  
QUIT  
REIN  
PORT  
PASV  
TYPE  
MODE  
RETR  
STOR  
STOU  
APPE  
ALLO  
REST  
RNFR  
RNT0  
ABOR  
DELE  
RMD  
MKD  
PWD  
LIST  
NLST  
SITE  
SYST

STAT  
HELP  
NOOP

- Features used by GridFTP

ASCII and Image types  
Stream mode  
File structure

RFC 2228, [FTP Security Extensions](#), Horowitz, M. and S. Lunt (October 1997)

- Commands used by GridFTP

AUTH  
ADAT  
MIC  
CONF  
ENC

- Features used by GridFTP

GSSAPI authentication

RFC 2389, [Feature negotiation mechanism for the File Transfer Protocol](#), Elz, P. and R. Hethmon, R. Elz (August 1998)

- Commands used by GridFTP

FEAT  
OPTS

- Features used by GridFTP

[FTP Extensions](#), R. Elz, P. Hethmon (September 2000)

- Commands used by GridFTP

SIZE

- Features used by GridFTP

Restart of a stream mode transfer

#### 7.1.4 Striped Passive (SPAS)

This extension is used to establish a vector of data socket listeners for for a server with one or more stripes. This command **MUST** be used in conjunction with the extended block mode. The response to this command includes a list of host and port addresses the server is listening on.

Due to the nature of the extended block mode protocol, SPAS must be used in conjunction with data transfer commands which receive data (such as STOR, ESTO, or APPE) and can not be used with commands which send data on the data channels.

##### Syntax

The syntax of the SPAS command is:

```
spas = "SPAS" <CRLF>
```

##### Responses

The server-PI will respond to the SPAS command with a 229 reply giving the list of host-port strings for the remote server-DTP or user-DTP to connect to.

```
spas-response = "229-Entering Striped Passive Mode" CRLF
                1*(<SP> host-port CRLF)
                229 End
```



Where the command is correctly parsed, but the server-DTP cannot process the SPAS request, it must return the same error responses as the PASV command.

#### OPTS for SPAS

There are no options in this SPAS specification, and hence there is no OPTS command defined.

#### 7.1.5 Striped Data Port (SPOR)

This extension is to be used as a complement to the SPAS command to implement striped third-party transfers. This command MUST always be used in conjunction with the extended block mode. The argument to SPOR is a vector of host/TCP listener port pairs to which the server is to connect. This

Due to the nature of the extended block mode protocol, SPOR must be used in conjunction with data transfer commands which send data (such as RETR, ERET, LIST, or NLST) and can not be used with commands which receive data on the data channels.

#### Syntax

The syntax of the SPOR command is:

```
SPOR 1*(<SP> <host-port>) <CRLF>
```

The host-port sequence in the command structure MUST match the host-port replies to a SPAS command.

#### Responses

The server-PI will respond to the SPOR command with the same response set as the PORT command described in the [ftp specification](#)

#### OPTS for SPOR

There are no options in this SPOR specification, and hence there is no OPTS command defined.

#### 7.1.6 Extended Retrieve (ERET)

The extended retrieve extension is used to request that a retrieve be done with some additional processing on the server. This command is an extensible way of providing server-side data reduction or other modifications to the RETR command. This command is used in place of OPTS to the RETR command to allow server side processing to be done with a single round trip (one command sent to the server instead of two) for latency-critical applications.

ERET may be used with either the data transports defined in RFC 959, or using extended block mode as defined in this document. Using an ERET creates a new virtual file which will be sent, with its own size and byte range starting at zero. Restart markers generated while processing an ERET are relative to the beginning of this view of the file.

#### Syntax

The syntax of the ERET command is

```
ERET <SP> <retrieve-mode> <SP> <filename>
```

```
retrieve-mode ::= P <SP> <offset> <SP> <size>
```

```
offset ::= 64 bit integer
```

```
size ::= 64 bit integer
```

The retrieve-mode defines behavior of the extended-retrieve mode. There is one mode defined by this specification, but other general purpose or application-specific ones may be added later.

## modes ERET Extended Retrieve Modes

### Partial Retrieve Mode (P)

A section of the file will be retrieved from the data server. The section is defined by the starting offset and extent size parameters. When used with extended block mode, the extended block headers sent along with data will send the data with offset of 0 meaning the beginning of the section of the file which was requested.

### 7.1.7 Extended Store (ESTO)

The extended store extension is used to request that a store be done with some additional processing on the server. Arbitrary data processing algorithms may be added by defining additional ESTO store-modes. Similar to the ERET, the ESTO command expects data sent to satisfy the request to be sent as if it were a new file with data block offset 0 being beginning the beginning of the new file.

The format of the ESTO command is

```
ESTO <SP> <store-mode> <filename>
```

```
store-mode ::= A <SP> <offset>
```

The store-mode defines the behavior of the extended store. There is one mode defined by this specification, but others may be added later.

### Extended Store Modes

#### Adjusted store (A)

The data in the file is to be stored with offset added to the file pointer before storing the blocks of the file. In extended block mode, this value is added to the offset in the extended block header by the server when writing to disk. Extended block headers should therefore send the beginning of the byte range on the data channel with offset of zero. In stream mode, the offset is added to the implicit offset of 0 for the beginning of the data before writing. If a stream mode restart marker is used in conjunction with this ESTO mode, the restart marker's offset is added to the offset passed as the parameter to the adjusted store.

### 7.1.8 Set Buffer Size (SBUF)

This extension adds the capability of a client to set the TCP buffer size for subsequent data connections to a value. This replaces the server-specific commands SITE RBUFSIZE, SITE RETRBUFSIZE, SITE RBUFSZ, SITE SBUFSIZE, SITE SBUFSZ, and SITE BUFSIZE. Clients may wish to consider supporting these other commands to ensure wider compatibility.

#### Syntax

The syntax of the SBUF command is

```
sbuf = SBUF <SP> <buffer-size>
```

```
buffer-size ::= <number>
```

The buffer-size value is the TCP buffer size in bytes. The TCP window size should be set accordingly by the server.

#### Response Codes

If the server-PI is able to set the buffer size state to the requested buffer-size, then it will return a 200 reply.

**Note:**

Even if the SBUF is accepted by the server, an error may occur later when the data connections are actually created, depending on how the server or client operating systems' TCP implementations.

**7.1.9 Data Channel Authentication (DCAU)**

This extension provides a method for specifying the type of authentication to be performed on FTP data channels. This extension may only be used when the control connection was authenticated using RFC 2228 Security extensions.

The format of the DCAU command is

```
DCAU <SP> <authentication-mode> <CRLF>
```

```
authentication-mode ::= <no-authentication>
                        | <authenticate-with-self>
                        | <authenticate-with-subject>
```

```
no-authentication ::= N
```

```
authenticate-with-self ::= A
```

```
authenticate-with-subject ::= S <subject-name>
```

```
subject-name ::= string
```

**Authentication Modes**

No authentication(N)

No authentication handshake will be done upon data connection establishment.

Self authentication(A)

A security-protocol specific authentication will be used on the data channel. The identity of the remote data connection will be the same as the identity of the user which authenticated to the control connection.

Subject-name authentication(S)

A security-protocol specific authentication will be used on the data channel. The identity of the remote data connection MUST match the supplied subject-name string.

The default data channel authentication mode for FTP sessions which are RFC 2228 authenticated—the client must explicitly send a DCAU N message to disable it if it does not implement data channel authentication.

If the security handshake fails, the server should return the error response 432 (Data channel authentication failed).

**7.1.10 Extended Block Mode**

The striped and parallel data transfer methods described above require an extended transfer mode to support out-of-sequence data delivery, and partial data transmission per data connection. The extended block mode described here extends the block mode header to provide support for these as well as large blocks, and end-of-data synchronization.

Clients indicate that they want to use extended block mode by sending the command


```
MODE <SP> E <CRLF>
```

on the control channel before a transfer command is sent.

The structure of the extended block header is

Extended Block Header

```
+-----+-----+-----+-----+-----+-----+
```



The descriptor codes are indicated by bits in the descriptor byte. Six codes have been assigned, where each code number is the decimal value of the corresponding bit in the byte.

Code	Meaning
128	End of data block is EOR (Legacy)
64	End of data block is EOF
32	Suspected errors in data block
16	Data block is a restart marker
8	End of data block is EOD for a parallel/stripped transfer
4	Sender will close the data connection

With this encoding, more than one descriptor coded condition may exist for a particular block. As many bits as necessary may be added.


Some additional protocol is added to the extended block mode data channels, to properly handle end-of-file detection in the presence of an unknown number of data streams.

When no more data is to be sent on the data channel, then the sender will mark the last block, or send a zero-length block after the last block with the EOD bit (8) set in the extended block header.

After receiving an EOD the data connection can be cached for use in a subsequent transfer. To signify that the data connection will be closed the sender sets the close bit (4) in the header on the last message sent.

The sender communicates end of file by sending an EOF message to all servers receiving data. The EOF message format follows.

#### Extended Block EOF Header



**EOF Descriptor.** The EOF header descriptor has the same definition as the regular data message header described above.

**EOD Count Expected.** This 64 bit field represents the total number of data connections that will be established with the server receiving the file. This number is used by the receiver to determine it has received all of the data. When the number of EOD messages received equals the number represented by the "EOD Count Expected" field the receiver has hit end of file.

Simply waiting for EOD on all open data connections is not sufficient. It is possible that the receiver reads an EOD message on all of its open data connects while an additional data connection is in flight. If the receiver were to assume it reached end of file it would fail to receive the data on the in flight connection.

To handle EOF in the multi-stripped server case a 126 response has been introduced. When receiving data from a striped server a client makes a control connection to a single host, but several host may create several data connections back to the client. Each host can independently decide how many data connections it will use, but only a single EOF message may be sent to back to the client, therefore it must be possible to aggregate the total number of data connections used in the transfer across the stripes. The 126 response serves this purpose.

The 126 is an intermediate response to RETR command. It has the following format.

"126" < SP> 1 (count of data connections)

Several "Count of data connections" can be in a single reply. They correspond to the stripes returned in the response to the SPAS command.

Discussion of protocol change to enable bidirectional data channels brought up the following problem if doing bidirectional data channels

If the client is pasv, and sending to a multi-stripe server, then the server creates data connections connections; since the client didn't do SPAS, it cannot associate HOST/PORT pairs on the data connections with stripes on the server (it doesn't even know how many there are). it cannot reliably determine which nodes to send data to. (Becomes even more complex in the third-party transfer case, because the sender may have multiple stripes of data.) The basic problem is that we need to know logical stripe numbers to know where to send the data.

#### EOF Handling in Extended Block Mode

If you are in either striped or parallel mode, you will get exactly one EOF on each SPAS-speci ed ports (stripes).

Hosts in extended block mode must be prepared to accept an arbitrary number of connections on each SPOR port before the EOF block is sent.

#### Restarting

In general, opaque restart markers passed via the block header should not be used in extended block mode. Instead, the destination server should send extended data marker responses over the control connection, in the following form:

```
extended-mark-response = "111" <SP> "Range Marker" <SP> <byte-ranges-list>
```

```
byte-ranges-list      = <byte-range> [ *("," <byte-range>) ]
byte-range            = <start-offset> "-" <end-offset>
```

```
start-offset          ::= <number>
end-offset            ::= <number>
```

The byte ranges in the marker are an incremental set of byte ranges which have been stored to disk by the data server. The complete restart marker is a concatenation of all byte ranges received by the client in 111 responses.

The client MAY combine adjacent ranges received over several range responses into any number of ranges when sending the REST command to the server to restart a transfer.

For example, the client, on receiving the responses:

```
111 Range Marker 0-29
111 Range Marker 30-89
```

may send, equivalently,

```
REST 0-29,30-89
REST 0-89
REST 30-59,0-29,60-89
```

to restart the transfer after those 90 bytes have been received.

The server MAY indicate that a given range of data has been received in multiple subsequent range markers. The client MUST be able to handle this. For example:

```
111 Range Marker 30-59
111 Range Marker 0-89
```

is equivalent to

111 Range Marker 30-59  
 111 Range Marker 0-29,60-89

Similarly, the client, if it is doing no processing of the restart markers, MAY send redundant information in a restart. Should these be allowed as restart markers for stream mode?

#### Performance Monitoring

In order to monitor the performance of extended block mode transfer, an additional preliminary reply MAY be transmitted over the control channel. This reply is of the form:

```
extended-perf-response = "112-Perf Marker" CRLF
                        <SP> "Timestamp:" <SP> <timestamp> CRLF
                        <SP> "Stripe Index:" <SP> <stripe-number> CRLF
                        <SP> "Stripe Bytes Transferred:" <SP> <byte count> CRLF
                        <SP> "Total Stripe Count:" <SP> <stripe count> CRLF
                        "112 End" CRLF

timestamp               = <number> [ "." <digit> ]
```

<timestamp> is seconds since the epoch

The performance marker can contain these or any other perf-line facts which provide useful information about the current performance.

All perf-line facts represent an instantaneous state of the transfer at the given timestamp. The meaning of the facts are

Timestamp - The time at which the server computed the performance information. This is in seconds since the epoch (00:00:00 UTC, January 1, 1970).

Stripe Index - the index (0-number of stripes on the STOR side of the transfer) which this marker pertains to.

Stripe Bytes Transferred - The number of bytes which have been received on this stripe.

A transfer start time can be specified by a perf marker with 'Stripe Bytes Transferred' set to zero. Only the first marker per stripe can be used to specify the start time of that stripe. Any subsequent markers with 'Stripe Bytes Transferred' set to zero simply indicates no data transfer over the interval.

A server should send a 'start' marker for each stripe. A server should also send a final perf marker for each stripe. This is a marker with 'Stripe Bytes Transferred' set to the total transfer size for that stripe.

#### 7.1.11 Options to RETR

The options described in this section provide a means to convey striping and transfer parallelism information to the server-DTP. For the RETR command, the Client-FTP may specify a parallelism and striping mode it wishes the server-DTP to use. These options are only used by the server-DTP if the retrieve operation is done in extended block mode. These options are implemented as C 2389 extensions.

The format of the RETR OPTS is specified by:

```
retr-opts      = "OPTS" <SP> "RETR" [<SP> option-list] CRLF
option-list    = [ layout-opts "; " ] [ parallel-opts "; " ]
layout-opts    = "StripeLayout=Partitioned"
                | "StripeLayout=Blocked;BlockSize=" <block-size>
parallel-opts  = "Parallelism=" <starting-parallelism> " "
                <minimum-parallelism> " "
                <maximum-parallelism>

block-size     ::= <number>
```

```

starting-parallelism ::= <number>
minimum-parallelism  ::= <number>
maximum-parallelism  ::= <number>

```

### Layout Options

The layout option is used by the source data node to send sections of the data file to the appropriate destination stripe. The various StripeLayout parameters are to be implemented as follows:

#### Partitioned

A partitioned data layout is one where the data is distributed evenly on the destination data nodes. Only one contiguous section of data is stored on each data node. A data node is defined here as a single host-port mentioned in the SPOR command.

#### Blocked

A blocked data layout is one where the data is distributed in round-robin fashion over the destination data nodes. The data distribution is ordered by the order of the host-port specifications in the SPOR command. The size of blocks to be distributed.

### PLVL Parallelism Options

The parallelism option is used by the source data node to control how many parallel data connections may be established to each destination data node. This extension option provides for both a fixed level of parallelism, and for adapting the parallelism to the host/network connection, within a range. If the starting-parallelism option is set, then the server-DTP will make starting-parallelism connections to each destination data node. If the minimum-parallelism option is set, then the server may reduce the number of parallel connections per destination data node to this value. If the maximum-parallelism option is set, then the server may increase the number of parallel connections to per destination data node to at most this value.

#### 7.1.12 References

- [1] Postel, J. and Reynolds, J., **FILE TRANSFER PROTOCOL (FTP)** STD 9, RFC 959, October 1985.
- [2] Hethmon, P. and Elz, R., **Feature negotiation mechanism for the File Transfer Protocol**, RFC 2389, August 1998.
- [3] Horowitz, M. and Lunt, S., **FTP Security Extensions**, RFC 2228, October 1997.
- [4] Elz, R. and Hethom, P., **FTP Extensions**, IETF Draft, May 2001.

#### 7.1.13 Appendix I: Implementation under GSI

There are several security components in this document which are extensions to the behavior of RFC 2228. This appendix attempts to clarify the protocol how these extensions map to the OpenSSL-based implementation of the GSSAPI known as GSI (Grid Security Infrastructure).

A client implementation which communicates with a server which supports the DCAU extension should delegate a limited credential set (using the `GSS_DELEG_FLAG` and `GSS_GLOBUS_LIMITED_DELEG_PROXY_FLAG` args to `gssinit_seccontext()`). If delegation is not performed, the client MUST request that DCAU be disabled by requesting DCAU N, or the server will be unable to perform the default of DCAU A as described by this document.

When DCAU mode "A" or "S" is used, a separate security context is established on each data channel. The context is established by performing the GSSAPI handshake with the active-DTP calling `gssinit_seccontext()` and the passive-DTP calling `gssaccept_seccontext()`. No delegation need be done on these data channels.

Data channel protection via the PROT command MUST always be used in conjunction with the DCAU A or DCAU S commands. If a PROT level is set, then messages will be wrapped according to RFC 2228 Appendix I using the contexts established on each data channel. Tokens transferred over the data channels when either PROT or DCAU is used

are not framed in any way when using GSI. (When implementing this specification with other GSSAPI mechanisms, a 4 byte, big endian, binary token length should precede all tokens).

If the DCAU mode or the PROT mode is changed between file transfers when caching data channels in extended block mode, all open data channels must be closed. This is because the GSI implementation does not support changing levels of protection on an existing connection.



---

## Index

CALLBACK\_INFO\_MALLOC  
    globusftp\_controldata.c [23](#)

DATA\_CONN\_MALLOC  
    globusftp\_controldata.c [23](#)

globusftp\_control.c, [4](#)  
    globus\_i\_ftp\_controldebuglevel, [4](#)  
    globus\_i\_ftp\_controlmodule, [4](#)  
globusftp\_control.h  
    GLOBUS\_FTP\_CONTROL\_TCPBUFFER-  
        AUTOMATIC, [12](#)  
    GLOBUS\_FTP\_CONTROL\_TCPBUFFER-  
        DEFAULT, [12](#)  
    GLOBUS\_FTP\_CONTROL\_TCPBUFFER-  
        FIXED, [12](#)  
globusftp\_control.h, [5](#)  
    globusftp\_controlauth.callbackt, [10](#)  
    globusftp\_controlauth.info\_t, [8](#)  
    globusftp\_controlauth.requirementst, [10](#)  
    globusftp\_control.callbackt, [9](#)  
    globusftp\_control.commandcallbackt, [9](#)  
    globusftp\_control.createdatainfo, [12](#)  
    globusftp\_control.datacallbackt, [10](#)  
    globusftp\_control.datasetinterface, [12](#)  
    globusftp\_control.datawrite\_stripe, [13](#)  
    globusftp\_controldcaumodee, [11](#)  
    globusftp\_controldcaumodet, [7](#)  
    globusftp\_controldcausubjectt, [8](#)  
    globusftp\_controldcaut, [8](#)  
    globusftp\_control.delaypassivet, [11](#)  
    globusftp\_control.layoutt, [8](#)  
    globusftp\_control.local.layout, [12](#)  
    globusftp\_control.modee, [11](#)  
    globusftp\_control.modet, [7](#)  
    GLOBUS\_FTP\_CONTROL\_MODULE, [7](#)  
    globusftp\_control.parallelismmodee, [12](#)  
    globusftp\_control.parallelismmodet, [8](#)  
    globusftp\_control.parallelismt, [8](#)  
    globusftp\_control.protectiont, [11](#)  
    globusftp\_control.releasedatainfo, [13](#)  
    globusftp\_control.responsecallbackt, [9](#)  
    globusftp\_control.roundrobin\_t, [8](#)  
    globusftp\_control.servercallbackt, [11](#)  
    globusftp\_control.striping.modee, [11](#)  
    globusftp\_control.striping.modet, [8](#)  
    globusftp\_control.structuree, [11](#)  
    globusftp\_control.structuret, [8](#)  
    globusftp\_controltcpbuffer.automatict, [8](#)  
    globusftp\_controltcpbuffer.modee, [12](#)  
    globusftp\_controltcpbuffer.modet, [8](#)

    globusftp\_controltcpbuffert, [8](#)  
    globusftp\_controltypee, [11](#)  
    globusftp\_controltypeet, [7](#)  
    globusX\_ftp\_controldatawrite\_stripe, [14](#)  
globusftp\_controlabort  
    globusftp\_controlclient.c, [18](#)  
globusftp\_controlauth.callbackt  
    globusftp\_control.h, [10](#)  
globusftp\_controlauth.info\_compare  
    globusftp\_controlclient.c, [21](#)  
globusftp\_controlauth.info\_init  
    globusftp\_controlclient.c, [20](#)  
globusftp\_controlauth.info\_s, [2](#)  
globusftp\_controlauth.info\_t  
    globusftp\_control.h, [8](#)  
globusftp\_controlauth.requirementst  
    globusftp\_control.h, [10](#)  
globusftp\_controlauthenticate  
    globusftp\_controlclient.c, [17](#)  
globusftp\_controlcallbackt  
    globusftp\_control.h, [9](#)  
globusftp\_controlclient.c, [14](#)  
    globusftp\_controlabort, [18](#)  
    globusftp\_controlauth.info\_compare, [21](#)  
    globusftp\_controlauth.info\_init, [20](#)  
    globusftp\_controlauthenticate, [17](#)  
    globusftp\_controlconnect, [15](#)  
    globusftp\_controlforce.close, [20](#)  
    globusftp\_controlhandledestroy, [15](#)  
    globusftp\_controlhandleinit, [15](#)  
    globusftp\_controlquit, [19](#)  
    globusftp\_controlresponsecopy, [16](#)  
    globusftp\_controlresponsedestroy, [16](#)  
    globusftp\_controlsendcommand, [18](#)  
globusftp\_controlcommandcallbackt  
    globusftp\_control.h, [9](#)  
globusftp\_controlcommandcopy  
    globusftp\_controlserver.c, [34](#)  
globusftp\_controlcommanddestroy  
    globusftp\_controlserver.c, [34](#)  
globusftp\_controlcommandinit  
    globusftp\_controlserver.c, [34](#)  
globusftp\_controlconnect  
    globusftp\_controlclient.c, [15](#)  
globusftp\_controlcreatedatainfo  
    globusftp\_control.h, [12](#)  
    globusftp\_controldata.c, [30](#)  
globusftp\_controldata.c, [21](#)  
    CALLBACK\_INFO\_MALLOC, [23](#)  
    DATA\_CONN\_MALLOC, [23](#)

---

- globusftp\_control.createdatainfo, 30
- globusftp\_control.dataadd.channels25
- globusftp\_control.dataconnectread,24
- globusftp\_control.dataconnectwrite, 24
- globusftp\_control.dataforce.close,32
- globusftp\_control.datagettotaldatachannels, 26
- globusftp\_control.dataquery.channels26
- globusftp\_control.dataread,30
- globusftp\_control.dataremovechannels25
- globusftp\_control.datasendeof, 25
- globusftp\_control.datasetinterface,24
- globusftp\_control.datawrite, 29
- globusftp\_control.datawrite\_stripe,31
- globusftp\_control.getpbsz,29
- globusftp\_control.local.dcau,28
- globusftp\_control.local.layout,30
- globusftp\_control.local.mode,28
- globusftp\_control.local.parallelism,26
- globusftp\_control.local.pasv,27
- globusftp\_control.local.pbsz,28
- globusftp\_control.local.port, 27
- globusftp\_control.local.sendeof, 26
- globusftp\_control.local.spas,27
- globusftp\_control.local.spor,27
- globusftp\_control.local.stru,29
- globusftp\_control.local.tcp.buffer, 28
- globusftp\_control.local.type,27
- globusftp\_control.releasedatainfo, 31
- globusX\_ftp\_control.datawrite\_stripe,31
- GlobusFTPControlDataTestMagi23
- GlobusFTPControlSetMagi23
- TABLE\_ENTRY\_MALLOC, 23
- globusftp\_control.dataadd.channels
  - globusftp\_control.data.c.25
- globusftp\_control.datacallbackt
  - globusftp\_control.h,10
- globusftp\_control.dataconnectread
  - globusftp\_control.data.c.24
- globusftp\_control.dataconnectwrite
  - globusftp\_control.data.c.24
- globusftp\_control.dataforce.close
  - globusftp\_control.data.c.32
- globusftp\_control.datagettotaldatachannels
  - globusftp\_control.data.c.26
- globusftp\_control.dataquery.channels
  - globusftp\_control.data.c.26
- globusftp\_control.dataread
  - globusftp\_control.data.c.30
- globusftp\_control.dataremovechannels
  - globusftp\_control.data.c.25
- globusftp\_control.datasendeof
  - globusftp\_control.data.c.25
- globusftp\_control.datasetinterface
  - globusftp\_control.h,12
  - globusftp\_control.data.c.24
- globusftp\_control.datawrite
  - globusftp\_control.data.c.29
- globusftp\_control.datawrite\_stripe
  - globusftp\_control.h,13
  - globusftp\_control.data.c.31
- globusftp\_control.dcaumodee
  - globusftp\_control.h,11
- globusftp\_control.dcaumodet
  - globusftp\_control.h,7
- globusftp\_control.dcausubjects, 2
- globusftp\_control.dcausubjectt
  - globusftp\_control.h,8
- globusftp\_control.dcaut
  - globusftp\_control.h,8
- globusftp\_control.dcauu, 3
- globusftp\_control.delaypassivet
  - globusftp\_control.h,11
- globusftp\_control.force.close
  - globusftp\_control.client.c,20
- globusftp\_control.getpbsz
  - globusftp\_control.data.c.29
- globusftp\_control.handedestroy
  - globusftp\_control.client.c,15
- globusftp\_control.handleinit
  - globusftp\_control.client.c,15
- globusftp\_control.layout.c,32
- globusftp\_control.layout.t
  - globusftp\_control.h,8
- globusftp\_control.layout.u, 3
- globusftp\_control.local.dcau
  - globusftp\_control.data.c.28
- globusftp\_control.local.layout
  - globusftp\_control.h,12
  - globusftp\_control.data.c.30
- globusftp\_control.local.mode
  - globusftp\_control.data.c.28
- globusftp\_control.local.parallelism
  - globusftp\_control.data.c.26
- globusftp\_control.local.pasv
  - globusftp\_control.data.c.27
- globusftp\_control.local.pbsz
  - globusftp\_control.data.c.28
- globusftp\_control.local.port
  - globusftp\_control.data.c.27
- globusftp\_control.local.sendeof
  - globusftp\_control.data.c.26
- globusftp\_control.local.spas
  - globusftp\_control.data.c.27
- globusftp\_control.local.spor
  - globusftp\_control.data.c.27

- globusftp\_controlLocalStru
  - globusftp\_controldata.c,29
- globusftp\_controlLocaltcp.buffer
  - globusftp\_controldata.c,28
- globusftp\_controlLocaltype
  - globusftp\_controldata.c,27
- globusftp\_controlmodee
  - globusftp\_control.h,11
- globusftp\_controlmodet
  - globusftp\_control.h,7
- GLOBUS.FTP.CONTROLMODULE
  - globusftp\_control.h,7
- globusftp\_controlparallelismmodee
  - globusftp\_control.h,12
- globusftp\_controlparallelismmodet
  - globusftp\_control.h,8
- globusftp\_controlparallelismt
  - globusftp\_control.h,8
- globusftp\_controlparallelismu, 3
- globusftp\_controlprotectiont
  - globusftp\_control.h,11
- globusftp\_controlquit
  - globusftp\_controlclient.c,19
- globusftp\_controlreadcommands
  - globusftp\_controlserver.c,36
- globusftp\_controlreleasedatainfo
  - globusftp\_control.h,13
  - globusftp\_controldata.c,31
- globusftp\_controlresponsecallbackt
  - globusftp\_control.h,9
- globusftp\_controlresponsecopy
  - globusftp\_controlclient.c,16
- globusftp\_controlresponsedestroy
  - globusftp\_controlclient.c,16
- globusftp\_controlroundrobin.s, 3
- globusftp\_controlroundrobin.t
  - globusftp\_control.h,8
- globusftp\_controlsendcommand
  - globusftp\_controlclient.c,18
- globusftp\_controlsendresponse
  - globusftp\_controlserver.c,36
- globusftp\_controlserver.c,32
  - globusftp\_controlcommandcopy,34
  - globusftp\_controlcommanddestroy,34
  - globusftp\_controlcommandinit, 34
  - globusftp\_controlreadcommands,36
  - globusftp\_controlsendresponse,36
  - globusftp\_controlserveraccept,35
  - globusftp\_controlserverauthenticate,35
  - globusftp\_controlserverhandledestroy,33
  - globusftp\_controlserverhandleinit, 33
  - globusftp\_controlserverlisten,33
  - globusftp\_controlserverstop,34
- globusi\_ftp\_server220.reply, 36
- globusi\_ftp\_server235.reply, 36
- globusi\_ftp\_server331.reply, 36
- globusi\_ftp\_server332.reply, 37
- globusi\_ftp\_server334.reply, 37
- globusftp\_controlserveraccept
  - globusftp\_controlserver.c,35
- globusftp\_controlserverauthenticate
  - globusftp\_controlserver.c,35
- globusftp\_controlservercallbackt
  - globusftp\_control.h,11
- globusftp\_controlserverhandledestroy
  - globusftp\_controlserver.c,33
- globusftp\_controlserverhandleinit
  - globusftp\_controlserver.c,33
- globusftp\_controlserverlisten
  - globusftp\_controlserver.c,33
- globusftp\_controlserverstop
  - globusftp\_controlserver.c,34
- globusftp\_controlstripingmodee
  - globusftp\_control.h,11
- globusftp\_controlstripingmodet
  - globusftp\_control.h,8
- globusftp\_controlstructuree
  - globusftp\_control.h,11
- globusftp\_controlstructuret
  - globusftp\_control.h,8
- GLOBUS.FTP.CONTROLTCPBUFFER-  
AUTOMATIC
  - globusftp\_control.h,12
- globusftp\_controltcpbuffer.automatics, 3
- globusftp\_controltcpbuffer.automatict
  - globusftp\_control.h,8
- GLOBUS.FTP.CONTROLTCPBUFFER-  
DEFAULT
  - globusftp\_control.h,12
- globusftp\_controltcpbuffer.defaultt, 3
- GLOBUS.FTP.CONTROLTCPBUFFERFIXED
  - globusftp\_control.h,12
- globusftp\_controltcpbuffer\_xed\_t, 4
- globusftp\_controltcpbuffer.modee
  - globusftp\_control.h,12
- globusftp\_controltcpbuffer.modet
  - globusftp\_control.h,8
- globusftp\_controltcpbuffert, 4
  - globusftp\_control.h,8
- globusftp\_controltypee
  - globusftp\_control.h,11
- globusftp\_controltype.t
  - globusftp\_control.h,7
- globusi\_ftp\_controldebuglevel
  - globusftp\_control.c,4
- globusi\_ftp\_controlmodule

- globusftp\_control.c, [4](#)
- globus\_i\_ftp\_server220\_reply
  - globusftp\_control\_server.c, [36](#)
- globus\_i\_ftp\_server235\_reply
  - globusftp\_control\_server.c, [36](#)
- globus\_i\_ftp\_server331\_reply
  - globusftp\_control\_server.c, [36](#)
- globus\_i\_ftp\_server332\_reply
  - globusftp\_control\_server.c, [37](#)
- globus\_i\_ftp\_server334\_reply
  - globusftp\_control\_server.c, [37](#)
- globusX\_ftp\_control\_datawrite\_stripe
  - globusftp\_control.h, [14](#)
  - globusftp\_control\_data.c, [31](#)
- GlobusFTPControlDataTestMagic
  - globusftp\_control\_data.c, [23](#)
- GlobusFTPControlSetMagic
  - globusftp\_control\_data.c, [23](#)
- TABLE\_ENTRY\_MALLOC
  - globusftp\_control\_data.c, [23](#)