globus xio Reference Manual

2.8

Generated by Doxygen 1.3.5

Tue Aug 11 21:16:01 2009

Contents

1   Globus XIO

The Globus eXtensible Input Output library.

- The globus_xio user API.
- User API Assistance.
- Globus XIO Driver
- Driver Programming

2   globus xio Module Index

2.1   globus xio Modules

Here is a list of all modules:

3   globus xio Data Structure Index

3.1   globus xio Data Structures

Here are the data structures with brief descriptions:

4   globus xio File Index

4.1   globus xio File List

Here is a list of all documented les with brief descriptions:

5   globus xio Page Index

5.1   globus xio Related Pages

Here is a list of all related documentation pages:

6   globus xio Module Documentation

6.1   The globus_xio user API.

Typedefs

- typedef void(globus_xio_accept_callback_)(globus_xio_server_t server, globus_xio_handle_t handle, globus_result_t result, void user_arg)
- typedef void(globus_xio_server_callback)(globus_xio_server_t server, void user_arg)
- typedef globus_bool_t(globus_xio_timeout_callback_t)(globus_xio_handle_t handle, globus_xio_- operation_type_t type, void user_arg)
- typedef void(globus_xio_callback_)(globus_xio_handle_t handle, globus_result_t result, void user_arg)
- typedef void(globus_xio_data_callback)(globus_xio_handle_t handle, globus_result_t result, globus_byte_t buffer, globus_size_t len, globus_size_t nbytes, globus_xio_data_descriptor_t data_desc, void user_arg)
- typedef void(globus_xio_iovec_callback)(globus_xio_handle_t handle, globus_result_t result, globus_xio_- iovec_t iovec, int count, globus_size_t nbytes, globus_xio_data_descriptor_t data_desc, void user_arg)
- typedef enum globus_i_xio_op_type_e globus_xio_operation_type_t

Enumerations

- enum globus_i_xio_op_type_e
- enum globus_xio_handle_cmd_t {
  GLOBUS_XIO_GET_LOCAL_CONTACT = 12345,
  GLOBUS_XIO_GET_LOCAL_NUMERIC_CONTACT,
  GLOBUS_XIO_GET_REMOTE_CONTACT,
  GLOBUS_XIO_GET_REMOTE_NUMERIC_CONTACT,
  GLOBUS_XIO_SEEK,
  GLOBUS_XIO_SET_STRING_OPTIONS }

Functions

- globus_result_t globus_xio_attr_init(globus_xio_attr_t attr)
- globus_result_t globus_xio_attr_cntl(globus_xio_attr_t attr, globus_xio_driver_t driver, int cmd,...)
- globus_result_t globus_xio_attr_copy(globus_xio_attr_t dst, globus_xio_attr_t src)
- globus_result_t globus_xio_attr_destroy(globus_xio_attr_t attr)
- globus_result_t globus_xio_stack_init(globus_xio_stack_t stack, globus_xio_attr_t stack_attr)
- globus_result_t globus_xio_stack_push_driver(globus_xio_stack_t stack, globus_xio_driver_t driver)
- globus_result_t globus_xio_stack_copy(globus_xio_stack_t dst, globus_xio_stack_t src)
- globus_result_t globus_xio_stack_destroy(globus_xio_stack_t stack)

- globus_result_t globus_xio_server_create (globus_xio_server_t server, globus_xio_attr_t server_attr, globus_xio_stack_t stack)
- globus_result_t globus_xio_server_get_contact_string (globus_xio_server_t server, char contact_string)
- globus_result_t globus_xio_server_register_close (globus_xio_server_t server, globus_xio_server_callback_t cb, void user_arg)
- globus_result_t globus_xio_server_close (globus_xio_server_t server)
- globus_result_t globus_xio_server_cntl (globus_xio_server_t server, globus_xio_driver_t driver, int cmd,...)
- globus_result_t globus_xio_server_accept (globus_xio_handle_t out_handle, globus_xio_server_t server)
- globus_result_t globus_xio_server_register_accept (globus_xio_server_t server, globus_xio_accept_callback_t cb, void user_arg)
- globus_result_t globus_xio_handle_create (globus_xio_handle_t handle, globus_xio_stack_t stack)
- globus_result_t globus_xio_data_descriptor_init (globus_xio_data_descriptor_t data_desc, globus_xio_handle_t handle)
- globus_result_t globus_xio_data_descriptor_destroy (globus_xio_data_descriptor_t data_desc)
- globus_result_t globus_xio_data_descriptor_cntl (globus_xio_data_descriptor_t data_desc, globus_xio_driver_t driver, int cmd,...)
- globus_result_t globus_xio_handle_cntl (globus_xio_handle_t handle, globus_xio_driver_t driver, int cmd,...)
- globus_result_t globus_xio_register_open (globus_xio_handle_t handle, const char contact_string, globus_xio_attr_t attr, globus_xio_callback_t cb, void user_arg)
- globus_result_t globus_xio_open (globus_xio_handle_t handle, const char contact_string, globus_xio_attr_t attr)
- globus_result_t globus_xio_register_read (globus_xio_handle_t handle, globus_byte_t buffer, globus_size_t buffer_length, globus_size_t waitforbytes, globus_xio_data_descriptor_t data_desc, globus_xio_data_callback_t cb, void user_arg)
- globus_result_t globus_xio_read (globus_xio_handle_t handle, globus_byte_t buffer, globus_size_t buffer_length, globus_size_t waitforbytes, globus_size_t nbytes, globus_xio_data_descriptor_t data_desc)
- globus_result_t globus_xio_register_readv (globus_xio_handle_t handle, globus_xio_iovec_t iovec, int iovec_count, globus_size_t waitforbytes, globus_xio_data_descriptor_t data_desc, globus_xio_iovec_callback_t cb, void user_arg)
- globus_result_t globus_xio_readv (globus_xio_handle_t handle, globus_xio_iovec_t iovec, int iovec_count, globus_size_t waitforbytes, globus_size_t nbytes, globus_xio_data_descriptor_t data_desc)
- globus_result_t globus_xio_register_write (globus_xio_handle_t handle, globus_byte_t buffer, globus_size_t buffer_length, globus_size_t waitforbytes, globus_xio_data_descriptor_t data_desc, globus_xio_data_callback_t cb, void user_arg)
- globus_result_t globus_xio_write (globus_xio_handle_t handle, globus_byte_t buffer, globus_size_t buffer_length, globus_size_t waitforbytes, globus_size_t nbytes, globus_xio_data_descriptor_t data_desc)
- globus_result_t globus_xio_register_writev (globus_xio_handle_t handle, globus_xio_iovec_t iovec, int iovec_count, globus_size_t waitforbytes, globus_xio_data_descriptor_t data_desc, globus_xio_iovec_callback_t cb, void user_arg)
- globus_result_t globus_xio_writev (globus_xio_handle_t handle, globus_xio_iovec_t iovec, int iovec_count, globus_size_t waitforbytes, globus_size_t nbytes, globus_xio_data_descriptor_t data_desc)
- globus_result_t globus_xio_register_close (globus_xio_handle_t handle, globus_xio_attr_t attr, globus_xio_callback_t cb, void user_arg)
- globus_result_t globus_xio_close (globus_xio_handle_t handle, globus_xio_attr_t attr)
- globus_result_t globus_xio_handle_create_from_url (globus_xio_handle_t out_h, const char scheme, globus_xio_attr_t attr, char param_string)
- EXTERN_C_END globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_GET_LOCAL_CONTACT, char contact_string_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_GET_LOCAL_NUMERIC_CONTACT, char contact_string_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_GET_REMOTE_CONTACT, char contact_string_out)

- globus_result_t globus_xio_handle_cntl(handle,   driver,   GLOBUS_XIO_GET_REMOTE_NUMERIC_-CONTACT, char   contact_string_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_SEEK, globus_off_t offset)
- globus_result_t globus_xio_handle_cntl(handle,   driver,   GLOBUS_XIO_SET_STRING_OPTIONS,   char con g_string)

6.1.1   Typedef Documentation

6.1.1.1   typedef void(globus_xio_accept_callback)(globus_xio_server_t server, globus_xio_handle_t handle, globus_result_t result, void   user_arg)

Callback signature for accept.

When a registered accept operation completes the users function of this signature is called.

Parameters:
   server The server object on which the accept was registered.

   handle The newly created handle that was created by the accept operation.

   result A result code indicating the success of the accept operation. GLOBUS_SUCCESS indicates a successful accept.

   user_arg A user argument that is threaded from the registration to the callback.

6.1.1.2   typedef void(globus_xio_server_callback)(globus_xio_server_t server, void user_arg)

Server callback signature.

This is the generic server callback signature. It is currently only used for the register close operation.

6.1.1.3   typedef globus_bool_t(globus_xio_timeout_callback)(globus_xio_handle_t handle, globus_xio_-operation_type_t type, void   user_arg)

The timeout callback function signature.

Parameters:
   handle The handle the handle on which the timeout operation was requested.

   type The type of opperation that timed out: GLOBUS_XIO_OPERATION_OPEN GLOBUS_XIO_-OPERATION_CLOSE GLOBUS_XIO_OPERATION_READ GLOBUS_XIO_OPERATION_WRITE

   arg A user arg threaded throw to the callback.

6.1.1.4   typedef void(globus_xio_callback)(globus_xio_handle_t handle, globus_result_t result, void user_arg)

globus_xio_callback_t

This callback is used for the open and close asynchronous operations.

6.1.1.5   typedef void(globus_xio_data_callback)(globus_xio_handle_t handle, globus_result_t result, globus_byte_t buffer, globus_size_t len, globus_size_t nbytes, globus_xio_data_descriptor_t data_desc, void user_arg)

globus_xio_data_callback_t

This callback is used for asychronous operations that send or receive data.

on eof, result_t will be of type GLOBUS_XIO_ERROR_EOF

6.1.1.6   typedef void(globus_xio_iovec_callback)(globus_xio_handle_t handle, globus_result_t result, globus_xio_iovec_t iovec, int count, globus_size_t nbytes, globus_xio_data_descriptor_t data_desc, void user_arg)

globus_xio_iovec_callback_t

This callback is used for asychronous operations that send or receive data with an ivec structure.

on eof, result_t will be of type GLOBUS_XIO_ERROR_EOF

6.1.1.7   typedef enum globus_i_xio_op_type_e globus_xio_operation_type_t

Operation types.

An enumeration of operation types. Used in the timeout callback to indicate what operation typed timedout.

6.1.2   Enumeration Type Documentation

6.1.2.1   enum globus_i_xio_op_type_e

Operation types.

An enumeration of operation types. Used in the timeout callback to indicate what operation typed timedout.

6.1.2.2   enum globus_xio_handle_cmd_t

Common driver handle cntls.

Enumeration values:
   GLOBUS_XIO_GET_LOCAL_CONTACT See usage for globus_xio_handle_cntl
   GLOBUS_XIO_GET_LOCAL_NUMERIC_CONTACT See usage for globus_xio_handle_cntl
   GLOBUS_XIO_GET_REMOTE_CONTACT See usage for globus_xio_handle_cntl
   GLOBUS_XIO_GET_REMOTE_NUMERIC_CONTACT See usage for globus_xio_handle_cntl
   GLOBUS_XIO_SEEK See usage for globus_xio_handle_cntl
   GLOBUS_XIO_SET_STRING_OPTIONS See usage for globus_xio_handle_cntl

6.1.3   Function Documentation

6.1.3.1   globus_result_t globus_xio_attr_init (globus_xio_attr_t attr)

Intialize a globus xio attribute.

Parameters:
   attr upon return from this function this out parameter will be initialized. Once the user is nished with the
      attribute they should make sure they destroy it in order to free resources associated with it.

6.1.3.2 globus_result_t globus_xio_attr_cntl (globus_xio_attr_t attr, globus_xio_driver_t driver, int cmd, ...)

Manipulate the values associated in the attr.

This function provides a means to access the attr structure. What exactly this function does is determined by the value in the parameter cmd and the value of the patameter driver. When the driver parameter is NULL it indicates that this function applies to general globus xio values. If it is not NULL it indicates that the function will effect driver speci c values. Each driver is resonsible for de ning its own enumeration of values for cmd and the var args associated with that command.

Parameters:

attr the attribute structure to be manipulated.

driver This parameter indicates which driver the user would like to perform the requested operation. If this parameter is NULL this request will be scoped to general attribure functions.

cmd an enum that determines what speci c operation the user is requesting. Each driver will determine the value for this enumeration.

6.1.3.3 globus_result_t globus_xio_attr_copy (globus_xio_attr_t dst, globus_xio_attr_t src)

Copy an attribute structure.

6.1.3.4 globus_result_t globus_xio_attr_destroy (globus_xio_attr_t attr)

Clean up resources associated with an attribute.

Parameters:

attr Upon completion of this function all resources associated with this structure will returned to the system and the attr will no longer be valid.

6.1.3.5 globus_result_t globus_xio_stack_init (globus_xio_stack_t stack, globus_xio_attr_t stack_attr)

Initialize a stack object.

6.1.3.6 globus_result_t globus_xio_stack_push_driver (globus_xio_stack_t stack, globus_xio_driver_t driver)

Push a driver onto a stack.

No attrs are associated with a driver. The stack represents the ordered lists of transform drivers and 1 transport driver. The transport driver must be pushed on rst.

6.1.3.7 globus_result_t globus_xio_stack_copy (globus_xio_stack_t dst, globus_xio_stack_t src)

Copy a stack object.

6.1.3.8 globus_result_t globus_xio_stack_destroy (globus_xio_stack_t stack)

Destroy a stack object.

6.1.3.9   globus_result_t globus_xio_server_create (globus_xio_server_t ∗server, globus_xio_attr_t server_attr, globus_xio_stack_t stack)

Create a server object.

This function allows the user to create a server object which can then be used to accept connections.

Parameters:

   server An out parameter. Once the function successfully returns this will point to a valid server object.

   server_attr an attributre structure used to alter the default server intialization. This will mostly be used in a driver speci c manner. can be NULL.

   stack

6.1.3.10   globus_result_t globus_xio_server_get_contact_string (globus_xio_server_t server, char ∗∗contact_-string)

get contact string

This function allows the user to get the contact string for a server. this string could be used as the contact string for the client side.

Parameters:

   server An initialized server handle created with globus_xio_server_create()

   contact_string an out varibale. Will point to a newly allocated string on success. must be freed by the caller.

6.1.3.11   globus_result_t globus_xio_server_register_close (globus_xio_server_t server, globus_xio_server_-callback_t cb, void ∗user_arg)

post a close on a server object

This function registers a close operation on a server. When the user function pointed to by parameter cb is called the server object is closed.

6.1.3.12   globus_result_t globus_xio_server_close (globus_xio_server_t server)

A blocking server close.

6.1.3.13   globus_result_t globus_xio_server_cntl (globus_xio_server_t server, globus_xio_driver_t driver, int cmd, ...)

Touch driver speci c information in a server object.

This function allows the user to comunicate directly with a driver in association with a server object. The driver de nes what operations can be preformed.

6.1.3.14   globus_result_t globus_xio_server_accept (globus_xio_handle_t ∗out_handle, globus_xio_server_t server)

Accept a connection.

This function will accept a connetion on the given server object and the parameter out_handle will be valid if the function returns successfully.

6.1.3.15   globus_result_t globus_xio_server_register_accept (globus_xio_server_t server, globus_xio_accept_-callback_t cb, void user_arg)

Asynchronous accept.

This function posts an nonblocking accept. Once the operation has completed the user function pointed to by the parameter cb is called.

6.1.3.16   globus_result_t globus_xio_handle_create (globus_xio_handle_t handle, globus_xio_stack_t stack)

Initialize a handle for client opens.

This funtion will initialize a handle for active opens (client side connections).

6.1.3.17   globus_result_t globus_xio_data_descriptor_init (globus_xio_data_descriptor_t data_desc, globus_-xio_handle_t handle)

Initialize a data descriptor.

Parameters:
    data_desc An out parameter. The data descriptor to be intialized.

    handle The handle this data descriptor will be used with. This parametter is require in order to optimize the code handling the data descriptors use.

6.1.3.18   globus_result_t globus_xio_data_descriptor_destroy (globus_xio_data_descriptor_t data_desc)

clean up a data descriptor.

6.1.3.19   globus_result_t globus_xio_data_descriptor_cntl (globus_xio_data_descriptor_t data_desc, globus_-xio_driver_t driver, int cmd, ...)

Touch driver speci c data in data descriptors.

This function allows the user to comunicate directly with a driver in association with a data descriptors. The driver de nes what operations can be preformed.

6.1.3.20   globus_result_t globus_xio_handle_cntl (globus_xio_handle_t handle, globus_xio_driver_t driver, int cmd, ...)

Touch driver speci c information in a handle object.

This function allows the user to comunicate directly with a driver in association with a handle object. The driver de nes what operations can be preformed.

pass the driver to control a speci c driver pass NULL for driver for XIO speci c cntls pass GLOBUS_XIO_QUERY for driver to try each driver in order until success

6.1.3.21   globus_result_t globus_xio_register_open (globus_xio_handle_t handle, const char contact_string, globus_xio_attr_t attr, globus_xio_callback_t cb, void user_arg)

Open a handle.

Creates an open handle based on the state contained in the given stack.

No operation can be preformed on a handle until it is initialized and then opened. If an already open handle used the information contaned in that handle will be destoyed.

Parameters:

handle The handle created with globus_xio_handle_create() or globus_xio_server_register_accept() that is to be opened.

attr how to open attribute. can be NULL

cb The function to be called when the open operation completes.

user_arg A user pointer that will be threaded through to the callback.

contact_string An url describing the resource. NULL is allowed. Drivers interpret the various parts of this url as descibed in their documentation. An alternative form is also supported: if contact_string does not specify a scheme (e.g. http://) and it contains a ':', it will be parsed as a host:port pair. if it does not contain a ':', it will be parsed as the path

the following are examples of valid formats:

```
$<$path to file$>$
host-name ":" $<$service or port$>$
"file:" $<$path to file$>$
$<$scheme$>$ "://" [ "/" [ $<$path to resource$>$ ]   ]
$<$scheme$>$ "://" location [ "/" [ $<$path to resource$>$ ] ]
    location:
        [ auth-part ] host-part
    auth-part:
        $<$user$>$ [ ":" $<$password$>$ ] "@"
    host-part:
        [ "<" $<$subject$>$ ">" ] host-name [ ":" $<$port or service$>$ ]
    host-name:
        $<$hostname$>$ | $<$dotted quad$>$ | "[" $<$ipv6 address$>$ "]"
```

Except for use as the above delimeters, the following special characters MUST be encoded with the %HH format where H == hex char.

```
"/" and "@" in location except subject
"<" and ">" in location
":" everywhere except ipv6 address and subject
"%" everywhere (can be encoded with %HH or %)
```

6.1.3.22   globus_result_t globus_xio_open (globus_xio_handle_t handle, const char * contact_string, globus_-xio_attr_t attr)

blocking open

6.1.3.23   globus_result_t globus_xio_register_read (globus_xio_handle_t handle, globus_byte_t * buffer, globus_size_t buffer_length, globus_size_t waitforbytes, globus_xio_data_descriptor_t data_desc, globus_xio_-data_callback_t cb, void * user_arg)

Read data from a handle.

6.1.3.24   globus_result_t globus_xio_read (globus_xio_handle_t handle, globus_byte_t buffer, globus_size_t buffer_length, globus_size_t waitforbytes, globus_size_t nbytes, globus_xio_data_descriptor_t data_desc)

Read data from a handle.

6.1.3.25   globus_result_t globus_xio_register_readv (globus_xio_handle_t handle, globus_xio_iovec_t iovec, int iovec_count, globus_size_t waitforbytes, globus_xio_data_descriptor_t data_desc, globus_xio_iovec_-callback_t cb, void user_arg)

Read data from a handle into a globus_xio_iovec_t (struct iovec).

6.1.3.26   globus_result_t globus_xio_readv (globus_xio_handle_t handle, globus_xio_iovec_t iovec, int iovec_-count, globus_size_t waitforbytes, globus_size_t nbytes, globus_xio_data_descriptor_t data_desc)

Read data from a handle into a globus_xio_iovec_t (struct iovec).

6.1.3.27   globus_result_t globus_xio_register_write (globus_xio_handle_t handle, globus_byte_t buffer, globus_size_t buffer_length, globus_size_t waitforbytes, globus_xio_data_descriptor_t data_desc, globus_xio_-data_callback_t cb, void user_arg)

Write data to a handle.

6.1.3.28   globus_result_t globus_xio_write (globus_xio_handle_t handle, globus_byte_t buffer, globus_size_t buffer_length, globus_size_t waitforbytes, globus_size_t nbytes, globus_xio_data_descriptor_t data_desc)

Write data to a handle.

6.1.3.29   globus_result_t globus_xio_register_writev (globus_xio_handle_t handle, globus_xio_iovec_t iovec, int iovec_count, globus_size_t waitforbytes, globus_xio_data_descriptor_t data_desc, globus_xio_iovec_-callback_t cb, void user_arg)

Write data to a handle from a globus_xio_iovec_t (struct iovec).

6.1.3.30   globus_result_t globus_xio_writev (globus_xio_handle_t handle, globus_xio_iovec_t iovec, int iovec_count, globus_size_t waitforbytes, globus_size_t nbytes, globus_xio_data_descriptor_t data_desc)

Write data to a handle from a globus_xio_iovec_t (struct iovec).

6.1.3.31   globus_result_t globus_xio_register_close (globus_xio_handle_t handle, globus_xio_attr_t attr, globus_xio_callback_t cb, void user_arg)

Close a handle.

This functions servers as a destoy for the handle. As soon as the operations completes (the callback is called). The handle is destroyed.

Parameters:
    handle the handle to be closed.
    attr how to close attribute
    cb The function to be called when the close operation completes.
    user_arg A user pointer that will be threaded through to the callback.

6.1.3.32   globus_result_t globus_xio_close (globus_xio_handle_t handle, globus_xio_attr_t attr)

Blocking close.

6.1.3.33   globus_result_t globus_xio_handle_create_from_url (globus_xio_handle_t out_h, const char scheme, globus_xio_attr_t attr, char param_string)

Initializes a handle based on the scheme given.

Parameters:

    out_h An uninitialized handle that will be initialized in the function to correspond to the scheme given. This handle should be used for any I/O operations.

    scheme A string containing the protocol which the handle should be initialized to. The string can either be a protocol by itself, for example, "http", or a complete scheme such as "http://www.example.com".

    attr Attribute to be used for setting parameter string. It is initialized by the function. Can be NULL if attributes are not being used.

    param_string A string containing attributes to be set for the drivers associated with the scheme. This should be in the form "protocol1:option1=value1;option2=value2,protocol2:option1=value1; option2=value2" Can be NULL if attributes are not being used.

6.1.3.34   EXTERN_C_END globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_GET_-LOCAL_CONTACT, char contact_string_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get local connection info.

Parameters:

    contact_string_out A pointer to a contact string for the local end of a connected handle. Where possible, it will be in symbolic form (FQDN).

The user must free the returned string.

See also:

    globus_xio_server_get_contact_string()

6.1.3.35   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_GET_LOCAL_-NUMERIC_CONTACT, char contact_string_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get local connection info.

Parameters:

    contact_string_out A pointer to a contact string for the local end of a connected handle. Where possible, it will be in numeric form. (IP)

The user must free the returned string.

6.1.3.36 globus_result_t globus_xio_handle_cntl (handle,   driver,   GLOBUS_XIO_GET_REMOTE_-
CONTACT, char   contact_string_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Get remote connection info.

Parameters:
    contact_string_outA pointer to a contact string for the remote end of a connected handle. Where possible, it will
        be in symbolic form (FQDN).

The user must free the returned string.

6.1.3.37 globus_result_t globus_xio_handle_cntl (handle,   driver,   GLOBUS_XIO_GET_REMOTE_-
NUMERIC_CONTACT, char   contact_string_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Get remote connection info.

Parameters:
    contact_string_outA pointer to a contact string for the remote end of a connected handle. Where possible, it will
        be in numeric form. (IP)

The user must free the returned string.

6.1.3.38   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_SEEK, globus_off offset)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Reposition read/write offset.

Parameters:
    offset Specify the desired offset.

6.1.3.39   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_SET_STRING_OPTIONS,
char   con g_string)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Set the driver speci c con guration string. The format of the string is de ned by the driver. It is typically a set of
key=value pairs

Parameters:
    con g_string The driver speci c paramter string.

6.2   User API Assistance.

Help understanding the globus_xio api.

Stack Constuction.

The driver stack that is used for a given xio handle is constructed using a globus_xio_stack_t. Each driver is loaded by name and pushed onto a stack.

```
stack setup example:

// First load the drivers
globus_xio_driver_load("tcp", &tcp_driver);
globus_xio_driver_load("gsi", &gsi_driver);

//build the stack
globus_xio_stack_init(&stack);
globus_xio_stack_push_driver(stack, tcp_driver, NULL);
globus_xio_stack_push_driver(stack, gsi_driver, NULL);
```

Servers

A server data structure provides functionality for passive opens. A server is initialized and bound to a protocol stack and set of attributes with the function globus_xio_server_create(). Once a server is created many "connections" can be accepted. Each connection will result in an intialized handle which can later be opened.

```
globus_xio_server_t                server;
globus_xio_attr_t                  attr;

globus_xio_attr_init(&attr);
globus_xio_server_create(&server_handle, attr, stack);
globus_xio_server_accept(&handle, server);
```

Handle Construction

There are two ways to create a handle. The rst is for use as a client (one that is doing an active open). The function: globus_xio_handle_create() is used to create such a handle and bind that handle to a protocol stack.

```
globus_xio_handle_create(&handle, stack);
```

The second means of creating a handle is for use as a server (one that is doing a passive open). This is created by accepting a connection on a server_handle with the function globus_xio_server_accept() or globus_xio_server_register_accept()

Mutable attrs can be altered via a call to globus_xio_handle_cntl() described later.

```
globus_xio_server_accept(&xio_handle, server_handle);
```

once a handle is intialized the user can call globus_xio_open() to begin the open process.

Timeouts

A user can set a timeout value for any io operation. Each IO operation (open close read write) can have its own timeout value. If no timeout is set the operation will be allowed to in nitly block.
When time expires the outstanding operation is canceled. If the timeout callback for the given operation is not NULL it is called rst to notify the user that the operation timed out and give the user a chance to ignore that timeout. If canceled, the user will get the callback they registered for the operation as well, but it will come with an error indicating that it has been canceled.
It is possiblie that part of an io operation will complete before the timeout expires. In this case the opperation can still be canceled. The user will receive there IO callback with and error set and the length value appropriately set to indicate how much of the operation completed.

Data Desciptor

The data descriptor ADT gives the user a means of attaching/extracting meta data to a read or write operation. Things like offset, out of band message, and other driver speci c meta data are contained in the data descriptor. Data descriptors are passed to globus_xio globus_xio_read() and globus_xio_write() Within the globus_xio framework it is acceptable to pass NULL instead of a valid data_descriptor,

```
    ex:
  globus_xio_data_descriptor_init(&desc);
  globus_xio_data_descriptor_cntl(desc,
       tcp_driver,
       GLOBUS_XIO_TCP_SET_SEND_FLAGS,
       GLOBUS_XIO_TCP_SEND_OOB);
```

User Attributes

Globus XIO uses a single attribute object for all of its functions. Attributes give an the user an extenable mechanism to alter default values which control parameters in an operation.

In most of the globus xio user api functions a user passes an attribute as a parameter. In many cases the user may ignore the attribute parameter and just pass in NULL. However at times the user will wish to tweak the operation. The attribute structure is used for this tweaking.

There are only three attribute functions globus_xio_attr_init globus_xio_attr_cntl and globus_xio_attr_destroy

The init and destroy functions are very simple and require little explaination. Before an attribute can be used it must be intialized, and to clean up all memory associated with it the user must call destroy on it.

The function globus_xio_attr_cntl manipulates values in the attribute. For more info on it see globus_xio_attr_-cntl.

6.3   Globus XIO Driver

Globus XIO introduces a notion of a driver stack to its API. With in globus_xio every IO operation must occur on a globus_xio handle. Associated with each handle is a stack of drivers. A driver is a module piece of code that implements the globus_xio driver interface. The purpose of a driver is manipulate data passed in by the user in someway. Each driver in a stack will serve its own unique purpose.

IO operations pass from driver to driver, starting at the top of the stack and ending at the bottom. When the bottom layer driver nishes with the operation it signals globus_xio that it has completed. Completion noti cation then follows the driver stack up to the top.

Driver Types:

Transport driver:
A transport driver is one that is responsible for actually putting bytes onto the wire. For example: A TCP driver or a UDP driver would be an example of transport drivers.
Per driver stack there must be exactly one transport driver and must be at the bottom of the stack. A transform driver is de ned by its lack of passing an operation to the next driver in the stack. This type of driver does not rely on globus_xio for further completion of an operation, rather it is self suf cent in this task.

Transform driver:
A tranform driver is any intermediate driver in the stack. These drivers are indenti ed by there reliance on the driver stack to complete the operation. These drivers must pass the operation down the stack because they cannot complete it themselves. An example of a transform driver would be a gsi driver. This driver would wrap and unwrap messages, but would not be able to complete the transport itself, so it would rely on the remaining drivers in the stack.

Driver API

The globus xio driver api is a set of functions and interfaces to allow a developer to create a backend driver for globus_xio. To create a driver the user must implement all of the interface functions in the driver speci cation. There are also a set of functions provide to assist the driver author in implemention.

Quick Start:
Four basic driver needs the user will have to pay attention to a few new structures and concepts.

globus_xio_operation_t
This structure represents a request for an operation. If the driver can service the operation it does so and the calls the appropriate nish_operation() function. If the driver cannot completely service the operation it can pass() it along to the next driver in the stack. As soon as the operation structure is either nished or passed it is no longer valid for use in any other function.

globus_xio_driver_handle_t
A driver_handle represents a open handle to the driver stack for xio. The driver obtains a driver_handle by calling globus_xio_driver_open(). When the open operation completes (it callback is called) the driver then has a driver_-handle. The driver_handle allows the user to do some complex things that will be described later.

globus_xio_stack_t
This structure provides the driver with information about the driver stack It is mainly used for creating driver_-handle as a parameter to lobus_xio_driver_open()..

Typical Sequence:
Here is a typcial sequence of events for a globus_xio transform driver:

Open
globus_xio_driver_open_t is called. The user calls globus_xio_driver_open() passing it the operation and the stack and a callback. When the open callback is called the driver is given a new operation as a parameter. The driver will then call globus_xio_driver_ nished_open() passing it the now initialized driver_handle and the newly received operation. The call to globus_xio_driver_ nished_open() does two things: 1) it tells globus_xio that this driver has nished its open operation, and 2) it gives xio the driver_handle (which contains information on the drivers below it).

Read/Write
The read or write interface funcion is called. It receives a operation as a parameter. The driver then calls the approriate pass operation and waits for the callback. When the callback is received the driver calls nished_-operation passing in the operation structure it received in the callback

Close
The close interface function is called and is passed an operation and a driver_handle. The driver will call globus_-xio_driver_close() passing it the operation. When the close callback is received the driver calls globus_xio_-driver_ nished_close() passing it the operation received in the close callback and the driver_handle received in the interface function. At this point the driver_handle is no longer valid..

Advanced Driver Programming
The typical driver implementatin is describe above. However globus_xio allows driver authors to do more advanced things. Some of these things will be explored here.

Read Ahead
Once a driver_handle is open a driver can spawn operation structures from it. This gives the driver the ability to request io from the driver stack before it receives a call to its own interface io interface function. So if a driver wishes to read ahead it does the following:

• it creats an operation by calling globus_xio_driver_create_operation() and passing it the driver_handle it is intereesting in using.

- call globus_xio_driver_read() using this operations. When the read callback is received the driver may call nished_operation() on the op it receives (this ultimitely results in very little, since this operation was started by this driver, but it is good practice and will free up resources that would otherwise leak).

- Now when the user nally does receive a read interface call from globus_xio it can imediately nish it using the operation it just received as a parameter and updating the iovec structure to represent the read that already occured.

Preopening handles.
Once the driver has received a globus_xio_driver_stack_t it can open a driver_handle. The globus_xio_driver_-stack_t comes in the call to the interface function globus_xio_server/client_init_t(). The driver uses this structure in a call to globus_xio_driver_open(). When this functionality completes the driver has an initialized driver_-handle and can use it to create operations as described above. The driver can now hang onto this driver_handle until it receives an open interface function call. At which time it can call globus_xio_driver_ nished_open() passing in the driver_handle and thereby glueing the pre opened driver_handle with the requested globus_xio operation.

6.4 Driver Programming

The set of interface functions that the driver author must implement to create a driver and the functions to assist in the creation.

Typedefs

- typedef void(globus_xio_driver_callback)(globus_xio_operation_t op, globus_result_t result, void user_-arg)
- typedef void(globus_xio_driver_data_callback)(globus_xio_operation_t op, globus_result_t result, globus_size_t nbytes, void user_arg)
- typedef globus_result_t(globus_xio_driver_attr_init)(void out_driver_attr)
- typedef globus_result_t(globus_xio_driver_attr_copy)(void dst, void src)
- typedef globus_result_t(globus_xio_driver_attr_destroy)(void driver_attr)
- typedef globus_result_t(globus_xio_driver_attr_cntl)(void attr, int cmd, va_list ap)
- typedef globus_result_t(globus_xio_driver_server_init)(void driver_attr, const globus_xio_contact_-t contact_info, globus_xio_operation_t op)
- typedef globus_result_t(globus_xio_driver_server_destroy)(void driver_server)
- typedef globus_result_t(globus_xio_driver_server_accept)(void driver_server, globus_xio_operation_t op)
- typedef globus_result_t(globus_xio_driver_server_cntl)(void driver_server, int cmd, va_list ap)
- typedef globus_result_t(globus_xio_driver_link_destroy)(void driver_link)
- typedef globus_result_t(globus_xio_driver_transform_open)(const globus_xio_contact_t contact_info, void driver_link, void driver_attr, globus_xio_operation_t op)
- typedef globus_result_t(globus_xio_driver_transport_open)(const globus_xio_contact_t contact_info, void driver_link, void driver_attr, globus_xio_operation_t op)
- typedef globus_result_t(globus_xio_driver_handle_cntl)(void handle, int cmd, va_list ap)
- typedef globus_result_t(globus_xio_driver_close)(void driver_handle, void driver_attr, globus_xio_-operation_t op)
- typedef globus_result_t(globus_xio_driver_read)(void driver_speci c_handle, const globus_xio_iovec_t iovec, int iovec_count, globus_xio_operation_t op)
- typedef globus_result_t(globus_xio_driver_write)(void driver_speci c_handle, const globus_xio_iovec_t iovec, int iovec_count, globus_xio_operation_t op)

Functions

- globus_result_t globus_xio_driver_handle_cntl(globus_xio_driver_handle_t handle, globus_xio_driver_-t driver, int cmd,...)
- void globus_xio_driver_finished_accept(globus_xio_operation_t op, void driver_link, globus_result_t result)
- globus_result_t globus_xio_driver_pass_open(globus_xio_operation_t op, const globus_xio_contact_-t contact_info, globus_xio_driver_callback_t cb, void user_arg)
- void globus_xio_driver_finished_open(void driver_handle, globus_xio_operation_t op, globus_result_t result)
- globus_result_t globus_xio_driver_operation_create(globus_xio_operation_t operation, globus_xio_driver_-handle_t handle)
- globus_bool_t globus_xio_driver_operation_is_blocking(globus_xio_operation_t operation)
- globus_result_t globus_xio_driver_pass_close(globus_xio_operation_t op, globus_xio_driver_callback_t cb, void user_arg)
- void globus_xio_driver_finished_close(globus_xio_operation_t op, globus_result_t result)
- globus_result_t globus_xio_driver_pass_read(globus_xio_operation_t op, globus_xio_iovec_t iovec, int iovec_count, globus_size_t wait_for, globus_xio_driver_data_callback_t cb, void user_arg)
- void globus_xio_driver_finished_read(globus_xio_operation_t op, globus_result_t result, globus_size_t nread)
- void globus_xio_driver_set_eof_received(globus_xio_operation_t op)
- globus_bool_t globus_xio_driver_eof_received(globus_xio_operation_t op)
- globus_result_t globus_xio_driver_pass_write(globus_xio_operation_t op, globus_xio_iovec_t iovec, int iovec_count, globus_size_t wait_for, globus_xio_driver_data_callback_t cb, void user_arg)
- void globus_xio_driver_finished_write(globus_xio_operation_t op, globus_result_t result, globus_size_t nwritten)
- globus_result_t globus_xio_driver_merge_operation(globus_xio_operation_t top_op, globus_xio_operation_t bottom_op)

6.4.1 Detailed Description

The set of interface functions that the driver author must implement to create a driver and the functions to assist in the creation.

Driver attribute functions

If the driver wishes to provide driver specific attributes to the user it must implement the following functions:

globus_xio_driver_attr_init_t globus_xio_driver_attr_copy_t globus_xio_driver_attr_cntl_t globus_xio_driver_attr_-destroy_t

6.4.2 Typedef Documentation

6.4.2.1 typedef void(globus_xio_driver_callback_t)(globus_xio_operation_t op, globus_result_t result, void user_arg)

callback interface

This is the function signature of callbacks for the globus_xio_driver_open/close().

Parameters:
  op The operation structure associated with the open or the close requested operation. The driver should call the appropriate finished operation to clean up this structure.

  result The result of the requested data operation

  user_arg The user pointer that is threaded through to the callback.

6.4.2.2 typedef void(globus_xio_driver_data_callback_t)(globus_xio_operation_t op, globus_result_t result, globus_size_t nbytes, void user_arg)

Data Callback interface.

This is the function signature of read and write operation callbacks.

Parameters:

op The operation structure associated with the read or write operation request. The driver should call the appror- iate nished operation when it receives this operation.

result The result of the requested data operation

nbytes the number of bytes read or written

user_arg The user pointer that is threaded through to the callback.

6.4.2.3 typedef globus_result_t(globus_xio_driver_attr_init_t)(void out_driver_attr)

Create a driver speci c attribute.

The driver should implement this function to create a driver speci c attribute and return it via the out_attr parameter.

6.4.2.4 typedef globus_result_t(globus_xio_driver_attr_copy_t)(void dst, void src)

Copy a driver attr.

When this function is called the driver will create a copy of the attr in parameter src and place it in the parameter dst.

6.4.2.5 typedef globus_result_t(globus_xio_driver_attr_destroy_t)(void driver_attr)

Destroy the driver attr.

Clean up all resources associate with the attr.

6.4.2.6 typedef globus_result_t(globus_xio_driver_attr_cntl_t)(void attr, int cmd, va_list ap)

get or set information in an attr.

The cmd parameter determines what functionality the user is requesting. The driver is resonsible for providing docu- mentation to the user on all the possible values that cmd can be.

Parameters:

driver_attr The driver speci c attr, created by globus_xio_driver_attr_init_t.

cmd An integer representing what functionality the user is requesting.

ap variable arguments. These are determined by the driver and the value of cmd.

6.4.2.7 typedef globus_result_t(globus_xio_driver_server_init_t)(void driver_attr, const globus_xio_- contact_t contact_info, globus_xio_operation_t op)

Initialize a server object.

The driver developer should implement this function if their driver handles server operations (pasive opens). In the tcp driver this function should create a listener.

Parameters:

    op An op which should be passed to globus_xio_driver_server_created. Note, that unlike most operations, the server is created from the bottom of the stack to the top.

    contact_info This the contact info for the stack below this driver. (entries will always be NULL for the transport driver)

    driver_attr A server attr if the user speci ed any driver speci c attributes. This may be NULL.

Returns:

    Returning GLOBUS_SUCCESS for this means that ` globus_xio_driver_pass_server_init returned success and the driver's server was successfully initialized.

6.4.2.8   typedef globus_result_t(globus_xio_driver_server_destroy_)(void   driver_server)

destroy a server.

When this function is called the driver should free up all resources associated with a server.

Parameters:

    server The server that the driver should clean up.

    driver_server The reference to the iunternal server that is being declaired invaild with this function call.

6.4.2.9   typedef globus_result_t(globus_xio_driver_server_accept_)(void   driver_server, globus_xio_-operation_t op)

Accept a server connection.

The driver developer should implement this function if their driver handles server operations. Once the accept operation completes, the connection is established. The user still has an opertunity to open the link or destroy it. They can query the link for additional information on which to base the decision to open.

Parameters:

    driver_server The server object from which the link connection will be accepted.

    op The requested operation. When the driver is nished acepting the server connection it uses this structure to signal globus_xio that it has completed the operation.

6.4.2.10   typedef globus_result_t(globus_xio_driver_server_cntl_)(void   driver_server, int cmd, va_list ap)

Query a server for information.

This function allows a user to request information from a driver speci c server handle.

Parameters:

    driver_server the server handle.

    cmd An integer telling the driver what operation to preform on this server handle.

    ap variable args.

6.4.2.11   typedef globus_result_t(globus_xio_driver_link_destroy_t)(void   driver_link)

destroy a link

The driver should clean up all resources associated with the link when this function is called.

Parameters:
    driver_link The link to be destroyed.

6.4.2.12   typedef globus_result_t(globus_xio_driver_transform_open_t)(const globus_xio_contact_t
contact_info, void   driver_link, void   driver_attr, globus_xio_operation_t op)

Open a handle.

This is called when a user requests to open a handle.

Parameters:
    driver_link Comes from server accept. Used to link an accepted connection to an xio handle. xio will destroy
        this object upon the return of this interface call.
    driver_attr A attribute describing how to open. This points to a piece of memory created by the globus_xio_-
        driver_driver_attr_init_t interface funstion.
    contact_info Contains information about the requested resource. Its members may all be null (especially when
        link is not null). XIO will destroy this contact info upon return from the interface function
    op The requested operation. When the driver is nished opening the handle it uses this structure to signal globus_-
        xio that it has completed the operation requested. It does this by calling globus_xio_driver_ nished_open()

6.4.2.13   typedef globus_result_t(globus_xio_driver_transport_open_t)(const globus_xio_contact_t
contact_info, void   driver_link, void   driver_attr, globus_xio_operation_t op)

transport open

6.4.2.14   typedef globus_result_t(globus_xio_driver_handle_cntl_t)(void   handle, int cmd, va_list ap)

this call must return an GLOBUS_XIO_ERROR_COMMAND error for unsupported command numbers.

(use GlobusXIOErrorInvalidCommand(cmd))

Drivers that have reason to support the commands listed in globus_xio_handle_cmd_t should accept the xio generic
cmd numbers and their driver speci c command number. Do NOT implement those handle cntls unless you really are
the de nitive source.

6.4.2.15   typedef globus_result_t(globus_xio_driver_close_t)(void   driver_handle, void   driver_attr,
globus_xio_operation_t op)

Close an open handle.

This is called when a user requests to close a handle. The driver implemntor should clean up all resources connected
to there driver handle when this function is called.

Parameters:
    driver_speci c_handle The driver handle to be closed.
    driver_attr A driver speci c attr which may be used to alter how a close is performed (e,g, caching drivers)
    op The requested operation. When the driver is nished closing the handle it uses this structure to signal globus_-
        xio that it has completed the operation requested. It does this by calling globus_xio_driver_ nished_close()

6.4.2.16   typedef globus_result_t(globus_xio_driver_read_t)(void   driver_speci c_handle, const globus_-
xio_iovec_t   iovec, int iovec_count, globus_xio_operation_t op)

Read data from an open handle.

This function is called when the user requests to read data from a handle. The driver author shall implement all code
needed to for there driver to complete a read operations.

Parameters:
    driver_handle The driver handle from which data should be read.

    iovec An io vector pointing to the buffers to be read into.

    iovec_count The number if entries in the io vector.

    op The requested operation. When the driver is nished full lling the requested read operation it must use this
       structure to signal globus_xio that the operation is completed. This is done by calling globus_xio_driver_-
       nished_operation()..

6.4.2.17   typedef globus_result_t(globus_xio_driver_write_t)(void   driver_speci c_handle, const globus_-
xio_iovec_t   iovec, int iovec_count, globus_xio_operation_t op)

Write data from an open handle.

This function is called when the user requests to write data to a handle. The driver author shall implement all code
needed to for there driver to complete write operations.

Parameters:
    driver_handle The driver handle to which data should be writen.

    iovec An io vector pointing to the buffers to be written.

    iovec_count The number if entries in the io vector.

    op The requested operation. When the driver is nished full lling the requested read operation it must use this
       structure to signal globus_xio that the operation is completed. This is done by calling globus_xio_driver_-
       nished_operation()..

6.4.3   Function Documentation

6.4.3.1   globus_result_t globus_xio_driver_handle_cntl (globus_xio_driver_handle_t handle,   globus_xio_-
driver_t driver, int cmd, ...)

Touch driver speci c information in a handle object.

pass the driver to control a speci c driver pass NULL for driver for XIO speci c cntls pass GLOBUS_XIO_QUERY
for driver to try each driver (below current) in order

6.4.3.2   void globus_xio_driver_ nished_accept (globus_xio_operation_t op, void   driver_link, globus_result_t
result)

Driver API nished accept.

This function should be called to signal globus_xio that it has completed the accept operation requested of it. It will
free up resources associated with the accept_op and potientially cause xio to pop the signal up the driver stack.

Parameters:
    op The requested accept operation that has completed.

driver_link This is the initialized driver link that is that will be passed to the open interface when this handle is
     opened.

result Return status of the completed operation

6.4.3.3   globus_result_t globus_xio_driver_pass_open (globus_xio_operation op, **const globus_xio_contact_t**
  contact_info, globus_xio_driver_callback_t cb, **void** user_arg)

Driver API Open.

This function will pass an open request down the driver stack. Upon completion of the open operation globus_xio will
call the cb function, at which point the handle structure will be intialized and available for use.

As soon as the function returns the handle is valid for creating other operations.

Parameters:
     op The operation from which the handle will be established. This parameter is used to determine what drivers are
          in the stack and other such information.

     contact_info The contact info describing the resource the driver below should open. This will normally be the
          same contact info that was passed in on the open interface.

     cb The function to be called wehn the open operation is complete.

     user_arg a user pointer that will be threaded through to the callback.

6.4.3.4   void globus_xio_driver_ nished_open (void driver_handle, **globus_xio_operation_t** op, **globus_-**
result_t result)

Driver API nished open.

This function should be called to signal globus_xio that it has completed the open operation requested of it. It will free
up resources associated with the op and potientially cause xio to pop the signal up the driver stack.

Parameters:
     driver_handle The driver speci c handle pointer that will be passed to future interface funstion calls.

     op The requested open operation that has completed.

     result Return status of the completed operation

6.4.3.5   globus_result_t globus_xio_driver_operation_create (globus_xio_operation_t operation, **globus_-**
xio_driver_handle_t handle)

Driver API Create Operation.

This function will create an operation from an initialized handle This operation can then be used for io operations
related to the handle that created them.

Parameters:
     operation The operation to be created. When this function returns this structure will be populated and available
          for use for the driver.

     handle The initialized handle representing the user handle from which the operation will be created.

6.4.3.6 globus_bool_t globus_xio_driver_operation_is_blocking (globus_xio_operation_t operation)

Is Operation blocking.

If the operation is blocking the driver developer may be able to make certian optimizations. The function returns true if the given operation was created via a user call to a blocking funciton.

6.4.3.7 globus_result_t globus_xio_driver_pass_close (globus_xio_operation_t op, globus_xio_driver_-callback_t cb, void * user_arg)

Driver API Close.

This function will pass a close request down the driver stack. Upon completion of the close operation globus_xio will call the funciton pointed to by the cb arguement.

Parameters:
  op The operation to pass along the driver stack for closing.

  cb A pointer to the function to be called once all drivers lower in the stack have closed.

  user_arg A user pointer that will be threaded through to the callback.

6.4.3.8 void globus_xio_driver_finished_close (globus_xio_operation_t op, globus_result_t result)

Driver API finished_close.

The driver calls this function after completing a close operation on a driver_handle. Once this function returns the driver_handle is no longer valid.

Parameters:
  op The close operation that has completed.

  result Return status of the completed operation

6.4.3.9 globus_result_t globus_xio_driver_pass_read (globus_xio_operation_t op, globus_xio_iovec_t * iovec, int iovec_count, globus_size_t wait_for, globus_xio_driver_data_callback_t cb, void * user_arg)

Driver read.

This function passes a read operation down the driver stack. After this function is called the op structure is no longer valid. However when the driver stack finishes servicing the read request it will pass a new operation structure in the funciton pointed to by cb. Finishe read can be called on the new operation received.

Parameters:
  op The operation structure representing this requested io operation.

  iovec A pointer to the array of iovecs.

  iovec_count The number of iovecs in the array.

  wait_for The minimum number of bytes to read before returning... if a driver has no specifc requirement, he should use the user's request... available via GlobusXIOOperationMinimumRead(op)

  cb The function to be called when the operation request is completed.

  user_arg A user pointer that will be threaded through to the callback.

6.4.3.10   void globus_xio_driver_ nished_read (globus_xio_operation_t op, globus_result_t result, globus_-size_t nread)

Finished Read.

This function is called to signal globus_xio that the requested read operation has been completed.

Parameters:

  op The operation structure representing the requested read operation.

  result Return status of the completed operation

  nread The number of bytes read

6.4.3.11   void globus_xio_driver_set_eof_received (globus_xio_operation_t op)

EOF state manipulation.

This function is used by drivers that allow multiple outstanding reads at a time. It can only be called on behalf of a read operation (while in the read interface call or the pass_read callback).

Typical use for this would be to hold a driver speci c lock and call this when an internal eof has been received. The read operation this is called on behalf of must be nished with an eof error or the results are unde ned.

In general, you should not have an eof ag in your driver. Use this call and globus_xio_driver_eof_received() instead. This is necessary to support xio's automatic eof resetting. If your driver absolutely can not be read after an eof has been set, then you will need your own eof ag.

This call will typically only be used just before a nished_read() call.

Parameters:

  op The operation structure representing the requested read operation.

6.4.3.12   globus_bool_t globus_xio_driver_eof_received (globus_xio_operation_t op)

EOF state checking.

This function is used by drivers that allow multiple outstanding reads at a time. It can only be called on behalf of a read operation (while in the read interface call or the pass_read callback).

Typical use for this would be to hold a driver speci c lock (the same one used when calling globus_xio_driver_set_-eof_received()) and call this to see if an eof has been received. If so, the operation should immediately be nished with an eof error (do not _return_ an eof error).

This call will typically only be used in the read interface call.

Parameters:

  op The operation structure representing the requested read operation.

Returns:

  GLOBUS_TRUE if eof received, GLOBUS_FALSE otherwise.

6.4.3.13   globus_result_t globus_xio_driver_pass_write (globus_xio_operation_t op, globus_xio_iovec_t iovec, int iovec_count, globus_size_t wait_for, globus_xio_driver_data_callback_t cb, void user_arg)

Driver write.

This function passes a write operation down the driver stack. After this function is called the op structure is no longer valid. However when the driver stack nishes servicing the write request it will pass a new operation structure in the funciton pointed to by cb. Finished write can be called on the new operation received.

Parameters:

op The operation structure representing this requested io operation.

iovec A pointer to the array of iovecs.

iovec_count The number of iovecs in the array.

wait_for The minimum number of bytes to write before returning... if a driver has no specifc requirement, he should use the user's request... available via GlobusXIOOperationMinimumWrite(op)

cb The function to be called when the operation request is completed.

user_arg A user pointer that will be threaded through to the callback.

6.4.3.14   void globus_xio_driver_ nished_write (globus_xio_operation_t op, globus_result_t result, globus_-size_t nwritten)

Finished Write.

This function is called to signal globus_xio that the requested write operation has been completed.

Parameters:

op The operation structure representing the requested write operation.

result Return status of the completed operation

nwritten The number of bytes written

6.4.3.15   globus_result_t globus_xio_driver_merge_operation (globus_xio_operation_t top_op, globus_xio_-operation_t bottom_op)

Finishes an operation and merge two op structures.

(XXX not implemented yet)

This function will join to operations together and signal globus_xio that it has completed. This is an advanced function. Most drivers will not require its use. This function takes an operation that was created by this driver and passed on to drivers lower on the stack and an operation that came in on the interface function (that has seen the top half of the stack) and joins them together. The purpose of this function is to join data descriptors that were prestaged and cached with those that have later come in at the users request. See the read ahead doc for more information.

Parameters:

top_op The operation that has seen the top part of the driver stack.

bottom_op The operation that has seen the bottom part of the driver stack.

(result is always success in this case.. if there is an error, use the other nish() call)

6.5   Driver Programming: String options

A driver can choose to expose parameters as in a string form.

Functions

- globus_result_t globus_xio_string_cntl_bounce (globus_xio_driver_attr_cntl_t cntl_func, void attr, int cmd,...)
- globus_result_t globus_xio_string_cntl_bool (void attr, const char key, const char val, int cmd, globus_xio_-driver_attr_cntl_t cntl_func)
- globus_result_t globus_xio_string_cntl_ oat (void attr, const char key, const char val, int cmd, globus_xio_-driver_attr_cntl_t cntl_func)
- globus_result_t globus_xio_string_cntl_int (void attr, const char key, const char val, int cmd, globus_xio_-driver_attr_cntl_t cntl_func)
- globus_result_t globus_xio_string_cntl_string (void attr, const char key, const char val, int cmd, globus_-xio_driver_attr_cntl_t cntl_func)
- globus_result_t globus_xio_string_cntl_int_int (void attr, const char key, const char val, int cmd, globus_-xio_driver_attr_cntl_t cntl_func)

6.5.1 Detailed Description

A driver can choose to expose parameters as in a string form.

Providing this feature makes dynamicly setting driver speci c options much easier. a user can then load the driver by name and set speci c options by name all at runtime with no object module references. For example, a TCP driver can be loaded with the string: tcp, and the options can be set with:

port=50668#keepalive=yes#nodelay=N

this would set the port to 50668, keepalive to true and nodelay to false. The particular string de nition is de ned by the tcp driver by properly creating a globus_i_xio_attr_parse_table_t array. Each element of the array is 1 options. There are 3 members of each array entry: key, cmd, and parse function. The key is a string that de nes what option is to be set. In the above example string "port" would be 1 key. cmd tells the driver what cntl is associated with the key. In otherwords, once the string is parsed out what driver speci c control must be called to set the requested option. For more information on controls see globus_xio_attr_cntl. The nal value in the array entry is the parsing function. The pasing function takes the value of the = portion of the string and parses it into data types. once parsed globus_xio_attr_cntl is called and thus the option is set. There are many available parsing functions but the developer is free to right their own if the provided ones are not suf cient. Sample parsing functions follow:

- globus_xio_string_cntl_bool
- globus_xio_string_cntl_ oat
- globus_xio_string_cntl_int
- globus_xio_string_cntl_string
- globus_xio_string_cntl_int_int

6.5.2 Function Documentation

6.5.2.1 globus_result_t globus_xio_string_cntl_bounce (globus_xio_driver_attr_cntl_t cntl_func, void attr, int cmd, ...)

New type functions call this one.

6.5.2.2 globus_result_t globus_xio_string_cntl_bool (void attr, const char key, const char val, int cmd, globus_xio_driver_attr_cntl_t cntl_func)

String option parsing function.

6.5.2.3   globus_result_t globus_xio_string_cntl_ oat (void attr, const char key, const char val, int cmd, [globus_xio_driver_attr_cntl_t](#) **cntl_func)**

String option parsing function.

6.5.2.4   globus_result_t globus_xio_string_cntl_int (void attr, const char key, const char val, int cmd, [globus_xio_driver_attr_cntl_t](#) **cntl_func)**

String option parsing function.

6.5.2.5   globus_result_t globus_xio_string_cntl_string (void attr, const char key, const char val, int cmd, [globus_xio_driver_attr_cntl_t](#) **cntl_func)**

String option parsing function.

6.5.2.6   globus_result_t globus_xio_string_cntl_int_int (void attr, const char key, const char val, int cmd, [globus_xio_driver_attr_cntl_t](#) **cntl_func)**

String option parsing function.

6.6   Globus XIO File Driver

The File I/O driver.

Modules

- [Opening/Closing](#)
- [Reading/Writing](#)
- [Env Variables](#)
- [Attributes and Cntls](#)
- [Types](#)
- [Error Types](#)

6.6.1   Detailed Description

The File I/O driver.

6.7   Opening/Closing

An XIO handle with the le driver can be created with [globus_xio_handle_create()](#)

If there is no handle set on the attr passed to the [globus_xio_open](#)() call, it performs the equivalent of an open() call. In this case, the contact string must contain either a pathname or one of stdin://, stdout://, or stderr://. If a pathname is used, that path is opened. If one of the schemes are used the corresponding stdio handle is used (retrieved with leno()).

In either of the above cases, it is most ef cient to call the blocking version of [globus_xio_open()](#) It is also safe to call within a locked critical section.

When the XIO handle is closed, the le driver will destroy its internal resources and close the fd (unless this fd was set on an attr or converted from one of the stdio handles).

6.8 Reading/Writing

Both the globus_xio_register_read() and globus_xio_register_write() calls follow similar semantics as described be-low.

If the waitforbytes parameter is greater than zero, the io will happen asynchronously and be completed when at least waitforbytes has been read/written.

If the waitforbytes parameter is equal to zero, one of the following alternative behaviors occur:

If the length of the buffer is > 0 the read or write happens synchronously. If the user is using one of the blocking xio calls, no internal callback will occur.

If the length of the buffer is also 0, the call behaves like an asynchronous noti cation of data ready to be either read or written. ie, an asynchronous select().

In any case, when an error or EOF occurs before the waitforbytes request has been met, the outgoing nbytes is set to the amount of data actually read/written before the error or EOF occurred.

You may either use GLOBUS_XIO_FILE_SEEK or GLOBUS_XIO_SEEK to position the le pointer before each read or write or you can specify the desired offset on a data descriptor with the xio cmd, GLOBUS_XIO_DD_SET_-OFFSET. simultaneous reading and writing is only predictable if the data descriptor method is used.

6.9 Env Variables

The le driver uses the following environment variables

- GLOBUS_XIO_FILE_DEBUG Available if using a debug build. See globus_debug.h for format. The File driver de nes the levels TRACE for all function call tracing and INFO for write buffer sizes

- GLOBUS_XIO_SYSTEM_DEBUG Available if using a debug build. See globus_debug.h for format. The File driver uses globus_xio_system (along with the TCP and UDP drivers) which de nes the following levels: TRACE for all function call tracing, DATA for data read and written counts, INFO for some special events, and RAW which dumps the raw buffers actually read or written. This can contain binary data, so be careful when you enable it.

6.10 Attributes and Cntls

Enumerations

- enum globus_xio_ le_attr_cmd_t {
  GLOBUS_XIO_FILE_SET_MODE,
  GLOBUS_XIO_FILE_GET_MODE,
  GLOBUS_XIO_FILE_SET_FLAGS,
  GLOBUS_XIO_FILE_GET_FLAGS,
  GLOBUS_XIO_FILE_SET_TRUNC_OFFSET,
  GLOBUS_XIO_FILE_GET_TRUNC_OFFSET,
  GLOBUS_XIO_FILE_SET_HANDLE,
  GLOBUS_XIO_FILE_GET_HANDLE,
  GLOBUS_XIO_FILE_SET_BLOCKING_IO,
  GLOBUS_XIO_FILE_GET_BLOCKING_IO,
  GLOBUS_XIO_FILE_SEEK }

Functions

- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_MODE, int mode)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_MODE, int mode_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_FLAGS, int ags)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_FLAGS, int ags_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_TRUNC_OFFSET, globus_off_t offset)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_TRUNC_OFFSET, globus_off_t offset_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_HANDLE, globus_xio_system_- le_t handle)
- globus_result_t globus_xio_attr_cntl (attr,   driver,   GLOBUS_XIO_FILE_GET_HANDLE, globus_xio_- system_ le_t handle_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_FILE_GET_HANDLE, globus_xio_- system_ le_t handle_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_BLOCKING_IO, globus_bool_t use_blocking_io)
- globus_result_t globus_xio_handle_cntl (handle,   driver,   GLOBUS_XIO_FILE_SET_BLOCKING_IO, globus_bool_t use_blocking_io)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_BLOCKING_IO, globus_bool_t use_blocking_io_out)
- globus_result_t globus_xio_handle_cntl (handle,   driver,   GLOBUS_XIO_FILE_GET_BLOCKING_IO, globus_bool_t use_blocking_io_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_FILE_SEEK, globus_off_t in_out_- offset, globus_xio_ le_whence_t whence)

6.10.1   Detailed Description

File driver speci c attrs and cntls.

See also:
  globus_xio_attr_cntl()
  globus_xio_handle_cntl()

6.10.2   Enumeration Type Documentation

6.10.2.1   enum globus_xio_ le_attr_cmd_t

File driver speci c cntls.

Enumeration values:
  GLOBUS_XIO_FILE_SET_MODE   See usage for globus_xio_attr_cntl
  GLOBUS_XIO_FILE_GET_MODE   See usage for globus_xio_attr_cntl
  GLOBUS_XIO_FILE_SET_FLAGS   See usage for globus_xio_attr_cntl
  GLOBUS_XIO_FILE_GET_FLAGS   See usage for globus_xio_attr_cntl
  GLOBUS_XIO_FILE_SET_TRUNC_OFFSET See usage for globus_xio_attr_cntl
  GLOBUS_XIO_FILE_GET_TRUNC_OFFSET See usage for globus_xio_attr_cntl
  GLOBUS_XIO_FILE_SET_HANDLE   See usage for globus_xio_attr_cntl

GLOBUS_XIO_FILE_GET_HANDLE See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_FILE_SET_BLOCKING_IO See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_FILE_GET_BLOCKING_IO See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_FILE_SEEK See usage for globus_xio_handle_cntl

6.10.3 Function Documentation

6.10.3.1 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_MODE, int mode)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the le create mode. Use this to set the permissions a non-existent le is created with, The default mode is 0644.

Parameters:
    mode A bitwise OR of all the modes desired

See also:
    globus_xio_ le_mode_t

string opt: mode=

6.10.3.2 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_MODE, int mode_-out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the le create mode.

Parameters:
    mode_out The current mode will be stored here.

6.10.3.3 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_FLAGS, int ags)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the le open ags. The default ags specify to create the le if it doesn't exist, open it for reading and writing, and interpret it as a binary le.

Parameters:
    ags A bitwise OR of all the ags desired

See also:
    globus_xio_ le_ ag_t

string opt: ags=

6.10.3.4   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_FLAGS, int   ags_-out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the le open ags.

Parameters:
    ags_out The current ags will be stored here.

6.10.3.5   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_TRUNC_OFFSET, globus_off_t offset)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the le truncate offset. Use this in conjunction with the GLOBUS_XIO_FILE_TRUNC ag to truncate a le to a non-zero offset. If the le was larger than offset bytes, the extra data is lost. If the le was shorter or non-existent, it is extended and the extended part reads as zeros. (default is 0)

Parameters:
    offset The desired size of the le.

6.10.3.6   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_TRUNC_OFFSET, globus_off_t   offset_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the le truncate offset.

Parameters:
    offset_out The offset will be stored here.

6.10.3.7   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_HANDLE, globus_-xio_system_ le_t handle)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the le handle to use. Do not open a new le, use this preopened handle instead.

Parameters:
    handle Use this handle (fd or HANDLE) for the le. Note: close() will not be called on this handle.

6.10.3.8   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_HANDLE, globus_-xio_system_ le_t   handle_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the le handle in use or in attr.

Parameters:
    handle_out The le handle (fd or HANDLE) will be stored here.   If none is set, GLOBUS_XIO_TCP_-
        INVALID_HANDLE will be set.

6.10.3.9   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_FILE_GET_HANDLE, globus_xio_system_ le_t handle_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the le handle in use or in attr.

Parameters:
    handle_out The le handle (fd or HANDLE) will be stored here.   If none is set, GLOBUS_XIO_TCP_-
        INVALID_HANDLE will be set.

6.10.3.10   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_BLOCKING_IO, globus_bool_t use_blocking_io)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Enable true blocking io when making globus_xio_read/write() calls. Note: use with caution. you can deadlock an entire app with this.

Parameters:
    use_blocking_io If GLOBUS_TRUE, true blocking io will be enabled. GLOBUS_FALSE will disable it (de-
        fault);

6.10.3.11   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_FILE_SET_BLOCKING_- IO, globus_bool_t use_blocking_io)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Enable true blocking io when making globus_xio_read/write() calls. Note: use with caution. you can deadlock an entire app with this.

Parameters:
    use_blocking_io If GLOBUS_TRUE, true blocking io will be enabled. GLOBUS_FALSE will disable it (de-
        fault);

6.10.3.12   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_BLOCKING_IO, globus_bool_t use_blocking_io_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the blocking io status in use or in attr.

Parameters:
    use_blocking_io_out The ag will be set here. GLOBUS_TRUE for enabled.

string opt: blocking=

6.10.3.13 globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_FILE_GET_-BLOCKING_IO, globus_bool_t use_blocking_io_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the blocking io status in use or in attr.

Parameters:
    use_blocking_io_out The ag will be set here. GLOBUS_TRUE for enabled.

string opt: blocking=

6.10.3.14 globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_FILE_SEEK, globus_off_t in_out_offset, globus_xio_ le_whence_t whence)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Reposition read/write le offset.

Parameters:
    in_out_offset Specify the desired offset (according to whence). On success, the actual le offset will be stored here.

    whence Specify how offset should be interpreted.

See also:
    globus_xio_ le_whence_t
    GLOBUS_XIO_SEEK

6.11 Types

De nes

- #de ne GLOBUS_XIO_FILE_INVALID_HANDLE

Enumerations

- enum globus_xio_ le_ ag_t {
  GLOBUS_XIO_FILE_CREAT = O_CREAT,
  GLOBUS_XIO_FILE_EXCL = O_EXCL,
  GLOBUS_XIO_FILE_RDONLY = O_RDONLY,
  GLOBUS_XIO_FILE_WRONLY = O_WRONLY,
  GLOBUS_XIO_FILE_RDWR = O_RDWR,
  GLOBUS_XIO_FILE_TRUNC = O_TRUNC,
  GLOBUS_XIO_FILE_APPEND = O_APPEND,
  GLOBUS_XIO_FILE_BINARY = 0,
  GLOBUS_XIO_FILE_TEXT = 0 }

- enum globus_xio_file_mode_t {
  GLOBUS_XIO_FILE_IRWXU = S_IRWXU,
  GLOBUS_XIO_FILE_IRUSR = S_IRUSR,
  GLOBUS_XIO_FILE_IWUSR = S_IWUSR,
  GLOBUS_XIO_FILE_IXUSR = S_IXUSR,
  GLOBUS_XIO_FILE_IRWXO = S_IRWXO,
  GLOBUS_XIO_FILE_IROTH = S_IROTH,
  GLOBUS_XIO_FILE_IWOTH = S_IWOTH,
  GLOBUS_XIO_FILE_IXOTH = S_IXOTH,
  GLOBUS_XIO_FILE_IRWXG = S_IRWXG,
  GLOBUS_XIO_FILE_IRGRP = S_IRGRP,
  GLOBUS_XIO_FILE_IWGRP = S_IWGRP,
  GLOBUS_XIO_FILE_IXGRP = S_IXGRP }
- enum globus_xio_file_whence_t {
  GLOBUS_XIO_FILE_SEEK_SET = SEEK_SET,
  GLOBUS_XIO_FILE_SEEK_CUR = SEEK_CUR,
  GLOBUS_XIO_FILE_SEEK_END = SEEK_END }

6.11.1 Define Documentation

6.11.1.1 #define GLOBUS_XIO_FILE_INVALID_HANDLE

Invalid handle type.

See also:
GLOBUS_XIO_FILE_SET_HANDLE

6.11.2 Enumeration Type Documentation

6.11.2.1 enum globus_xio_file_flag_t

File driver open flags.

OR together all the flags you want

See also:
GLOBUS_XIO_FILE_SET_FLAGS

Enumeration values:
GLOBUS_XIO_FILE_CREAT Create a new file if it doesn't exist (default).
GLOBUS_XIO_FILE_EXCL Fail if file already exists.
GLOBUS_XIO_FILE_RDONLY Open for read only.
GLOBUS_XIO_FILE_WRONLY Open for write only.
GLOBUS_XIO_FILE_RDWR Open for reading and writing (default).
GLOBUS_XIO_FILE_TRUNC Truncate file.
See also:
GLOBUS_XIO_FILE_SET_TRUNC_OFFSET

GLOBUS_XIO_FILE_APPEND Open le for appending.

GLOBUS_XIO_FILE_BINARY   File is binary (default).

GLOBUS_XIO_FILE_TEXT   File is text.

6.11.2.2   enum globus_xio_ le_mode_t

File driver create mode.

OR these modes together to get the mode you want.

See also:
   GLOBUS_XIO_FILE_SET_MODE

NOTE: for Win32, you only have a choice between read-only and read-write. If the chosen mode does not specify writability, the le will be read only

Enumeration values:
   GLOBUS_XIO_FILE_IRWXU   User read, write, and execute.

   GLOBUS_XIO_FILE_IRUSR   User read.

   GLOBUS_XIO_FILE_IWUSR   User write.

   GLOBUS_XIO_FILE_IXUSR   User execute.

   GLOBUS_XIO_FILE_IRWXO   Others read, write, and execute.

   GLOBUS_XIO_FILE_IROTH   Others read.

   GLOBUS_XIO_FILE_IWOTH   Others write.

   GLOBUS_XIO_FILE_IXOTH   Others execute.

   GLOBUS_XIO_FILE_IRWXG   Group read, write, and execute.

   GLOBUS_XIO_FILE_IRGRP   Group read.

   GLOBUS_XIO_FILE_IWGRP   Group write.

   GLOBUS_XIO_FILE_IXGRP   Group execute.

6.11.2.3   enum globus_xio_ le_whence_t

File driver seek options.

See also:
   GLOBUS_XIO_FILE_SEEK

Enumeration values:
   GLOBUS_XIO_FILE_SEEK_SET set the le pointer at the speci ed offset

   GLOBUS_XIO_FILE_SEEK_CUR set the le pointer at current position + offset

   GLOBUS_XIO_FILE_SEEK_END set the le pointer at size of le + offest

6.12   Error Types

The File driver is very close to the system code, so most errors reported by it are converted from the system errno. A few of the exceptions are GLOBUS_XIO_ERROR_EOF, GLOBUS_XIO_ERROR_COMMAND, GLOBUS_XIO_-ERROR_CONTACT_STRING, and GLOBUS_XIO_ERROR_CANCELED

See also:
   globus_error_errno_match()

6.13 Globus XIO HTTP Driver

This driver implements the HTTP/1.0 and HTTP/1.1 protocols within the Globus XIO framework.

Modules

- Opening/Closing
- Reading/Writing
- Server
- Attributes and Cntls
- Error Types

Data Structures

- struct globus_xio_http_header_t

    HTTP Header.

Enumerations

- enum globus_xio_http_version_t {,

    GLOBUS_XIO_HTTP_VERSION_1_0,

    GLOBUS_XIO_HTTP_VERSION_1_1 }

6.13.1 Detailed Description

This driver implements the HTTP/1.0 and HTTP/1.1 protocols within the Globus XIO framework.

It may be used with the tcp driver for the standard HTTP protcol stack, or may be combined with the gsi driver for a HTTPS implementation.

This implementation supports user-de ned HTTP headers, persistent connections, and chunked transfer encoding.

6.13.2 Enumeration Type Documentation

6.13.2.1 enum globus_xio_http_version_t

Valid HTTP versions, used with the GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_HTTP_VERSION attribute and the GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_HTTP_VERSION handle control.

Enumeration values:
    GLOBUS_XIO_HTTP_VERSION_1_0 HTTP/1.0.

    GLOBUS_XIO_HTTP_VERSION_1_1 HTTP/1.1.

6.14 Opening/Closing

An XIO handle with the http driver can be created with either globus_xio_handle_create() or globus_xio_server_-register_accept().

If the handle is created with globus_xio_server_register_accept() then an HTTP service handle will be created when globus_xio_register_open() is called. The XIO application must call one of the functions in the globus_xio_read() family to receive the HTTP request metadata. This metadata will be returned in the data descriptor associated with that rst read: the application should use the GLOBUS_XIO_HTTP_GET_REQUEST descriptor cntl to extract this metadata.

If the handle is created with globus_xio_handle_create() then an HTTP client handle will be created when globus_xio_register_open() is called. HTTP request headers, version and method may be chosen by setting attributes.

6.15 Reading/Writing

The HTTP driver behaves similar to the underlying transport driver with respect to reads and writes with the exception that metadata must be passed to the handle via open attributes on the client side and will be received as data descriptors as part of the rst request read or response read.

6.16 Server

The globus_xio_server_create() causes a new transport-speci c listener socket to be created to handle new HTTP connections. globus_xio_server_register_accept() will accept a new connection for processing. globus_xio_server_register_close() cleans up the internal resources associated with the http server and calls close on the listener.

Multiple HTTP requests may be read in sequence from an HTTP server. After each request is processed and the response is sent (either by writing the entire entity body as speci ed by the Content-Length header or by using the GLOBUS_XIO_HTTP_HANDLE_SET_END_OF_ENTITY handle cntl), the next read will contain the metadata related to the next operation. Only one request will be in process at once–the previous request must have sent or received and EOF (whichever is applicable to the request type).

6.17 Attributes and Cntls

Enumerations

- enum globus_xio_http_handle_cmd_t {
  GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_HEADER,
  GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_STATUS_CODE,
  GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_REASON_PHRASE,
  GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_HTTP_VERSION,
  GLOBUS_XIO_HTTP_HANDLE_SET_END_OF_ENTITY }
- enum globus_xio_http_attr_cmd_t {
  GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_METHOD,
  GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_HTTP_VERSION,
  GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_HEADER,
  GLOBUS_XIO_HTTP_ATTR_DELAY_WRITE_HEADER,
  GLOBUS_XIO_HTTP_GET_REQUEST,
  GLOBUS_XIO_HTTP_GET_RESPONSE }

Functions

- globus_result_t globus_xio_handle_cntl (handle,   driver,   GLOBUS_XIO_HTTP_HANDLE_SET_-
  RESPONSE_HEADER, const char header_name, const char header_value)
- globus_result_t globus_xio_handle_cntl (handle,   driver,   GLOBUS_XIO_HTTP_HANDLE_SET_-
  RESPONSE_STATUS_CODE, int status)
- globus_result_t globus_xio_handle_cntl (handle,   driver,   GLOBUS_XIO_HTTP_HANDLE_SET_-
  RESPONSE_REASON_PHRASE, const char reason)
- globus_result_t globus_xio_handle_cntl (handle,   driver,   GLOBUS_XIO_HTTP_HANDLE_SET_-
  RESPONSE_HTTP_VERSION, globus_xio_http_version_t version)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_HTTP_HANDLE_SET_END_OF_-
  ENTITY)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_METHOD,
  const char method)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_HTTP_-
  VERSION, globus_xio_http_version_t version)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_HEADER,
  const char header_name, const char header_value)

6.17.1   Detailed Description

HTTP driver speci c attrs and cntls.

See also:
    globus_xio_attr_cntl()
    globus_xio_handle_cntl()

6.17.2   Enumeration Type Documentation

6.17.2.1   enum globus_xio_http_handle_cmd_t

HTTP driver speci c cntls.

Enumeration values:
    GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_HEADER See usage for globus_xio_handle_cntl

    GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_STATUS_CODE See usage for globus_xio_handle_-
        cntl .

    GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_REASON_PHRASE See usage for: globus_xio_-
        handle_cntl

    GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_HTTP_VERSION See   usage   for: globus_xio_-
        handle_cntl

    GLOBUS_XIO_HTTP_HANDLE_SET_END_OF_ENTITY See usage for globus_xio_handle_cntl

6.17.2.2   enum globus_xio_http_attr_cmd_t

HTTP driver speci c attribute and data descriptor cntls.

Enumeration values:
    GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_METHOD See usage for globus_xio_attr_cntl

GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_HTTP_VERSION See usage for globus_xio_attr_cntl

GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_HEADER See usage for globus_xio_attr_cntl

GLOBUS_XIO_HTTP_ATTR_DELAY_WRITE_HEADER See usage for globus_xio_attr_cntl

GLOBUS_XIO_HTTP_GET_REQUEST See usage for globus_xio_data_descriptor_cntl

GLOBUS_XIO_HTTP_GET_RESPONSE See usage for globus_xio_data_descriptor_cntl

6.17.3   Function Documentation

6.17.3.1   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_HTTP_HANDLE_SET_-RESPONSE_HEADER, const char header_name, const char header_value)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the value of a response HTTP header.

Parameters:
    header_name Name of the HTTP header to set.

    header_value Value of the HTTP header

Certain headers will cause changes in how the HTTP protocol will be handled. These include:

- Transfer-Encoding: {identity, chunked} Override the default transfer encoding. If a server knows the exact length of the message body, or does not intend to support persistent connections, it may set this header to be "identity".

    If this is set to "identity" and any of the following are true, then the connection will be closed after the end of the response is sent:

    - A Content-Length header is not present
    - The HTTP version is set to "HTTP/1.0"
    - The Connection header is set to "close" Attempts to set this to "chunked" with an "HTTP/1.0" client will fail with a GLOBUS_XIO_ERROR_HTTP_INVALID_HEADER error.

- Content-Length: 1Digit

    - Provide a content length for the response message. If the "chunked" transfer encoding is being used, then this header will be silently ignored by the HTTP driver.

- Connection: close

    - The HTTP connection will be closed after the end of the data response is written.

Returns:
    This handle control function can fail with
        - GLOBUS_XIO_ERROR_MEMORY
        - GLOBUS_XIO_ERROR_PARAMETER
        - GLOBUS_XIO_ERROR_HTTP_INVALID_HEADER

6.17.3.2   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_HTTP_HANDLE_SET_-
RESPONSE_STATUS_CODE, int status)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Set the response status code.

Parameters:
    status Value in the range 100-599 which will be used as the HTTP response code, as per RFC 2616.

If this cntl is not called by a server, then the default value of 200 ("Ok") will be used. If this is called on the client-side
of an HTTP connection, the handle control will fail with a GLOBUS_XIO_ERROR_PARAMETER error.

Returns:
    This handle control function can fail with

        • GLOBUS_XIO_ERROR_PARAMETER

6.17.3.3   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_HTTP_HANDLE_SET_-
RESPONSE_REASON_PHRASE, const char reason)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Set the response reason phrase.

Parameters:
    reason The value of the HTTP response string, as per RFC 2616.

If this cntl is not called by a server, then a default value based on the handle's response status code will be generated. If
this is called on the client-side of an HTTP connection, the handle control will fail with a GLOBUS_XIO_ERROR_-
PARAMETER error.

Returns:
    This handle control function can fail with

        • GLOBUS_XIO_ERROR_MEMORY
        • GLOBUS_XIO_ERROR_PARAMETER

6.17.3.4   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_HTTP_HANDLE_SET_-
RESPONSE_HTTP_VERSION, globus_xio_http_version_t version)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Set the response HTTP version.

Parameters:
    version The HTTP version to be used in the server response line.

If this cntl is not called by a server, then the default of GLOBUS_XIO_HTTP_VERSION_1_1 will be used, though
no HTTP/1.1 features (chunking, persistent connections, etc) will be assumed if the client request was an HTTP/1.0
request. If this is called on the client-side of an HTTP connection, the handle control will fail with GLOBUS_XIO_-
ERROR_PARAMETER.

Returns:

   This handle control function can fail with

   • GLOBUS_XIO_ERROR_MEMORY

   • GLOBUS_XIO_ERROR_PARAMETER

**6.17.3.5   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_HTTP_HANDLE_SET_-
END_OF_ENTITY)**

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Indicate end-of-entity for an HTTP body.

HTTP clients and servers must call this command to indicate to the driver that the entity-body which is being sent is
completed. Subsequent attempts to write data on the handle will fail.

This handle command MUST be called on the client side of an HTTP connection when the HTTP method is OPTIONS,
POST, or PUT, or when the open attributes indicate that an entity will be sent. This handle command MUST be called
on the server side of an HTTP request connection when the HTTP method was OPTIONS, GET, POST, or TRACE.

**6.17.3.6   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_-
METHOD, const char method)**

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Set the HTTP method to use for a client request.

Parameters:

   method The request method string ("GET", "PUT", "POST", etc) that will be used in the HTTP request.

If this is not set on the target before it is opened, it will default to GET.

This attribute is ignored when opening the server side of an HTTP connection.

Setting this attribute may fail with

   • GLOBUS_XIO_ERROR_MEMORY

   • GLOBUS_XIO_ERROR_PARAMETER

**6.17.3.7   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_-
HTTP_VERSION, globus_xio_http_version_t version)**

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Set the HTTP version to use for a client request.

Parameters:

   version The HTTP version to use for the client request.

If the client is using HTTP/1.0 in a request which will send a request message body (such as a POST or PUT), then the
client MUST set the "Content-Length" HTTP header to be the length of the message. If this attribute is not present,
then the default of GLOBUS_XIO_HTTP_VERSION_1_1 will be used.

This attribute is ignored when opening the server side of an HTTP connection.

6.17.3.8   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_-
HEADER, const char   header_name, const char   header_value)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Set the value of an HTTP request header.

Parameters:
>   header_nameName of the HTTP header to set.
>   header_valueValue of the HTTP header

Certain headers will cause the HTTP driver to behave differently than normal. This must be called before

- Transfer-Encoding: {identity, chunked} Override the default transfer encoding. If a server knows the exact
  length of the message body, or does not intend to support persistent connections, it may set this header to be
  "identity".

  If this is set to "identity" and any of the following are true, then the connection will be closed after the end of
  the message is sent:

    – A Content-Length header is not present
    – The HTTP version is set to "HTTP/1.0"
    – The Connection header is set to "close" Attempts to set this to "chunked" with an "HTTP/1.0" client will
      fail with a GLOBUS_XIO_ERROR_HTTP_INVALID_HEADER error.

- Content-Length: 1Digit

    – Provide a content length for the response message. If the "chunked" transfer encoding is being used, then
      this header will be silently ignored by the HTTP driver.

- Connection: close

    – If present in the server response, the connection will be closed after the end of the data response is writ-
      ten. Otherwise, when persistent connections are enabled, the connection may be left open by the driver.
      Persistent connections are not yet implemented.

6.18   Error Types

Enumerations

- enum globus_xio_http_errors { t
  GLOBUS_XIO_HTTP_ERROR_INVALID_HEADER,
  GLOBUS_XIO_HTTP_ERROR_PARSE,
  GLOBUS_XIO_HTTP_ERROR_NO_ENTITY,
  GLOBUS_XIO_HTTP_ERROR_EOF,
  GLOBUS_XIO_HTTP_ERROR_PERSISTENT_CONNECTION_DROPPED }

6.18.1   Detailed Description

In addition to errors generated by underlying protocol drivers, the XIO HTTP driver de nes a few error conditions
speci c to the HTTP protocol.

See also:
>   globus_xio_driver_error_match()

6.18.2   Enumeration Type Documentation

6.18.2.1   enum globus_xio_http_errors_t

Error types used to generate errors using the globus_error_generic module.

Enumeration values:

> GLOBUS_XIO_HTTP_ERROR_INVALID_HEADER An attempt to set a header which is not compatible with the HTTP version being used.
>
> GLOBUS_XIO_HTTP_ERROR_PARSE Error parsing HTTP protocol.
>
> GLOBUS_XIO_HTTP_ERROR_NO_ENTITY There is no entity body to read or write.
>
> GLOBUS_XIO_HTTP_ERROR_EOF Server side fake EOF.
>
> GLOBUS_XIO_HTTP_ERROR_PERSISTENT_CONNECTION_DROPPED Persistent connection dropped by the server.

6.19   Globus XIO MODE_E Driver

Modules

- Opening/Closing
- Reading/Writing
- Server
- Env Variables
- Attributes and Cntls
- Types
- Error Types

6.20   Opening/Closing

An XIO handle with the mode_e driver can be created with either globus_xio_handle_create() or globus_xio_server_-register_accept().

If the handle is created with globus_xio_handle_create(), the contact string passed to globus_xio_register_open() call must contain a host name and service/port. The number of streams required can be speci ed on the attr using GLOBUS_XIO_MODE_E_SET_NUM_STREAMS (default is one stream). The stack of drivers to be used on the streams can be speci ed on the attr using GLOBUS_XIO_MODE_E_SET_STACK (default is a stack containing TCP driver).

When the XIO handle is closed, the mode_e driver will destroy its internal resources and close the stream(s).

6.21   Reading/Writing

Mode E is unidirectional. Clients can only write and the server can only read. The globus_xio_register_read() enforce that the waitforbytes parameter should be one. When multiple transport streams are used between the client and the server, data might not be delivered in order. globus_xio_data_descriptor_cntl() can be used to get the offset of the data.

globus_xio_register_write() does not enforce any restriction on the waitforbytes parameter.

In any case, when an error or EOF occurs before the waitforbytes request has been met, the outgoing nbytes is set to the amount of data actually read/written before the error or EOF occurred.

6.22 Server

globus_xio_server_create() causes a mode_e listener to be created and listened upon. globus_xio_server_register_-accept() performs an asynchronous accept. globus_xio_server_register_close() cleans up the internal resources associated with the mode_e server.

All accepted handles inherit all mode_e speci c attributes set in the attr to globus_xio_server_create()

6.23 Env Variables

The mode_e driver uses the following environment variable

- GLOBUS_XIO_MODE_E_DEBUG Available if using a debug build. See globus_debug.h for format.

6.24 Attributes and Cntls

Enumerations

- enum globus_xio_mode_e_cmd_t {
  GLOBUS_XIO_MODE_E_SET_STACK,
  GLOBUS_XIO_MODE_E_GET_STACK,
  GLOBUS_XIO_MODE_E_SET_NUM_STREAMS,
  GLOBUS_XIO_MODE_E_GET_NUM_STREAMS,
  GLOBUS_XIO_MODE_E_SET_OFFSET_READS,
  GLOBUS_XIO_MODE_E_GET_OFFSET_READS,
  GLOBUS_XIO_MODE_E_SET_MANUAL_EODC,
  GLOBUS_XIO_MODE_E_GET_MANUAL_EODC,
  GLOBUS_XIO_MODE_E_SEND_EOD,
  GLOBUS_XIO_MODE_E_SET_EODC,
  GLOBUS_XIO_MODE_E_DD_GET_OFFSET,
  GLOBUS_XIO_MODE_E_SET_STACK_ATTR,
  GLOBUS_XIO_MODE_E_GET_STACK_ATTR }

Functions

- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_SET_STACK, globus_xio_-stack_t stack)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_STACK, globus_xio_-stack_t stack_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_SET_NUM_STREAMS, int num_streams)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_NUM_STREAMS, int num_streams_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_SET_OFFSET_READS, globus_bool_t offset_reads)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_OFFSET_READS, globus_bool_t offset_reads_out)

- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_SET_MANUAL_EODC, globus_bool_t manual_eodc)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_MANUAL_EODC, globus_bool_t manual_eodc_out)
- globus_result_t globus_xio_data_descriptor_cntl(dd, driver, GLOBUS_XIO_MODE_E_SEND_EOD, globus_bool_t send_eod)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_MODE_E_SET_EODC, int eod_-count)
- globus_result_t globus_xio_data_descriptor_cntl(dd, driver, GLOBUS_XIO_MODE_E_DD_GET_OFFSET, globus_off_t offset_out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_MODE_E_GET_STACK_ATTR, globus_-xio_attr_t stack_out)

6.24.1 Detailed Description

Mode_e driver speci c attrs and cntls.

See also:
globus_xio_attr_cntl()
globus_xio_handle_cntl()
globus_xio_server_cntl()
globus_xio_data_descriptor_cntl()

6.24.2 Enumeration Type Documentation

6.24.2.1 enum globus_xio_mode_e_cmd_t

MODE_E driver speci c cntls.

Enumeration values:

GLOBUS_XIO_MODE_E_SET_STACK	See usage for globus_xio_attr_cntl
GLOBUS_XIO_MODE_E_GET_STACK	See usage for globus_xio_attr_cntl
GLOBUS_XIO_MODE_E_SET_NUM_STREAMS	See usage for globus_xio_attr_cntl
GLOBUS_XIO_MODE_E_GET_NUM_STREAMS	See usage for globus_xio_attr_cntl
GLOBUS_XIO_MODE_E_SET_OFFSET_READS	See usage for globus_xio_attr_cntl
GLOBUS_XIO_MODE_E_GET_OFFSET_READS	See usage for globus_xio_attr_cntl
GLOBUS_XIO_MODE_E_SET_MANUAL_EODC	See usage for globus_xio_attr_cntl
GLOBUS_XIO_MODE_E_GET_MANUAL_EODC	See usage for globus_xio_attr_cntl
GLOBUS_XIO_MODE_E_SEND_EOD	See usage for globus_xio_data_descriptor_cntl
GLOBUS_XIO_MODE_E_SET_EODC	See usage for globus_xio_handle_cntl
GLOBUS_XIO_MODE_E_DD_GET_OFFSET	See usage for globus_xio_data_descriptor_cntl
GLOBUS_XIO_MODE_E_SET_STACK_ATTR	See usage for globus_xio_attr_cntl
GLOBUS_XIO_MODE_E_GET_STACK_ATTR	See usage for globus_xio_attr_cntl

6.24.3   Function Documentation

6.24.3.1   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_SET_STACK, globus_-xio_stack_t stack)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the stack (of xio drivers) to be used for the connection(s). Do not create a new ftp client handle, use this handle instead.

Parameters:

   stack Speci es the stack to use for the connection(s). Note: this stack will not be destroyed.

6.24.3.2   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_STACK, globus_xio_stack_t stack_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the stack on the attr.

Parameters:

   stack_out The stack will be stored here. If none is set, GLOBUS_NULL will be set.

6.24.3.3   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_SET_NUM_-STREAMS, int num_streams)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the number of streams to be used between the client and the server.

Parameters:

   num_streams Speci es the number of streams to use.

6.24.3.4   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_NUM_-STREAMS, int num_streams_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the number of streams on the attr.

Parameters:

   num_streams_out The stream count will be stored here.

6.24.3.5   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_SET_OFFSET_-READS, globus_bool_t offset_reads)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set ag to indicate whether the data read from user would always be preceded by an offset read or not. The user can do a read with wait_for_bytes set to zero, to nd the offset of the data that he is going to get in his next read operation

Parameters:
offset_readsGLOBUS_TRUE to enable offset reads, GLOBUS_FALSE to disable offset reads (default).

6.24.3.6 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_OFFSET_-READS, globus_bool_t offset_reads_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get OFFSET_READS ag on the attr.

Parameters:
offset_reads_outThe OFFSET_READS ag will be stored here.

6.24.3.7 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_SET_MANUAL_-EODC, globus_bool_t manual_eodc)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set ag to indicate whether EODC will be set manually by the user on a data_desc or the driver has to calculate the EODC

Parameters:
manual_eodcGLOBUS_TRUE to set EODC manually, GLOBUS_FALSE to not set EODC manually (default).

6.24.3.8 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_MANUAL_-EODC, globus_bool_t manual_eodc_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get MANUAL_EODC ag on the attr.

Parameters:
manual_eodc_outThe MANUAL_EODC ag will be stored here.

6.24.3.9 globus_result_t globus_xio_data_descriptor_cntl (dd, driver, GLOBUS_XIO_MODE_E_SEND_-EOD, globus_bool_t send_eod)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set SEND_EOD ag Used only for data descriptors to write calls.

Parameters:
send_eodGLOBUS_TRUE to send EOD, GLOBUS_FALSE to not send EOD (default).

6.24.3.10   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_MODE_E_SET_EODC, int eod_coun)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set EOD count Used only if MANUAL_EODC ag is set to GLOBUS_TRUE.

Parameters:
    eod_count speci es the eod count

6.24.3.11   globus_result_t globus_xio_data_descriptor_cntl (dd, driver, GLOBUS_XIO_MODE_E_DD_-GET_OFFSET, globus_off_t offset_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get offset of the next available data Used only if OFFSET_READS is enabled.

Parameters:
    offset_out offset will be stored here

6.24.3.12   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_STACK_ATTR, globus_xio_attr_t stack_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the attr that will be used with the stack. This is intended for use with GLOBUS_XIO_MODE_E_SET_STACK.

Parameters:
    stack_out The stack will be stored here. If none is set, GLOBUS_NULL will be set.

6.25   Types

6.26   Error Types

Enumerations

- enum globus_xio_mode_e_error_type { GLOBUS_XIO_MODE_E_HEADER_ERROR }

6.26.1   Detailed Description

The errors reported by MODE_E driver include GLOBUS_XIO_ERROR_COMMAND, GLOBUS_XIO_ERROR_-MEMORY, GLOBUS_XIO_ERROR_STATE, GLOBUS_XIO_ERROR_PARAMETER, GLOBUS_XIO_ERROR_-EOF, GLOBUS_XIO_ERROR_CANCELED, GLOBUS_XIO_MODE_E_HEADER_ERROR

See also:
    globus_xio_driver_error_match()
    globus_error_errno_match()

6.26.2   Enumeration Type Documentation

6.26.2.1   enum globus_xio_mode_e_error_type_t

MODE_E driver speci c error types.

Enumeration values:
GLOBUS_XIO_MODE_E_HEADER_ERROR Indicates that the mode_e header is erroneous.

6.27   Globus XIO ORDERING Driver

Modules

- Opening/Closing
- Reading/Writing
- Env Variables
- Attributes and Cntls
- Types
- Error Types

6.28   Opening/Closing

Ordering driver is a transform driver and thus has to be used on top of a transport driver. An XIO handle with the ordering driver can be created with either globus_xio_handle_create() or globus_xio_server_register_accept()

When the XIO handle is closed, the ordering driver will destroy its internal resources.

6.29   Reading/Writing

Ordering driver does not allow multiple globus_xio_register_read() to be outstanding. This limitation is there to enforce that the users get the read callback in order. There is a known issue in enforcing the order in which read callbacks are delivered with multiple outstanding reads. This limitation does not restrict the use of parallel reads feature provided by the underlying transport driver. GLOBUS_XIO_ORDERING_SET_MAX_READ_COUNT on the attr can be used to specify the number of parallel reads. Ordering will have a maximum of this many number of reads outstanding to the driver below it on the stack. It buffers the data read and delivers it to the user in order.

globus_xio_register_write() does not enforce any restriction.

6.30   Env Variables

The ordering driver uses the following environment variable

- GLOBUS_XIO_ORDERING_DEBUG Available if using a debug build. See globus_debug.h for format.

6.31   Attributes and Cntls

Enumerations

- enum globus_xio_ordering_cmd_t {
  GLOBUS_XIO_ORDERING_SET_OFFSET,

GLOBUS_XIO_ORDERING_SET_MAX_READ_COUNT

GLOBUS_XIO_ORDERING_GET_MAX_READ_COUNT

GLOBUS_XIO_ORDERING_SET_BUFFERING

GLOBUS_XIO_ORDERING_GET_BUFFERING

GLOBUS_XIO_ORDERING_SET_BUF_SIZE

GLOBUS_XIO_ORDERING_GET_BUF_SIZE

GLOBUS_XIO_ORDERING_SET_MAX_BUF_COUNT

GLOBUS_XIO_ORDERING_GET_MAX_BUF_COUNT

Functions

- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_ORDERING_SET_OFFSET, globus_off_t offset)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_SET_MAX_READ_COUNT, int max_read_count)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_GET_MAX_READ_COUNT, int max_read_count_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_SET_BUFFERING, globus_-bool_t buffering)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_GET_BUFFERING, globus_-bool_t buffering_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_SET_BUF_SIZE, int buf_size)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_GET_BUF_SIZE, int buf_-size_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_SET_MAX_BUF_COUNT, int max_buf_count)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_GET_MAX_BUF_COUNT, int max_buf_count_out)

6.31.1 Detailed Description

Ordering driver speci c attrs and cntls.

See also:
  globus_xio_attr_cntl()
  globus_xio_handle_cntl()

6.31.2 Enumeration Type Documentation

6.31.2.1 enum globus_xio_ordering_cmd_t

ORDERING driver speci c cntls.

Enumeration values:
  GLOBUS_XIO_ORDERING_SET_OFFSET See usage for globus_xio_handle_cntl
  GLOBUS_XIO_ORDERING_SET_MAX_READ_COUNT See usage for globus_xio_attr_cntl
  GLOBUS_XIO_ORDERING_GET_MAX_READ_COUNT See usage for globus_xio_attr_cntl
  GLOBUS_XIO_ORDERING_SET_BUFFERING See usage for globus_xio_attr_cntl

GLOBUS_XIO_ORDERING_GET_BUFFERING See usage for globus_xio_attr_cntl

GLOBUS_XIO_ORDERING_SET_BUF_SIZE See usage for globus_xio_attr_cntl

GLOBUS_XIO_ORDERING_GET_BUF_SIZE See usage for globus_xio_attr_cntl

GLOBUS_XIO_ORDERING_SET_MAX_BUF_COUNT See usage for globus_xio_attr_cntl

GLOBUS_XIO_ORDERING_GET_MAX_BUF_COUNT See usage for globus_xio_attr_cntl

6.31.3   Function Documentation

6.31.3.1   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_ORDERING_SET_-OFFSET, globus_off_t offset)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set offset for the next IO operation. This is not allowed when there is an outstanding IO operation. This operation clears all the buffered data.

Parameters:
    offset Speci es the offset to use in the next IO operation.

6.31.3.2   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_SET_MAX_-READ_COUNT, int max_read_count)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the maximum number of reads that ordering driver can have outstanding on driver(s) below.

Parameters:
    max_read_count Speci es the maximum number of parallel reads (default is 1).

6.31.3.3   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_GET_MAX_-READ_COUNT, int ∗ max_read_count_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the maximum number of parallel reads set on the attr.

Parameters:
    max_read_count_out The maximum number of parallel reads allowed will be stored here.

6.31.3.4   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_SET_BUFFERING, globus_bool_t buffering)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

This driver can be used in 2 modes; ordering (care about offsets of the data read - underlying transport driver may deliver data out of order - this driver will rearrange data based on the offset and deliver inorder to user) and buffering (do not care about offsets - just buffer the data read abd deliver it when requested). This attribute control can be used to enable buffering.

Parameters:
      buffering GLOBUS_TRUE to enable buffering, GLOBUS_FALSE (default) to disable buffering.

6.31.3.5 globus_result_t   globus_xio_attr_cntl   (attr,   driver,   GLOBUS_XIO_ORDERING_GET_-BUFFERING, globus_bool_t   buffering_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the buffering ag on the attr.

Parameters:
      buffering_out Buffering ag will be stored in here.

6.31.3.6   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_SET_BUF_SIZE, int buf_size)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the size of the buffer that ordering driver creates to use for reading data from the driver below it.

Parameters:
      buf_size Speci es the buffer size for internal reads (default is 100 KB).

6.31.3.7   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_GET_BUF_SIZE, int   buf_size_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the size of the buffer used for the internal reads.

Parameters:
      buf_size_out The buffer size will be stored in here.

6.31.3.8   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_SET_MAX_BUF_-COUNT, int max_buf_count)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the maximum number of buffers that this driver can create for reading data from the driver below it.

Parameters:
      max_buf_count Speci es the max buffer count for internal reads (default is 100).

6.31.3.9   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_ORDERING_GET_MAX_BUF_-
COUNT, int   max_buf_count_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Get the maximum buffer count set on the attr.

Parameters:
    max_buf_count_out   The maximun buffer count will be stored in here.

6.32   Types

6.33   Error Types

Enumerations

- enum globus_xio_ordering_error_type_t {
    GLOBUS_XIO_ORDERING_ERROR_READ,
    GLOBUS_XIO_ORDERING_ERROR_CANCEL }

6.33.1   Detailed Description

The errors reported by ORDERING driver include GLOBUS_XIO_ERROR_COMMAND, GLOBUS_XIO_-
ERROR_MEMORY, GLOBUS_XIO_ERROR_STATE, GLOBUS_XIO_ERROR_CANCELED

See also:
    globus_xio_driver_error_match()
    globus_error_errno_match()

6.33.2   Enumeration Type Documentation

6.33.2.1   enum globus_xio_ordering_error_type_t

ORDERING driver speci c error types.

Enumeration values:
    GLOBUS_XIO_ORDERING_ERROR_READ   Indicates that an error occured in reading data.
    GLOBUS_XIO_ORDERING_ERROR_CANCEL   Indicates an error occured in canceling an operation.

6.34   Globus XIO TCP Driver

The IPV4/6 TCP socket driver.

Modules

- Opening/Closing
- Reading/Writing
- Server
- Env Variables

- Attributes and Cntls
- Types
- Error Types

6.34.1   Detailed Description

The IPV4/6 TCP socket driver.

6.35   Opening/Closing

An XIO handle with the tcp driver can be created with either globus_xio_handle_create() or globus_xio_server_-register_accept().

If the handle is created with globus_xio_server_register_accept() the globus_xio_register_open() call does nothing more than initialize the internal handle with the accepted socket.

If the handle is created with globus_xio_handle_create() and there is no handle set on the attr passed to the globus_-xio_register_open() call, it performs the equivalent of an asynchronous connect() call. In this case, the contact string must contain a host name and service/port. Both the hostname and port number can be numeric or symbolic (eg: some.webserver.com:80 or 214.123.12.1:http). If the hostname is symbolic and it resolves to multiple ip addresses, each one will be attempted in succession, until the connect is successful or there are no more addresses.

When the XIO handle is closed, the tcp driver will destroy its internal resources and close the socket (unless this socket was set on an attr). Any write data pending in system buffers will be sent unless the linger option has been set. Any remaining data in recv buffers will be discarded and (on some systems) a connection reset sent to the peer.

6.36   Reading/Writing

Both the globus_xio_register_read() and globus_xio_register_write() calls follow similar semantics as described below.

If the waitforbytes parameter is greater than zero, the io will happen asynchronously and be completed when at least waitforbytes has been read/written.

If the waitforbytes parameter is equal to zero, one of the following alternative behaviors occur:

If the length of the buffer is > 0 the read or write happens synchronously. If the user is using one of the blocking xio calls, no internal callback will occur.

If the length of the buffer is also 0, the call behaves like an asynchronous noti cation of data ready to be either read or written. ie, an asynchronous select().

In any case, when an error or EOF occurs before the waitforbytes request has been met, the outgoing nbytes is set to the amount of data actually read/written before the error or EOF occurred.

6.37   Server

globus_xio_server_create() causes a tcp listener socket to be created and listened on. globus_xio_server_register_-accept() performs an asynchronous accept. globus_xio_server_register_close() cleans up the internal resources associated with the tcp server and calls close() on the listener socket (unless the socket was set on the server via the attr)

All accepted handles inherit all tcp speci c attributes set in the attr to globus_xio_server_create() but can be overridden with the attr to globus_xio_register_open().

6.38   Env Variables

The tcp driver uses the following environment variables

- GLOBUS_HOSTNAME Used when setting the hostname in the contact string

- GLOBUS_TCP_PORT_RANGE Used to restrict anonymous listener ports ex: GLOBUS_TCP_PORT_-RANGE=4000,4100

- GLOBUS_TCP_PORT_RANGE_STATE_FILE Used in conjunction with GLOBUS_TCP_PORT_RANGE to maintain last used port among many applications making use of the same port range. That last port + 1 will be used as a starting point within the speci ed tcp port range instead of always starting at the beginning. This is really only necessary when a machine is behind a stateful rewall which is holding a port in a different state than the application's machine. See bugzilla.globus.org, bug 1851 for more info. ex: GLOBUS_TCP_PORT_-RANGE_STATE_FILE=/tmp/port_state (le will be created if it does not exist)

- GLOBUS_TCP_SOURCE_RANGE Used to restrict local ports used in a connection

- GLOBUS_XIO_TCP_DEBUG Available if using a debug build. See globus_debug.h for format. The TCP driver de nes the levels TRACE for all function call tracing and INFO for write buffer sizes

- GLOBUS_XIO_SYSTEM_DEBUG Available if using a debug build. See globus_debug.h for format. The TCP driver uses globus_xio_system (along with the File and UDP drivers) which de nes the following levels: TRACE for all function call tracing, DATA for data read and written counts, INFO for some special events, and RAW which dumps the raw buffers actually read or written. This can contain binary data, so be careful when you enable it.

6.39   Attributes and Cntls

Enumerations

- enum globus_xio_tcp_cmd_t {
  GLOBUS_XIO_TCP_SET_SERVICE ,
  GLOBUS_XIO_TCP_GET_SERVICE ,
  GLOBUS_XIO_TCP_SET_PORT ,
  GLOBUS_XIO_TCP_GET_PORT ,
  GLOBUS_XIO_TCP_SET_BACKLOG ,
  GLOBUS_XIO_TCP_GET_BACKLOG ,
  GLOBUS_XIO_TCP_SET_LISTEN_RANGE ,
  GLOBUS_XIO_TCP_GET_LISTEN_RANGE ,
  GLOBUS_XIO_TCP_GET_HANDLE ,
  GLOBUS_XIO_TCP_SET_HANDLE ,
  GLOBUS_XIO_TCP_SET_INTERFACE ,
  GLOBUS_XIO_TCP_GET_INTERFACE ,
  GLOBUS_XIO_TCP_SET_RESTRICT_PORT ,
  GLOBUS_XIO_TCP_GET_RESTRICT_PORT ,
  GLOBUS_XIO_TCP_SET_REUSEADDR ,
  GLOBUS_XIO_TCP_GET_REUSEADDR ,
  GLOBUS_XIO_TCP_SET_NO_IPV6 ,

GLOBUS_XIO_TCP_GET_NO_IPV6,

GLOBUS_XIO_TCP_SET_CONNECT_RANGE,

GLOBUS_XIO_TCP_GET_CONNECT_RANGE,

GLOBUS_XIO_TCP_SET_KEEPALIVE,

GLOBUS_XIO_TCP_GET_KEEPALIVE,

GLOBUS_XIO_TCP_SET_LINGER,

GLOBUS_XIO_TCP_GET_LINGER,

GLOBUS_XIO_TCP_SET_OOBINLINE,

GLOBUS_XIO_TCP_GET_OOBINLINE,

GLOBUS_XIO_TCP_SET_SNDBUF,

GLOBUS_XIO_TCP_GET_SNDBUF,

GLOBUS_XIO_TCP_SET_RCVBUF,

GLOBUS_XIO_TCP_GET_RCVBUF,

GLOBUS_XIO_TCP_SET_NODELAY,

GLOBUS_XIO_TCP_GET_NODELAY,

GLOBUS_XIO_TCP_SET_SEND_FLAGS,

GLOBUS_XIO_TCP_GET_SEND_FLAGS,

GLOBUS_XIO_TCP_GET_LOCAL_CONTACT,

GLOBUS_XIO_TCP_GET_LOCAL_NUMERIC_CONTACT,

GLOBUS_XIO_TCP_GET_REMOTE_CONTACT,

GLOBUS_XIO_TCP_GET_REMOTE_NUMERIC_CONTACT,

GLOBUS_XIO_TCP_AFFECT_ATTR_DEFAULTS,

GLOBUS_XIO_TCP_SET_BLOCKING_IO,

GLOBUS_XIO_TCP_GET_BLOCKING_IO)

Functions

- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_SERVICE, const char *service_-name)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_SERVICE, char *service_-name_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_PORT, int listener_port)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_PORT, int *listener_port_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_BACKLOG, int listener_backlog)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_BACKLOG, int *listener_-backlog_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_LISTEN_RANGE, int listener_-min_port, int listener_max_port)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_LISTEN_RANGE, int *listener_min_port_out, int *listener_max_port_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_HANDLE, globus_xio_system_-socket_t *handle_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_HANDLE, globus_xio_-system_socket_t *handle_out)

- globus_result_t globus_xio_server_cntl(server, driver, GLOBUS_XIO_TCP_GET_HANDLE, globus_xio_-system_socket_t handle_out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_SET_HANDLE, globus_xio_system_-socket_t handle)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_INTERFACE, const char interface)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_GET_INTERFACE, char interface_-out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_SET_RESTRICT_PORT, globus_-bool_t restrict_port)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_GET_RESTRICT_PORT, globus_-bool_t restrict_port_out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_SET_REUSEADDR, globus_bool_t re-suseaddr)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_GET_REUSEADDR, globus_bool_t resuseaddr_out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_SET_NO_IPV6, globus_bool_t no_-ipv6)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_GET_NO_IPV6, globus_bool no_-ipv6_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_CONNECT_RANGE, int connector_min_port, int connector_max_port)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_CONNECT_RANGE, int connector_min_port_out, int connector_max_port_out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_SET_KEEPALIVE, globus_bool_-t keepalive)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_SET_KEEPALIVE, globus_-bool_t keepalive)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_GET_KEEPALIVE, globus_bool_-t keepalive_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_GET_KEEPALIVE, globus_-bool_t keepalive_out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_SET_LINGER, globus_bool_t linger, int linger_time)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_SET_LINGER, globus_bool_t linger, int linger_time)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_LINGER, globus_bool_-t linger_out, int linger_time_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_GET_LINGER, globus_bool_t linger_out, int linger_time_out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_SET_OOBINLINE, globus_bool_-t oobinline)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_SET_OOBINLINE, globus_-bool_t oobinline)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_GET_OOBINLINE, globus_bool_-t oobinline_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_GET_OOBINLINE, globus_-bool_t oobinline_out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_SET_SNDBUF, int sndbuf)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_SET_SNDBUF, int sndbuf)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_GET_SNDBUF, int sndbuf_out)

- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_GET_SNDBUF, int sndbuf_-
  out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_SET_RCVBUF, int rcvbuf)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_SET_RCVBUF, int rcvbuf)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_GET_RCVBUF, int rcvbuf_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_GET_RCVBUF, int rcvbuf_-
  out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_SET_NODELAY, globus_bool_t node-
  lay)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_SET_NODELAY, globus_-
  bool_t nodelay)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_GET_NODELAY, globus_bool_-
  t nodelay_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_GET_NODELAY, globus_-
  bool_t nodelay_out)
- globus_result_t globus_xio_data_descriptor_cntl(dd, driver, GLOBUS_XIO_TCP_SET_SEND_FLAGS, int
  send_flags)
- globus_result_t globus_xio_data_descriptor_cntl(dd, driver, GLOBUS_XIO_TCP_GET_SEND_FLAGS, int
  send_flags_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_GET_LOCAL_CONTACT, char
  contact_string_out)
- globus_result_t globus_xio_server_cntl(server, driver, GLOBUS_XIO_TCP_GET_LOCAL_CONTACT, char
  contact_string_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_GET_LOCAL_NUMERIC_-
  CONTACT, char contact_string_out)
- globus_result_t globus_xio_server_cntl(server, driver, GLOBUS_XIO_TCP_GET_LOCAL_NUMERIC_-
  CONTACT, char contact_string_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_GET_REMOTE_CONTACT,
  char contact_string_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_GET_REMOTE_NUMERIC_-
  CONTACT, char contact_string_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_AFFECT_ATTR_DEFAULTS,
  globus_bool_t affect_global)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_SET_BLOCKING_IO, globus_bool_t
  use_blocking_io)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_TCP_SET_BLOCKING_IO, globus_-
  bool_t use_blocking_io)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_TCP_GET_BLOCKING_IO, globus_bool_t
  use_blocking_io_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_BLOCKING_IO,
  globus_bool_t use_blocking_io_out)

6.39.1   Detailed Description

Tcp driver specific attrs and cntls.

See also:
   globus_xio_attr_cntl()
   globus_xio_handle_cntl()
   globus_xio_server_cntl()
   globus_xio_data_descriptor_cntl()

6.39.2   Enumeration Type Documentation

6.39.2.1   enum globus_xio_tcp_cmd_t

TCP driver speci c cntls.

Enumeration values:

GLOBUS_XIO_TCP_SET_SERVICE See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_GET_SERVICE See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_SET_PORT See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_GET_PORT See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_SET_BACKLOG See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_GET_BACKLOG See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_SET_LISTEN_RANGE See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_GET_LISTEN_RANGE See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_GET_HANDLE See usage for: globus_xio_attr_cntl, globus_xio_handle_cntl, globus_xio_server_cntl

GLOBUS_XIO_TCP_SET_HANDLE See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_SET_INTERFACE See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_GET_INTERFACE See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_SET_RESTRICT_PORT See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_GET_RESTRICT_PORT See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_SET_REUSEADDR See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_GET_REUSEADDR See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_SET_NO_IPV6 See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_GET_NO_IPV6 See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_SET_CONNECT_RANGE See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_GET_CONNECT_RANGE See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_SET_KEEPALIVE See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_GET_KEEPALIVE See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_SET_LINGER See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_GET_LINGER See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_SET_OOBINLINE See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_GET_OOBINLINE See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_SET_SNDBUF See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_GET_SNDBUF See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_SET_RCVBUF See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_GET_RCVBUF See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_SET_NODELAY See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_GET_NODELAY See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_SET_SEND_FLAGS See usage for globus_xio_data_descriptor_cntl

GLOBUS_XIO_TCP_GET_SEND_FLAGS See usage for globus_xio_data_descriptor_cntl

GLOBUS_XIO_TCP_GET_LOCAL_CONTACT See usage for: globus_xio_handle_cntl, globus_xio_server_cntl

GLOBUS_XIO_TCP_GET_LOCAL_NUMERIC_CONTACT See usage for: globus_xio_handle_cntl, globus_xio_server_cntl

GLOBUS_XIO_TCP_GET_REMOTE_CONTACT See usage for globus_xio_handle_cntl

GLOBUS_XIO_TCP_GET_REMOTE_NUMERIC_CONTACT See usage for globus_xio_handle_cntl

GLOBUS_XIO_TCP_AFFECT_ATTR_DEFAULTS See usage for globus_xio_attr_cntl

GLOBUS_XIO_TCP_SET_BLOCKING_IO See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_TCP_GET_BLOCKING_IO See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

6.39.3 Function Documentation

6.39.3.1 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_SERVICE, const char service_name)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the tcp service name to bind to. Used only on attrs for globus_xio_server_create()

Parameters:
    service_name The service name to use when setting up the listener. If the service name cannot be resolved, the port (if one is set) will be used instead.

string opt: port=

6.39.3.2 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_SERVICE, char service_name_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp service name to bind to.

Parameters:
    service_name_out A pointer to the service name will be stored here If none is set, NULL will be passed back. Otherwise, the name will be duplicated with strdup() and the user should call free() on it.

6.39.3.3 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_PORT, int listener_-port)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the tcp port number to bind to. Used only on attrs for globus_xio_server_create() The default port number is 0 (system assigned)

Parameters:
    listener_port The port number to use when setting up the listener. If the service name is also set, this will only be used if that can't be resolved.

string opt: port=

6.39.3.4   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_PORT, int listener_-port_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp port number to bind to.

Parameters:
     listener_port_out The port will be stored here.

6.39.3.5   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_BACKLOG, int listener_backlog)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the listener backlog on a server. Used only on attrs for globus_xio_server_create() The default backlog is -1 (system maximum)

Parameters:
     listener_backlog This indicates the maximum length of the system's queue of pending connections. Any connec-
          tion attempts when the queue is full will fail. If backlog is equal to -1, then the system-speci c maximum
          queue length will be used.

6.39.3.6   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_BACKLOG, int listener_backlog_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the listener backlog on an attr.

Parameters:
     listener_backlog_out The backlog will be stored here.

6.39.3.7   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_LISTEN_RANGE, int listener_min_port, int listener_max_port)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the tcp port range to con ne the server to. Used only on attrs for globus_xio_server_create() where no speci c service or port has been set. It overrides the range set in the GLOBUS_TCP_PORT_RANGE env variable. If 'restrict port' is true, the server's listening port will be constrained to the range speci ed.

Parameters:
     listener_min_port The lower bound on the listener port. (default 0 – no bound)
     listener_max_port The upper bound on the listener port. (default 0 – no bound)

See also:
     GLOBUS_XIO_TCP_SET_RESTRICT_PORT

string opt: listen_range=,

6.39.3.8   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_LISTEN_RANGE, int listener_min_port_out, int listener_max_port_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp port range on an attr.

Parameters:

　　listener_min_port_outThe lower bound will be stored here.

　　listener_max_port_outThe upper bound will be stored here.

6.39.3.9   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_HANDLE, globus_-xio_system_socket_t handle_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp socket handle on an attr, handle, or server.

Parameters:

　　handle_out The tcp socket will be stored here. If none is set, GLOBUS_XIO_TCP_INVALID_HANDLE will be set.

6.39.3.10   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_HANDLE, globus_xio_system_socket_t handle_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp socket handle on an attr, handle, or server.

Parameters:

　　handle_out The tcp socket will be stored here. If none is set, GLOBUS_XIO_TCP_INVALID_HANDLE will be set.

6.39.3.11   globus_result_t globus_xio_server_cntl (server, driver, GLOBUS_XIO_TCP_GET_HANDLE, globus_xio_system_socket_t handle_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp socket handle on an attr, handle, or server.

Parameters:

　　handle_out The tcp socket will be stored here. If none is set, GLOBUS_XIO_TCP_INVALID_HANDLE will be set.

6.39.3.12   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_HANDLE, globus_-xio_system_socket_t handle)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the tcp socket to use for a handle or server. Used only on attr for globus_xio_server_create() or globus_xio_register_open().

Parameters:
    handle Use this handle (fd or SOCKET) for the listener or connection. Note: close() will not be called on this handle.

6.39.3.13   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_INTERFACE, const char interface)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the interface to bind a listener or connection to. Used only on attr for globus_xio_server_create() or globus_xio_register_open.

Parameters:
    interface The interface to use. Can be a hostname or numeric IP

string opt: iface=

6.39.3.14   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_INTERFACE, char interface_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the interface on the attr.

Parameters:
    interface_out A pointer to the interface will be stored here If one is set, NULL will be passed back. Otherwise, the interface will be duplicated with strdup() and the user should call free() on it.

6.39.3.15   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_RESTRICT_PORT, globus_bool_t restrict_port)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Enable or disable the listener or connector range constraints. Used only on attr for globus_xio_server_create() or globus_xio_register_open(). This enables or ignores the port range found in the attr or in then env. By default, those ranges are enabled.

Parameters:
    restrict_port GLOBUS_TRUE to enable (default), GLOBUS_FALSE to disable.

See also:
    GLOBUS_XIO_TCP_SET_LISTEN_RANGE
    GLOBUS_XIO_TCP_SET_CONNECT_RANGE

6.39.3.16 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_RESTRICT_PORT, globus_bool_t restrict_port_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the restrict port ag.

Parameters:

    restrict_port_out The restrict port ag will be stored here.

6.39.3.17 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_REUSEADDR, globus_bool_t resuseaddr)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Reuse addr when binding. Used only on attrs for globus_xio_server_create() or globus_xio_register_open() to determine whether or not to allow reuse of addresses when binding a socket to a port number.

Parameters:

    resuseaddr GLOBUS_TRUE to allow, GLOBUS_FALSE to disallow (default)

string opt: reuse=

6.39.3.18 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_REUSEADDR, globus_bool_t resuseaddr_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the reuseaddr ag on an attr.

Parameters:

    resuseaddr_out The reuseaddr ag will be stored here.

6.39.3.19 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_NO_IPV6, globus_- bool_t no_ipv6)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Restrict to IPV4 only. Used only on attrs for globus_xio_server_create() or globus_xio_register_open(). Disallow IPV6 sockets from being used (default is to use either ipv4 or ipv6)

Parameters:

    no_ipv6 GLOBUS_TRUE to disallow ipv6, GLOBUS_FALSE to allow (default)

string opt: noipv6=

6.39.3.20   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_NO_IPV6, globus_-bool_t   no_ipv6_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the no ipv6 ag on an attr.

Parameters:
> no_ipv6_out The no ipv6 ag will be stored here.

6.39.3.21   globus_result_t   globus_xio_attr_cntl   (attr,   driver,   GLOBUS_XIO_TCP_SET_CONNECT_-RANGE, int connector_min_port, int connector_max_port)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the tcp port range to con ne the server to. Used only on attrs for globus_xio_register_open(). It overrides the range set in the GLOBUS_TCP_SOURCE_RANGE env variable. If 'restrict port' is true, the connecting socket's local port will be constrained to the range speci ed.

Parameters:
> connector_min_port The lower bound on the listener port. (default 0 – no bound)
> connector_max_port The upper bound on the listener port. (default 0 – no bound)

See also:
> GLOBUS_XIO_TCP_SET_RESTRICT_PORT

6.39.3.22   globus_result_t   globus_xio_attr_cntl   (attr,   driver,   GLOBUS_XIO_TCP_GET_CONNECT_-RANGE, int   connector_min_port_out, int   connector_max_port_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp source port range on an attr.

Parameters:
> connector_min_port_out The lower bound will be stored here.
> connector_max_port_out The upper bound will be stored here.

6.39.3.23   globus_result_t   globus_xio_attr_cntl   (attr,   driver,   GLOBUS_XIO_TCP_SET_KEEPALIVE, globus_bool_t keepalive)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Enable tcp keepalive. Used on attrs for globus_xio_server_create(), globus_xio_register_open(), and with globus_xio_-handle_cntl() to determine whether or not to periodically send "keepalive" messages on a connected socket handle. This may enable earlier detection of broken connections.

Parameters:
> keepalive GLOBUS_TRUE to enable, GLOBUS_FALSE to disable (default)

string opt: keepalive=

6.39.3.24   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_KEEPALIVE, globus_bool_t keepalive)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Enable tcp keepalive. Used on attrs (for globus_xio_server_create(), globus_xio_register_open() and with globus_xio_-handle_cntl()) to determine whether or not to periodically send "keepalive" messages on a connected socket handle. This may enable earlier detection of broken connections.

Parameters:
    keepalive GLOBUS_TRUE to enable, GLOBUS_FALSE to disable (default)

string opt: keepalive=

6.39.3.25   globus_result_t globus_xio_attr_cntl (attr,   driver,   GLOBUS_XIO_TCP_GET_KEEPALIVE, globus_bool_t   keepalive_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp keepalive ag.

Parameters:
    keepalive_out The tcp keepalive ag will be stored here.

6.39.3.26   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_KEEPALIVE, globus_bool_t   keepalive_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp keepalive ag.

Parameters:
    keepalive_out The tcp keepalive ag will be stored here.

6.39.3.27   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_LINGER, globus_-bool_t linger, int linger_time)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set tcp linger.   Used on attrs for globus_xio_server_create() globus_xio_register_open() and with globus_xio_-handle_cntl()) to determine what to do when data is in the socket's buffer when the socket is closed. If linger is set to true, then the close operation will block until the socket buffers are empty, or the linger_time has expired. If this is enabled, any data remaining after the linger time has expired, will be discarded. If this is disabled, close nishes immediately, but the OS will still attempt to transmit the remaining data.

Parameters:
    linger GLOBUS_TRUE to enable, GLOBUS_FALSE to disable (default)
    linger_time The time (in seconds) to block at close time if linger is true and data is queued in the socket buffer.

6.39.3.28   globus_result_t globus_xio_handle_cntl (handle,   driver,   GLOBUS_XIO_TCP_SET_LINGER, globus_bool_t linger, int linger_time)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set tcp linger. Used on attrs for globus_xio_server_create() globus_xio_register_open() and with globus_xio_-handle_cntl() to determine what to do when data is in the socket's buffer when the socket is closed. If linger is set to true, then the close operation will block until the socket buffers are empty, or the linger_time has expired. If this is enabled, any data remaining after the linger time has expired, will be discarded. If this is disabled, close nishes immediately, but the OS will still attempt to transmit the remaining data.

Parameters:
    linger GLOBUS_TRUE to enable, GLOBUS_FALSE to disable (default)
    linger_time The time (in seconds) to block at close time if linger is true and data is queued in the socket buffer.

6.39.3.29   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_LINGER, globus_-bool_t   linger_out, int   linger_time_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp linger ag and time.

Parameters:
    linger_out The linger ag will be stored here.
    linger_time_out The linger time will be set here.

6.39.3.30   globus_result_t globus_xio_handle_cntl (handle,   driver,   GLOBUS_XIO_TCP_GET_LINGER, globus_bool_t   linger_out, int   linger_time_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp linger ag and time.

Parameters:
    linger_out The linger ag will be stored here.
    linger_time_out The linger time will be set here.

6.39.3.31   globus_result_t globus_xio_attr_cntl (attr,   driver,   GLOBUS_XIO_TCP_SET_OOBINLINE, globus_bool_t oobinline)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Receive out of band data (tcp urgent data) in normal stream. Used on attrs for globus_xio_server_create() globus_-xio_register_open() and with globus_xio_handle_cntl() to choose whether out-of-band data is received in the normal data queue. (Currently, there is no other way to receive OOB data)

Parameters:
    oobinline GLOBUS_TRUE to enable, GLOBUS_FALSE to disable (default)

6.39.3.32   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_OOBINLINE, globus_bool_toobinline)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Receive out of band data (tcp urgent data) in normal stream. Used on attribs for globus_xio_server_create(), globus_-xio_register_open() and with globus_xio_handle_cntl() to choose whether out-of-band data is received in the normal data queue. (Currently, there is no other way to receive OOB data)

Parameters:
    oobinline GLOBUS_TRUE to enable, GLOBUS_FALSE to disable (default)

6.39.3.33   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_OOBINLINE, globus_bool_t oobinline_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the oobinline ag.

Parameters:
    oobinline_out The oobinline ag will be stored here.

6.39.3.34   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_OOBINLINE, globus_bool_t oobinline_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the oobinline ag.

Parameters:
    oobinline_out The oobinline ag will be stored here.

6.39.3.35   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_SNDBUF, int sndbuf)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the tcp socket send buffer size. Used on attr for globus_xio_server_create(), globus_xio_register_open() and with globus_xio_handle_cntl() to set the size of the send buffer used on the socket.

Parameters:
    sndbuf The send buffer size in bytes to use. (default is system speci c)

string opt: sndbuf=

6.39.3.36 globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_SNDBUF, int sndbuf)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the tcp socket send buffer size. Used on attr for globus_xio_server_create(), globus_xio_register_open() and with globus_xio_handle_cntl() to set the size of the send buffer used on the socket.

Parameters:

 sndbuf The send buffer size in bytes to use. (default is system speci c)

string opt: sndbuf=

6.39.3.37 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_SNDBUF, int sndbuf_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp send buffer size on the attr or handle.

Parameters:

 sndbuf_out The send buffer size will be stored here.

6.39.3.38 globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_SNDBUF, int sndbuf_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp send buffer size on the attr or handle.

Parameters:

 sndbuf_out The send buffer size will be stored here.

6.39.3.39 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_RCVBUF, int rcvbuf)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the tcp socket receive buffer size. Used on attr for globus_xio_server_create(), globus_xio_register_open() and with globus_xio_handle_cntl() to set the size of the receive buffer used on the socket. The receive buffer size is often used by the operating system to choose the appropriate TCP window size.

Parameters:

 rcvbuf The receive buffer size in bytes. (default is system speci c)

string opt: rcvbuf=

6.39.3.40 globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_RCVBUF, int rcvbuf)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the tcp socket receive buffer size. Used on attrs for globus_xio_server_create(), globus_xio_register_open() and with globus_xio_handle_cntl() to set the size of the receive buffer used on the socket. The receive buffer size is often used by the operating system to choose the appropriate TCP window size.

Parameters:
    rcvbuf The receive buffer size in bytes. (default is system speci c)

string opt: rcvbuf=

6.39.3.41 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_RCVBUF, int rcvbuf_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp receive buffer size on the attr or handle.

Parameters:
    rcvbuf_out The receive buffer size will be stored here.

6.39.3.42 globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_RCVBUF, int rcvbuf_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp receive buffer size on the attr or handle.

Parameters:
    rcvbuf_out The receive buffer size will be stored here.

6.39.3.43 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_NODELAY, globus_-bool_t nodelay)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Disable Nagle's algorithm. Used on attrs for globus_xio_server_create(), globus_xio_register_open() and with globus_xio_handle_cntl() to determine whether or not to disable Nagle's algorithm. If set to GLOBUS_TRUE, the socket will send packets as soon as possible with no unnecessary delays introduced.

Parameters:
    nodelay GLOBUS_TRUE to disable nagle, GLOBUS_FALSE to enable (default)

string opt: nodelay=

6.39.3.44   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_NODELAY, globus_bool_tnodelay)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Disable Nagle's algorithm. Used on attrs for globus_xio_server_create(), globus_xio_register_open() and with globus_xio_handle_cntl() to determine whether or not to disable Nagle's algorithm. If set to GLOBUS_TRUE, the socket will send packets as soon as possible with no unnecessary delays introduced.

Parameters:
     nodelay GLOBUS_TRUE to disable nagle, GLOBUS_FALSE to enable (default)

string opt: nodelay=

6.39.3.45   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_NODELAY, globus_-bool_t   nodelay_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp nodelay ag.

Parameters:
     nodelay_out The no delay ag will be stored here.

6.39.3.46   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_NODELAY, globus_bool_t   nodelay_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the tcp nodelay ag.

Parameters:
     nodelay_out The no delay ag will be stored here.

6.39.3.47   globus_result_t globus_xio_data_descriptor_cntl (dd, driver, GLOBUS_XIO_TCP_SET_SEND_-FLAGS, int send_ ags)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set tcp send ags. Used only for data descriptors to write calls.

Parameters:
     send_ ags The ags to use when sending data.

See also:
     globus_xio_tcp_send_ ags_t

6.39.3.48 globus_result_t globus_xio_data_descriptor_cntl (dd, driver, GLOBUS_XIO_TCP_GET_SEND_-FLAGS, int   send_ ags_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get tcp send ags.

Parameters:
    send_ ags_out The ags to use will be stored here.

6.39.3.49 globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_LOCAL_-CONTACT, char   contact_string_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get local socket info.

Parameters:
    contact_string_out A pointer to a contact string for the local end of a connected socket or listener will be stored here. The user should free() it when done with it. It will be in the format < hostname > :< port >

See also:
    globus_xio_server_get_contact_string()
    GLOBUS_XIO_GET_LOCAL_CONTACT

6.39.3.50 globus_result_t globus_xio_server_cntl (server, driver, GLOBUS_XIO_TCP_GET_LOCAL_-CONTACT, char   contact_string_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get local socket info.

Parameters:
    contact_string_out A pointer to a contact string for the local end of a connected socket or listener will be stored here. The user should free() it when done with it. It will be in the format < hostname > :< port >

See also:
    globus_xio_server_get_contact_string()
    GLOBUS_XIO_GET_LOCAL_CONTACT

6.39.3.51 globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_LOCAL_-NUMERIC_CONTACT, char   contact_string_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get local socket info.

Parameters:
    contact_string_out A pointer to a contact string for the local end of a connected socket or listener will be stored here. The user should free() it when done with it. It will be in the format < ip > :< port >

See also:
   GLOBUS_XIO_GET_LOCAL_NUMERIC_CONTACT

**6.39.3.52   globus_result_t globus_xio_server_cntl (server, driver, GLOBUS_XIO_TCP_GET_LOCAL_-
NUMERIC_CONTACT, char contact_string_out)**

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Get local socket info.

Parameters:
   contact_string_out A pointer to a contact string for the local end of a connected socket or listener will be stored
      here. The user should free() it when done with it. It will be in the format < ip > :< port >

See also:
   GLOBUS_XIO_GET_LOCAL_NUMERIC_CONTACT

**6.39.3.53   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_REMOTE_-
CONTACT, char contact_string_out)**

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Get remote socket info.

Parameters:
   contact_string_out A pointer to a contact string for the remote end of a connected socket will be stored here. The
      user should free() it when done with it. It will be in the format < hostname > :< port >

See also:
   GLOBUS_XIO_GET_REMOTE_CONTACT

**6.39.3.54   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_REMOTE_-
NUMERIC_CONTACT, char contact_string_out)**

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Get remote socket info.

Parameters:
   contact_string_out A pointer to a contact string for the remote end of a connected socket will be stored here. The
      user should free() it when done with it. It will be in the format < ip > :< port >

See also:
   GLOBUS_XIO_GET_REMOTE_NUMERIC_CONTACT

6.39.3.55   globus_result_t   globus_xio_attr_cntl   (attr,   driver,   GLOBUS_XIO_TCP_AFFECT_ATTR_-
DEFAULTS, globus_bool_t affect_global)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Change the default attr values.

Parameters:
    affect_global If GLOBUS_TRUE, any future cntls on this attr will access the global default attr (which all new
        attrs are initialized from) The default is GLOBUS_FALSE. Note: this should only be used at the application
        level and there should only be one. There is no mutex protecting the global attr. This feature should not be
        abused. There are some attrs that make no sense to change globally. Attrs that do include the tcp port range
        stuff, socket buffer sizes, etc.

6.39.3.56   globus_result_t globus_xio_attr_cntl (attr,   driver,   GLOBUS_XIO_TCP_SET_BLOCKING_IO,
globus_bool_t use_blocking_io)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Enable true blocking io when making globus_xio_read/write() calls. Note: use with caution. you can deadlock an
entire app with this.

Parameters:
    use_blocking_io If GLOBUS_TRUE, true blocking io will be enabled. GLOBUS_FALSE will disable it (de-
        fault);

6.39.3.57   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_BLOCKING_-
IO, globus_bool_t use_blocking_io)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Enable true blocking io when making globus_xio_read/write() calls. Note: use with caution. you can deadlock an
entire app with this.

Parameters:
    use_blocking_io If GLOBUS_TRUE, true blocking io will be enabled. GLOBUS_FALSE will disable it (de-
        fault);

6.39.3.58   globus_result_t globus_xio_attr_cntl (attr,   driver,   GLOBUS_XIO_TCP_GET_BLOCKING_IO,
globus_bool_t ∗ use_blocking_io_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what
argument(s) it accepts.

Get the blocking io status in use or in attr.

Parameters:
    use_blocking_io_out The flag will be set here. GLOBUS_TRUE for enabled.

6.39.3.59 globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_BLOCKING_-IO, globus_bool_t use_blocking_io_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the blocking io status in use or in attr.

Parameters:
*use_blocking_io_out*The ag will be set here. GLOBUS_TRUE for enabled.

6.40 Types

De nes

- #de ne GLOBUS_XIO_TCP_INVALID_HANDLE

Enumerations

- enum globus_xio_tcp_send_ ags { GLOBUS_XIO_TCP_SEND_OOB = MSG_OOB }

6.40.1 De ne Documentation

6.40.1.1 #de ne GLOBUS_XIO_TCP_INVALID_HANDLE

Invalid handle type.

See also:
GLOBUS_XIO_TCP_SET_HANDLE

6.40.2 Enumeration Type Documentation

6.40.2.1 enum globus_xio_tcp_send_ ags_t

TCP driver speci c types.

Enumeration values:
*GLOBUS_XIO_TCP_SEND_OOB*Use this with GLOBUS_XIO_TCP_SET_SEND_FLAGS to send a TCP message out of band (Urgent data ag set).

6.41 Error Types

Enumerations

- enum globus_xio_tcp_error_type { GLOBUS_XIO_TCP_ERROR_NO_ADDRS }

6.41.1 Detailed Description

The TCP driver is very close to the system code, so most errors reported by it are converted from the system errno. A few of the exceptions are GLOBUS_XIO_ERROR_EOF, GLOBUS_XIO_ERROR_COMMAND, GLOBUS_-XIO_ERROR_CONTACT_STRING, GLOBUS_XIO_ERROR_CANCELED, and GLOBUS_XIO_TCP_ERROR_-NO_ADDRS

See also:
    globus_xio_driver_error_match()
    globus_error_errno_match()

6.41.2   Enumeration Type Documentation

6.41.2.1   enum globus_xio_tcp_error_type_t

TCP driver speci c error types.

Enumeration values:
    GLOBUS_XIO_TCP_ERROR_NO_ADDRS Indicates that no IPv4/6 compatible sockets could be resolved for
        the speci ed hostname.

6.42   Globus XIO UDP Driver

The IPV4/6 UDP socket driver.

Modules

- Opening/Closing
- Reading/Writing
- Env Variables
- Attributes and Cntls
- Types
- Error Types

6.42.1   Detailed Description

The IPV4/6 UDP socket driver.

6.43   Opening/Closing

An XIO handle with the udp driver can be created with globus_xio_handle_create().

The handle can be created in two modes: open server or connected client. If the contact string does not have a host
and port, the udp socket will accept messages from any sender. If a host and port is speci ed, the udp socket will be
'connected' immediately to that host:port. This blocks packets from any sender other than the contact string. A handle
that starts out as an open server can later be 'connected' with GLOBUS_XIO_UDP_CONNECT (presumably after
the rst message is received from a sender and his contact info is available).

When the XIO handle is closed, the udp driver will destroy its internal resources and close the socket (unless this
socket was set on the attr globus_xio_register_open()).

6.44   Reading/Writing

globus_xio_register_read() semantics:

If the waitforbytes parameter is greater than zero, the read will happen asynchronously and be completed when at least
waitforbytes has been read/written.

If the waitforbytes parameter is equal to zero, one of the following alternative behaviors occur:

If the length of the buffer is > 0 the read happens synchronously. If the user is using one of the blocking xio calls, no internal callback will occur.

If the length of the buffer is also 0, the call behaves like an asynchronous noti cation of data ready to be read. ie, an asynchronous select().

In any case, when an error occurs before the waitforbytes request has been met, the outgoing nbytes is set to the amount of data actually read before the error occurred.

If the handle is not connected, the user should pass in a data descriptor. After the read, this data_descriptor will contain the contact string of the sender. The user can either get this contact string with GLOBUS_XIO_UDP_GET_-CONTACT or pass the data descriptor directly to globus_xio_register_write() to send a message back to the sender.

Also, if the handle is not connected, the waitforbytes should probably be 1 to guarantee that only one packet is received and the sender contact isnt overwritten by multiple packets from different senders.

globus_xio_register_write() semantics:

When performing a write, exactly one UDP packet is sent of the entire buffer length. The waitforbytes parameter is ignored. If the entire buffer can not be written a GLOBUS_XIO_UDP_ERROR_SHORT_WRITE error will be returned with nbytes set to the number of bytes actually sent.

If the handle is not 'connected', a contact string must be set in the data descriptor to globus_xio_register_write(). This can either be done explicitly with GLOBUS_XIO_UDP_SET_CONTACT or implicitly by passing in a data descriptor received from globus_xio_register_read()

The udp write semantics are always synchronous. No blocking or internal callback will occur when using globus_-xio_write().

6.45   Env Variables

The udp driver uses the following environment variables

- GLOBUS_HOSTNAME Used when setting the hostname in the contact string

- GLOBUS_UDP_PORT_RANGE Used to restrict the port the udp socket binds to

- GLOBUS_XIO_SYSTEM_DEBUG Available if using a debug build. See globus_debug.h for format. The UDP driver uses globus_xio_system (along with the File and TCP drivers) which de nes the following levels: TRACE for all function call tracing, DATA for data read and written counts, INFO for some special events, and RAW which dumps the raw buffers actually read or written. This can contain binary data, so be careful when you enable it.

6.46   Attributes and Cntls

Enumerations

- enum globus_xio_udp_cmd_t {
  GLOBUS_XIO_UDP_SET_HANDLE ,
  GLOBUS_XIO_UDP_SET_SERVICE ,
  GLOBUS_XIO_UDP_GET_SERVICE ,
  GLOBUS_XIO_UDP_SET_PORT ,
  GLOBUS_XIO_UDP_GET_PORT ,

GLOBUS_XIO_UDP_SET_LISTEN_RANGE,

GLOBUS_XIO_UDP_GET_LISTEN_RANGE,

GLOBUS_XIO_UDP_SET_INTERFACE,

GLOBUS_XIO_UDP_GET_INTERFACE,

GLOBUS_XIO_UDP_SET_RESTRICT_PORT,

GLOBUS_XIO_UDP_GET_RESTRICT_PORT,

GLOBUS_XIO_UDP_SET_REUSEADDR,

GLOBUS_XIO_UDP_GET_REUSEADDR,

GLOBUS_XIO_UDP_SET_NO_IPV6,

GLOBUS_XIO_UDP_GET_NO_IPV6,

GLOBUS_XIO_UDP_GET_HANDLE,

GLOBUS_XIO_UDP_SET_SNDBUF,

GLOBUS_XIO_UDP_GET_SNDBUF,

GLOBUS_XIO_UDP_SET_RCVBUF,

GLOBUS_XIO_UDP_GET_RCVBUF,

GLOBUS_XIO_UDP_GET_CONTACT,

GLOBUS_XIO_UDP_GET_NUMERIC_CONTACT,

GLOBUS_XIO_UDP_SET_CONTACT,

GLOBUS_XIO_UDP_CONNECT,

GLOBUS_XIO_UDP_SET_MULTICAST}

Functions

- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_HANDLE, globus_xio_system_-socket_t handle)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_SERVICE, const char ∗service_-name)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_SERVICE, char ∗service_-name_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_PORT, int listener_port)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_PORT, int ∗listener_port_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_LISTEN_RANGE, int listener_-min_port, int listener_max_port)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_LISTEN_RANGE, int listener_min_port_out, int ∗listener_max_port_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_INTERFACE, const char ∗interface)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_INTERFACE, char ∗interface_-out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_RESTRICT_PORT, globus_-bool_t restrict_port)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_RESTRICT_PORT, globus_-bool_t ∗restrict_port_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_REUSEADDR, globus_bool_t resuseaddr)

- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_UDP_GET_REUSEADDR, globus_bool_t resuseaddr_out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_UDP_SET_NO_IPV6, globus_bool_t no_-ipv6)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_UDP_GET_NO_IPV6, globus_bool_t no_-ipv6_out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_UDP_GET_HANDLE, globus_xio_system_-socket_t handle_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_UDP_GET_HANDLE, globus_xio_-system_socket_t handle_out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_UDP_SET_SNDBUF, int sndbuf)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_UDP_SET_SNDBUF, int sndbuf)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_UDP_GET_SNDBUF, int sndbuf_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_UDP_GET_SNDBUF, int sndbuf_-out)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_UDP_SET_RCVBUF, int rcvbuf)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_UDP_SET_RCVBUF, int rcvbuf)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_UDP_GET_RCVBUF, int rcvbuf_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_UDP_GET_RCVBUF, int rcvbuf_-out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_UDP_GET_CONTACT, char contact_string_out)
- globus_result_t globus_xio_data_descriptor_cntl(dd, driver, GLOBUS_XIO_UDP_GET_CONTACT, char contact_string_out)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_UDP_GET_NUMERIC_CONTACT, char contact_string_out)
- globus_result_t globus_xio_data_descriptor_cntl(dd, driver, GLOBUS_XIO_UDP_GET_NUMERIC_-CONTACT, char contact_string_out)
- globus_result_t globus_xio_data_descriptor_cntl(dd, driver, GLOBUS_XIO_UDP_SET_CONTACT, char contact_string)
- globus_result_t globus_xio_handle_cntl(handle, driver, GLOBUS_XIO_UDP_CONNECT, char contact_-string)
- globus_result_t globus_xio_attr_cntl(attr, driver, GLOBUS_XIO_UDP_SET_MULTICAST, char contact_-string)

6.46.1   Detailed Description

UDP driver speci c attrs and cntls.

See also:
    globus_xio_attr_cntl()
    globus_xio_handle_cntl()
    globus_xio_data_descriptor_cntl()

6.46.2   Enumeration Type Documentation

6.46.2.1   enum globus_xio_udp_cmd_t

UDP driver speci c cntls.

Enumeration values:
    GLOBUS_XIO_UDP_SET_HANDLE See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_SET_SERVICE See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_GET_SERVICE See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_SET_PORT See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_GET_PORT See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_SET_LISTEN_RANGE See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_GET_LISTEN_RANGE See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_SET_INTERFACE See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_GET_INTERFACE See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_SET_RESTRICT_PORT See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_GET_RESTRICT_PORT See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_SET_REUSEADDR See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_GET_REUSEADDR See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_SET_NO_IPV6 See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_GET_NO_IPV6 See usage for globus_xio_attr_cntl

GLOBUS_XIO_UDP_GET_HANDLE See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_UDP_SET_SNDBUF See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_UDP_GET_SNDBUF See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_UDP_SET_RCVBUF See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_UDP_GET_RCVBUF See usage for globus_xio_attr_cntl, globus_xio_handle_cntl

GLOBUS_XIO_UDP_GET_CONTACT See usage for: globus_xio_handle_cntl, globus_xio_data_-descriptor_cntl

GLOBUS_XIO_UDP_GET_NUMERIC_CONTACT See usage for: globus_xio_handle_cntl, globus_xio_-data_descriptor_cntl

GLOBUS_XIO_UDP_SET_CONTACT See usage for globus_xio_data_descriptor_cntl

GLOBUS_XIO_UDP_CONNECT See usage for globus_xio_handle_cntl

GLOBUS_XIO_UDP_SET_MULTICAST See usage for globus_xio_attr_cntl

6.46.3   Function Documentation

6.46.3.1   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_HANDLE, globus_-xio_system_socket_t handle)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the udp socket to use.

Parameters:
       handle Use this handle (fd or SOCKET). Note: close() will not be called on this handle.

6.46.3.2   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_SERVICE, const char service_name)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the udp service name to listen on.

Parameters:

service_nameThe service name to use when setting up the listener. If the service name cannot be resolved, the port (if one is set) will be used instead.

6.46.3.3   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_SERVICE, char service_name_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the service name to listen on.

Parameters:

service_name_outA pointer to the service name will be stored here If none is set, NULL will be passed back. Otherwise, the name will be duplicated with strdup() and the user should call free() on it.

6.46.3.4   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_PORT, intlistener_-port)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the port number to listen on. The default is 0 (system assigned)

Parameters:

listener_port The port number to use when setting up the listener. If the service name is also set, this will only be used if that can't be resolved.

6.46.3.5   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_PORT, int listener_-port_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

the port number to listen on.

Parameters:

listener_port_outThe port will be stored here.

6.46.3.6   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_LISTEN_RANGE, int listener_min_port, int listener_max_port)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the port range to con ne the listener to. Used only where no speci c service or port has been set. It overrides the range set in the GLOBUS_UDP_PORT_RANGE env variable. If 'restrict port' is true, the listening port will be constrained to the range speci ed.

Parameters:
   listener_min_port The lower bound on the listener port. (default 0 – no bound)
   listener_max_portThe upper bound on the listener port. (default 0 – no bound)

See also:
   GLOBUS_XIO_UDP_SET_RESTRICT_PORT

6.46.3.7   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_LISTEN_RANGE, int listener_min_port_out, int   listener_max_port_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the udp port range on an attr.

Parameters:
   listener_min_port_outThe lower bound will be stored here.
   listener_max_port_outThe upper bound will be stored here.

6.46.3.8   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_INTERFACE, const char   interface)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the interface to bind the socket to.

Parameters:
   interface The interface to use. Can be a hostname or numeric IP

6.46.3.9   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_INTERFACE, char interface_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the interface on the attr.

Parameters:
   interface_out A pointer to the interface will be stored here If one is set, NULL will be passed back. Otherwise, the interface will be duplicated with strdup() and the user should call free() on it.

6.46.3.10   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_RESTRICT_PORT, globus_bool_trestrict_port)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Enable or disable the listener range constraints. This enables or ignores the port range found in the attr or in then env. By default, those ranges are enabled.

Parameters:
   restrict_port GLOBUS_TRUE to enable (default), GLOBUS_FALSE to disable.

See also:
   GLOBUS_XIO_UDP_SET_LISTEN_RANGE

6.46.3.11 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_RESTRICT_PORT, globus_bool_t restrict_port_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the restrict port ag.

Parameters:
   restrict_port_out The restrict port ag will be stored here.

6.46.3.12 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_REUSEADDR, globus_bool_t resuseaddr)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Reuse addr when binding. Used to determine whether or not to allow reuse of addresses when binding a socket to a port number.

Parameters:
   resuseaddr GLOBUS_TRUE to allow, GLOBUS_FALSE to disallow (default)

6.46.3.13 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_REUSEADDR, globus_bool_t resuseaddr_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the reuseaddr ag on an attr.

Parameters:
   resuseaddr_out The reuseaddr ag will be stored here.

6.46.3.14 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_NO_IPV6, globus_-bool_t no_ipv6)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Restrict to IPV4 only. Disallow IPV6 sockets from being used (default is to use either ipv4 or ipv6)

Parameters:
   no_ipv6 GLOBUS_TRUE to disallow ipv6, GLOBUS_FALSE to allow (default)

6.46.3.15   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_NO_IPV6, globus_-bool_t   no_ipv6_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the no ipv6 ag on an attr.

Parameters:

no_ipv6_out The no ipv6 ag will be stored here.

6.46.3.16   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_HANDLE, globus_-xio_system_socket_t handle_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the socket handle on an attr or handle.

Parameters:

handle_out The udp socket will be stored here. If none is set, GLOBUS_XIO_UDP_INVALID_HANDLE will be set.

6.46.3.17   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_GET_HANDLE, globus_xio_system_socket_t handle_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the socket handle on an attr or handle.

Parameters:

handle_out The udp socket will be stored here. If none is set, GLOBUS_XIO_UDP_INVALID_HANDLE will be set.

6.46.3.18   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_SNDBUF, int sndbuf)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the socket send buffer size. Used to set the size of the send buffer used on the socket.

Parameters:

sndbuf The send buffer size in bytes to use. (default is system speci c)

6.46.3.19   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_SET_SNDBUF, int sndbuf)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the socket send buffer size. Used to set the size of the send buffer used on the socket.

Parameters:

sndbuf The send buffer size in bytes to use. (default is system speci c)

6.46.3.20   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_SNDBUF, int sndbuf_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the send buffer size on the attr or handle.

Parameters:

   sndbuf_out The send buffer size will be stored here.

6.46.3.21   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_GET_SNDBUF, int sndbuf_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the send buffer size on the attr or handle.

Parameters:

   sndbuf_out The send buffer size will be stored here.

6.46.3.22   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_RCVBUF, int rcvbuf)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the socket receive buffer size. Used to set the size of the receive buffer used on the socket.

Parameters:

   rcvbuf The receive buffer size in bytes. (default is system speci c)

6.46.3.23   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_SET_RCVBUF, int rcvbuf)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the socket receive buffer size. Used to set the size of the receive buffer used on the socket.

Parameters:

   rcvbuf The receive buffer size in bytes. (default is system speci c)

6.46.3.24   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_RCVBUF, int rcvbuf_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the receive buffer size on the attr or handle.

Parameters:

   rcvbuf_out The receive buffer size will be stored here.

6.46.3.25   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_GET_RCVBUF, int rcvbuf_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the receive buffer size on the attr or handle.

Parameters:

> rcvbuf_out The receive buffer size will be stored here.

6.46.3.26   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_GET_CONTACT, char   contact_string_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the contact string associated with a handle or data descriptor. Use with globus_xio_handle_cntl() to get a contact string for the udp listener. Use with globus_xio_data_descriptor_cntl() to get the sender's contact string from a data descriptor passed to globus_xio_register_read()

Parameters:

> contact_string_out A pointer to a contact string will be stored here. The user should free() it when done with it. It will be in the format:< hostname> :< port>

See also:

> GLOBUS_XIO_GET_LOCAL_CONTACT

6.46.3.27   globus_result_t globus_xio_data_descriptor_cntl (dd, driver, GLOBUS_XIO_UDP_GET_-CONTACT, char   contact_string_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the contact string associated with a handle or data descriptor. Use with globus_xio_handle_cntl() to get a contact string for the udp listener. Use with globus_xio_data_descriptor_cntl() to get the sender's contact string from a data descriptor passed to globus_xio_register_read()

Parameters:

> contact_string_out A pointer to a contact string will be stored here. The user should free() it when done with it. It will be in the format:< hostname> :< port>

See also:

> GLOBUS_XIO_GET_LOCAL_CONTACT

6.46.3.28   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_GET_NUMERIC_-CONTACT, char   contact_string_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the contact string associated with a handle or data descriptor. Use with globus_xio_handle_cntl() to get a contact string for the udp listener. Use with globus_xio_data_descriptor_cntl() to get the sender's contact string from a data descriptor passed to globus_xio_register_read()

Parameters:
>   contact_string_out A pointer to a contact string will be stored here. The user should free() it when done with it.
>   It will be in the format: < ip > :< port >

See also:
>   GLOBUS_XIO_GET_LOCAL_NUMERIC_CONTACT

6.46.3.29   globus_result_t   globus_xio_data_descriptor_cntl   (dd,   driver,   GLOBUS_XIO_UDP_GET_-NUMERIC_CONTACT, char   contact_string_out)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get the contact string associated with a handle or data descriptor. Use with globus_xio_handle_cntl() to get a contact string for the udp listener. Use with globus_xio_data_descriptor_cntl() to get the sender's contact string from a data descriptor passed to globus_xio_register_read()

Parameters:
>   contact_string_out A pointer to a contact string will be stored here. The user should free() it when done with it.
>   It will be in the format: < ip > :< port >

See also:
>   GLOBUS_XIO_GET_LOCAL_NUMERIC_CONTACT

6.46.3.30   globus_result_t   globus_xio_data_descriptor_cntl   (dd,   driver,   GLOBUS_XIO_UDP_SET_-CONTACT, char   contact_string)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the destination contact. Use on a data descriptor passed to globus_xio_register_write() to specify the recipient of the data. This is necessary with unconnected handles or to send to recipients other than the connected one.

Parameters:
>   contact_string A pointer to a contact string of the format: hostname/ip :< port/service >

See also:
>   GLOBUS_XIO_UDP_CONNECT

6.46.3.31   globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_CONNECT, char contact_string)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Set the default destination contact. Connecting a handle to a speci c contact blocks packets from any other contact. It also sets the default destination of all outgoing packets so, using GLOBUS_XIO_UDP_SET_CONTACT is unnecessary.

Parameters:
>   contact_string A pointer to a contact string of the format: hostname/ip :< port/service >

6.46.3.32 globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_MULTICAST, char contact_string)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Join a multicast group. Speci y a multicast group to join. All packets received will be to the speci ed multicast address. Do not use GLOBUS_XIO_UDP_CONNECT, GLOBUS_XIO_UDP_SET_PORT, or pass a contact string on the open. Consider using GLOBUS_XIO_UDP_SET_REUSEADDR to allow other apps to join this group. Use GLOBUS_XIO_UDP_SET_INTERFACE to specify the interface to use. Will not affect handles set with GLOBUS_-XIO_UDP_SET_HANDLE. GLOBUS_XIO_UDP_SET_RESTRICT_PORT is ignored.

Parameters:
    contact_string A pointer to a contact string of the multicast group to join with the format: < hostname/ip > :< port/service >

6.47 Types

De nes

- #de ne GLOBUS_XIO_UDP_INVALID_HANDLE

6.47.1 De ne Documentation

6.47.1.1 #de ne GLOBUS_XIO_UDP_INVALID_HANDLE

Invalid handle type.

See also:
    GLOBUS_XIO_UDP_SET_HANDLE

6.48 Error Types

Enumerations

- enum globus_xio_udp_error_type_t {
    GLOBUS_XIO_UDP_ERROR_NO_ADDRS,
    GLOBUS_XIO_UDP_ERROR_SHORT_WRITE }

6.48.1 Detailed Description

The UDP driver is very close to the system code, so most errors reported by it are converted from the system errno. A few of the exceptions are GLOBUS_XIO_ERROR_COMMAND, GLOBUS_XIO_ERROR_CONTACT_STRING, GLOBUS_XIO_ERROR_CANCELED, GLOBUS_XIO_UDP_ERROR_NO_ADDRS, and GLOBUS_XIO_UDP_-ERROR_SHORT_WRITE

See also:
    globus_xio_driver_error_match()
    globus_error_errno_match()

6.48.2 Enumeration Type Documentation

6.48.2.1   enum globus_xio_udp_error_type_t

UDP driver speci c error types.

Enumeration values:

    GLOBUS_XIO_UDP_ERROR_NO_ADDRS Indicates that no IPv4/6 compatible sockets could be resolved for the speci ed hostname.

    GLOBUS_XIO_UDP_ERROR_SHORT_WRITE Indicates that a write of the full buffer failed. Possibly need to increase the send buffer size.

7   globus xio Data Structure Documentation

7.1   globus_xio_http_header_t Struct Reference

HTTP Header.

Data Fields

- char name
- char value

7.1.1   Detailed Description

HTTP Header.

7.1.2   Field Documentation

7.1.2.1   char globus_xio_http_header_t::name

Header Name.

7.1.2.2   char globus_xio_http_header_t::value

Header Value.

8   globus xio File Documentation

8.1   globus_xio_ le_driver.h File Reference

Header le for XIO File Driver.

De nes

- #de ne GLOBUS_XIO_FILE_INVALID_HANDLE

Enumerations

- enum globus_xio_ le_attr_cmd_t {
  GLOBUS_XIO_FILE_SET_MODE,
  GLOBUS_XIO_FILE_GET_MODE,
  GLOBUS_XIO_FILE_SET_FLAGS,
  GLOBUS_XIO_FILE_GET_FLAGS,
  GLOBUS_XIO_FILE_SET_TRUNC_OFFSET,
  GLOBUS_XIO_FILE_GET_TRUNC_OFFSET,
  GLOBUS_XIO_FILE_SET_HANDLE,
  GLOBUS_XIO_FILE_GET_HANDLE,
  GLOBUS_XIO_FILE_SET_BLOCKING_IO,
  GLOBUS_XIO_FILE_GET_BLOCKING_IO,
  GLOBUS_XIO_FILE_SEEK }
- enum globus_xio_ le_ ag_t {
  GLOBUS_XIO_FILE_CREAT = O_CREAT,
  GLOBUS_XIO_FILE_EXCL = O_EXCL,
  GLOBUS_XIO_FILE_RDONLY = O_RDONLY,
  GLOBUS_XIO_FILE_WRONLY = O_WRONLY,
  GLOBUS_XIO_FILE_RDWR = O_RDWR,
  GLOBUS_XIO_FILE_TRUNC = O_TRUNC,
  GLOBUS_XIO_FILE_APPEND = O_APPEND,
  GLOBUS_XIO_FILE_BINARY = 0,
  GLOBUS_XIO_FILE_TEXT = 0 }
- enum globus_xio_ le_mode_t {
  GLOBUS_XIO_FILE_IRWXU = S_IRWXU,
  GLOBUS_XIO_FILE_IRUSR = S_IRUSR,
  GLOBUS_XIO_FILE_IWUSR = S_IWUSR,
  GLOBUS_XIO_FILE_IXUSR = S_IXUSR,
  GLOBUS_XIO_FILE_IRWXO = S_IRWXO,
  GLOBUS_XIO_FILE_IROTH = S_IROTH,
  GLOBUS_XIO_FILE_IWOTH = S_IWOTH,
  GLOBUS_XIO_FILE_IXOTH = S_IXOTH,
  GLOBUS_XIO_FILE_IRWXG = S_IRWXG,
  GLOBUS_XIO_FILE_IRGRP = S_IRGRP,
  GLOBUS_XIO_FILE_IWGRP = S_IWGRP,
  GLOBUS_XIO_FILE_IXGRP = S_IXGRP }
- enum globus_xio_ le_whence_t {
  GLOBUS_XIO_FILE_SEEK_SET = SEEK_SET,
  GLOBUS_XIO_FILE_SEEK_CUR = SEEK_CUR,
  GLOBUS_XIO_FILE_SEEK_END = SEEK_END }

Functions

- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_MODE, int mode)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_MODE, int mode_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_FLAGS, int ags)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_FLAGS, int ags_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_TRUNC_OFFSET, globus_off_t offset)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_TRUNC_OFFSET, globus_off_t offset_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_HANDLE, globus_xio_system_- le_t handle)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_HANDLE, globus_xio_- system_ le_t handle_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_FILE_GET_HANDLE, globus_xio_- system_ le_t handle_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_SET_BLOCKING_IO, globus_bool_t use_blocking_io)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_FILE_SET_BLOCKING_IO, globus_bool_t use_blocking_io)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_FILE_GET_BLOCKING_IO, globus_bool_t use_blocking_io_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_FILE_GET_BLOCKING_IO, globus_bool_t use_blocking_io_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_FILE_SEEK, globus_off_t in_out_- offset, globus_xio_ le_whence_t whence)

8.1.1 Detailed Description

Header le for XIO File Driver.

8.2 globus_xio_http.h File Reference

Globus XIO HTTP Driver Header.

Data Structures

- struct globus_xio_http_header_t
    HTTP Header.

Enumerations

- enum globus_xio_http_handle_cmd_t {
  GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_HEADER,
  GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_STATUS_CODE,
  GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_REASON_PHRASE,
  GLOBUS_XIO_HTTP_HANDLE_SET_RESPONSE_HTTP_VERSION,
  GLOBUS_XIO_HTTP_HANDLE_SET_END_OF_ENTITY }

- enum globus_xio_http_attr_cmd_t {

  GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_METHOD,

  GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_HTTP_VERSION,

  GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_HEADER,

  GLOBUS_XIO_HTTP_ATTR_DELAY_WRITE_HEADER,

  GLOBUS_XIO_HTTP_GET_REQUEST,

  GLOBUS_XIO_HTTP_GET_RESPONSE }

- enum globus_xio_http_errors_t {

  GLOBUS_XIO_HTTP_ERROR_INVALID_HEADER,

  GLOBUS_XIO_HTTP_ERROR_PARSE,

  GLOBUS_XIO_HTTP_ERROR_NO_ENTITY,

  GLOBUS_XIO_HTTP_ERROR_EOF,

  GLOBUS_XIO_HTTP_ERROR_PERSISTENT_CONNECTION_DROPPED }

- enum globus_xio_http_version_t {,

  GLOBUS_XIO_HTTP_VERSION_1_0,

  GLOBUS_XIO_HTTP_VERSION_1_1 }

Functions

- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_HTTP_HANDLE_SET_-RESPONSE_HEADER, const char header_name, const char header_value)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_HTTP_HANDLE_SET_-RESPONSE_STATUS_CODE, int status)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_HTTP_HANDLE_SET_-RESPONSE_REASON_PHRASE, const char reason)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_HTTP_HANDLE_SET_-RESPONSE_HTTP_VERSION, globus_xio_http_version_t version)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_HTTP_HANDLE_SET_END_OF_-ENTITY)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_METHOD, const char method)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_HTTP_-VERSION, globus_xio_http_version_t version)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_HTTP_ATTR_SET_REQUEST_HEADER, const char header_name, const char header_value)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_HTTP_ATTR_DELAY_WRITE_HEADER)
- globus_result_t globus_xio_data_descriptor_cntl (dd, driver, GLOBUS_XIO_HTTP_GET_REQUEST, char method, char uri, globus_xio_http_version_t http_version, globus_hashtable_t headers)
- globus_result_t globus_xio_data_descriptor_cntl (dd, driver, GLOBUS_XIO_HTTP_GET_RESPONSE, int status_code, char reason_phrase, globus_xio_http_version_t http_version, globus_hashtable_t headers)

8.2.1 Detailed Description

Globus XIO HTTP Driver Header.

8.2.2   Function Documentation

8.2.2.1   globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_HTTP_ATTR_DELAY_WRITE_-HEADER)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Delay writing HTTP request until rst data write.

If this attribute is present when opening an HTTP handle, the HTTP request will not be sent immediately upon opening the handle. Instead, it will be delayed until the rst data write is done. This allows other HTTP headers to be sent after the handle is opened.

This attribute cntl takes no arguments.

8.2.2.2   globus_result_t globus_xio_data_descriptor_cntl (dd, driver, GLOBUS_XIO_HTTP_GET_-REQUEST, char method, char uri, globus_xio_http_version_t http_version, globus_hashtable_t headers)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get HTTP Request Information.

Returns in the passed parameters values concerning the HTTP request. Any of the parameters may be NULL if the application is not interested in that part of the information.

Parameters:

method Pointer to be set to the HTTP request method (typically GET, PUT, or POST). The caller must not access this value outside of the lifetime of the data descriptor nor free it.

uri   Pointer to be set to the requested HTTP path. The caller must not access this value outside of the lifetime of the data descriptor nor free it.

http_version Pointer to be set to the HTTP version used for this request.

headers Pointer to be set to point to a hashtable of globus_xio_http_header_t values, keyed by the HTTP header names. The caller must not access this value outside of the lifetime of the data descriptor nor free it or any values in it.

8.2.2.3   globus_result_t globus_xio_data_descriptor_cntl (dd, driver, GLOBUS_XIO_HTTP_GET_-RESPONSE, int status_code, char reason_phrase, globus_xio_http_version_t http_version, globus_-hashtable_t headers)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Get HTTP Response Information

Returns in the passed parameters values concerning the HTTP response. Any of the parameters may be NULL if the application is not interested in that part of the information.

Parameters:

status_code Pointer to be set to the HTTP response status code (such as 404), as per RFC 2616. The caller must not access this value outside of the lifetime of the data descriptor nor free it or any values in it.

reason_phrase Pointer to be set to the HTTP response reason phrase (such as Not Found). The caller must not access this value outside of the lifetime of the data descriptor nor free it or any values in it.

http_version Pointer to be set to the HTTP version used for this request.

headers Pointer to be set to point to a hashtable of globus_xio_http_header values, keyed by the HTTP header names. The caller must not access this value outside of the lifetime of the data descriptor nor free it or any values in it.

8.3   globus_xio_mode_e_driver.h File Reference

Header le for XIO MODE_E Driver.

Enumerations

- enum globus_xio_mode_e_error_type_t { GLOBUS_XIO_MODE_E_HEADER_ERROR }
- enum globus_xio_mode_e_cmd_t {

  GLOBUS_XIO_MODE_E_SET_STACK,

  GLOBUS_XIO_MODE_E_GET_STACK,

  GLOBUS_XIO_MODE_E_SET_NUM_STREAMS,

  GLOBUS_XIO_MODE_E_GET_NUM_STREAMS,

  GLOBUS_XIO_MODE_E_SET_OFFSET_READS,

  GLOBUS_XIO_MODE_E_GET_OFFSET_READS,

  GLOBUS_XIO_MODE_E_SET_MANUAL_EODC,

  GLOBUS_XIO_MODE_E_GET_MANUAL_EODC,

  GLOBUS_XIO_MODE_E_SEND_EOD,

  GLOBUS_XIO_MODE_E_SET_EODC,

  GLOBUS_XIO_MODE_E_DD_GET_OFFSET,

  GLOBUS_XIO_MODE_E_SET_STACK_ATTR,

  GLOBUS_XIO_MODE_E_GET_STACK_ATTR }

Functions

- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_SET_STACK, globus_xio_-stack_t stack)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_STACK, globus_xio_-stack_t stack_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_SET_NUM_STREAMS, int num_streams)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_NUM_STREAMS, int num_streams_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_SET_OFFSET_READS, globus_bool_t offset_reads)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_OFFSET_READS, globus_bool_t offset_reads_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_SET_MANUAL_EODC, globus_bool_t manual_eodc)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_MODE_E_GET_MANUAL_EODC, globus_bool_t manual_eodc_out)

- globus_result_t globus_xio_data_descriptor_cnt(dd,   driver,   GLOBUS_XIO_MODE_E_SEND_EOD,
  globus_bool_t send_eod)
- globus_result_t globus_xio_handle_cnt(handle, driver, GLOBUS_XIO_MODE_E_SET_EODC, int eod_-
  count)
- globus_result_t globus_xio_data_descriptor_cnt(dd, driver, GLOBUS_XIO_MODE_E_DD_GET_OFFSET,
  globus_off_t offset_out)
- globus_result_t globus_xio_attr_cnt(attr, driver, GLOBUS_XIO_MODE_E_GET_STACK_ATTR, globus_-
  xio_attr_t stack_out)

8.3.1   Detailed Description

Header le for XIO MODE_E Driver.

8.4   globus_xio_ordering_driver.h File Reference

Header le for XIO ORDERING Driver.

Enumerations

- enum globus_xio_ordering_error_type_{ t
  GLOBUS_XIO_ORDERING_ERROR_READ,
  GLOBUS_XIO_ORDERING_ERROR_CANCEL }
- enum globus_xio_ordering_cmd_{ t
  GLOBUS_XIO_ORDERING_SET_OFFSET,
  GLOBUS_XIO_ORDERING_SET_MAX_READ_COUNT,
  GLOBUS_XIO_ORDERING_GET_MAX_READ_COUNT,
  GLOBUS_XIO_ORDERING_SET_BUFFERING,
  GLOBUS_XIO_ORDERING_GET_BUFFERING,
  GLOBUS_XIO_ORDERING_SET_BUF_SIZE,
  GLOBUS_XIO_ORDERING_GET_BUF_SIZE,
  GLOBUS_XIO_ORDERING_SET_MAX_BUF_COUNT,
  GLOBUS_XIO_ORDERING_GET_MAX_BUF_COUNT }

Functions

- globus_result_t globus_xio_handle_cntl (handle,   driver,   GLOBUS_XIO_ORDERING_SET_OFFSET,
  globus_off_t offset)
- globus_result_t globus_xio_attr_cnt(attr, driver, GLOBUS_XIO_ORDERING_SET_MAX_READ_COUNT,
  int max_read_count)
- globus_result_t globus_xio_attr_cnt(attr, driver, GLOBUS_XIO_ORDERING_GET_MAX_READ_COUNT,
  int max_read_count_out)
- globus_result_t globus_xio_attr_cnt(attr, driver, GLOBUS_XIO_ORDERING_SET_BUFFERING, globus_-
  bool_t buffering)
- globus_result_t globus_xio_attr_cnt(attr, driver, GLOBUS_XIO_ORDERING_GET_BUFFERING, globus_-
  bool_t buffering_out)
- globus_result_t globus_xio_attr_cnt(attr, driver, GLOBUS_XIO_ORDERING_SET_BUF_SIZE, int buf_size)

- globus_result_t globus_xio_attr_cnt (attr, driver, GLOBUS_XIO_ORDERING_GET_BUF_SIZE, int buf_-size_out)
- globus_result_t globus_xio_attr_cnt (attr, driver, GLOBUS_XIO_ORDERING_SET_MAX_BUF_COUNT, int max_buf_count)
- globus_result_t globus_xio_attr_cnt (attr, driver, GLOBUS_XIO_ORDERING_GET_MAX_BUF_COUNT, int   max_buf_count_out)

8.4.1   Detailed Description

Header le for XIO ORDERING Driver.

8.5   globus_xio_tcp_driver.h File Reference

Header le for XIO TCP Driver.

De nes

- #de ne GLOBUS_XIO_TCP_INVALID_HANDLE

Enumerations

- enum globus_xio_tcp_error_type { GLOBUS_XIO_TCP_ERROR_NO_ADDRS }
- enum globus_xio_tcp_cmd_t {
  GLOBUS_XIO_TCP_SET_SERVICE,
  GLOBUS_XIO_TCP_GET_SERVICE,
  GLOBUS_XIO_TCP_SET_PORT,
  GLOBUS_XIO_TCP_GET_PORT,
  GLOBUS_XIO_TCP_SET_BACKLOG,
  GLOBUS_XIO_TCP_GET_BACKLOG,
  GLOBUS_XIO_TCP_SET_LISTEN_RANGE,
  GLOBUS_XIO_TCP_GET_LISTEN_RANGE,
  GLOBUS_XIO_TCP_GET_HANDLE,
  GLOBUS_XIO_TCP_SET_HANDLE,
  GLOBUS_XIO_TCP_SET_INTERFACE,
  GLOBUS_XIO_TCP_GET_INTERFACE,
  GLOBUS_XIO_TCP_SET_RESTRICT_PORT,
  GLOBUS_XIO_TCP_GET_RESTRICT_PORT,
  GLOBUS_XIO_TCP_SET_REUSEADDR,
  GLOBUS_XIO_TCP_GET_REUSEADDR,
  GLOBUS_XIO_TCP_SET_NO_IPV6,
  GLOBUS_XIO_TCP_GET_NO_IPV6,
  GLOBUS_XIO_TCP_SET_CONNECT_RANGE,
  GLOBUS_XIO_TCP_GET_CONNECT_RANGE,
  GLOBUS_XIO_TCP_SET_KEEPALIVE,

GLOBUS_XIO_TCP_GET_KEEPALIVE,

GLOBUS_XIO_TCP_SET_LINGER,

GLOBUS_XIO_TCP_GET_LINGER,

GLOBUS_XIO_TCP_SET_OOBINLINE,

GLOBUS_XIO_TCP_GET_OOBINLINE,

GLOBUS_XIO_TCP_SET_SNDBUF,

GLOBUS_XIO_TCP_GET_SNDBUF,

GLOBUS_XIO_TCP_SET_RCVBUF,

GLOBUS_XIO_TCP_GET_RCVBUF,

GLOBUS_XIO_TCP_SET_NODELAY,

GLOBUS_XIO_TCP_GET_NODELAY,

GLOBUS_XIO_TCP_SET_SEND_FLAGS,

GLOBUS_XIO_TCP_GET_SEND_FLAGS,

GLOBUS_XIO_TCP_GET_LOCAL_CONTACT,

GLOBUS_XIO_TCP_GET_LOCAL_NUMERIC_CONTACT,

GLOBUS_XIO_TCP_GET_REMOTE_CONTACT,

GLOBUS_XIO_TCP_GET_REMOTE_NUMERIC_CONTACT,

GLOBUS_XIO_TCP_AFFECT_ATTR_DEFAULTS,

GLOBUS_XIO_TCP_SET_BLOCKING_IO,

GLOBUS_XIO_TCP_GET_BLOCKING_IO }

- enum globus_xio_tcp_send_flags_t { GLOBUS_XIO_TCP_SEND_OOB = MSG_OOB }

Functions

- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_SERVICE, const char *service_-name)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_SERVICE, char **service_-name_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_PORT, int listener_port)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_PORT, int *listener_port_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_BACKLOG, int listener_backlog)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_BACKLOG, int *listener_-backlog_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_LISTEN_RANGE, int listener_-min_port, int listener_max_port)
- globus_result_t globus_xio_attr_cntl (attr,   driver,   GLOBUS_XIO_TCP_GET_LISTEN_RANGE,   int listener_min_port_out, int listener_max_port_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_HANDLE, globus_xio_system_-socket_t handle_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_HANDLE, globus_xio_-system_socket_t handle_out)
- globus_result_t globus_xio_server_cntl (server, driver, GLOBUS_XIO_TCP_GET_HANDLE, globus_xio_-system_socket_t handle_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_HANDLE, globus_xio_system_-socket_t handle)

- globus_result_t globus_xio_attr_cntl (attr,   driver,   GLOBUS_XIO_TCP_SET_INTERFACE,   const   char
  interface)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_INTERFACE, char interface_-
  out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_RESTRICT_PORT, globus_-
  bool_t restrict_port)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_RESTRICT_PORT, globus_-
  bool_t restrict_port_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_REUSEADDR, globus_bool_t re-
  suseaddr)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_REUSEADDR, globus_bool_t
  resuseaddr_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_NO_IPV6, globus_bool_t no_-
  ipv6)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_NO_IPV6, globus_bool no_-
  ipv6_out)
- globus_result_t globus_xio_attr_cntl (attr,   driver,   GLOBUS_XIO_TCP_SET_CONNECT_RANGE,   int
  connector_min_port, int connector_max_port)
- globus_result_t globus_xio_attr_cntl (attr,   driver,   GLOBUS_XIO_TCP_GET_CONNECT_RANGE,   int
  connector_min_port_out, int connector_max_port_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_KEEPALIVE, globus_bool_-
  t keepalive)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_KEEPALIVE, globus_-
  bool_t keepalive)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_KEEPALIVE, globus_bool_-
  t keepalive_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_KEEPALIVE, globus_-
  bool_t keepalive_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_LINGER, globus_bool_t linger,
  int linger_time)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_LINGER, globus_bool_t
  linger, int linger_time)
- globus_result_t globus_xio_attr_cntl (attr,   driver,   GLOBUS_XIO_TCP_GET_LINGER,   globus_bool_-
  t linger_out, int linger_time_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_LINGER, globus_bool_t
  linger_out, int linger_time_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_OOBINLINE, globus_bool_-
  t oobinline)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_OOBINLINE, globus_-
  bool_t oobinline)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_OOBINLINE, globus_bool_-
  t oobinline_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_OOBINLINE, globus_-
  bool_t oobinline_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_SNDBUF, int sndbuf)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_SNDBUF, int sndbuf)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_SNDBUF, int sndbuf_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_SNDBUF, int sndbuf_-
  out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_RCVBUF, int rcvbuf)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_RCVBUF, int rcvbuf)

- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_RCVBUF, int rcvbuf_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_RCVBUF, int rcvbuf_-out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_NODELAY, globus_bool_t node-lay)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_NODELAY, globus_-bool_t nodelay)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_NODELAY, globus_bool_-t nodelay_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_NODELAY, globus_-bool_t nodelay_out)
- globus_result_t globus_xio_data_descriptor_cntl (dd, driver, GLOBUS_XIO_TCP_SET_SEND_FLAGS, int send_flags)
- globus_result_t globus_xio_data_descriptor_cntl (dd, driver, GLOBUS_XIO_TCP_GET_SEND_FLAGS, int send_flags_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_LOCAL_CONTACT, char contact_string_out)
- globus_result_t globus_xio_server_cntl (server, driver, GLOBUS_XIO_TCP_GET_LOCAL_CONTACT, char contact_string_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_LOCAL_NUMERIC_-CONTACT, char contact_string_out)
- globus_result_t globus_xio_server_cntl (server, driver, GLOBUS_XIO_TCP_GET_LOCAL_NUMERIC_-CONTACT, char contact_string_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_REMOTE_CONTACT, char contact_string_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_REMOTE_NUMERIC_-CONTACT, char contact_string_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_AFFECT_ATTR_DEFAULTS, globus_bool_t affect_global)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_SET_BLOCKING_IO, globus_bool_t use_blocking_io)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_SET_BLOCKING_IO, globus_-bool_t use_blocking_io)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_TCP_GET_BLOCKING_IO, globus_bool_t use_blocking_io_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_TCP_GET_BLOCKING_IO, globus_bool_t use_blocking_io_out)

8.5.1   Detailed Description

Header file for XIO TCP Driver.

8.6   globus_xio_udp_driver.h File Reference

Header file for XIO UDP Driver.

De nes

- #de ne GLOBUS_XIO_UDP_INVALID_HANDLE

Enumerations

- enum globus_xio_udp_error_type { t
  GLOBUS_XIO_UDP_ERROR_NO_ADDRS,
  GLOBUS_XIO_UDP_ERROR_SHORT_WRITE }
- enum globus_xio_udp_cmd { t
  GLOBUS_XIO_UDP_SET_HANDLE,
  GLOBUS_XIO_UDP_SET_SERVICE,
  GLOBUS_XIO_UDP_GET_SERVICE,
  GLOBUS_XIO_UDP_SET_PORT,
  GLOBUS_XIO_UDP_GET_PORT,
  GLOBUS_XIO_UDP_SET_LISTEN_RANGE,
  GLOBUS_XIO_UDP_GET_LISTEN_RANGE,
  GLOBUS_XIO_UDP_SET_INTERFACE,
  GLOBUS_XIO_UDP_GET_INTERFACE,
  GLOBUS_XIO_UDP_SET_RESTRICT_PORT,
  GLOBUS_XIO_UDP_GET_RESTRICT_PORT,
  GLOBUS_XIO_UDP_SET_REUSEADDR,
  GLOBUS_XIO_UDP_GET_REUSEADDR,
  GLOBUS_XIO_UDP_SET_NO_IPV6,
  GLOBUS_XIO_UDP_GET_NO_IPV6,
  GLOBUS_XIO_UDP_GET_HANDLE,
  GLOBUS_XIO_UDP_SET_SNDBUF,
  GLOBUS_XIO_UDP_GET_SNDBUF,
  GLOBUS_XIO_UDP_SET_RCVBUF,
  GLOBUS_XIO_UDP_GET_RCVBUF,
  GLOBUS_XIO_UDP_GET_CONTACT,
  GLOBUS_XIO_UDP_GET_NUMERIC_CONTACT,
  GLOBUS_XIO_UDP_SET_CONTACT,
  GLOBUS_XIO_UDP_CONNECT,
  GLOBUS_XIO_UDP_SET_MULTICAST }

Functions

- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_HANDLE, globus_xio_system_-socket_t handle)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_SERVICE, const char ∗service_-name)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_SERVICE, char ∗service_-name_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_PORT, int listener_port)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_PORT, int ∗listener_port_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_LISTEN_RANGE, int listener_-min_port, int listener_max_port)

- globus_result_t globus_xio_attr_cntl (attr,   driver,   GLOBUS_XIO_UDP_GET_LISTEN_RANGE,   int listener_min_port_out, intlistener_max_port_out)
- globus_result_t globus_xio_attr_cntl (attr,   driver,   GLOBUS_XIO_UDP_SET_INTERFACE,   const char interface)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_INTERFACE, charinterface_-out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_RESTRICT_PORT, globus_-bool_t restrict_port)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_RESTRICT_PORT, globus_-bool_t restrict_port_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_REUSEADDR, globus_bool_t resuseaddr)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_REUSEADDR, globus_bool_t resuseaddr_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_NO_IPV6, globus_bool_t no_-ipv6)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_NO_IPV6, globus_bool_t no_-ipv6_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_HANDLE, globus_xio_system_-socket_t handle_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_GET_HANDLE, globus_xio_-system_socket_thandle_out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_SNDBUF, int sndbuf)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_SET_SNDBUF, int sndbuf)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_SNDBUF, int sndbuf_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_GET_SNDBUF, int sndbuf_-out)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_RCVBUF, int rcvbuf)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_SET_RCVBUF, int rcvbuf)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_GET_RCVBUF, intrcvbuf_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_GET_RCVBUF, intrcvbuf_-out)
- globus_result_t globus_xio_handle_cntl (handle,   driver,   GLOBUS_XIO_UDP_GET_CONTACT,   char contact_string_out)
- globus_result_t globus_xio_data_descriptor_cntl (dd, driver, GLOBUS_XIO_UDP_GET_CONTACT, char contact_string_out)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_GET_NUMERIC_CONTACT, char   contact_string_out)
- globus_result_t globus_xio_data_descriptor_cntl (dd,   driver,   GLOBUS_XIO_UDP_GET_NUMERIC_-CONTACT, char   contact_string_out)
- globus_result_t globus_xio_data_descriptor_cntl (dd,   driver,   GLOBUS_XIO_UDP_SET_CONTACT,   char contact_string)
- globus_result_t globus_xio_handle_cntl (handle, driver, GLOBUS_XIO_UDP_CONNECT, charcontact_-string)
- globus_result_t globus_xio_attr_cntl (attr, driver, GLOBUS_XIO_UDP_SET_MULTICAST, charcontact_-string)

8.6.1   Detailed Description

Header le for XIO UDP Driver.

9 globus xio Page Documentation

9.1 Data descriptors

globus_xio uses data descriptors to associate meta data with the data being written or the data read.

Data descriptors ow into the drivers read and write interface functions by way of the operation structure. If the driver is interested in viewing the data decriptor it can request it from the operation structure via a call to globus_xio_driver_-operation_get_data_descriptor() and it can view any driver speci c data descriptor via a call to globus_xio_driver_-data_descriptor_get_speci c(). The driver can modify values in the data descriptor by setting values before passing the request down the stack. Several functions are available to modify the data descriptors. There is no need to "set()" the data descriptors back into the operation. The functions for manipluating the values in a DD affect the values xio has directly.

Data descriptors ow back to the driver in the callbacks for the data operations. When calling nished operation on a data operation the driver must pass in a data descriptor. It should get this data descriptor from the io operation callback.

Life Cycle:

Passing in a data descriptor: A data descriptor is rst created by the globus_xio user. The user can add driver speci c data descriptors to it. Once the usre has created and set the attributes on its data descriptor to their liking they pass it into a globus_xio data operation (either read or write). When the data descriptor is passed on globus_xio will make an internal copy of it. It does this by rst coping the user the level data descriptor and then walkinging through the list of driver speci c data descriptor contianed in to and requesting the the driver make a copy of the driver speci c data descriptor. If ever a driver speci c data descriptor is NULL globus_xio need not call into its drivers dd_copy function. If ever the user level data descriptor is NULL globus_xio need not deal with the data descriptor functionality at all.

A data descriptor coming back up the stack Once an io operation reachs the transport driver (the bottom of the stack) it takes on a slightly different role. On the way in it is describing what is requested to be done with the data, on the way out it is describing what has actually been done. Once the transport driver performs the operation it should adjust the data descriptor to re ect what has actually happened (few drivers will need to worry about this). Each driver on the way up can adjust the data descriptor and its driver speci c data decriptor. When xio reachs the the top of the stack it calls a user callback. When that callback returns all memory associated with the data descriptor is cleaned up. The interface function globus_xio_driver_data_descriptor_free() is used for this.

Index