

# globus gsi openssl error Reference Manual

## 0.14

Generated by Doxygen 1.4.6

Sat Feb 6 13:25:35 2010

# Contents

<a href="#">1 globus gsi openssl error Module Index</a>	<a href="#">1</a>
<a href="#">2 globus gsi openssl error Module Documentation</a>	<a href="#">1</a>

## 1 globus gsi openssl error Module Index

### 1.1 globus gsi openssl error Modules


Here is a list of all modules:

<b>Globus OPENSSL Error API</b>	<a href="#">1</a>
<b>Activation</b>	<a href="#">1</a>
<b>Error Construction</b>	<a href="#">2</a>
<b>Error Helper Functions</b>	<a href="#">6</a>

## 2 globus gsi openssl error Module Documentation

### 2.1 Globus OPENSSL Error API

Collaboration diagram for Globus OPENSSL Error API:



These globus\_openssl\_error functions provide a wrapper to error types defined by OpenSSL

#### Modules


- [Activation](#)
- [Error Construction](#)
- [Error Helper Functions](#)

#### 2.1.1 Detailed Description

These globus\_openssl\_error functions provide a wrapper to error types defined by OpenSSL  
Any program that uses Globus OpenSSL Error functions must include "globus\_error\_openssl.h".

### 2.2 Activation

Collaboration diagram for Activation:



Globus GSI OpenSSL Error uses standard Globus module activation and deactivation.

## Defines

- #define [GLOBUS\\_GSI\\_OPENSSL\\_ERROR\\_MODULE](#)

### 2.2.1 Detailed Description

Globus GSI OpenSSL Error uses standard Globus module activation and deactivation.

Before any Globus GSI OpenSSL Error functions are called, the following function must be called:

```
globus_module_activate(GLOBUS_GSI_OPENSSL_ERROR_MODULE)
```

This function returns `GLOBUS_SUCCESS` if Globus GSI OpenSSL Error was successfully initialized, and you are therefore allowed to subsequently call Globus GSI OpenSSL Error functions. Otherwise, an error code is returned, and Globus GSI OpenSSL Error functions should not be subsequently called. This function may be called multiple times.

To deactivate Globus GSI OpenSSL Error, the following function must be called:

```
globus_module_deactivate(GLOBUS_GSI_OPENSSL_ERROR_MODULE)
```

This function should be called once for each time Globus GSI OpenSSL Error was activated.

### 2.2.2 Define Documentation

#### 2.2.2.1 #define GLOBUS\_GSI\_OPENSSL\_ERROR\_MODULE

Module descriptor.

## 2.3 Error Construction

Collaboration diagram for Error Construction:



Create and initialize a Globus OpenSSL Error object.

### Get Error Code

- unsigned long [globus\\_openssl\\_error\\_handle\\_get\\_error\\_code](#) (globus\_openssl\_error\_handle\_t handle)

### Get Error Data

- const char \* [globus\\_openssl\\_error\\_handle\\_get\\_data](#) (globus\_openssl\_error\_handle\_t handle)

## Get Error Data Flags

- int [globus\\_openssl\\_error\\_handle\\_get\\_data\\_flags](#) (globus\_openssl\_error\_handle\_t handle)

## Get Filename

- const char \* [globus\\_openssl\\_error\\_handle\\_get\\_filename](#) (globus\_openssl\_error\_handle\_t handle)

## Get Linenumber

- int [globus\\_openssl\\_error\\_handle\\_get\\_linenumber](#) (globus\_openssl\_error\_handle\_t handle)

## Get Library

- const char \* [globus\\_openssl\\_error\\_handle\\_get\\_library](#) (globus\_openssl\_error\_handle\_t handle)

## Get Function

- const char \* [globus\\_openssl\\_error\\_handle\\_get\\_function](#) (globus\_openssl\_error\_handle\_t handle)

## Get Reason

- const char \* [globus\\_openssl\\_error\\_handle\\_get\\_reason](#) (globus\_openssl\_error\_handle\_t handle)

## Construct Error

- globus\_object\_t \* [globus\\_error\\_construct\\_openssl\\_error](#) (globus\_module\_descriptor\_t \*base\_source, globus\_object\_t \*base\_cause)

## Initialize Error

- globus\_object\_t \* [globus\\_error\\_initialize\\_openssl\\_error](#) (globus\_object\_t \*error, globus\_module\_descriptor\_t \*base\_source, globus\_object\_t \*base\_cause, globus\_openssl\_error\_handle\_t openssl\_error\_handle)

## Defines

- #define [GLOBUS\\_ERROR\\_TYPE\\_OPENSSL](#)

### 2.3.1 Detailed Description

Create and initialize a Globus OpenSSL Error object.

This section defines operations to create and initialize Globus OpenSSLError objects.

### 2.3.2 Define Documentation

#### 2.3.2.1 #define GLOBUS\_ERROR\_TYPE\_OPENSSL

Error type definition.

### 2.3.3 Function Documentation

#### 2.3.3.1 unsigned long globus\_openssl\_error\_handle\_get\_error\_code (globus\_openssl\_error\_handle\_t *handle*)

Get the openssl error code which represents the openssl error from the openssl error handle.

**Parameters:**

*handle* The openssl error handle

**Returns:**

The error code

#### 2.3.3.2 const char\* globus\_openssl\_error\_handle\_get\_data (globus\_openssl\_error\_handle\_t *handle*)

Get the openssl error data which contains additional data about the error from the openssl error handle.

**Parameters:**

*handle* The openssl error handle

**Returns:**

The error data

#### 2.3.3.3 int globus\_openssl\_error\_handle\_get\_data\_flags (globus\_openssl\_error\_handle\_t *handle*)

Get the openssl error data flags from the openssl error handle.

**Parameters:**

*handle* The openssl error handle

**Returns:**

The error data flags

#### 2.3.3.4 const char\* globus\_openssl\_error\_handle\_get\_filename (globus\_openssl\_error\_handle\_t *handle*)

Get the filename where the openssl error occurred from the openssl error handle.

**Parameters:**

*handle* The openssl error handle

**Returns:**

The filename

#### 2.3.3.5 int globus\_openssl\_error\_handle\_get\_linenumber (globus\_openssl\_error\_handle\_t *handle*)

Get the linenumber on which the openssl error occurred from the openssl error handle.

**Parameters:**

*handle* The openssl error handle

**Returns:**

The linenumber

#### 2.3.3.6 **const char\* globus\_openssl\_error\_handle\_get\_library (globus\_openssl\_error\_handle\_t handle)**

Get the library name where the openssl error occurred in from the openssl error handle.

**Parameters:**

*handle* The openssl error handle

**Returns:**

The library name

#### 2.3.3.7 **const char\* globus\_openssl\_error\_handle\_get\_function (globus\_openssl\_error\_handle\_t handle)**

Get the function name where the openssl error occurred from the openssl error handle.

**Parameters:**

*handle* The openssl error handle

**Returns:**

The function name

#### 2.3.3.8 **const char\* globus\_openssl\_error\_handle\_get\_reason (globus\_openssl\_error\_handle\_t handle)**

Get the reason string which caused the openssl error from the openssl error handle.

**Parameters:**

*handle* The openssl error handle

**Returns:**

The reason string

#### 2.3.3.9 **globus\_object\_t\* globus\_error\_construct\_openssl\_error (globus\_module\_descriptor\_t \* base\_source, globus\_object\_t \* base\_cause)**

Allocate and initialize an error of type GLOBUS\_ERROR\_TYPE\_OPENSSL. This function, combined with [globus\\_error\\_initialize\\_openssl\\_error\(\)](#) will recursively generate globus error objects (of type globus\_object\_t) from the errors on openssl's static error stack.

The errors will be chained in a causal fashion to provide a path to the root cause of the actual error.

NOTE: the static stack openssl implements for its errors currently only supports at most 16 errors, so if more are added, the errors that were added first will be wiped out. If 16 errors are counted in the chain of openssl errors, it's possible that some errors (including the original error) are missing.

**Parameters:**

*base\_source* Pointer to the originating globus module.

*base\_cause* The error object causing the error. This parameter should be NULL in nearly all cases, as the root cause of an error will most likely be in the openssl code itself. The actual cause of the error is determined from the static stack of openssl errors.

**Returns:**

The resulting error object. It is the user's responsibility to eventually free this object using [globus\\_object\\_free\(\)](#). A globus\_result\_t may be obtained by calling [globus\\_error\\_put\(\)](#) on this object.

**2.3.3.10 globus\_object\_t\* globus\_error\_initialize\_openssl\_error (globus\_object\_t \* *error*, globus\_module\_descriptor\_t \* *base\_source*, globus\_object\_t \* *base\_cause*, globus\_openssl\_error\_handle\_t *openssl\_error\_handle*)**

Initialize a previously allocated error of type GLOBUS\_ERROR\_TYPE\_OPENSSL.

**Parameters:**

- error* The previously allocated error object.
- base\_source* Pointer to the originating module.
- base\_cause* The error object causing the error. If this is the original error this parameter may be NULL.
- openssl\_error\_handle* The openssl error handle associated with this error, this parameter should already be initialized to contain the openssl error code associated with the error.

**Returns:**

The resulting error object. You may have to call globus\_error\_put() on this object before passing it on.

## 2.4 Error Helper Functions

Collaboration diagram for Error Helper Functions:



Utility functions that deal with Globus OpenSSL Error objects.

### OpenSSL Error Match

- globus\_bool\_t [globus\\_error\\_match\\_openssl\\_error](#) (globus\_object\_t \**error*, unsigned long *library*, unsigned long *function*, unsigned long *reason*)

### Wrap OpenSSL Error

- globus\_object\_t \* [globus\\_error\\_wrap\\_openssl\\_error](#) (globus\_module\_descriptor\_t \**base\_source*, int *error\_type*, const char \**source\_file*, const char \**source\_func*, int *source\_line*, const char \**format*,...)

#### 2.4.1 Detailed Description

Utility functions that deal with Globus OpenSSL Error objects.

This section defines utility function for Globus OpenSSL Error objects.

#### 2.4.2 Function Documentation

**2.4.2.1 globus\_bool\_t globus\_error\_match\_openssl\_error (globus\_object\_t \* *error*, unsigned long *library*, unsigned long *function*, unsigned long *reason*)**

Check whether the error originated from a specific library, from a specific function and is of a specific type.

This function checks whether the error or any of its causative errors originated from a specific library, specific function and is of a specific type.

**Parameters:**

- error* The error object for which to perform the check

*library* The library to check for

*function* The function to check for

*reason* The type to check for

**Returns:**

GLOBUS\_TRUE - the error matched GLOBUS\_FALSE - the error failed to match

**2.4.2.2** `globus_object_t* globus_error_wrap_openssl_error (globus_module_descriptor_t * base_source,  
int error_type, const char * source_file, const char * source_func, int source_line, const char * format, ...)`

Wrap the OpenSSL error and create a wrapped globus error object from the error.

This function gets all the openssl errors from the error list, and chains them using the globus error string object. The resulting globus error object is a wrapper to the openssl error at the end of the chain.

**Parameters:**

*base\_source* The module that the error was generated from

*error\_type* The type of error encapsulating the openssl error

*source\_file* Name of file. Use `__FILE__`

*source\_func* Name of function. Use `_globus_func_name` and declare your func with `GlobusFunc-Name(<name>)`

*source\_line* Line number. Use `__LINE__`

*format* format string for the description of the error entry point where the openssl error occurred, should be followed by parameters to fill the format string (like in printf).

**Returns:**

The globus error object. A `globus_result_t` object can be created using the `globus_error_put` function

**See also:**

`globus_error_put()`



# Index

Activation, [1](#)

Error Construction, [2](#)

Error Helper Functions, [6](#)

Globus OPENSSL Error API, [1](#)

globus\_error\_construct\_openssl\_error

    globus\_openssl\_error\_object, [5](#)

globus\_error\_initialize\_openssl\_error

    globus\_openssl\_error\_object, [5](#)

globus\_error\_match\_openssl\_error

    globus\_openssl\_error\_utility, [6](#)

GLOBUS\_ERROR\_TYPE\_OPENSSL

    globus\_openssl\_error\_object, [3](#)

globus\_error\_wrap\_openssl\_error

    globus\_openssl\_error\_utility, [7](#)

globus\_gsi\_openssl\_error\_activation

    GLOBUS\_GSI\_OPENSSL\_ERROR\_MODULE,  
    [2](#)

GLOBUS\_GSI\_OPENSSL\_ERROR\_MODULE

    globus\_gsi\_openssl\_error\_activation, [2](#)

globus\_openssl\_error\_handle\_get\_data

    globus\_openssl\_error\_object, [4](#)

globus\_openssl\_error\_handle\_get\_data\_flags

    globus\_openssl\_error\_object, [4](#)

globus\_openssl\_error\_handle\_get\_error\_code

    globus\_openssl\_error\_object, [4](#)

globus\_openssl\_error\_handle\_get\_filename

    globus\_openssl\_error\_object, [4](#)

globus\_openssl\_error\_handle\_get\_function

    globus\_openssl\_error\_object, [5](#)

globus\_openssl\_error\_handle\_get\_library

    globus\_openssl\_error\_object, [4](#)

globus\_openssl\_error\_handle\_get\_linenumber

    globus\_openssl\_error\_object, [4](#)

globus\_openssl\_error\_handle\_get\_reason

    globus\_openssl\_error\_object, [5](#)

globus\_openssl\_error\_object

    globus\_error\_construct\_openssl\_error, [5](#)

    globus\_error\_initialize\_openssl\_error, [5](#)

    GLOBUS\_ERROR\_TYPE\_OPENSSL, [3](#)

    globus\_openssl\_error\_handle\_get\_data, [4](#)

    globus\_openssl\_error\_handle\_get\_data\_flags, [4](#)

    globus\_openssl\_error\_handle\_get\_error\_code, [4](#)

    globus\_openssl\_error\_handle\_get\_filename, [4](#)

    globus\_openssl\_error\_handle\_get\_function, [5](#)

    globus\_openssl\_error\_handle\_get\_library, [4](#)

    globus\_openssl\_error\_handle\_get\_linenumber, [4](#)

    globus\_openssl\_error\_handle\_get\_reason, [5](#)

globus\_openssl\_error\_utility

    globus\_error\_match\_openssl\_error, [6](#)

    globus\_error\_wrap\_openssl\_error, [7](#)