

globus gsi proxy core Reference Manual

3.4

Generated by Doxygen 1.2.18

Fri Jun 26 15:33:04 2009

Contents

1 Globus GSI Proxy API	1
2 globus gsi proxy core Module Index	1
3 globus gsi proxy core Module Documentation	1

1 Globus GSI Proxy API

The `globusgsi.proxy` library is motivated by the desire to provide a abstraction layer for the proxy creation and delegation process. For background on this process please refer to the proxy certificate profile draft.

Any program that uses Globus GSI Proxy functions must include "`globusgsi.proxy.h`".

We envision the API being used in the following manner:

Delegator:	Delegatee:
	set desired cert info extension in the handle by using the handle set functions.
	<code>globusgsi.proxy.createreq</code>
<code>globusgsi.proxy.inquire.req</code>	
modify cert info extension by using handle set/get/clear functions.	
<code>globusgsi.proxy.sign.req</code>	
	<code>globusgsi.proxy.assemble.req</code>

2 globus gsi proxy core Module Index

2.1 globus gsi proxy core Modules

Here is a list of all modules:

Activation	1
Handle Management	2
Handle Attributes	13
Proxy Operations	18
Proxy Constants	21

3 globus gsi proxy core Module Documentation

3.1 Activation

Globus GSI Proxy uses standard Globus module activation and deactivation.

De nes

```
#define GLOBUS_GSI_PROXY_MODULE
```

3.1.1 Detailed Description

Globus GSI Proxy uses standard Globus module activation and deactivation.

Before any Globus GSI Proxy functions are called, the following function must be called:

```
globus_module_activate(GLOBUS_GSI_PROXY_MODULE)
```

This function returns `GLOBUS_SUCCESS` if Globus GSI Proxy was successfully initialized, and you are therefore allowed to subsequently call Globus GSI Proxy functions. Otherwise, an error code is returned, and Globus GSI Proxy functions should not be subsequently called. This function may be called multiple times.

To deactivate Globus GSI Proxy, the following function must be called:

```
globus_module_deactivate(GLOBUS_GSI_PROXY_MODULE)
```

This function should be called once for each time Globus GSI Proxy was activated.

3.1.2 De ne Documentation

3.1.2.1 #define GLOBUS_GSI_PROXY_MODULE

Module descriptor.

3.2 Handle Management

Create/Destroy/Modify a GSI Proxy Handle.

Initialize and Destroy

```
globus_result_t globus_gsi_proxy_handle_init (globus_gsi_proxy_handle_t handle, globus_gsi_proxy_handle-
attr_t handle_attrs)
globus_result_t globus_gsi_proxy_handle_destroy(globus_gsi_proxy_handle_t handle)
```

Get/Set Request

```
globus_result_t globus_gsi_proxy_handle_get_req(globus_gsi_proxy_handle_t handle, X509REQ req)
globus_result_t globus_gsi_proxy_handle_set_req(globus_gsi_proxy_handle_t handle, X509REQ req)
```

Get/Set Private Key

```
globus_result_t globus_gsi_proxy_handle_get_private_key (globus_gsi_proxy_handle_t handle, EVP_PKEY
proxy_key)
globus_result_t globus_gsi_proxy_handle_set_private_key (globus_gsi_proxy_handle_t handle, EVP_PKEY
proxy_key)
```

Get/Set Proxy Type

```

globusresultt globusgsi_proxy_handleget_type (globusgsi_proxy_handlet handle, globusgsi_cert_utils_
certtype_t type)
globusresultt globusgsi_proxy_handleset_type (globusgsi_proxy_handlet handle, globusgsi_cert_utils_
certtype_t type)

```

Get/Set Policy

```

globusresultt globusgsi_proxy_handleset_policy (globusgsi_proxy_handlet handle, unsigned char policy_
data, int policy_length, int policy_language_NID)
globusresultt globusgsi_proxy_handleget_policy (globusgsi_proxy_handlet handle, unsigned char
policy_data, int policy_length, int policy_NID)

```

Get/Set X509 Extensions

```

globusresultt globusgsi_proxy_handleadd_extension (globusgsi_proxy_handlet handle, X509-
EXTENSION ext)
globusresultt globusgsi_proxy_handleset_extensions (globusgsi_proxy_handlet handle, STACKOF(X509-
EXTENSION) exts)
globusresultt globusgsi_proxy_handleget_extensions (globusgsi_proxy_handlet handle, STACK-
OF(X509EXTENSION) exts)

```

Get/Set Path Length

```

globusresultt globusgsi_proxy_handleset_pathlen (globusgsi_proxy_handlet handle, long pathlen)
globusresultt globusgsi_proxy_handleget_pathlen (globusgsi_proxy_handlet handle, int pathlen)

```

Get/Set Time Valid

```

globusresultt globusgsi_proxy_handleget_time_valid (globusgsi_proxy_handlet handle, int time_valid)
globusresultt globusgsi_proxy_handleset_time_valid (globusgsi_proxy_handlet handle, int timevalid)

```

Clear Cert Info

```

globusresultt globusgsi_proxy_handleclear_cert_info (globusgsi_proxy_handlet handle)

```

Get/Set Cert Info

```

globusresultt globusgsi_proxy_handleget_proxy_cert_info (globusgsi_proxy_handlet handle, PROXYC-
ERTINFO pci)
globusresultt globusgsi_proxy_handleset_proxy_cert_info (globusgsi_proxy_handlet handle, PROXYCERT-
INFO pci)

```

Get Signing Algorithm

```

globusresultt globusgsi_proxy_handleget_signing_algorithm (globusgsi_proxy_handlet handle, EVPMD
signing_algorithm)

```

Get Key Bits

```
globusresultt globusgsi_proxy_handlegetkeybits(globusgsi_proxy_handlet handle, int key_bits)
```

Get Init Prime

```
globusresultt globusgsi_proxy_handlegetinit_prime(globusgsi_proxy_handlet handle, int init_prime)
```

Get Clock Skew

```
globusresultt globusgsi_proxy_handlegetclock_skew.allowable (globusgsi_proxy_handlet handle, int skew)
```

Get Callback for Creating Keys

```
globusresultt globusgsi_proxy_handlegetkey_gen.callback (globusgsi_proxy_handlet handle, void( callback)(int, int, void ))
```

Get/Set Proxy Common Name

```
globusresultt globusgsi_proxy_handlegetcommonname (globusgsi_proxy_handlet handle, char commonname)
globusresultt globusgsi_proxy_handlesetcommonname (globusgsi_proxy_handlet handle, char commonname)
```

Set/Check Proxy Is Limited

```
globusresultt globusgsi_proxy_handlesetis.limited (globusgsi_proxy_handlet handle, globus_bool_t is_limited)
globusresultt globusgsi_proxy_is.limited (globusgsi_proxy_handlet handle, globus_bool_t is_limited)
```

Typedefs

```
typedef globus_gsi_proxy_handles globusgsi_proxy_handlet
```

3.2.1 Detailed Description

Create/Destroy/Modify a GSI Proxy Handle.

Within the Globus GSI Proxy Library, all proxy operations require a handle parameter. Currently, only one proxy operation may be in progress at once per proxy handle.

This section defines operations to create, modify and destroy GSI Proxy handles.

3.2.2 Typedef Documentation

3.2.2.1 typedef struct globus_gsi_proxy_handle_s globusgsi_proxy_handle_t

GSI Proxy Handle.

An GSI Proxy handle is used to associate state with a group of operations. Handles can have immutable attributes associated with them. All proxy operations take a handle pointer as a parameter.

See also:

[globus.gsi.proxy.handleinit\(\)](#), [globus.gsi.proxy.handledestroy\(\)](#) [Handle Attributes](#)

3.2.3 Function Documentation

3.2.3.1 `globusresult_t globus_gsi_proxy_handle_init (globus.gsi.proxy_handle_t handle, globus.gsi.proxy_handle_attrs_t handle_attrs)`

Initialize a GSI Proxy handle.

Initialize a proxy handle which can be used in subsequent operations. The handle may only be used in one sequence of operations at a time.

Parameters:

handle A pointer to the handle to be initialized. If the handle is originally NULL, space is allocated for it. Otherwise, the current values of the handle are overwritten.

handle_attrs Initial attributes to be used to create this handle.

Returns:

GLOBUS.SUCCESS unless an error occurred, in which case, a globus error object ID is returned

See also:

[globus.gsi.proxy.handledestroy\(\)](#)

3.2.3.2 `globusresult_t globus_gsi_proxy_handle_get_req (globus.gsi.proxy_handle_t handle, X509_REQ req)`

Get the certificate request from a GSI Proxy handle.

Parameters:

handle The handle from which to get the certificate request

req Parameter used to return the request. It is the users responsibility to free the returned request.

Returns:

GLOBUS.SUCCESS unless an error occurred, in which case, a globus error object ID is returned

See also:

[globus.gsi.proxy.handlesetreq\(\)](#)

3.2.3.3 `globusresult_t globus_gsi_proxy_handle_get_private_key (globus.gsi.proxy_handle_t handle, EVP_PKEY proxy_key)`

Get the private key from a GSI Proxy handle.

Parameters:

handle The handle from which to get the private key

proxy_key Parameter used to return the key. It is the users responsibility to free the returned key.

Returns:

GLOBUS_SUCCESS unless an error occurred, in which case, a globus error object ID is returned

See also:

[globusgsi_proxy_handlesetprivatekey\(\)](#)

3.2.3.4 `globusresult_t globus_gsi_proxy_handle_get_type (globus_gsi_proxy_handle_t handle, globus_gsi_cert_utils_cert_type_t type)`

Determine the type of proxy that will be generated when using this handle.

Parameters:

handle The handle from which to get the type

type Parameter used to return the type.

Returns:

GLOBUS_SUCCESS unless an error occurred, in which case, a globus error object ID is returned

See also:

[globusgsi_proxy_handlesettype\(\)](#)

3.2.3.5 `globusresult_t globus_gsi_proxy_handle_set_policy (globus_gsi_proxy_handle_t handle, unsigned char policy_data, int policy_length, int policy_languageNID)`

Set the policy to be used in the GSI Proxy handle.

This function sets the policy to be used in the proxy cert info extension.

Parameters:

handle The handle to be modified.

policy_data The policy data.

policy_length The length of the policy data

policy_languageNID The NID of the policy language.

Returns:

GLOBUS_SUCCESS if the handle and its associated fields are valid otherwise an error is returned

See also:

[globusgsi_proxy_handlegetpolicy\(\)](#)

3.2.3.6 `globusresult_t globus_gsi_proxy_handle_add_extension (globus_gsi_proxy_handle_t handle, X509_EXTENSION ext)`

Add an X509 extension to the GSI Proxy handle to be added to certificate.

This function adds a X509 extension to the proxy certificate.

Parameters:

handle The handle for the proxy to which the extension should be added.

extension The extension to be added.

Returns:

GLOBUS.SUCCESS if the addition was successful, otherwise an error is returned.

See also:

`globus_gsi_proxy_handle_get_extensions()` , `globus_gsi_proxy_handle_set_extensions()`

3.2.3.7 `globusresult_t globus_gsi_proxy_handle_set_pathlen (globus_gsi_proxy_handle_t handle, long pathlen)`

Set the path length to be used in the GSI Proxy handle.

This function sets the path length to be used in the proxy cert info extension.

Parameters:

`handle` The handle to be modified.

`pathlen` The maximum allowable path length

Returns:

GLOBUS.SUCCESS if the handle is valid, otherwise an error is returned

See also:

`globus_gsi_proxy_handle_get_pathlen()`

3.2.3.8 `globusresult_t globus_gsi_proxy_handle_get_time_valid (globus_gsi_proxy_handle_t handle, int time_valid)`

Get the validity time of the proxy

Parameters:

`handle` The proxy handle to get the expiration date of

`time_valid` expiration date of the proxy handle

Returns:

GLOBUS.SUCCESS unless an error occurred, in which case, a globus error object ID is returned

3.2.3.9 `globusresult_t globus_gsi_proxy_handle_clear_cert_info (globus_gsi_proxy_handle_t handle)`

Clear the proxy cert info extension stored in the GSI Proxy handle.

This function clears proxy cert info extension related setting in the GSI Proxy handle.

Parameters:

`handle` The handle for which to clear the proxy cert info extension.

Returns:

GLOBUS.SUCCESS if the handle is valid, otherwise an error is returned

3.2.3.10 `globus_result_t globus_gsi_proxy_handle_get_proxy_cert_info (globus_gsi_proxy_handle_t handle, PROXYCERTINFO pci)`

Get the proxy cert info extension stored in the GSI Proxy handle.

This function retrieves the proxy cert info extension from the GSI Proxy handle.

Parameters:

`handle` The handle from which to get the proxy cert info extension.

`pci` Contains the proxy cert info extension upon successful return. If the handle does not contain a pci extension, this parameter will be NULL upon return.

Returns:

GLOBUS.SUCCESS upon success GLOBUS.GSI_PROXY_ERROR_WITH_HANDLE if handle is invalid

GLOBUS.GSI_PROXY_ERROR_WITH_PROXYCERTINFO if the pci pointer is invalid or if the get failed.

3.2.3.11 `globus_result_t globus_gsi_proxy_handle_get_signing_algorithm (globus_gsi_proxy_handle_t handle, EVP_MD signing_algorithm)`

Get the signing algorithm used to sign the proxy cert request

Parameters:

`handle` The proxy handle containing the type of signing algorithm used

`signing_algorithm` signing algorithm of the proxy handle

Returns:

GLOBUS.SUCCESS unless an error occurred, in which case, a globus error object ID is returned GLOBUS.SUCCESS

3.2.3.12 `globus_result_t globus_gsi_proxy_handle_get_keybits (globus_gsi_proxy_handle_t handle, int key_bits)`

Get the key bits used for the pub/private key pair of the proxy

Parameters:

`handle` The proxy handle to get the key bits of

`key_bits` key bits of the proxy handle

Returns:

GLOBUS.SUCCESS unless an error occurred, in which case, a globus error object ID is returned GLOBUS.SUCCESS

3.2.3.13 `globus_result_t globus_gsi_proxy_handle_get_init_prime (globus_gsi_proxy_handle_t handle, int init_prime)`

Get the init prime of the proxy handle

Parameters:

`handle` The handle to get the init prime used in generating the key pair

`init_prime` The resulting init prime

Returns:

GLOBUS.SUCCESS unless an error occurred, in which case an error object identifier (in the form of a globus result_t) is returned

3.2.3.14 `globus_result_t globus_gsi_proxy_handle_get_clock_skew_allowable (globus_gsi_proxy_handle_t handle, int skew)`

Get the clock skew of the proxy handle

Parameters:

handle The handle to get the clock skew of
skew The resulting clock skew

Returns:

GLOBUS_SUCCESS unless an error occurred, in which case an error object identifier (in the form of a `globus_result_t`) is returned

3.2.3.15 `globus_result_t globus_gsi_proxy_handle_get_key_gen_callback (globus_gsi_proxy_handle_t handle, void(callback)(int, int, void))`

Get the callback for creating the public/private key pair

Parameters:

handle The proxy handle to get the callback from
callback Parameter used for returning the callback

Returns:

GLOBUS_SUCCESS or an error object identifier

3.2.3.16 `globus_result_t globus_gsi_proxy_handle_get_common_name (globus_gsi_proxy_handle_t handle, char common_name)`

Get the proxy common name stored in the GSI Proxy handle.

This function retrieves the proxy common name from the GSI Proxy handle. The common name only impacts draft compliant proxies.

Parameters:

handle The handle from which to get the proxy common name.
common_name Contains the proxy common name upon successful return. If the handle does not contain a common name, this parameter will be NULL upon return.

Returns:

GLOBUS_SUCCESS upon success GLOBUS_GSI_PROXY_ERROR_WITH_HANDLE if handle is invalid

3.2.3.17 `globus_result_t globus_gsi_proxy_handle_set_is_limited (globus_gsi_proxy_handle_t handle, globus_bool_t is_limited)`

Set the limited proxy flag on the proxy handle

Parameters:

handle the proxy handle
is_limited boolean value to set on the proxy handle

Returns:

GLOBUS_SUCCESS unless an error occurred, in which case, a globus error object ID is returned

3.2.3.18 `globus_result_t globus_gsi_proxy_handle_destroy (globus_gsi_proxy_handle_t handle)`

Destroy a GSI Proxy handle.

Parameters:

`handle` The handle to be destroyed.

Returns:

GLOBUS_SUCCESS unless an error occurred, in which case, a globus error object ID is returned

See also:

[globus_gsi_proxy_handle_init\(\)](#)

3.2.3.19 `globus_result_t globus_gsi_proxy_handle_set_req (globus_gsi_proxy_handle_t handle, X509_REQ req)`

Set the certificate request in a GSI Proxy handle.

Parameters:

`handle` The handle for which to set the certificate request

`req` Request to be copied to handle.

Returns:

GLOBUS_SUCCESS unless an error occurred, in which case, a globus error object ID is returned

See also:

[globus_gsi_proxy_handle_get_req\(\)](#)

3.2.3.20 `globus_result_t globus_gsi_proxy_handle_set_private_key (globus_gsi_proxy_handle_t handle, EVP_PKEY proxy_key)`

Set the private key in a GSI Proxy handle.

Parameters:

`handle` The handle for which to set the private key

`proxy_key` Parameter used to pass the key

Returns:

GLOBUS_SUCCESS unless an error occurred, in which case, a globus error object ID is returned

See also:

[globus_gsi_proxy_handle_get_private_key\(\)](#)

3.2.3.21 `globus_result_t globus_gsi_proxy_handle_set_type (globus_gsi_proxy_handle_t handle, globus_gsi_cert_utils_cert_type_t type)`

Set the type of proxy that will be generated when using this handle.

Note that this will have no effect when generating a proxy from a proxy. In that case the generated proxy will inherit the type of the parent.

Parameters:

handle The handle for which to set the type

type Parameter used to pass the type.

Returns:

GLOBUS_SUCCESS unless an error occurred, in which case, a globus error object ID is returned

See also:

[globusgsi_proxy_handlesettype\(\)](#)

3.2.3.22 `globus_result_t globus_gsi_proxy_handle_get_policy (globus_gsi_proxy_handle_t handle, unsigned char policy_data, int policy_length, int policy_NID)`

Get the policy from the GSI Proxy handle.

This function gets the policy that is being used in the proxy cert info extension.

Parameters:

handle The handle to be interrogated.

policy_data The policy data.

policy_length The length of the returned policy

policy_NID The NID of the policy language.

Returns:

GLOBUS_SUCCESS if the handle is valid, otherwise an error is returned

See also:

[globusgsi_proxy_handlesetpolicy\(\)](#)

3.2.3.23 `globus_result_t globus_gsi_proxy_handle_set_extensions (globus_gsi_proxy_handle_t handle, STACK_OF(X509_EXTENSION) exts)`

Set the X509 extensions from a GSI Proxy handle.

This function sets the X509 extensions for a proxy certificate.

Parameters:

handle The handle for the proxy from which the extension should be set.

extensions The extensions to be set. Can be NULL to clear extensions.

Returns:

GLOBUS_SUCCESS if the addition was successful, otherwise an error is returned.

See also:

[globusgsi_proxy_handleaddextension\(\)](#) , [globusgsi_proxy_handleget_extensions\(\)](#)

3.2.3.24 `globus_result_t globus_gsi_proxy_handle_get_extensions (globus_gsi_proxy_handle_t handle, STACK_OF(X509_EXTENSION) *exts)`

Get the X509 extensions from a GSI Proxy handle.

This function returns the X509 extensions from the proxy certificate.

Parameters:

`handle` The handle for the proxy from which the extensions should be retrieved.

`extensions` The variable to hold the extensions. The caller is responsible for freeing the extensions with `sk_X509_EXTENSION_free()` when they are done with them.

Returns:

`GLOBUS_SUCCESS` if the retrieval was successful, otherwise an error is returned.

See also:

`globus_gsi_proxy_handle_add_extension()` , `globus_gsi_proxy_handle_set_extensions()`

3.2.3.25 `globus_result_t globus_gsi_proxy_handle_get_pathlen (globus_gsi_proxy_handle_t handle, int *pathlen)`

Get the path length from the GSI Proxy handle.

This function gets the path length that is being used in the proxy cert info extension.

Parameters:

`handle` The handle to be interrogated.

`pathlen` The maximum allowable path length

Returns:

`GLOBUS_SUCCESS` if the handle is valid, otherwise an error is returned

See also:

`globus_gsi_proxy_handle_set_pathlen()`

3.2.3.26 `globus_result_t globus_gsi_proxy_handle_set_time_valid (globus_gsi_proxy_handle_t handle, int time_valid)`

Set the validity time of the proxy.

Parameters:

`handle` The proxy handle to set the expiration date for

`time_valid` desired expiration date of the proxy

Returns:

`GLOBUS_SUCCESS` unless an error occurred, in which case, a globus error object ID is returned `GLOBUS_SUCCESS`

3.2.3.27 `globus_result_t globus_gsi_proxy_handle_set_proxy_cert_info (globus_gsi_proxy_handle_t handle, PROXYCERTINFO pci)`

Set the proxy cert info extension stored in the GSI Proxy handle.

This function sets the proxy cert info extension in the GSI Proxy handle.

Parameters:

handle The handle for which to set the proxy cert info extension.

pci The proxy cert info extension to set.

Returns:

GLOBUS_SUCCESS upon success GLOBUS_GSI_PROXY_ERROR_WITH_HANDLE if handle is invalid
GLOBUS_GSI_PROXY_ERROR_WITH_PROXYCERTINFO if the pci pointer is invalid or if the set failed.

3.2.3.28 `globus_result_t globus_gsi_proxy_handle_set_common_name (globus_gsi_proxy_handle_t handle, char commonname)`

Set the proxy common name stored in the GSI Proxy handle.

This function sets the proxy common name in the GSI Proxy handle. Note that the common name is only used for draft compliant proxies.

Parameters:

handle The handle for which to set the proxy common name.

commonname The proxy common name to set.

Returns:

GLOBUS_SUCCESS upon success GLOBUS_GSI_PROXY_ERROR_WITH_HANDLE if handle is invalid

3.2.3.29 `globus_result_t globus_gsi_proxy_is_limited (globus_gsi_proxy_handle_t handle, globus_bool_t is_limited)`

Check to see if the proxy is a limited proxy.

Parameters:

handle the proxy handle to check

is_limited boolean value to set depending on the type of proxy

Returns:

GLOBUS_SUCCESS unless an error occurred, in which case, a globus error object ID is returned

3.3 Handle Attributes

Handle attributes are used to control additional features of the GSI Proxy handle.

Initialize & Destroy

```
globus_result_t globus_gsi_proxy_handleattrs_init (globus_gsi_proxy_handleattrs_t handleattrs)
globus_result_t globus_gsi_proxy_handleattrs_destroy (globus_gsi_proxy_handleattrs_t handleattrs)
```

Get/Set Key Bits

```

globusresultt globusgsi_proxy_handleattrs.setkeybits(globusgsi_proxy_handleattrs_t handleattrs, int bits)
globusresultt globusgsi_proxy_handleattrs.getkeybits (globusgsi_proxy_handleattrs_t handleattrs, int
bits)

```

Get/Set Initial Prime Number

```

globusresultt globusgsi_proxy_handleattrs.setinit_prime (globusgsi_proxy_handleattrs_t handleattrs, int
prime)
globusresultt globusgsi_proxy_handleattrs.getinit_prime (globusgsi_proxy_handleattrs_t handleattrs, int
prime)

```

Get/Set Signing Algorithm

```

globusresultt globusgsi_proxy_handleattrs.setsigning.algorithm (globusgsi_proxy_handleattrs_t handle-
attrs, EVPMD algorithm)
globusresultt globusgsi_proxy_handleattrs.getsigning.algorithm (globusgsi_proxy_handleattrs_t handle-
attrs, EVPMD algorithm)

```

Get/Set Clock Skew Allowable

```

globusresultt globusgsi_proxy_handleattrs.setclock_skew.allowable (globusgsi_proxy_handleattrs_t han-
dle_attrs, int skew)
globusresultt globusgsi_proxy_handleattrs.getclock_skew.allowable (globusgsi_proxy_handleattrs_t han-
dle_attrs, int skew)

```

Get/Set Key Gen Callback

```

globusresultt globusgsi_proxy_handleattrs.getkey_gen.callback (globusgsi_proxy_handleattrs_t handle-
attrs, void( callback)(int, int, void ))
globusresultt globusgsi_proxy_handleattrs.setkey_gen.callback (globusgsi_proxy_handleattrs_t handle-
attrs, void( callback)(int, int, void ))

```

Copy Attributes

```

globusresultt globusgsi_proxy_handleattrs.copy (globusgsi_proxy_handleattrs_t a, globusgsi_proxy_-
handleattrs_t b)

```

Typedefs

```

typedef globus_gsi_proxy_handleattrs_s globusgsi_proxy_handleattrs_t

```

3.3.1 Detailed Description

Handle attributes are used to control additional features of the GSI Proxy handle.

These features are operation independent.

Currently there are no attributes.

See also:

[globusgsi.proxy_handlet](#)

3.3.2 Typedef Documentation

3.3.2.1 typedef struct globus_gsi_proxy_handle_attrs_s globus_gsi_proxy_handle_attrs_t

Handle Attributes.

A GSI Proxy handle attributes type is used to associate immutable parameter values [Handle Management](#) handle. A handle attributes object should be created with immutable parameters and then passed to the proxy handle init function [globusgsi.proxy_handleinit\(\)](#).

See also:

[Handle Management](#)

3.3.3 Function Documentation

3.3.3.1 globusresult_t globus_gsi_proxy_handle_attrs_init ([globus_gsi_proxy_handle_attrs_t](#) handle_attrs)

Initialize GSI Proxy Handle Attributes.

Initialize proxy handle attributes, which can (and should) be associated with a proxy handle. For most purposes, these attributes should primarily be used by the proxy handle.

Currently, no attribute values are initialized.

Parameters:

handle_attrs The handle attributes structure to be initialized

Returns:

GLOBUS.SUCCESS unless an error occurred, in which case, a globus error object ID is returned

See also:

[globusgsi.proxy_handleattrs.destroy\(\)](#)

3.3.3.2 globusresult_t globus_gsi_proxy_handle_attrs_setkeybits ([globus_gsi_proxy_handle_attrs_t](#) handle_attrs, int bits)

Set the length of the public key pair used by the proxy certificate

Parameters:

handle_attrs the attributes to set

bits the length to set it to (usually 1024)

Returns:

GLOBUS.SUCCESS

3.3.3.3 globusresult_t globus_gsi_proxy_handle_attrs_setinit_prime ([globus_gsi_proxy_handle_attrs_t](#) handle_attrs, int prime)

Set the initial prime number used for generating public key pairs in the RSA algorithm

Parameters:

handle.attrs The attributes to set

prime The prime number to set it to This value needs to be a prime number

Returns:

GLOBUS.SUCCESS

3.3.3.4 globusresult_t globus_gsi_proxy_handle_attrs_set_signing_algorithm ([globus_gsi_proxy_handle_attrs_t](#) handle.attrs, EVP_MD algorithm)

Sets the Signing Algorithm to be used to sign the certificate request. In most cases, the signing party will ignore this value, and sign with an algorithm of its choice.

Parameters:

handle.attrs The proxy handle to set the signing algorithm of

algorithm The signing algorithm to set

Returns:

Returns GLOBUSSUCCESS if the handle is valid, otherwise an error object is returned.

3.3.3.5 globusresult_t globus_gsi_proxy_handle_attrs_set_clock_skew_allowable ([globus_gsi_proxy_handle_attrs_t](#) handle.attrs, int skew)

Sets the clock skew in minutes of the proxy cert request so that time differences between hosts won't cause problems. This value defaults to 5 minutes.

Parameters:

handle.attrs the handleattrs containing the clock skew to be set

skew the amount to skew by (in seconds)

Returns:

GLOBUS.SUCCESS if the handleattrs is valid - otherwise an error is returned.

3.3.3.6 globusresult_t globus_gsi_proxy_handle_attrs_get_key_gen_callback ([globus_gsi_proxy_handle_attrs_t](#) handle.attrs, void(callback)(int, int, void))

Get the public/private key generation callback that provides status during the generation of the keys

Parameters:

handle.attrs The handleattrs to get the callback from

callback The callback from the handle attributes

Returns:

GLOBUS.SUCCESS if the handleattrs is valid, otherwise an error is returned

3.3.3.7 `globusresult_t globus_gsi_proxy_handle_attrs_copy (globus_gsi_proxy_handle_attrs_t a, globus_gsi_proxy_handle_attrs_t b)`

Make a copy of GSI Proxy handle attributes

Parameters:

- a The handle attributes to copy
- b The copy

Returns:

GLOBUS.SUCCESS

3.3.3.8 `globusresult_t globus_gsi_proxy_handle_attrs_destroy (globus_gsi_proxy_handle_attrs_t handle_attrs)`

Destroy the GSI Proxy handle attributes.

Parameters:

- handle_attrs The handle attributes to be destroyed.

Returns:

GLOBUS.SUCCESS

See also:

[globus_gsi_proxy_handleattrs_init\(\)](#)

3.3.3.9 `globusresult_t globus_gsi_proxy_handle_attrs_get_keybits (globus_gsi_proxy_handle_attrs_t handle_attrs, int bits)`

Gets the length of the public key pair used by the proxy certificate.

Parameters:

- handle_attrs the attributes to get the key length from
- bits the length of the key pair in bits

Returns:

GLOBUS.SUCCESS

3.3.3.10 `globusresult_t globus_gsi_proxy_handle_attrs_get_init_prime (globus_gsi_proxy_handle_attrs_t handle_attrs, int prime)`

Get the initial prime number used for generating the public key pair in the RSA algorithm.

Parameters:

- handle_attrs The attributes to get the initial prime number from
- prime The initial prime number taken from the attributes

Returns:

GLOBUS.SUCCESS

3.3.3.11 `globus_result_t globus_gsi_proxy_handle_attrs_get_signing_algorithm` ([globus_gsi_proxy_handle_attrs_t](#) handle_attrs, EVP_MD algorithm)

Gets the Signing Algorithm to used to sign the certificate request.

In most cases, the signing party will ignore this value, and sign with an algorithm of its choice.

Parameters:

handle_attrs The proxy handle_attrs to get the signing algorithm of
algorithm Parameter used to return the signing algorithm used

Returns:

Returns GLOBUSSUCCESS if the handle is valid, otherwise an error object is returned.

3.3.3.12 `globus_result_t globus_gsi_proxy_handle_attrs_get_clock_skew_allowable` ([globus_gsi_proxy_handle_attrs_t](#) handle_attrs, int skew)

Get the allowable clock skew for the proxy certificate.

Parameters:

handle_attrs The handle_attrs to get the clock skew from
skew The allowable clock skew (in seconds) to get from the proxy certificate request. This value gets set by the function, so it needs to be a pointer.

Returns:

GLOBUS.SUCCESS if the handle_attrs is valid, otherwise an error is returned

3.3.3.13 `globus_result_t globus_gsi_proxy_handle_attrs_set_key_gen_callback` ([globus_gsi_proxy_handle_attrs_t](#) handle_attrs, void(callback)(int, int, void))

Set the public/private key generation callback that provides status during the generation of the keys.

Parameters:

handle_attrs The handle_attrs to get the callback from
callback The callback from the handle attributes

Returns:

GLOBUS.SUCCESS if the handle_attrs is valid, otherwise an error is returned

3.4 Proxy Operations

Initiate a proxy operation.

Create Request

`globus_result_t globus_gsi_proxy_createreq`([globus_gsi_proxy_handle_t](#) handle, BIO output_bio)

Inquire Request

`globus_result_t globus_gsi_proxy_inquire_req`([globus_gsi_proxy_handle_t](#) handle, BIO input_bio)

Resign Certificate

```
globus_result_t globus_gsi_proxy_resign_cert (globus_gsi_proxy_handle_t handle, globus_gsi_cred_handle_t issuer_credential, globus_gsi_cred_handle_t peer_credential, globus_gsi_cred_handle_t resigned_credential)
```

Sign Request

```
globus_result_t globus_gsi_proxy_sign_req (globus_gsi_proxy_handle_t handle, globus_gsi_cred_handle_t issuer_credential, BIO output_bio)
```

Create Signed

```
globus_result_t globus_gsi_proxy_createsigned (globus_gsi_proxy_handle_t handle, globus_gsi_cred_handle_t issuer, globus_gsi_cred_handle_t proxy_credential)
```

Assemble credential

```
globus_result_t globus_gsi_proxy_assemble_cred (globus_gsi_proxy_handle_t handle, globus_gsi_cred_handle_t proxy_credential, BIO input_bio)
```

3.4.1 Detailed Description

Initiate a proxy operation.

This module contains the API functions for a user to request proxy request generation, proxy request inspection and proxy request signature.

3.4.2 Function Documentation

3.4.2.1 `globus_result_t globus_gsi_proxy_create_req (globus_gsi_proxy_handle_t handle, BIO output_bio)`

Create a proxy credential request

This function creates a proxy credential request, ie. a unsigned certificate and the corresponding private key, based on the handle that is passed in. The public part of the request is written to the BIO supplied in the `output_bio` parameter. After the request is written, the PROXYCERTINFO extension contained in the handle is written to the BIO. The proxy handle is updated with the private key.

Parameters:

- handle A GSI Proxy handle to use for the request operation.
- output_bio A BIO to write the resulting request structure to.

Returns:

GLOBUS_SUCCESS unless an error occurred, in which case, a globus error object ID is returned

3.4.2.2 `globus_result_t globus_gsi_proxy_inquire_req (globus_gsi_proxy_handle_t handle, BIO input_bio)`

Inquire a proxy credential request

This function reads the public part of a proxy credential request from `input_bio` and if the request contains a Proxy-CertInfo extension, updates the handle with the information contained in the extension.

Parameters:

handle A GSI Proxy handle to use for the inquire operation.
 input.bio A BIO to read a request structure from.

Returns:

GLOBUS.SUCCESS unless an error occurred, in which case, a globus error object ID is returned

3.4.2.3 `globusresult_t globus_gsi_proxy_resign_cert (globus_gsi_proxy_handle_t handle, globus_gsi_cred_handle_t issuer_credential, globus_gsi_cred_handle_t peer_credential, globus_gsi_cred_handle_t resigned_credential)`

Resign a existing certi cate into a proxy

This function use the public key in a existing certi cate to create a new proxy certi cate chained to the issuers credentials. This operation will add a ProxyCertInfo extension to the proxy certi cate if values contained in the extension are speci ed in the handle.

Parameters:

handle A GSI Proxy handle to use for the signing operation.
 issuer_credential The credential structure to be used for signing the proxy certi cate.
 peer_credential The credential structure that contains the certi cate to be resigned.
 resignedcredential A credential structure that upon return will contain the resigned certi cate and associated certi cate chain.

Returns:

GLOBUS.SUCCESS unless an error occurred, in which case, a globus error object ID is returned

3.4.2.4 `globusresult_t globus_gsi_proxy_sign_req (globus_gsi_proxy_handle_t handle, globus_gsi_cred_handle_t issuer_credential, BIO output_bio)`

Sign a proxy certi cate request

This function signs the public part of a proxy credential request, i.e. the unsigned certi cate, previously read by inquire req using the supplied issuercredential. This operation will add a ProxyCertInfo extension to the proxy certi cate if values contained in the extension are speci ed in the handle. The resulting signed certi cate is written to the output bio.

Parameters:

handle A GSI Proxy handle to use for the signing operation.
 issuer_credential The credential structure to be used for signing the proxy certi cate.
 output.bio A BIO to write the resulting certi cate to.

Returns:

GLOBUS.SUCCESS unless an error occurred, in which case, a globus error object ID is returned

3.4.2.5 `globusresult_t globus_gsi_proxy_create_signed (globus_gsi_proxy_handle_t handle, globus_gsi_cred_handle_t issuer, globus_gsi_cred_handle_t proxy_credential)`

Create Signed Proxy Certi cate

Parameters:

handle The proxy handle used to create and sign the proxy certificate
 issuer The issuing credential, used for signing the proxy certificate
 proxy_credential The new proxy credential, containing the signed cert, private key, etc.

Returns:

GLOBUS_SUCCESS if no error occurred, an error object ID otherwise

3.4.2.6 `globusresult_t globus_gsi_proxy_assemblecred (globus_gsi_proxy_handle_t handle, globus_gsi_cred_handle_t proxy_credential, BIO input_bio)`

Assemble a proxy credential

This function assembles a proxy credential. It reads a signed proxy certificate and a associated certificate chain from the inputbio and combines them with a private key previously generated by a call to `globus_gsi_proxy_createkey`. The resulting credential is then returned through the proxy_credential parameter.

Parameters:

handle A GSI Proxy handle to use for the assemble operation.
 proxy_credential This parameter will contain the assembled credential upon successful return.
 input_bio A BIO to read a signed certificate and corresponding certificate chain from.

Returns:

GLOBUS_SUCCESS if no error occurred, an error object ID otherwise

3.5 Proxy Constants

Enumerations

```
enum globus_gsi_proxy_error_t { GLOBUS_GSI_PROXY_ERROR_SUCCESS = 0, GLOBUS_GSI_PROXY_ERROR_WITH_HANDLE = 1, GLOBUS_GSI_PROXY_ERROR_WITH_HANDLE_ATTRS = 2, GLOBUS_GSI_PROXY_ERROR_WITH_PROXYCERTINFO = 3, GLOBUS_GSI_PROXY_ERROR_WITH_PROXYPOLICY = 4, GLOBUS_GSI_PROXY_ERROR_WITH_PATHLENGTH = 5, GLOBUS_GSI_PROXY_ERROR_WITH_X509_REQ = 6, GLOBUS_GSI_PROXY_ERROR_WITH_X509 = 7, GLOBUS_GSI_PROXY_ERROR_WITH_X509_EXTENSIONS = 8, GLOBUS_GSI_PROXY_ERROR_WITH_PRIVATE_KEY = 9, GLOBUS_GSI_PROXY_ERROR_WITH_BIO = 10, GLOBUS_GSI_PROXY_ERROR_WITH_CREDENTIAL = 11, GLOBUS_GSI_PROXY_ERROR_WITH_CRED_HANDLE = 12, GLOBUS_GSI_PROXY_ERROR_WITH_CRED_HANDLE_ATTRS = 13, GLOBUS_GSI_PROXY_ERROR_ERRNO = 14, GLOBUS_GSI_PROXY_ERROR_SETTING_HANDLE_TYPE = 15, GLOBUS_GSI_PROXY_INVALID_PARAMETER = 16, GLOBUS_GSI_PROXY_ERROR_SIGNING = 17, GLOBUS_GSI_PROXY_ERROR_LAST = 18 }
```

3.5.1 Enumeration Type Documentation

3.5.1.1 `enum globus_gsi_proxy_error_t`

Proxy Error codes.

Enumeration values:

GLOBUS_GSI_PROXY_ERROR_SUCCESS Success - never used.
 GLOBUS_GSI_PROXY_ERROR_WITH_HANDLE Invalid proxy handle state.

GLOBUS_GSI_PROXY_ERROR_WITH_HANDLE_ATTRS Invalid proxy handle attributes state.
GLOBUS_GSI_PROXY_ERROR_WITH_PROXYCERTINFO Error with ASN.1 proxycertinfo structure.
GLOBUS_GSI_PROXY_ERROR_WITH_PROXYPOLICY Error with ASN.1 proxypolicy structure.
GLOBUS_GSI_PROXY_ERROR_WITH_PATHLENGTH Error with proxy path length.
GLOBUS_GSI_PROXY_ERROR_WITH_X509_REQ Error with the X.509 request structure.
GLOBUS_GSI_PROXY_ERROR_WITH_X509 Error with X.509 structure.
GLOBUS_GSI_PROXY_ERROR_WITH_X509_EXTENSIONS Error with X.509 extensions.
GLOBUS_GSI_PROXY_ERROR_WITH_PRIVATE_KEY Error with private key.
GLOBUS_GSI_PROXY_ERROR_WITH_BIO Error with OpenSSL's BIO handle.
GLOBUS_GSI_PROXY_ERROR_WITH_CREDENTIAL Error with credential.
GLOBUS_GSI_PROXY_ERROR_WITH_CRED_HANDLE Error with credential handle.
GLOBUS_GSI_PROXY_ERROR_WITH_CRED_HANDLE_ATTRS Error with credential handle attributes.
GLOBUS_GSI_PROXY_ERROR_ERRNO System error.
GLOBUS_GSI_PROXY_ERROR_SETTING_HANDLE_TYPE Unable to set proxy type.
GLOBUS_GSI_PROXY_INVALID_PARAMETER Invalid function parameter.
GLOBUS_GSI_PROXY_ERROR_SIGNING A error occurred while signing the proxy certificate.
GLOBUS_GSI_PROXY_ERROR_LAST Last marker - never used.

Index

Activation, [1](#)

globusgsi.proxy.activation
 GLOBUS_GSI_PROXY_MODULE, [2](#)
globusgsi.proxy.assembled
 globusgsi.proxy.operations [21](#)
globusgsi.proxy.constants
 GLOBUS_GSI_PROXY_ERROR_ERRNO, [22](#)
 GLOBUS_GSI_PROXY_ERROR_LAST, [22](#)
 GLOBUS_GSI_PROXY_ERROR_SETTING_-
 HANDLE_TYPE, [22](#)
 GLOBUS_GSI_PROXY_ERROR_SIGNING, [22](#)
 GLOBUS_GSI_PROXY_ERROR_SUCCESS [21](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_BIO,
 [22](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_-
 CRED_HANDLE, [22](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_-
 CRED_HANDLE_ATTRS, [22](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_-
 CREDENTIAL, [22](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_-
 HANDLE, [21](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_-
 HANDLE_ATTRS, [21](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_-
 PATHLENGTH, [22](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_-
 PRIVATE_KEY, [22](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_-
 PROXYCERTINFO, [22](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_-
 PROXYPOLICY, [22](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_X509,
 [22](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_X509_-
 EXTENSIONS, [22](#)
 GLOBUS_GSI_PROXY_ERROR_WITH_X509_-
 REQ, [22](#)
 GLOBUS_GSI_PROXY_INVALID_-
 PARAMETER, [22](#)
globusgsi.proxy.constants
 globusgsi.proxy.error.t, [21](#)
globusgsi.proxy.createreq
 globusgsi.proxy.operations, [19](#)
globusgsi.proxy.createsigned
 globusgsi.proxy.operations [20](#)
GLOBUS_GSI_PROXY_ERROR_ERRNO
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_LAST
 globusgsi.proxy.constants [22](#)

GLOBUS_GSI_PROXY_ERROR_SETTING_-
 HANDLE_TYPE
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_SIGNING
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_SUCCESS
 globusgsi.proxy.constants [21](#)
globusgsi.proxy.error.t
 globusgsi.proxy.constants [21](#)
GLOBUS_GSI_PROXY_ERROR_WITH_BIO
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_WITH_CRED_-
 HANDLE
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_WITH_CRED_-
 HANDLE_ATTRS
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_WITH_-
 CREDENTIAL
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_WITH_HANDLE
 globusgsi.proxy.constants [21](#)
GLOBUS_GSI_PROXY_ERROR_WITH_HANDLE_-
 ATTRS
 globusgsi.proxy.constants [21](#)
GLOBUS_GSI_PROXY_ERROR_WITH_-
 PATHLENGTH
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_WITH_PRIVATE_-
 KEY
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_WITH_-
 PROXYCERTINFO
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_WITH_-
 PROXYPOLICY
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_WITH_X509
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_WITH_X509_-
 EXTENSIONS
 globusgsi.proxy.constants [22](#)
GLOBUS_GSI_PROXY_ERROR_WITH_X509_REQ
 globusgsi.proxy.constants [22](#)
globusgsi.proxy.handle
 globusgsi.proxy.handle.add.extension [6](#)
 globusgsi.proxy.handle.clear.cert.info, [7](#)
 globusgsi.proxy.handle.destroy, [9](#)
 globusgsi.proxy.handle.get.clock.skew_-
 allowable, [8](#)

- globusgsi.proxy.handleget.commonname, 9
- globusgsi.proxy.handleget.extensions, 11
- globusgsi.proxy.handleget.init_prime, 8
- globusgsi.proxy.handleget.key_gen.callback, 9
- globusgsi.proxy.handleget.keybits, 8
- globusgsi.proxy.handleget.pathlen, 12
- globusgsi.proxy.handleget.policy, 11
- globusgsi.proxy.handleget.private.key, 5
- globusgsi.proxy.handleget.proxy_cert.info, 7
- globusgsi.proxy.handleget.req, 5
- globusgsi.proxy.handleget.signing.algorithm, 8
- globusgsi.proxy.handleget.time.valid, 7
- globusgsi.proxy.handleget.type, 6
- globusgsi.proxy.handleinit, 5
- globusgsi.proxy.handle.set.commonname, 13
- globusgsi.proxy.handle.set.extensions, 11
- globusgsi.proxy.handle.set.is_limited, 9
- globusgsi.proxy.handle.set.pathlen, 7
- globusgsi.proxy.handle.set.policy, 6
- globusgsi.proxy.handle.set.private.key, 10
- globusgsi.proxy.handle.set.proxy_cert.info, 12
- globusgsi.proxy.handle.set.req, 10
- globusgsi.proxy.handle.set.time.valid, 12
- globusgsi.proxy.handle.set.type, 10
- globusgsi.proxy.handlet, 4
- globusgsi.proxy.is_limited, 13
- globusgsi.proxy.handle.add.extension
 - globusgsi.proxy.handle, 6
- globusgsi.proxy.handleattrs
 - globusgsi.proxy.handleattrs.copy, 16
 - globusgsi.proxy.handleattrs.destroy, 17
 - globusgsi.proxy.handleattrs.get.clock.skew.allowable, 18
 - globusgsi.proxy.handleattrs.get.init_prime, 17
 - globusgsi.proxy.handleattrs.get.key_gen.callback, 16
 - globusgsi.proxy.handleattrs.get.keybits, 17
 - globusgsi.proxy.handleattrs.get.signing.algorithm, 17
 - globusgsi.proxy.handleattrs.init, 15
 - globusgsi.proxy.handleattrs.set.clock.skew.allowable, 16
 - globusgsi.proxy.handleattrs.set.init_prime, 15
 - globusgsi.proxy.handleattrs.set.key_gen.callback, 18
 - globusgsi.proxy.handleattrs.set.keybits, 15
 - globusgsi.proxy.handleattrs.set.signing.algorithm, 16
 - globusgsi.proxy.handleattrst, 15
- globusgsi.proxy.handleattrs.copy
 - globusgsi.proxy.handleattrs, 16
- globusgsi.proxy.handleattrs.destroy
 - globusgsi.proxy.handleattrs, 17
- globusgsi.proxy.handleattrs.get.clock.skew.allowable
 - globusgsi.proxy.handleattrs, 18
- globusgsi.proxy.handleattrs.get.init_prime
 - globusgsi.proxy.handleattrs, 17
- globusgsi.proxy.handleattrs.get.key_gen.callback
 - globusgsi.proxy.handleattrs, 16
- globusgsi.proxy.handleattrs.get.keybits
 - globusgsi.proxy.handleattrs, 17
- globusgsi.proxy.handleattrs.get.signing.algorithm
 - globusgsi.proxy.handleattrs, 17
- globusgsi.proxy.handleattrs.init
 - globusgsi.proxy.handleattrs, 15
- globusgsi.proxy.handleattrs.set.clock.skew.allowable
 - globusgsi.proxy.handleattrs, 16
- globusgsi.proxy.handleattrs.set.init_prime
 - globusgsi.proxy.handleattrs, 15
- globusgsi.proxy.handleattrs.set.key_gen.callback
 - globusgsi.proxy.handleattrs, 18
- globusgsi.proxy.handleattrs.set.keybits
 - globusgsi.proxy.handleattrs, 15
- globusgsi.proxy.handleattrs.set.signing.algorithm
 - globusgsi.proxy.handleattrs, 16
- globusgsi.proxy.handleattrst
 - globusgsi.proxy.handleattrs, 15
- globusgsi.proxy.handleclear.cert.info
 - globusgsi.proxy.handle, 7
- globusgsi.proxy.handle.destroy
 - globusgsi.proxy.handle, 9
- globusgsi.proxy.handle.get.clock.skew.allowable
 - globusgsi.proxy.handle, 8
- globusgsi.proxy.handle.get.commonname
 - globusgsi.proxy.handle, 9
- globusgsi.proxy.handle.get.extensions
 - globusgsi.proxy.handle, 11
- globusgsi.proxy.handle.get.init_prime
 - globusgsi.proxy.handle, 8
- globusgsi.proxy.handle.get.key_gen.callback
 - globusgsi.proxy.handle, 9
- globusgsi.proxy.handle.get.keybits
 - globusgsi.proxy.handle, 8
- globusgsi.proxy.handle.get.pathlen
 - globusgsi.proxy.handle, 12
- globusgsi.proxy.handle.get.policy
 - globusgsi.proxy.handle, 11
- globusgsi.proxy.handle.get.private.key
 - globusgsi.proxy.handle, 5
- globusgsi.proxy.handle.get.proxy_cert.info
 - globusgsi.proxy.handle, 7
- globusgsi.proxy.handle.get.req

[globusgsi.proxy.handle](#),5
[globusgsi.proxy.handle.get.signing.algorithm](#)
[globusgsi.proxy.handle](#),8
[globusgsi.proxy.handle.get.time.valid](#)
[globusgsi.proxy.handle](#),7
[globusgsi.proxy.handle.get.type](#)
[globusgsi.proxy.handle](#),6
[globusgsi.proxy.handle.init](#)
[globusgsi.proxy.handle](#),5
[globusgsi.proxy.handle.set.common.name](#)
[globusgsi.proxy.handle](#),13
[globusgsi.proxy.handle.set.extensions](#)
[globusgsi.proxy.handle](#),11
[globusgsi.proxy.handle.set.is.limited](#)
[globusgsi.proxy.handle](#),9
[globusgsi.proxy.handle.set.path.len](#)
[globusgsi.proxy.handle](#),7
[globusgsi.proxy.handle.set.policy](#)
[globusgsi.proxy.handle](#),6
[globusgsi.proxy.handle.set.private.key](#)
[globusgsi.proxy.handle](#),10
[globusgsi.proxy.handle.set.proxy.cert.info](#)
[globusgsi.proxy.handle](#),12
[globusgsi.proxy.handle.set.req](#)
[globusgsi.proxy.handle](#),10
[globusgsi.proxy.handle.set.time.valid](#)
[globusgsi.proxy.handle](#),12
[globusgsi.proxy.handle.set.type](#)
[globusgsi.proxy.handle](#),10
[globusgsi.proxy.handle.set](#)
[globusgsi.proxy.handle](#),4
[globusgsi.proxy.inquire.req](#)
[globusgsi.proxy.operations](#),19
[GLOBUS_GSI_PROXY_INVALID_PARAMETER](#)
[globusgsi.proxy.constants](#),22
[globusgsi.proxy.is.limited](#)
[globusgsi.proxy.handle](#),13
[GLOBUS_GSI_PROXY_MODULE](#)
[globusgsi.proxy.activation](#),2
[globusgsi.proxy.operations](#)
[globusgsi.proxy.assemble.req](#),21
[globusgsi.proxy.create.req](#),19
[globusgsi.proxy.create.signed](#),20
[globusgsi.proxy.inquire.req](#),19
[globusgsi.proxy.resign.cert](#),20
[globusgsi.proxy.sign.req](#),20
[globusgsi.proxy.resign.cert](#)
[globusgsi.proxy.operations](#),20
[globusgsi.proxy.sign.req](#)
[globusgsi.proxy.operations](#),20

[Handle Attributes](#),13
[Handle Management](#),2

[Proxy Constants](#),21
[Proxy Operations](#),18