



NORDUGRID-MANUAL-4

28/9/2015

EXTENDED RESOURCE SPECIFICATION LANGUAGE

Reference Manual for ARC versions 0.8 and above

Contents

1	Introduction	5
2	xRSL syntax and rules	7
2.1	Syntax	7
2.2	URLs	8
3	Attributes	13
3.1	User-side attributes	13
	executable	13
	arguments	14
	inputFiles	14
	executables	15
	cache	15
	outputFiles	15
	cpuTime	16
	wallTime	17
	gridTime	18
	benchmarks	18
	memory	18
	disk	19
	runTimeEnvironment	19
	middleware	19
	opsys	20
	stdin	20
	stdout	20
	stderr	21
	join	21
	gmlog	21
	jobName	21
	ftpThreads	22
	acl	22
	queue	22
	startTime	23

lifeTime	23
notify	24
rerun	24
architecture	24
nodeAccess	25
dryRun	25
rsl_substitution	25
environment	25
count	26
countpernode	26
exclusiveexecution	26
jobreport	26
credentialserver	27
priority	27
3.2 GM-side attributes	27
sstdin	27
action	28
savestate	28
lrmstype	28
hostName	28
jobid	28
clientxrsl	29
clientsoftware	29
3.3 Unsupported Globus RSL attributes	29
3.3.1 Unsupported RSL 1.0 attributes	29
3.3.2 Unsupported GRAM RSL attributes	30
4 XRSL and JSDL	31
A Examples	33
A.1 User-side xRSL script	33
A.2 GM-side xRSL script	34
A.3 JSDL script	35
B JSDL-ARC schema	37

Chapter 1

Introduction

Computational tasks, such as data mining, data transformation, simulation of various conditions, execution of Monte Carlo algorithms and so on, are normally formalized as series of *jobs* submitted to computing resources. Such computing resources can be mainframe supercomputers, high-performance computing clusters, or even pools of regular desktop PCs. In a conventional approach, application experts obtain user accounts at computing centers and learn peculiarities of their *batch systems* in order to formulate and submit computational jobs to the assigned resource. In the Grid infrastructure [7], experts get simultaneous access to a large number of very different computing resources, which are often widely distributed geographically. In order to abstract from the heterogeneous nature of Grid resources, a high-level job description language is necessary. The diversity of Grid resources implies special requirements for a proper description of a job, introducing many new options as opposed to a conventional high-performance computing center use case.

Globus Alliance [6] developed a Grid middleware toolkit, early versions of which made use of the *Resource Specification Language (RSL)* [1] to parse job options and definitions to resource management systems. The NorduGrid project [2] decided to re-use RSL when they developed the Advanced Resource Connector (ARC), – a solution [5] for a Grid facility, suitable for complex tasks, like, for example, High Energy Physics data processing. To match the complexity of such tasks, this solution requires certain extensions to the RSL.

To describe a task to be submitted to ARC-enabled resources, an extended version of the Globus® RSL is used*. Extensions concern not only introduction of new attributes, but also differentiation between the two levels of job option specifications:

User-side RSL, i.e., the set of attributes specified by a user in a job-specific file. This file is interpreted by a *Client* [4], and after the necessary modifications is passed to the ARC computing service: the *Grid Manager (GM)* [8]

GM-side RSL, i.e., the set of attributes pre-processed by a client, and ready to be interpreted by the GM. Effectively, this is an *internal* job representation of ARC.

A user only has to know the user-side part, and utilize it to describe the Grid tasks. The Grid Manager, however, uses slightly different notations, supplied by the client tools; therefore developers of such tools must take care of converting user-submitted RSL to the internal job description (GM-side RSL).

In what follows, description of the NorduGrid-extended RSL, further denoted as **xRSL**, is given, using the following notations:

<xxxx>	parameter to be substituted with a corresponding string or a number
[xxxx]	optional parameter
xxx yyy zzz	list of possible values of a parameter
–	”same as above”

*One can also use a Grid-standard JSDL language; however, it is less versatile

Usage examples are given for the standard ARC command-line client (also known as *User Interface*) [4]; other clients may introduce additional features, please refer to their respective documentation for details.

Chapter 2

xRSL syntax and rules

For a complete description of Globus® RSL, see reference [1]. xRSL uses the same syntax conventions, although changes the meaning and interpretation of some attributes.

2.1 Syntax

A Grid task is described by means of xRSL attributes, which can be either passed via a command-line, or, more conveniently, be collected in a so-called xRSL-file (suggested extension *.xrsf*). Such a file contains a plain list of attribute-value pairs and boolean operators "&" (for AND) and "|" (for OR). Attribute names are case-insensitive.

If the attributes are specified from the command line, the entire description must be enclosed either in single or in double quotes. Single quotes enclosure is completely analogous to xRSL-file usage, while double quotes imply standard shell expansion of the enclosed string. This has implications when strings contain local shell variables: they **will not be expanded** unless the task description is entered from the command line and is enclosed in double quotes.

An attribute-value pair is a key element of specification. It consists of an expression that assigns one or more values to an attribute, and is enclosed in round brackets:

```
(attribute="value")  
(attribute="value1" "value2") (for multi-valued attributes)
```

Certain attributes do not have assigned value; instead, they contain a list of values that should be put in proper correspondence with each other:

```
(attribute=("value1" "value2")("value3" "value4"))
```

In the example above, **value1** and **value3** are put in correspondence to **value2** and **value4** respectively, according to the context of the attribute.

Values should be enclosed in quotes if they contain blank spaces or special characters. The **special characters** are:

```
+ & | ( ) = < > ! " ' ^ # $
```

To quote a string containing special characters, you can use either single or double quotes. If your string, however, contains both such quotes, you can define any character as an own delimiter, by preceding it with the "carat" (^) character: `attribute=~*My "good" value~*` makes use of a carat-escaped asterisk as a delimiter.

An xRSL job description starts with an ampersand ("&") , to indicate implicit **conjunction** of all the attributes:

```
&(attribute1=value1)(attribute2="value 2")...
```

Whenever a **disjunct**-request of two or more attributes is needed, the following construction can be used:

```
(|(attribute="value1")(attribute="value2")...)
```

Only few selected attributes (indicated further in the document) can be requested by the user multiple times, like in the disjunct request example above. Most attributes **must be unique**, i.e., appear only once in the job description document.

In expressions, the following relational operators are allowed, in general:

```
=    !=    >    <    >=    <=
```

However, most attributes can **only be used with equality operator** “=”. For few attributes (as indicated in the document), some other operators can be used in client-side job description as well*.

Commented lines should start with “(“ and be closed with “*)”:

```
(*attribute="value1"*)
```

Comments can not be nested.

Multiple job description in one file is realized via a standard Globus[®] RSL multi-request operator “+”, which should precede multiple job description:

```
+(&(...))(&(...))(&(...))
```

The xRSL attributes can be written in a single string, or split in lines arbitrary; blank spaces between and inside (attribute="value") relations are ignored.

2.2 URLs

File locations in ARC can be specified both as local file names, and as Internet standard *Uniform Resource Locators (URL)*. There are also some additional URL *options* that can be used.

Depending on the installed ARC components some or all of the following transfer protocols and metadata services are supported:

ftp	ordinary <i>File Transfer Protocol (FTP)</i>
gsiftp	GridFTP, the Globus [®] -enhanced FTP protocol with security, encryption, etc. developed by The Globus Alliance [6]
http	ordinary <i>Hyper-Text Transfer Protocol (HTTP)</i> with PUT and GET methods using multiple streams
https	HTTP with SSL v3
httpg	HTTP with Globus [®] GSI
ldap	ordinary <i>Lightweight Data Access Protocol (LDAP)</i> [11]
srm	Storage Resource Manager (SRM) service [10]
root	Xrootd protocol (available in ARC 2.0.0 and later (read-only), 4.2.0 and later (full functionality))
rucio	Next generation ATLAS data management system (read only, available in ARC 4.1.0 and later)
acix	ARC Cache Index (read only, available in ARC 4.1.0 and later)
file	local to the host file name with a full path

*Job description document received by the server must only contain “=” operators

An URL can be used in a standard form, i.e.

```
protocol://[host[:port]]/file
```

Or, to enhance the performance or take advantage of various features, it can have additional options:

```
protocol://[host[:port]][;option[;option[...]]]/file[:metadataoption[:metadataoption[...]]]
```

For a metadata service URL, construction is the following:

```
protocol://[url[|url[...]]@]host[:port][;option[;option[...]]]
        /lfn[:metadataoption[:metadataoption[...]]]
```

where the nested URL(s) are physical replicas. Options are passed on to all replicas, but if it is desired to use the same option with a different value for all replicas, the option can be specified as a common option using the following syntax:

```
protocol://[;commonoption[;commonoption]] [url[|url[...]]@]host[:port]
        [;option[;option[...]]/lfn[:metadataoption[:metadataoption[...]]]
```

In user-level tools, URLs may be expressed in this syntax, or there may simpler ways to construct complex URLs. In particular, command line tools such as `arccp` and the xRSL and JSDL job description languages provide methods to express URLs and options in a simpler way.

For the SRM service, the syntax is

```
srm://host[:port][;options]/[service_path?SFN=]file[:metadataoptions]
```

Versions 1.1 and 2.2 of the SRM protocol are supported. The default *service_path* is `srm/managerv2` when the server supports v2.2, `srm/managerv1` otherwise.

For Rucio the URLs look like

```
rucio://rucio-lb-prod.cern.ch/replicas/scope/lfn
```

The Rucio authorisation URL can be specified with the environment variable `$RUCIO_AUTH_URL`. The Rucio account to use can be specified either through the `rucioaccount` URL option or `$RUCIO_ACCOUNT` environment variable. If neither are specified the account is taken from the VOMS nickname attribute.

For ACIX the URLs look like

```
acix://cacheindex.ndgf.org:6443/data/index?url=http://host.org/file1
```

The URL components are:

<code>host[:port]</code>	Hostname or IP address [and port] of a server
<code>lfn</code>	Logical File Name
<code>url</code>	URL of the file as registered in indexing service
<code>service_path</code>	End-point path of the web service
<code>file</code>	File name with full path
<code>option</code>	URL option
<code>commonoption</code>	URL option for all replicas
<code>metadataoption</code>	Metadata option

The following URL options are supported:

<code>threads=<number></code>	specifies number of parallel streams to be used by GridFTP or HTTP(s,g); default value is 1, maximal value is 10
<code>exec=yes no</code>	means the file should be treated as executable
<code>preserve=yes no</code>	specify if file must be uploaded to this destination even if job processing failed (default is no)
<code>cache=yes no renew copy check invariant</code>	indicates whether the file should be cached; default for input files in A-REX is yes . renew forces a download of the file, even if the cached copy is still valid. copy forces the cached file to be copied (rather than linked) to the session dir, this is useful if for example the file is to be modified. check forces a check of the permission and modification time against the original source. invariant disables checking the original source modification time. (check option is available in ARC 2.0.0 and above, invariant option is available in ARC 3.0.0 and above).
<code>readonly=yes no</code>	for transfers to <code>file://</code> destinations, specifies whether the file should be read-only (unmodifiable) or not; default is yes
<code>secure=yes no</code>	indicates whether the GridFTP data channel should be encrypted; default is no
<code>blocksize=<number></code>	specifies size of chunks/blocks/buffers used in GridFTP or HTTP(s,g) transactions; default is protocol dependent
<code>checksum=cksum md5 adler32 no</code>	specifies the algorithm for checksum to be computed (for transfer verification or provided to the indexing server). This is overridden by any metadata options specified (see below). If this option is not provided, the default for the protocol is used. checksum=no disables checksum calculation.
<code>overwrite=yes no</code>	make software try to overwrite existing file(s), i.e. before writing to destination, tools will try to remove any information/content associated with specified URL
<code>protocol=gsi gssapi ssl tls ssl3</code>	to distinguish between different kinds of https/httpg and srn protocols. Here gssapi stands for httpg implementation using only GSSAPI functions to wrap data and gsi uses additional headers as implemented in Globus IO. The ssl and tls stand for usual https and especially usable only if used with srn protocol. The ssl3 is mostly same as ssl but uses SSLv3 handshake while establishing https connection. The default is gssapi for srn connections, tls for https and gssapi for httpg . In case of srn if default fails, gsi is then tried.
<code>spacetoken=<pattern></code>	specify the space token to be used for uploads to SRM storage elements supporting SRM version 2.2 or higher
<code>autodir=yes no</code>	specify if before writing to specified location software should try to create all directories mentioned in specified URL. Currently this applies to FTP and GridFTP only. Default for those protocols is yes
<code>tcpnodelay=yes no</code>	controls the use of the TCP_NODELAY socket option (which disables the Nagle algorithm). Applies to http(s) only. Default is no (supported only in arcls and other arc* tools)
<code>transferprotocol=protocols</code>	specify transfer protocols for meta-URLs such as SRM. Multiple protocols can be specified as a comma-separated list in order of preference.
<code>rucioaccount=account</code>	specify the Rucio account to use when authenticating with Rucio.

<code>httpputpartial=yes no</code>	while storing file on HTTP(S) server software will try to send it in chunks/parts. If server reports error for partial PUT command software will fall back to tranfering file in single piece. This behavior is non-standard and not all servers report error properly. Hence default is safer 'no'.
<code>httpgetpartial=yes no</code>	while retrieving file from HTTP(S) server software will try to read in in chunks/parts. If server does not support partial GET command it usually ignores request for partial transfer range and file is transfered in one piece. Default is 'yes'.

Local files are referred to by specifying either a location relative to the job submission working directory, or by an absolute path (the one that starts with `"/`), preceded with a `file://` prefix.

URLs also support metadata options which can be used for registering additional metadata attributes or querying the service using metadata attributes. These options are specified at the end of the LFN and consist of name and value pairs separated by colons. The following attributes are supported:

<code>checksumtype</code>	Type of checksum. Supported values are cksum (default), md5 and Adler32
<code>checksumvalue</code>	The checksum of the file

The checksum attributes may also be used to validate files that were uploaded to remote storage.

Examples of URLs are:

```
http://grid.domain.org/dir/script.sh
gsiftp://grid.domain.org:2811;threads=10;secure=yes/dir/input_12378.dat
ldap://grid.domain.org:389/lc=collection1,rc=Nordugrid,dc=nordugrid,dc=org
file:///home/ausser/griddir/steer.cra
srm://srm.domain.org/griddir/user/file1:checksumtype=adler32:checksumvalue=123456781
srm://srm.domain.org;transferprotocol=https/data/file22
```

¹This is a destination URL. The file will be copied to `srm.domain.org` at the path `griddir/user/file1` and the checksum will be compared to what is reported by the SRM service after the transfer.

²This is a source or destination URL. When getting a TURL from SRM the HTTPS transfer protocol will be requested.

Chapter 3

Attributes

Most of the job description attributes introduced originally by Globus® RSL 1.0 are supported, some with modifications as indicated in this document. Many new attributes are introduced by ARC, of which some are to be specified in the user's script, and others are internal for the GM (are added or modified by client tools).

Attribute names are case-insensitive, although assigned values may well be case-sensitive, if they represent file names, environment variables etc..

It is possible to use unsupported attributes in job description. Standard ARC client submission commands (`arcsub` and `arcresub`) must be used with a command line option “-U” in order to accept unknown attributes. Without this command line option, the client tool will consider job description invalid if it contains unsupported attributes.

3.1 User-side attributes

The following attributes can be specified in a user's xRSL script. Some have to be modified by the client tool before being passed to the GM. If this is the case, the corresponding modified GM input is described in this document as well.

executable

Unique: yes
Operators: =
User input: (`executable=<string>`)
GM input: --
Example: (`executable="local_to_job.exe"`)

The executable to be submitted as a main task to a Local Resource Management System (LRMS).

string file name (including path), local to the computing element (CE)

Executable is a file that has to be executed as the main process of the task. It could be either a pre-compiled binary, or a script. Users may transfer their own executables, or use the ones known to be already installed on the remote system (CE).

If an executable has to be transferred to the destination site (CE) from some source, it has to be specified in the `inputFiles` list. If it is not specified in `inputFiles`, the source is expected to be local to the user (client) and will be added as such to the `inputFiles` list by the ARC Client.

If the file name starts with a leading slash (“/”), it is considered to be **the full path to the executable at the destination site (CE)**; otherwise the location of the file is **relative** to the session directory (where job input and files are stored).

If the xRSL string is entered from the command line and is enclosed in double quotes, standard shell expansion of variables takes place. That is, if the file name contains an environment variable ("\$. . ."), the value of this variable is resolved locally, but if the name itself is also enclosed in double quotes, it will be resolved at the remote computing element:

(executable=\$ROOT_DIR/myprog.exe) – \$ROOT_DIR is resolved locally (*will cause errors if the path does not exist at the execution machine*)

(executable="\$ROOT_DIR/myprog.exe") – \$ROOT_DIR will be resolved remotely

arguments

Unique: yes

Operators: =

User input: (arguments=<string> [string] ...)

GM input: (arguments=<executable> <string> [string] ...)

Example: (arguments="10000" \$(ATLAS)/input.dat)

List of the arguments for the executable.

string	an argument
executable	the executable to be run by LRMS, taken by the ARC Client from the user-specified executable attribute

inputFiles

Unique: yes

Operators: =

User input: (inputFiles=(<filename> <source> [option] ...) ...)

GM input: (inputFiles=(<filename> <URL>
(<filename> [size] [.checksum]) ...)

Example: (inputFiles=("local_to_job" "gsiftp://se1.lu.se/p1/remote.1" "threads=5")
("local_to_job.dat" "/scratch/local_to_me.dat")
("same_name_as_in_my_current_dir" ""))

List of files to be copied to the computing element before job execution.

filename	destination file name, local to the computing element and always relative to the session directory
source	source of the file: (remote URLs, or a path, local to the submission node). If void ("", use the quotes!), the input file is taken from the submission directory.
option	(ARC \geq 1.0) URL options for source. See Section 2.2 for possible values. The ARC Client converts source and any options given here to a URL with the syntax described in Section 2.2.
URL	URL of the file (see Section 2.2)
size	file size in bytes
checksum	file checksum (as returned by cksum)

If the **inputFiles** list does not contain the standard input file (as specified by **stdin**) and/or the executable file (as specified by **executable**), an ARC client must append these files to the list. If the <source> is a URL, any options given by **option** are added to it, then it is passed by the ARC Client to the GM as shown in the example above. GM recognizes all URLs except **file:///**.

Internally, the client must forward the (`<filename> <source> [option] ...`) request to the execution service without changes, unless `<source>` is a local path, void (`""`) or `file:///`. In case `<source>` is a local path, void (`""`) or `file:///`, the client must extract file size and checksum, and substitute the `<source>` string with `[size].[checksum]`. In the unlikely case when it is impossible to extract file size, the `<source>` string must be substituted by a void one (`""`).

Please note that the `inputFiles` attribute is not meant to operate with directories, for reasons of access control and checksum verifications. You must specify a pair ("`<local_to_job>`" "`<source>`") for each file.

executables

Unique: yes
 Operators: =
 User input: (`executables=<string> [string] ...`)
 GM input: --
 Example: (`executables="myscript.sh" "myjob.exe"`)

List of files from the `inputFiles` set, which will be given executable permissions.

string file name, local to the computing element and relative to the session directory

If the executable file (as specified in `executable` and if relative to the session directory) is not in the `executables` list, it will be added to the list by the ARC Client.

cache

Unique: yes
 Operators: =
 User input: (`cache="yes"|"no"`)
 GM input: --
 Example: (`cache="yes"`)

Specifies whether input files specified in the `inputFiles` should be placed by default in the cache or not. This affects all input files, even those described by `executables`.

If not specified, default value is "yes".

Cached files can not be modified by jobs by default. If your job has to modify input files, please use the (`readonly="no"`) URL option for those files. This option does not affect whether or not the file is cached.

outputFiles

Unique: yes
 Operators: =
 User input: (`outputFiles=(<string> <URL> [option] ...) ...`)
 GM input: (`outputFiles=(<string> <URL>) ...`)
 Example: (`outputFiles=("local_to_job.dat" "gsiftp://se1.uio.no/stored.dat")`
 (`"local_to_job_dir/" ""`))

The client converts time specified in the user-side XRSL file to seconds. If no time unit is specified, the client assumes the time given in minutes. Otherwise, a text format is accepted, i.e., any of the following will be interpreted properly (make sure to enclose such strings in quotes!):

```
"1 week"
"3 days"
"2 days, 12 hours"
"1 hour, 30 minutes"
"36 hours"
"9 days"
"240 minutes"
```

If both `cpuTime` and `wallTime` are specified, the ARC Client converts them both. `cpuTime` can not be specified together with `gridTime` or `benchmarks`.

This attribute should be used to direct the job to a system with sufficient CPU resources, typically, a batch queue with the sufficient upper time limit. Jobs exceeding this maximum most likely will be **terminated** by remote systems! If time limits are not specified, the limit is not set and jobs can run as long as the system settings allow (note that in this case you can not avoid queues with too short time limits).

wallTime

```
Unique:      yes
Operators:   =
User input:  (wallTime=<time>)
GM input:    (wallTime=<tttt>)
Example:     (wallTime="240")
```

Maximal wall clock time request for the job.

```
time  time (in minutes if no unit is specified)
tttt  time converted by the ARC Client to seconds
```

The client converts time specified in the user-side XRSL file seconds. If no time unit is specified, the client assumes the time given in minutes. Otherwise, a text format is accepted, i.e., any of the following will be interpreted properly (make sure to enclose such strings in quotes!):

```
"1 week"
"3 days"
"2 days, 12 hours"
"1 hour, 30 minutes"
"36 hours"
"9 days"
"240 minutes"
```

If both `cpuTime` and `wallTime` are specified, the ARC Client converts them both. `wallTime` can not be specified together with `gridTime` or `benchmarks`. If only `wallTime` is specified, but not `cpuTime`, the corresponding `cpuTime` value is evaluated by the ARC Client and added to the job description.

This attribute should be used to direct the job to a system with sufficient CPU resources, typically, a batch queue with the sufficient upper time limit. Jobs exceeding this maximum most likely will be

terminated by remote systems! If time limits are not specified, the limit is not set and jobs can run as long as the system settings allow (note that in this case you can not avoid queues with too short time limits).

gridTime

Unique: yes
 Operators: =
 User input: (gridTime=<time>)
 GM input: none
 Example: (gridTime="2 h")

Maximal CPU time request for the job scaled to the 2.8 GHz Intel® Pentium® 4 processor.

time time (in minutes if no unit is specified)

The attribute is completely analogous to **cpuTime**, except that it will be recalculated to the actual CPU time request for each queue, depending on the published processor clock speed.

gridTime can not be specified together with **cpuTime** or **wallTime**. If only **gridTime** is specified, but not **cpuTime**, the corresponding **cpuTime** value is evaluated by the ARC Client and added to the job description.

benchmarks

Unique: yes
 Operators: =
 User input: (benchmarks=(<string> <value> <time>) ...)
 GM input:
 Example: (benchmarks=("mybenchmark" "10" "1 hour, 30 minutes"))

Evaluate a job's **cpuTime** based on benchmark values.

string benchmark name
value benchmark value of reference machine
time the **cpuTime** the job requires on the reference machine

benchmarks can not be specified together with **cpuTime** or **wallTime**. If only **benchmarks** is specified, but not **cpuTime**, the corresponding **cpuTime** value is evaluated by the ARC Client and added to the job description.

memory

Unique: yes
 Operators: =
 User input: (memory=<integer>)
 GM input: --
 Example: (memory>="500")

Memory required for the job, per count for parallel jobs.

integer size (Mbytes)

Similarly to `cpuTime`, this attribute should be used to direct a job to a resource with a sufficient capacity. Jobs exceeding this memory limit will most likely be **terminated** by the remote system.

disk

Unique: no
 Operators: = != > < >= <=
 User input: (disk=<integer>)
 GM input: none
 Example: (disk="500")

Disk space required for the job.

integer disk space, Mbytes

This attribute is used at the job submission time to find a system with sufficient disk space. However, it **does not guarantee** that this space will be available at the end of the job, as most known systems do not allow for disk space allocation. Eventually, a remote system can terminate a job that exceeds the requested disk space.

runTimeEnvironment

Unique: no
 Operators: = != > < >= <=
 User input: (runTimeEnvironment=<string>)(runTimeEnvironment=<string>)
 GM input: only = is allowed
 Example: (runTimeEnvironment>="APPS/HEP/ATLAS-10.0.1")

Required runtime environment.

string environment name

The site to submit the job to will be chosen by the ARC Client among those advertising specified runtime environments. Before starting the job, the GM will set up environment variables and paths according to those requested. Runtime environment names are defined by Virtual Organizations, and tend to be organized in name spaces.

To request several environments, repeat the attribute string:
 (runTimeEnvironment="ENV1")(runTimeEnvironment="ENV2") etc.

To make a disjunct-request, use a boolean expression:
 (|(runTimeEnvironment="env1")(runTimeEnvironment="env2")).

You can use ">=" or "<=" operators: job will be submitted to any suitable site that satisfies such requirements, and among the available at the sites runtime environments, the highest version satisfying a requirement will be requested in the pre-processed xRSL script.

Runtime environment string interpretation is case-insensitive. If a runtime environment string consists of a name and a version number, a partial specification is possible: it is sufficient to request only the name and use ">" or ">=" operators to select the highest version.

middleware

Unique: no
 Operators: = != > < >= <=
 User input: (middleware=<string>)
 GM input: only = is allowed
 Example: (middleware="nordugrid-arc-0.5.99")

Required middleware version. Make sure to specify full name and version number.

string Grid middleware name.

The site to submit the job to will be chosen by the ARC Client among those advertising specified middleware. Usage is identical to that of the `runTimeEnvironment`. Use the ">=" operator to request a version "equal or higher".

opsys

Unique: no
 Operators: = != > < >= <=
 User input: (opsys=<string>)
 GM input: only = is allowed
 Example: (opsys="FC3")

Required operating system.

string Operating system name and version.

The site to submit the job to will be chosen by the ARC Client among those advertising specified operating system. Usage is identical to that of `runTimeEnvironment` and `middleware`. Use the ">=" operator to request a version "equal or higher".

stdin

Unique: yes
 Operators: =
 User input: (stdin=<string>)
 GM input: --
 Example: (stdin="myinput.dat")

The standard input file.

string file name, local to the computing element

The standard input file should be listed in the `inputFiles` attribute; otherwise it will be forced to that list by the ARC Client.

stdout

Unique: yes
 Operators: =
 User input: (stdout=<string>)
 GM input: --
 Example: (stdout="myoutput.txt")

The standard output file.

string file name, local to the computing element and relative to the session directory.

The standard output file should be listed in the **outputFiles** attribute; otherwise it will be forced to that list by the ARC Client. If the standard output is not defined, ARC Client assigns a name.

stderr

Unique: yes
 Operators: =
 User input: (stderr=<string>)
 GM input: --
 Example: (stderr="myjob.err")

The standard error file.

string file name, local to the computing element and relative to the session directory.

The standard error file should be listed as an **outputFiles** attribute; otherwise it will be forced to that list by the ARC Client. If the standard error is not defined, ARC Client assigns a name. If **join** is specified with value "yes", ARC Client adds **stderr** to the pre-processed xRSL script with the same value as **stdout**.

join

Unique: yes
 Operators: =
 User input: (join="yes"|"no")
 GM input: none
 Example: (join="yes")

If "yes", joins **stderr** and **stdout** files into the **stdout** one. Default is no.

gmlog

Unique: yes
 Operators: =
 User input: (gmlog=<string>)
 GM input: --
 Example: (gmlog="myjob.log")

A name of the directory containing grid-specific diagnostics per job.

string a directory, local to the computing element and relative to the session directory

This directory is kept in the session directory to be available for retrieval (ARC Client forces it to the list if **outputFiles**)

jobName

Unique: yes
 Operators: =
 User input: (jobName=<string>)
 GM input: -"
 Example: (jobName="My Job nr. 1")

User-specified job name.

string job name

This name is meant for convenience of the user. It can be used to select the job while using the ARC Client. It is also available through the Information System.

ftpThreads

Unique: yes
 Operators: =
 User input: (ftpThreads=<integer>)
 GM input: -"
 Example: (ftpThreads="4")

Defines how many parallel streams will be used by the GM during **gsiftp** and **http(s|g)** transfers of files.

integer a number from 1 to 10

If not specified, parallelism is not used.

acl

Unique: no
 Operators: =
 User input: (acl=<xml>)
 GM input: -"
 Example: (acl="<?xml version=""1.0""?>
 <gac1 version=""0.0.1""><entry><any-user></any-user>
 <allow><write/><read/><list/><admin/></allow></entry></gac1>")

Makes use of GACL [9] rules to list users who are allowed to access and control job in addition to job's owner. Access and control levels are specified per user. **any-user** tag refers to any user authorized at the execution cluster. To get more information about GACL please refer to <http://www.gridsite.org>.

xml a GACL-compliant XML string defining access control list

Following job control levels can be specified via **acl**:

write - allows to modify contents of job data (job directory) and control job flow
 (cancel, clean, etc.)
read - allows to read content of job data (contents of job directory)
list - allows to list files available for the job (contents of job directory)
admin - allows to do everything – full equivalence to job ownership

queue

Unique: yes
 Operators: = !=
 User input: (queue=<string>)
 GM input: only = is allowed
 Example: (queue="pclong")

The name of the remote batch queue.

Use only when you are sure that the queue by this name does exist.

string known queue name

While users are not expected to specify **queue** in job descriptions, this attribute **must** be present in the GM-side xRSL. In fact, this is primarily an internal attribute, added to the job description by client tools after resource discovery and matchmaking. Still, users can specify this attribute to explicitly force job submission to a queue: when specified explicitly by the user, this value will not be overwritten by the ARC Client, and an attempt will be made to submit the job to the specified queue.

If for some reason (e.g. due to a client tool error) **queue** is absent from the GM-side xRSL, GM on the selected cluster will attempt to submit the job to the default queue if such is specified in the GM configuration.

startTime

Unique: yes
 Operators: =
 User input: (startTime=<time>)
 GM input: (startTime=<tttt>)
 Example: (startTime="2002-05-25 21:30")

Time to start job processing by the Grid Manager, such as e.g. start downloading input files.

time time string, YYYY-MM-DD hh:mm:ss
tttt time string, YYYYMMDDhhmmss[Z] (converted by the ARC Client from **time**)

Actual job processing on a worker node starts depending on local scheduling mechanisms, but not sooner than **startTime**.

lifeTime

Unique: yes
 Operators: =
 User input: (lifeTime=<time>)
 GM input: (lifeTime=<tttt>)
 Example: (lifeTime="2 weeks")

Maximal time to keep job files (the session directory) on the gatekeeper upon job completion.

time time (in minutes if no unit is specified)
tttt time (seconds, converted by the ARC Client from **time**)

Typical life time is 1 day (24 hours). Specified life time can not exceed local settings.

notify

Unique: yes
 Operators: =
 User input: (notify=<string> [string] ...)
 GM input: -"-
 Example: (notify="be your.name@your.domain.com")

Request e-mail notifications on job status change.

string string of the format: [b] [q] [f] [e] [c] [d] user1@domain1 [user2@domain2] ...
 here flags indicating the job status are:
 b – begin (PREPARING)
 q – queued (INLRMS)
 f – finalizing (FINISHING)
 e – end (FINISHED)
 c – cancellation (CANCELLED)
 d – deleted (DELETED)

When no notification flags are specified, default value of “eb” will be used, i.e., notifications will be sent at the job’s beginning and at its end.

No more than 3 e-mail addresses per status change accepted.

rerun

Unique: yes
 Operators: =
 User input: (rerun=<integer>)
 GM input: -"-
 Example: (rerun="2")

Number of reruns (if a system failure occurs).

integer an integer number

If not specified, the default is 0. Default maximal allowed value is 5. The job may be rerun after failure in any state for which reruning has sense. To initiate rerun user has to use the **arcresume** command.

architecture

Unique: no
 Operators: = !=
 User input: (architecture=<string>)
 GM input: none
 Example: (architecture="i686")

Request a specific architecture.

string architecture (e.g., as produced by `uname -a`)

nodeAccess

Unique: yes
 Operators: =
 User input: (`nodeAccess="inbound"|"outbound"`)
 GM input: none
 Example: (`nodeAccess="inbound"`)

Request cluster nodes with inbound or outbound IP connectivity. If both are needed, a conjunct request should be specified.

dryRun

Unique: yes
 Operators: =
 User input: (`dryRun="yes"|"no"`)
 GM input: `--`
 Example: (`dryRun="yes"`)

If "yes", do dry-run: job description is sent to the optimal destination, input files are transferred, but no actual job submission to LRMS is made. Typically used for xRSL and communication validation.

rsl_substitution

Unique: no
 Operators: =
 User input: (`rsl_substitution=(<string1> <string2>)`)
 GM input: `--`
 Example: (`rsl_substitution=("ATLAS" "/opt/atlas")`)

Substitutes *<string2>* with *<string1>* for **internal** RSL use.

string1 new internal RSL variable
string2 any string, e.g., existing combination of variables or a path

Use this attribute to define variables that simplify xRSL editing, e.g. when same path is used in several values, typically in `inputFiles`. Only one pair per substitution is allowed. To request several substitution, concatenate such requests. Bear in mind that substitution must be defined **prior** to actual use of a new variable **string1**.

After the substitution is defined, it should be used in a way similar to shell variables in scripts: enclosed in round brackets, preceded with a dollar sign, **without quotes**:

(`inputfiles=("myfile" $(ATLAS)/data/somefile)`)

Unlike the `environment` attribute, `rsl_substitution` definition is only used by the client and is valid inside xRSL script. It can not be used to define environment or shell variable at the execution site.

environment

Unique: no
 Operators: =
 User input: (environment=(**<VAR>** **<string>**) [(**<VAR>** **<string>**)] ...)
 GM input: --
 Example: (environment=("ATLSRC" "/opt/atlas/src")
 ("ALISRC" "/opt/alice/src"))

Defines execution shell environment variables.

VAR new variable name
string any string, e.g., existing combination of variables or a path

Use this to define variables at an execution site. Unlike the `rsl_substitution` attribute, it can not be used to define variables on the client side.

count

Unique: yes
 Operators: =
 User input: (count=**<integer>**)
 GM input: --
 Example: (count="4")

Specifies amount of sub-jobs to be submitted for parallel tasks.

countpernode

(ARC \geq 3.0)

Unique: yes
 Operators: =
 User input: (countpernode=**<integer>**)
 GM input: --
 Example: (countpernode="2")

Specifies amount of sub-jobs per node to be submitted for parallel tasks. Note: The `count` attribute must be specified when this attribute is specified.

exclusiveexecution

(ARC \geq 3.0)

Unique: yes
 Operators: =
 User input: (exclusiveexecution="yes"|"no")
 GM input: --
 Example: (exclusiveexecution="yes")

Specifies whether the node should be allocated for exclusive use by the job.

jobreport

Unique: yes
 Operators: =
 User input: (jobreport=<URL>)
 GM input: -"-
 Example: (jobreport="https://grid.uio.no:8001/logger")

Specifies an URL for an accounting service to send reports about job to. The default is set up in the cluster configuration.

URL URL

It is up to users to make sure the requested accounting service accepts reports from the set of clusters they intend to use.

credentialserver

Unique: yes
 Operators: =
 User input: (credentialserver=<URL>)
 GM input: -"-
 Example: (credentialserver="myproxy://myproxy.nordugrid.org;username=user")

Specifies an URL which Grid Manager may contact to renew/extend delegated proxy of job. Only MyProxy servers are supported.

URL URL of MyProxy server

It is up to a user to make sure the specified MyProxy server will accept requests from Grid Manager to renew expired credentials. URL may contain options `username` and `credname` to specify user name and credentials name which Grid Manager should pass to MyProxy server. If `username` is not specified DN of user credentials is used instead.

priority

Unique: yes
 Operators: =
 User input: (priority=<integer>)
 GM input: -"-
 Example: (priority="80")

Specifies priority given to this job during staging of input and output files when the new data staging framework is used by A-REX. Values are limited to between 1 (lowest priority) and 100 (highest priority). Default if this attribute is not specified is 50.

3.2 GM-side attributes

The following attributes are a part of the internal ARC job representation, and must be provided by ARC client tools and passed to the GM. Users may even specify them manually (**not advised!**), while developers of new ARC client tools and utilities must make sure these attributes are added to the user job description before it is submitted to a GM.

sstdin

GM input: (sstdin=<filename>)

Example: (sstdin="myinput.dat")

Internal attribute for the standard input. Can also be spelled `stdininput`. Only needed for GRAM compatibility, not used by ARC as such.

`filename` standard input file name

action

GM input: (action="request"|"cancel"|"clean"|"renew"|"restart")

Example: (action="request")

Action to be taken by the gatekeeper: submit the job, cancel job execution, clear the results of the job (also cancels the job), renew the proxy of the job, or restart the job from a previous failed state.

savestate

GM input: (savestate="yes"|"no")

Example: (savestate="yes")

If "yes", input RSL is stored in a temporary file at the gatekeeper. Must be always set as "yes" in the current implementation. Only needed for GRAM compatibility, not used by ARC as such.

lrms type

GM input: (lrms type=<string>)

Example: (lrms type="pbs")

LRMS type, indicating which submission script is to be invoked.

`string` LRMS type

hostName

GM input: (hostname=<string>)

Example: (hostName="grid.quark.lu.se")

Name (e.g. as returned by the Linux `hostname` command) of the client machine from which the submission was made.

`string` client host name, as passed by the ARC client

jobid

GM input: (jobid=<string>)

Example: (jobid="grid.quark.lu.se:2119/jobmanager-ng/157111017133827")

Unique job identification string, needed for cancellation and clean-up.

`string` global job ID

It can also be provided during submission of the job and should be unique to a computing element (cluster).

clientxrsl

GM input: (clientxrsl=<string>)

Example: (clientxrsl="&(executable=/bin/echo)(arguments=boo)")

Job description XRSL string as submitted by the user, before being pre-processed by the client.

string original XRSL description submitted by the user

This attribute is added by the User Interface during pre-processing, and is used for job re-submission in order to repeat brokering and matchmaking.

clientsoftware

GM input: (clientsoftware=<string>)

Example: (clientsoftware="nordugrid-arc-0.5.39")

Version of ARC client used to submit the job.

string

This attribute is added by the User Interface during pre-processing.

3.3 Unsupported Globus RSL attributes

The following Globus[®] attributes are not supported by the ARC middleware. Whenever they are specified, either an error or a warning should be issued by the client tool, and the corresponding attribute should be ignored*.

3.3.1 Unsupported RSL 1.0 attributes

- (resourceManagerContact=<string>)
- (directory=<string>)
- (maxCpuTime=<time>)
- (maxWallTime=<time>)
- (maxTime=<time>)
- (maxMemory=<memory>)
- (minMemory=<memory>)
- (gramMyJob=independent|collective)
- (project=<string>)
- (hostCount=<number>)
- (label=<string>)
- (subjobCommsType=blocking-join|independent)
- (subjobStartType=strict-barrier|loose-barrier|no-barrier)

*Standard ARC client will throw an error, unless option "-U" is specified

3.3.2 Unsupported GRAM RSL attributes

- (directory=<string>)
- (fileCleanUp=<array>)
- (fileStageIn=<array>)
- (fileStageInShared=<array>)
- (fileStageOut=<array>)
- (gassCache=<path>)
- (gramMyJob=independent|collective)
- (hostCount=<number>)
- (jobType=<string>)
- (libraryPath=<path>)
- (maxCpuTime=<time>)
- (maxWallTime=<time>)
- (maxTime=<time>)
- (maxMemory=<memory>)
- (minMemory=<memory>)
- (project=<string>)
- (remoteIoUrl=<string>)
- (scratchDir=<string>)

Chapter 4

XRSL and JSDL

ARC has adopted JSDL [3] as second format for describing job requests*. ARC also adds own extensions to JSDL. Below supported JSDL elements are listed together with corresponding XRSL attributes. Here *jsdl* stands for jsdl namespace, *jsdlPOSIX* – for POSIX extensions, and *jsdlARC* – for ARC extensions.

XRSL attribute	JSDL element	Comments
executable	jsdlPOSIX:Executable	
cpuTime	jsdlPOSIX:CPULimit jsdl:Resources jsdl:TotalCpuTime jsdl:IndividualCpuTime	
arguments	jsdlPOSIX:Argument	
inputFiles	jsdl:DataStaging jsdl:Source jsdl:FileName jsdl:URI jsdl-arc:URIOption	jsdl:DataStaging without URI in Source are treated like user-uploadable files
outputFiles	jsdl:DataStaging jsdl:Target jsdl:FileName jsdl:URI jsdl-arc:URIOption jsdl-arc:Location jsdl:URI	jsdl:DataStaging without Target and Source or without URI in Target are treated like user-downloadable files
wallTime	jsdlPOSIX:WallTimeLimit	
memory	jsdlPOSIX:MemoryLimit jsdl:Resources jsdl:TotalPhysicalMemory jsdl:IndividualPhysicalMemory	
disk	jsdl:Resources jsdl:TotalDiskSpace jsdl:IndividualDiskSpace	
stdin	jsdlPOSIX:Input	
stdout	jsdlPosix:Output	
stderr	jsdlPOSIX>Error	
jobName	jsdl:JobIdentification	
architecture	jsdl:Resources jsdl:CPUArchitectureName jsdl:CPUArchitecture	

* Available in releases $\geq 0.5.37$, ARC 0.6, ARC 0.8

count	jsdl:Resources jsdl:TotalCpuCount jsdl:IndividualCpuCount	
executables	jsdl:DataStaging jsdl-arc:IsExecutable	
gridTime	jsdl:Resources jsdl-arc:GridTimeLimit	
runTimeEnvironment	jsdl:Resources jsdl-arc:RunTimeEnvironment	Only "Exact" condition with one Version is supported so far
middleware	jsdl:Resources jsdl-arc:Middleware	Only "Exact" condition with one Version is supported so far
gmlog	jsdl-arc:LocalLogging jsdl-arc:Directory	
acl	jsdl-arc:AccessControl Type=GACL Content	
cluster	jsdl:Resources jsdl-arc:CandidateTarget jsdl-arc:HostName	
queue	jsdl:Resource jsdl-arc:CandidateTarget jsdl-arc:QueueName	
startTime	jsdl-arc:ProcessingStartTime	
lifeTime	jsdl:Resources jsdl-arc:SessionFileTime	
notify	jsdl-arc:Notify jsdl-arc:Type=Email	
rerun	jsdl-arc:Reruns	
jobreport	jsdl-arc:RemoteLogging jsdl-arc:URL	
credentialserver	jsdl-arc:CredentialServer jsdl-arc:URL	

Conditional requests are supported through recursive jsdl:JobDescription - jsdl:JobDescriptin inside jsdl:JobDescription.

Appendix A

Examples

A.1 User-side xRSL script

```
&
(* test run: if "yes", only submits RSL without actual job start *)
  (dryRun="no")
(* some local variables defined for further convenience *)
  (rsl_substitution=("TOPDIR" "/home/johndoe"))
  (rsl_substitution=("NGTEST" "${TOPDIR}/ngtest"))
  (rsl_substitution=("BIGFILE" "/scratch/johndoe/100mb.tmp"))
(* some environment variables, to be used by the job *)
  (environment=("ATLAS" "/opt/atlas") ("CERN" "/cern"))
(* the main executable file to be staged in and submitted to the PBS *)
  (executable="checkall.sh")
(* the arguments for the executable above *)
  (arguments="pal")
(* files to be staged in before the execution *)
  (inputFiles = ("be_kaons" ""))
  ("file1" gsiftp://grid.uio.no${TOPDIR}/remfile.txt)
  ("bigfile.dat" ${BIGFILE} )
(* files to be given executable permissions after staging in *)
  (executables="be_kaons")
(* files to be staged out after the execution *)
  (outputFiles=
    ("file1" "gsiftp://grid.tsl.uu.se/tmp/file1.tmp")
    ("100mb.tmp" "rls://rls.nordugrid.org:39281/test/bigfile")
    ("be_kaons.hbook" gsiftp://ce1.grid.org${NGTEST}/kaons.hbook) )
(* user-specified job name *)
  (jobName="NGtest")
(* standard input file *)
  (stdin="myinput.dat")
(* standard output file *)
  (stdout="myoutput.dat")
(* standard error file *)
  (stderr="myerror.dat")
(* GM logs directory name *)
  (gmlog="gmlog")
(* flag whether to merge stdout and stderr *)
  (join="no")
(* request e-mail notification on status change *)
  (notify="bqfe john.doe@gmail.com jane.doe@mail.org")
(* maximal CPU time required for the job, minutes for PBS*)
  (CpuTime="60")
(* maximal time for the session directory to exist on the remote node, days *)
  (lifeTime="7")
(* memory required for the job, per count, Mbytes *)
```

```

    (Memory="200")
(* wall time to start job processing *)
    (startTime="2002-04-28 17:15:00")
(* disk space required for the job, Mbytes *)
    (Disk="500")
(* required architecture of the execution node *)
    (architecture="i686")
(* required run-time environment *)
    (runTimeEnvironment="APPS/HEP/Atlas-1.1")
(* number of re-runs, in case of a system failure *)
    (rerun="2")

```

A.2 GM-side xRSL script

Note that a client tool must do matchmaking and modify correspondingly the job document before submitting it to the matching resource. Specifically, a client tool has to:

- expand all the `rsl_substitution` values
- add double quotes to **all** strings
- insert `queue` attribute in case such is missing
- make sure every logical or comparison operator is expanded and replaced with a deterministic “=” statement
- streamline blank spaces

Comment lines are removed from the GM-side xRSL; below they are shown to explain details.

```

&
(* saves RSL in a temporary file if "yes" *)
    ("savestate" = "yes" )
(* job submission to be performed if action is "request" *)
    ("action" = "request" )
(* submission host name *)
    ("hostname" = "ce1.grid.org" )
(* client software version *)
    ("clientsoftware" = "nordugrid-arc-0.6.0.3" )
(* walltime value added by the client, in seconds *)
    ("walltime" = "3600" )
(* test run: if "yes", only submits RSL without actual job start *)
    ("dryRun" = "no" )
(* some local variables defined for further convenience *)
    ("rsl_substitution" = ("TOPDIR" "/home/johndoe" ) )
    ("rsl_substitution" = ("NGTEST" "/home/johndoe/ngtest" ) )
    ("rsl_substitution" = ("BIGFILE" "/scratch/johndoe/100mb.tmp" ) )
(* some environment variables, to be used by the job *)
    ("environment" = ("ATLAS" "/opt/atlas" ) ("CERN" "/cern" ) )
(* executable *)
    ("executable" = "checkall.sh" )
(* arguments *)
    ("arguments" = "pal" )
(* files to be staged in before the execution *)
    ("inputfiles" = ("checkall.sh" "279320" )
        ("myinput.dat" "39806" )
        ("be_kaons" "8807" )
        ("file1" "gsiftp://grid.uio.no/home/johndoe/remfile.txt" )
        ("bigfile.dat" "104857600" )
    )
(* files to be given executable permissions after staging in *)

```

```

    ("executables" = "checkall.sh" "be_kaons" )
(* files to be staged out after the execution *)
    ("outputfiles" = ("file1" "gsiftp://grid.tsl.uu.se/tmp/file1.tmp" )
      ("100mb.tmp" "rls://rls.nordugrid.org:39281/test/bigfile" )
      ("be_kaons.hbook" "gsiftp://ce1.grid.org/home/johndoe/ngtest/kaons.hbook" )
      ("myoutput.dat" "" )
      ("myerror.dat" "" )
    )
(* user-specified job name *)
    ("jobName" = "NGtest" )
(* standard input file *)
    ("stdin" = "myinput.dat" )
(* standard output file *)
    ("stdout" = "myoutput.dat" )
(* standard error file *)
    ("stderr" = "myerror.dat" )
(* flag whether to merge stdout and stderr *)
    ("join" = "no" )
(* request e-mail notification on status change *)
    ("notify" = "bqfe john.doe@gmail.com jane.doe@mail.org" )
(* specific queue to submit the job *)
    ("queue" = "atlas" )
(* CPU time required for the job, converted into seconds *)
    ("cputime" = "3600" )
(* maximal time for the session directory to exist on the remote node, seconds *)
    ("lifetime" = "604800" )
(* memory required for the job, per count, Mbytes *)
    ("memory" = "200" )
(* wall time to start job processing *)
    ("startTime" = "20020128171500" )
(* disk space required for the job, Mbytes *)
    ("disk" = "500" )
(* required architecture of the execution node *)
    ("architecture" = "i686" )
(* required run-time environment *)
    ("runtimeenvironment" = "APPS/HEP/Atlas-1.1" )
(* number of re-runs, in case of a system failure *)
    ("rerun" = "2" )
(* original client xRSL with expanded string substitutions; shortened here *)
    ("clientxrsl" = "&(" "dryrun" = "no" ) (... ) ("rerun" = "2" ) " )

```

A.3 JSDL script

```

<?xml version="1.0" encoding="UTF-8"?>
<jSDL:JobDefinition
  xmlns="http://schemas.ggf.org/jSDL/2005/11/jSDL"
  xmlns:posix="http://schemas.ggf.org/jSDL/2005/11/jSDL-posix"
  xmlns:arc="http://www.nordugrid.org/ws/schemas/jSDL-arc">
  <JobDescription>
    <!-- Generic job description (jobname in XRSL) -->
    <JobIdentification>
      <JobName>JSDL Hello World job</JobName>
      <Description>
        This is a simple Hello World job test
      </Description>
    </JobIdentification>
    <!-- Standard application (same as executable, arguments in XRSL) -->
    <Application>
      <ApplicationName>Echo</ApplicationName>
      <posix:POSIXApplication>

```

```
        <posix:Executable>/bin/echo</posix:Executable>
        <posix:Argument>Hello world</posix:Argument>
    </posix:POSIXApplication>
</Application>
<!-- Get the GM diagnostics (same as gmlog in XRSL) -->
<arc:LocalLogging>
    <arc:Directory>gmlog</arc:Directory>
</arc:LocalLogging>
</JobDescription>
</JobDefinition>
```

Appendix B

JSDL-ARC schema

```
<?xml version="1.0" encoding="UTF-8"?>
<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns="http://www.nordugrid.org/ws/schemas/jsdl-arc"
  xmlns:jsdl-arc="http://www.nordugrid.org/ws/schemas/jsdl-arc"
  targetNamespace="http://www.nordugrid.org/ws/schemas/jsdl-arc">

  <xsd:simpleType name="GMState_Type">
    <xsd:restriction base="xsd:string">
      <xsd:enumeration value="ACCEPTED"/>
      <xsd:enumeration value="PREPARING"/>
      <xsd:enumeration value="SUBMIT"/>
      <xsd:enumeration value="INLRMS"/>
      <xsd:enumeration value="FINISHING"/>
      <xsd:enumeration value="FINISHED"/>
      <xsd:enumeration value="DELETED"/>
      <xsd:enumeration value="CANCELING"/>
    </xsd:restriction>
  </xsd:simpleType>

  <xsd:complexType name="Version_Type">
    <xsd:sequence>
      <xsd:element name="UpperExclusive" type="xsd:string" minOccurs="0"/>
      <xsd:element name="LowerExclusive" type="xsd:string" minOccurs="0"/>
      <xsd:element name="Exact" type="xsd:string" minOccurs="0" maxOccurs="unbounded"/>
      <xsd:element name="Exclusive" type="xsd:boolean" minOccurs="0"/>
    </xsd:sequence>
  </xsd:complexType>

  <xsd:simpleType name="SessionType_Type">
    <xsd:documentation> For jsdl:Resources_Type </xsd:documentation>
    <!-- xsd:element ref="SessionType" minOccurs="0"/ -->
    <xsd:restriction base="xsd:string">
      <xsd:enumeration value="INTERNAL"/>
      <xsd:enumeration value="LIMITED"/>
      <xsd:enumeration value="READONLY"/>
      <xsd:enumeration value="FULL"/>
    </xsd:restriction>
  </xsd:simpleType>

  <xsd:simpleType name="IsExecutable_Type">
    <xsd:documentation> For jsdl:DataStaging_Type (default: false) </xsd:documentation>
    <!-- xsd:element ref="IsExecutable" minOccurs="0"/ -->
    <xsd:restriction base="xsd:boolean"/>
  </xsd:simpleType>
```

```

<xsd:simpleType name="FileParameters_Type">
  <xsd:documentation> For jsdl:DataStaging_Type </xsd:documentation>
  <!-- xsd:element ref="IsExecutable" minOccurs="0"/ -->
  <xsd:restriction base="xsd:string"/>
</xsd:simpleType>

<xsd:simpleType name="JoinOutputs_Type">
  <xsd:documentation> For jsdl:JobDescription_Type (default: false) </xsd:documentation>
  <!-- xsd:element ref="JoinOutputs" minOccurs="0"/ -->
  <xsd:restriction base="xsd:boolean"/>
</xsd:simpleType>

<xsd:simpleType name="Reruns_Type">
  <xsd:documentation> For jsdl:JobDescription_Type (default: false) </xsd:documentation>
  <!-- xsd:element ref="Reruns" minOccurs="0"/ -->
  <xsd:restriction base="xsd:integer"/>
</xsd:simpleType>

<xsd:complexType name="RunTimeEnvironment_Type">
  <xsd:documentation> For jsdl:Resources_Type </xsd:documentation>
  <!-- xsd:element ref="RunTimeEnvironment" minOccurs="0" maxOccurs="unbounded"/ -->
  <xsd:sequence>
    <xsd:element name="Name" type="xsd:string"/>
    <xsd:element name="Version" type="Version_Type" minOccurs="0"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="Middleware_Type">
  <xsd:documentation> For jsdl:Resources_Type </xsd:documentation>
  <!-- xsd:element ref="Middleware" minOccurs="0" maxOccurs="unbounded"/ -->
  <xsd:sequence>
    <xsd:element name="Name" type="xsd:string"/>
    <xsd:element name="Version" type="Version_Type" minOccurs="0"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="RemoteLogging_Type">
  <xsd:documentation> For jsdl:JobDescription_Type </xsd:documentation>
  <!-- xsd:element ref="RemoteLogging" minOccurs="0" maxOccurs="3"/ -->
  <xsd:sequence>
    <xsd:element name="URL" minOccurs="1" maxOccurs="1" type="xsd:anyURI"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="CredentialServer_Type">
  <xsd:documentation> For jsdl:JobDescription_Type </xsd:documentation>
  <!-- xsd:element ref="CredentialServer" minOccurs="0"/ -->
  <xsd:sequence>
    <xsd:element name="URL" minOccurs="1" maxOccurs="1" type="xsd:anyURI"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="LocalLogging_Type">
  <xsd:documentation> For jsdl:JobDescription_Type </xsd:documentation>
  <!-- xsd:element ref="LocalLogging" minOccurs="0" maxOccurs="1"/ -->
  <xsd:sequence>
    <xsd:element name="Directory" minOccurs="1" maxOccurs="1" type="xsd:string"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:simpleType name="AccessControlType_Type">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="GACL"/>
  </xsd:restriction>
</xsd:simpleType>

```

```

</xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="AccessControl_Type">
  <xsd:documentation> For jsdl:JobDescription_Type </xsd:documentation>
  <!-- xsd:element ref="AccessControl" minOccurs="0"/ -->
  <xsd:sequence>
    <xsd:element name="OwnerAlwaysAllowed" type="xsd:boolean" minOccurs="0"/>
    <xsd:element name="Type" type="AccessControlType_Type" minOccurs="0"/>
    <xsd:element name="Content" minOccurs="0" type="xsd:string"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:simpleType name="NotificationType_Type">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="Email"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="Notify_Type">
  <xsd:documentation> For jsdl:JobDescription_Type </xsd:documentation>
  <!-- xsd:element ref="Notify" minOccurs="0" maxOccurs="3"/ -->
  <xsd:sequence>
    <xsd:element name="Type" type="NotificationType_Type" minOccurs="0"/>
    <xsd:element name="Endpoint" minOccurs="0" type="xsd:string"/>
    <xsd:element name="State" minOccurs="1" maxOccurs="unbounded" type="GMState_Type"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:simpleType name="SessionLifeTime_Type">
  <xsd:documentation> For jsdl:Resources_Type </xsd:documentation>
  <!-- xsd:element ref="SessionLifeTime" minOccurs="0" maxOccurs="1"/ -->
  <xsd:restriction base="xsd:long"/>
</xsd:simpleType>

<xsd:simpleType name="GridTimeLimit_Type">
  <xsd:documentation> For jsdl:Resources_Type </xsd:documentation>
  <!-- xsd:element ref="GridTimeLimit" minOccurs="0" maxOccurs="1"/ -->
  <xsd:restriction base="xsd:positiveInteger"/>
</xsd:simpleType>

<xsd:complexType name="CandidateTarget_Type">
  <xsd:documentation> For jsdl:Resources_Type </xsd:documentation>
  <!-- xsd:element ref="jsdl-arc:CandidateTarget" minOccurs="0" maxOccurs="1"/ -->
  <xsd:sequence>
    <xsd:element name="HostName" minOccurs="0" type="xsd:string"/>
    <xsd:element name="QueueName" minOccurs="0" type="xsd:string"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:simpleType name="Time_Type">
  <xsd:documentation> For jsdl:JobDescription_Type </xsd:documentation>
  <!-- xsd:element ref="ProcessingStartTime" minOccurs="0" maxOccurs="1"/ -->
  <xsd:restriction base="xsd:dateTime"/>
</xsd:simpleType>

<!--=====-->
<xsd:element name="IsExecutable" type="IsExecutable_Type"/>
<xsd:element name="FileParameters" type="FileParameters_Type"/>
<xsd:element name="RunTimeEnvironment" type="RunTimeEnvironment_Type"/>
<xsd:element name="Middleware" type="Middleware_Type"/>
<xsd:element name="RemoteLogging" type="RemoteLogging_Type"/>
<xsd:element name="LocalLogging" type="LocalLogging_Type"/>
<xsd:element name="AccessControl" type="AccessControl_Type"/>
<xsd:element name="Notify" type="Notify_Type"/>

```

```
<xsd:element name="SessionLifeTime" type="SessionLifeTime_Type"/>
<xsd:element name="SessionType" type="SessionType_Type"/>
<xsd:element name="JoinOutputs" type="JoinOutputs_Type"/>
<xsd:element name="Reruns" type="Reruns_Type"/>
<xsd:element name="CredentialServer" type="CredentialServer_Type"/>
<xsd:element name="GridTimeLimit" type="GridTimeLimit_Type"/>
<xsd:element name="CandidateTarget" type="CandidateTarget_Type"/>
<xsd:element name="ProcessingStartTime" type="Time_Type"/>

</xsd:schema>
```

Acknowledgements

This work was supported in parts by: the Nordunet 2 programme, the Nordic DataGrid Facility, the EU KnowARC project (Contract nr. 032691) and the EU EMI project (Grant agreement nr. 261611).

Bibliography

- [1] The Globus Resource Specification Language RSL v1.0. URL http://www.globus.org/toolkit/docs/2.4/gram/rsl_spec1.html.
- [2] The NorduGrid Collaboration. URL <http://www.nordugrid.org>. Web site.
- [3] A. Anjomshoaa et al. Job Submission Description Language (JSDL) Specification, Version 1.0 (first errata update). URL <http://www.gridforum.org/documents/GFD.136.pdf>. GFD-R.136, July 2008.
- [4] M. Ellert. *ARC User Interface*. The NorduGrid Collaboration. URL <http://www.nordugrid.org/documents/ui.pdf>. NORDUGRID-MANUAL-1.
- [5] M. Ellert, M. Grønager, A. Konstantinov, et al. Advanced Resource Connector middleware for lightweight computational Grids. *Future Gener. Comput. Syst.*, 23(1):219–240, 2007. ISSN 0167-739X.
- [6] I. Foster and C. Kesselman. Globus: A Metacomputing Infrastructure Toolkit. *International Journal of Supercomputer Applications*, 11(2):115–128, 1997. Available at: <http://www.globus.org>.
- [7] I. Foster and C. Kesselman. *The Grid: Blueprint for a New Computing Infrastructure*. Morgan Kaufmann, 1999.
- [8] A. Konstantinov. *The NorduGrid Grid Manager And GridFTP Server: Description And Administrator's Manual*. The NorduGrid Collaboration. URL <http://www.nordugrid.org/documents/GM.pdf>. NORDUGRID-TECH-2.
- [9] A. McNab. The GridSite Web/Grid security system: Research Articles. *Softw. Pract. Exper.*, 35(9): 827–834, 2005. ISSN 0038-0644.
- [10] A. Sim, A. Shoshani, et al. The Storage Resource Manager Interface (SRM) Specification v2.2. URL <http://www.ggf.org/documents/GFD.129.pdf>. GFD-R-P.129, May 2008.
- [11] M. Smith and T. A. Howes. *LDAP : Programming Directory-Enabled Applications with Lightweight Directory Access Protocol*. Macmillan, 1997.

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in roman refer to the pages where the entry is used.

A		G		U	
attributes	13	Globus	5	URL	8
user-side	13	Grid Manager	5	options	9
C		N		X	
Client	5	NorduGrid	5	XRSL	
Computing Element	16	R		attribute	
		RSL	5	acl	22
				action	28

architecture	24	ftpThreads	22	outputFiles	15
arguments	14	gmlog	21	priority	27
benchmarks	18	gridTime	18	queue	22
cache	15	hostName	28	rerun	24
clientsoftware	29	inputFiles	14	rsl_substitution	25
clientxrsl	29	jobid	28	runTimeEnvironment . .	19
count	26	jobName	21	savestate	28
countpernode	26	jobreport	26	sstdin	27
cpuTime	16	join	21	startTime	23
credentialserver	27	lifeTime	23	stderr	21
disk	19	lrmstype	28	stdin	20
dryRun	25	memory	18	stdout	20
environment	25	middleware	19	wallTime	17
exclusiveexecution	26	nodeAccess	25	xRSL	5
executable	13	notify	24		
executables	15	opsys	20		