



*Nordic Testbed for Wide Area Com-
puting And Data Handling*

5/10/2004

PROTOCOLS, UNIFORM RESOURCE LOCATORS (URL) AND EXTENSIONS SUPPORTED IN ARC.

*Description.**

A.Konstantinov

*Comments to: aleks@fys.uio.no

Contents

1	Protocols	3
2	Extensions	3
2.1	Options	3
2.2	Quasi-URLs aka Meta-URLs	4

1 Protocols

URLs

All components of Nordugrid's ARC [1] should support following data transfer protocols and corresponding URLs:

- *ftp* - ordinary FTP without user and password fields.
- *gsiftp* - GridFTP [2], enhanced FTP protocol with security, encryption, etc. developed by The Globus Alliance [3].
- *http* - ordinary HTTP with PUT and GET methods.
- *httpg* - HTTP wrapped with Globus' GSI.
- *https* - HTTP wrapped with SSL (SSL v3 only).
- *file* - local file.

2 Extensions

2.1 Options

In addition to standard URL fields GM supports *options*. Options are of kind *name* or *name=value* and are inserted into URL after host and port and are separated by ';'.

protocol://host[:port][;option[;option[...]]]/path

Following options are supported:

threads=# specify number of parallel transfers to use (currently works for GridFTP, HTTP, HTTPS and HTTPG, default is one),

blocksize=# specify size of chunks/blocks/buffers used in transactions (currently works for GridFTP, HTTP, HTTPS and HTTPG, default is protocol dependent),

cache=yes/no whether file is allowed to be cached on local side (for transfers to local destinations, default is *yes*),

secure=yes/no whether data should be transferred using encryption (currently works for GridFTP only, default is *no* unless specified differently in configuration),

readonly=yes/no if file after transfer to local location can be stored in a way which prevents user, job, etc. from modifying it (use *readonly=no* if You plan to modify file),

checksum=cksum/md5 specifies type of checksum to be computed and provided to the indexing server,

exec=yes/no means file should be treated as executable (currently only used internally).

Example: `gsiftp://grid.domain.org:2811;threads=10;secure=yes/dir/input_12378.dat`

2.2 Quasi-URLs aka Meta-URLs

There are also few quasi-URLs supported.

- *se* - to contact “Smart” Storage Element being developed at NorduGrid project is also supported. It’s syntax is `se://[host[:port]][;options]/path[?file_id]`. For more information see document “The NorduGrid “Smart” Storage Element”.

Also following quasi-URLs of meta-data (indexing) servers are supported:

- *rc* - Globus Replica Catalog: `rc://[location[/location[...]]][@host[:port]/distinguished_name]/fn`
- *rls* - Globus Replica Location Service: `rls://[url[/url[...]]]@Jhost[:port]/fn`

Here

fn Logical File Name, that should be used for registering/querying in the Indexing Service,

distinguished_name DN of collection in LDAP server used for registering/querying,

location name of location (usually this is host[:port] of SE), each *location* can have *options* appended to it in a way *location;options*. If only ;*options* part is preset, those options are treated as specified for every location.

url full or partial URL corresponding to physical location of file.

References

[1] NorduGrid project. <http://www.nordugrid.org>

[2] GridFTP: Universal Data Transfer for the Grid. <http://www.globus.org/datagrid/deliverables/C2WPdraft3.pdf>

[3] The Globus Alliance. <http://www.nordugrid.org>