

Hosting Environment (Daemon) Chain Components

Generated by Doxygen 1.6.1

Thu Nov 8 20:46:51 2012

Contents

1	Namespace Index	1
1.1	Namespace List	1
2	Data Structure Index	3
2.1	Class Hierarchy	3
3	Data Structure Index	7
3.1	Data Structures	7
4	Namespace Documentation	11
4.1	ArcSec Namespace Reference	11
4.1.1	Detailed Description	13
4.1.2	Typedef Documentation	13
4.1.2.1	AndList	13
4.1.2.2	Match	14
5	Data Structure Documentation	15
5.1	ArcSec::AllowPDP Class Reference	15
5.1.1	Detailed Description	15
5.2	ArcSec::ArcAlgFactory Class Reference	16
5.2.1	Detailed Description	16
5.2.2	Member Function Documentation	16
5.2.2.1	createAlg	16
5.3	ArcSec::ArcAttributeFactory Class Reference	17
5.3.1	Detailed Description	17
5.3.2	Member Function Documentation	17
5.3.2.1	createValue	17
5.4	ArcSec::ArcAttributeProxy< TheAttribute > Class Template Reference	18
5.4.1	Detailed Description	18
5.5	ArcSec::ArcAuthZ Class Reference	19

5.5.1	Detailed Description	19
5.5.2	Member Function Documentation	19
5.5.2.1	Handle	19
5.5.2.2	MakePDPs	19
5.6	ArcSec::ArcEvaluationCtx Class Reference	20
5.6.1	Detailed Description	20
5.6.2	Constructor & Destructor Documentation	20
5.6.2.1	ArcEvaluationCtx	20
5.6.3	Member Function Documentation	20
5.6.3.1	split	20
5.7	ArcSec::ArcEvaluator Class Reference	21
5.7.1	Detailed Description	21
5.7.2	Member Function Documentation	21
5.7.2.1	evaluate	21
5.8	ArcSec::ArcFnFactory Class Reference	22
5.8.1	Detailed Description	22
5.8.2	Member Function Documentation	22
5.8.2.1	createFn	22
5.9	ArcSec::ArcPDP Class Reference	23
5.9.1	Detailed Description	23
5.10	ArcSec::ArcPolicy Class Reference	24
5.10.1	Detailed Description	24
5.10.2	Constructor & Destructor Documentation	24
5.10.2.1	ArcPolicy	24
5.10.2.2	ArcPolicy	24
5.10.2.3	ArcPolicy	24
5.10.3	Member Function Documentation	24
5.10.3.1	make_policy	24
5.11	ArcSec::ArcRequest Class Reference	25
5.12	ArcSec::ArcRequestItem Class Reference	26
5.12.1	Detailed Description	26
5.13	ArcSec::ArcRequestTuple Class Reference	27
5.13.1	Detailed Description	27
5.14	ArcSec::ArcRule Class Reference	28
5.14.1	Detailed Description	28
5.15	ArcSec::AttributeDesignator Class Reference	29

5.16	ArcSec::AttributeSelector Class Reference	30
5.17	ArcSHCLegacy::AuthUser Class Reference	31
5.18	ArcSHCLegacy::AuthVO Class Reference	32
5.19	ArcSHCLegacy::ConfigParser Class Reference	33
5.20	ArcMCCTLS::ConfigTlsmcc Class Reference	34
5.21	Arc::DataPointARC Class Reference	35
5.21.1	Detailed Description	35
5.22	Arc::DataPointFile Class Reference	36
5.22.1	Detailed Description	36
5.23	Arc::DataPointGFAL Class Reference	37
5.23.1	Detailed Description	37
5.24	Arc::DataPointGridFTP Class Reference	38
5.24.1	Detailed Description	38
5.25	Arc::DataPointHTTP Class Reference	39
5.25.1	Detailed Description	39
5.26	Arc::DataPointLDAP Class Reference	40
5.26.1	Detailed Description	40
5.27	Arc::DataPointLFC Class Reference	41
5.27.1	Detailed Description	41
5.28	Arc::DataPointRLS Class Reference	42
5.28.1	Detailed Description	42
5.29	Arc::DataPointSRM Class Reference	43
5.29.1	Detailed Description	43
5.30	Arc::DataPointXrootd Class Reference	44
5.30.1	Detailed Description	44
5.31	ArcMCCTLSSec::DelegationCollector Class Reference	45
5.32	ArcMCCTLSSec::DelegationMultiSecAttr Class Reference	46
5.33	ArcSec::DelegationPDP Class Reference	47
5.33.1	Detailed Description	47
5.34	ArcMCCTLSSec::DelegationSecAttr Class Reference	48
5.35	ArcSec::DelegationSH Class Reference	49
5.36	ArcSec::DenyPDP Class Reference	50
5.36.1	Detailed Description	50
5.37	ArcSec::GACLEvaluator Class Reference	51
5.37.1	Member Function Documentation	51
5.37.1.1	evaluate	51

5.38	ArcSec::GACLPDP Class Reference	52
5.39	ArcSec::GACLPolicy Class Reference	53
5.40	ArcSec::GACLRequest Class Reference	54
5.41	Arc::LDAPQuery Class Reference	55
5.41.1	Detailed Description	55
5.41.2	Constructor & Destructor Documentation	55
5.41.2.1	LDAPQuery	55
5.41.2.2	~LDAPQuery	55
5.41.3	Member Function Documentation	55
5.41.3.1	Query	55
5.41.3.2	Result	55
5.42	ArcSHCLegacy::LegacyMap Class Reference	56
5.43	ArcSHCLegacy::LegacyPDP Class Reference	57
5.44	ArcSHCLegacy::LegacySecAttr Class Reference	58
5.45	ArcSHCLegacy::LegacySecHandler Class Reference	59
5.46	Arc::Lister Class Reference	60
5.47	ArcMCCGSI::MCC_GSI_Client Class Reference	61
5.48	ArcMCCGSI::MCC_GSI_Service Class Reference	62
5.49	ArcMCCHTTP::MCC_HTTP Class Reference	63
5.49.1	Detailed Description	63
5.50	ArcMCCHTTP::MCC_HTTP_Client Class Reference	64
5.50.1	Detailed Description	64
5.51	ArcMCCHTTP::MCC_HTTP_Service Class Reference	65
5.51.1	Detailed Description	65
5.52	ArcMCCMsgValidator::MCC_MsgValidator Class Reference	66
5.53	ArcMCCMsgValidator::MCC_MsgValidator_Service Class Reference	67
5.54	ArcMCCSOAP::MCC_SOAP Class Reference	68
5.54.1	Detailed Description	68
5.55	ArcMCCSOAP::MCC_SOAP_Client Class Reference	69
5.56	ArcMCCSOAP::MCC_SOAP_Service Class Reference	70
5.56.1	Detailed Description	70
5.57	ArcMCCTCP::MCC_TCP Class Reference	71
5.57.1	Detailed Description	71
5.58	ArcMCCTCP::MCC_TCP_Client Class Reference	72
5.58.1	Detailed Description	72
5.59	ArcMCCTCP::MCC_TCP_Service Class Reference	73

5.59.1 Detailed Description	73
5.59.2 Constructor & Destructor Documentation	73
5.59.2.1 MCC_TCP_Service	73
5.60 ArcMCCTLS::MCC_TLS Class Reference	74
5.60.1 Detailed Description	74
5.61 ArcMCCTLS::MCC_TLS_Client Class Reference	75
5.61.1 Detailed Description	75
5.62 ArcMCCTLS::MCC_TLS_Service Class Reference	76
5.62.1 Detailed Description	76
5.63 ArcMCCGSI::PayloadGSISStream Class Reference	77
5.64 ArcMCCHTTP::PayloadHTTP Class Reference	78
5.64.1 Detailed Description	78
5.64.2 Constructor & Destructor Documentation	79
5.64.2.1 PayloadHTTP	79
5.64.2.2 PayloadHTTP	79
5.64.2.3 PayloadHTTP	79
5.64.2.4 PayloadHTTP	79
5.64.2.5 PayloadHTTP	79
5.64.3 Member Function Documentation	79
5.64.3.1 Attribute	79
5.64.3.2 Attribute	79
5.64.3.3 Attributes	79
5.64.3.4 Body	80
5.64.3.5 Flush	80
5.64.3.6 get_body	80
5.64.3.7 read	80
5.64.3.8 read_header	80
5.64.3.9 readline	80
5.64.4 Field Documentation	80
5.64.4.1 attributes_	80
5.64.4.2 body_own_	80
5.64.4.3 chunk_size_	80
5.64.4.4 chunked_	80
5.64.4.5 code_	81
5.64.4.6 end_	81
5.64.4.7 length_	81

5.64.4.8	method_	81
5.64.4.9	rbody_	81
5.64.4.10	reason_	81
5.64.4.11	sbody_	81
5.64.4.12	stream_	81
5.64.4.13	stream_own_	81
5.64.4.14	uri_	81
5.64.4.15	version_major_	81
5.64.4.16	version_minor_	82
5.65	ArcMCCTCP::PayloadTCPSocket Class Reference	83
5.65.1	Detailed Description	83
5.65.2	Constructor & Destructor Documentation	83
5.65.2.1	PayloadTCPSocket	83
5.65.2.2	PayloadTCPSocket	83
5.65.2.3	PayloadTCPSocket	83
5.65.2.4	PayloadTCPSocket	83
5.65.2.5	PayloadTCPSocket	83
5.66	ArcMCCTLS::PayloadTLSMCC Class Reference	84
5.66.1	Constructor & Destructor Documentation	84
5.66.1.1	PayloadTLSMCC	84
5.66.1.2	PayloadTLSMCC	84
5.66.1.3	PayloadTLSMCC	84
5.67	ArcMCCTLS::PayloadTLSStream Class Reference	85
5.67.1	Detailed Description	85
5.67.2	Constructor & Destructor Documentation	85
5.67.2.1	PayloadTLSStream	85
5.67.2.2	~PayloadTLSStream	85
5.67.3	Member Function Documentation	85
5.67.3.1	GetCert	85
5.67.3.2	GetPeerCert	86
5.67.3.3	STACK_OF	86
5.67.4	Field Documentation	86
5.67.4.1	ssl_	86
5.68	ArcSec::PDPSERVICEInvoker Class Reference	87
5.68.1	Detailed Description	87
5.69	ArcSec::SAML2SSO_AssertionConsumerSH Class Reference	88

5.69.1 Detailed Description	88
5.70 ArcSec::SAMLTokenSH Class Reference	89
5.70.1 Detailed Description	89
5.71 ArcSec::SimpleListPDP Class Reference	90
5.71.1 Detailed Description	90
5.72 ArcSHCLegacy::SimpleMap Class Reference	91
5.73 Arc::SRM1Client Class Reference	92
5.73.1 Member Function Documentation	92
5.73.1.1 abort	92
5.73.1.2 checkPermissions	93
5.73.1.3 copy	93
5.73.1.4 getRequestTokens	93
5.73.1.5 getSpaceTokens	93
5.73.1.6 getTURLs	94
5.73.1.7 getTURLsStatus	94
5.73.1.8 info	94
5.73.1.9 info	95
5.73.1.10 mkdir	95
5.73.1.11 ping	96
5.73.1.12 putTURLs	96
5.73.1.13 putTURLsStatus	96
5.73.1.14 release	97
5.73.1.15 releaseGet	97
5.73.1.16 releasePut	97
5.73.1.17 remove	97
5.73.1.18 requestBringOnline	98
5.73.1.19 requestBringOnlineStatus	98
5.74 Arc::SRM22Client Class Reference	99
5.74.1 Constructor & Destructor Documentation	99
5.74.1.1 SRM22Client	99
5.74.1.2 ~SRM22Client	99
5.74.2 Member Function Documentation	100
5.74.2.1 abort	100
5.74.2.2 checkPermissions	100
5.74.2.3 copy	100
5.74.2.4 getRequestTokens	100

5.74.2.5	getSpaceTokens	100
5.74.2.6	getTURLs	100
5.74.2.7	getTURLsStatus	100
5.74.2.8	info	101
5.74.2.9	info	101
5.74.2.10	mkDir	101
5.74.2.11	ping	101
5.74.2.12	putTURLs	101
5.74.2.13	putTURLsStatus	101
5.74.2.14	release	101
5.74.2.15	releaseGet	102
5.74.2.16	releasePut	102
5.74.2.17	remove	102
5.74.2.18	requestBringOnline	102
5.74.2.19	requestBringOnlineStatus	102
5.75	Arc::SRMClient Class Reference	103
5.75.1	Detailed Description	104
5.75.2	Constructor & Destructor Documentation	104
5.75.2.1	~SRMClient	104
5.75.3	Member Function Documentation	104
5.75.3.1	abort	104
5.75.3.2	checkPermissions	104
5.75.3.3	copy	105
5.75.3.4	getInstance	105
5.75.3.5	getRequestTokens	105
5.75.3.6	getSpaceTokens	106
5.75.3.7	getTURLs	106
5.75.3.8	getTURLsStatus	106
5.75.3.9	getVersion	107
5.75.3.10	info	107
5.75.3.11	info	107
5.75.3.12	mkDir	107
5.75.3.13	ping	108
5.75.3.14	putTURLs	108
5.75.3.15	putTURLsStatus	108
5.75.3.16	release	109

5.75.3.17	releaseGet	109
5.75.3.18	releasePut	109
5.75.3.19	remove	110
5.75.3.20	requestBringOnline	110
5.75.3.21	requestBringOnlineStatus	110
5.75.4	Field Documentation	110
5.75.4.1	service_endpoint	110
5.76	Arc::SRMClientRequest Class Reference	112
5.76.1	Detailed Description	112
5.76.2	Constructor & Destructor Documentation	112
5.76.2.1	SRMClientRequest	112
5.76.2.2	SRMClientRequest	112
5.76.3	Member Function Documentation	112
5.76.3.1	waiting_time	112
5.77	SRMFileInfo Class Reference	113
5.77.1	Detailed Description	113
5.78	Arc::SRMFileMetaData Struct Reference	114
5.78.1	Detailed Description	114
5.79	SRMInfo Class Reference	115
5.79.1	Detailed Description	115
5.80	Arc::SRMInvalidRequestException Class Reference	116
5.80.1	Detailed Description	116
5.81	SRMURL Class Reference	117
5.81.1	Constructor & Destructor Documentation	117
5.81.1.1	SRMURL	117
5.81.2	Member Function Documentation	117
5.81.2.1	BaseURL	117
5.81.2.2	ContactURL	117
5.81.2.3	Endpoint	117
5.81.2.4	FileName	117
5.81.2.5	FullURL	117
5.81.2.6	PortDefined	117
5.81.2.7	SetSRMVersion	118
5.81.2.8	ShortURL	118
5.82	ArcSHCLegacy::UnixMap Class Reference	119
5.83	ArcSec::UsernameTokenSH Class Reference	120

5.83.1 Detailed Description	120
5.84 ArcSHCLegacy::voms Struct Reference	121
5.84.1 Detailed Description	121
5.84.2 Field Documentation	121
5.84.2.1 attrs	121
5.84.2.2 server	121
5.84.2.3 voname	121
5.85 ArcSHCLegacy::voms_attrs Struct Reference	122
5.85.1 Detailed Description	122
5.85.2 Field Documentation	122
5.85.2.1 cap	122
5.85.2.2 group	122
5.85.2.3 role	122
5.86 ArcSec::X509TokenSH Class Reference	123
5.86.1 Detailed Description	123
5.87 ArcSec::XACMLAlgFactory Class Reference	124
5.87.1 Detailed Description	124
5.87.2 Member Function Documentation	124
5.87.2.1 createAlg	124
5.88 ArcSec::XACMLApply Class Reference	125
5.89 ArcSec::XACMLAttributeFactory Class Reference	126
5.89.1 Detailed Description	126
5.89.2 Member Function Documentation	126
5.89.2.1 createValue	126
5.90 ArcSec::XACMLAttributeProxy< TheAttribute > Class Template Reference	127
5.90.1 Detailed Description	127
5.91 ArcSec::XACMLCondition Class Reference	128
5.91.1 Detailed Description	128
5.91.2 Constructor & Destructor Documentation	128
5.91.2.1 XACMLCondition	128
5.92 ArcSec::XACMLEvaluationCtx Class Reference	129
5.92.1 Detailed Description	129
5.92.2 Constructor & Destructor Documentation	129
5.92.2.1 XACMLEvaluationCtx	129
5.93 ArcSec::XACMLEvaluator Class Reference	130
5.93.1 Detailed Description	130

5.93.2	Member Function Documentation	130
5.93.2.1	evaluate	130
5.94	ArcSec::XACMLFnFactory Class Reference	131
5.94.1	Detailed Description	131
5.94.2	Member Function Documentation	131
5.94.2.1	createFn	131
5.95	ArcSec::XACMLPDP Class Reference	132
5.95.1	Detailed Description	132
5.96	ArcSec::XACMLPolicy Class Reference	133
5.96.1	Detailed Description	133
5.96.2	Constructor & Destructor Documentation	133
5.96.2.1	XACMLPolicy	133
5.96.2.2	XACMLPolicy	133
5.96.2.3	XACMLPolicy	133
5.96.3	Member Function Documentation	133
5.96.3.1	make_policy	133
5.97	ArcSec::XACMLRequest Class Reference	134
5.97.1	Member Function Documentation	134
5.97.1.1	getEvalName	134
5.97.1.2	getName	134
5.98	ArcSec::XACMLRule Class Reference	135
5.98.1	Detailed Description	135
5.99	ArcSec::XACMLTarget Class Reference	136
5.99.1	Detailed Description	136
5.99.2	Constructor & Destructor Documentation	136
5.99.2.1	XACMLTarget	136
5.100	ArcSec::XACMLTargetMatch Class Reference	137
5.101	ArcSec::XACMLTargetMatchGroup Class Reference	138
5.102	ArcSec::XACMLTargetSection Class Reference	139

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

ArcSec (ArcRequest , Parsing the specified Arc request format)	11
--	----

Chapter 2

Data Structure Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

ArcSec::AllowPDP	15
ArcSec::ArcAlgFactory	16
ArcSec::ArcAttributeFactory	17
ArcSec::ArcAttributeProxy< TheAttribute >	18
ArcSec::ArcAuthZ	19
ArcSec::ArcEvaluationCtx	20
ArcSec::ArcEvaluator	21
ArcSec::ArcFnFactory	22
ArcSec::ArcPDP	23
ArcSec::ArcPolicy	24
ArcSec::ArcRequest	25
ArcSec::ArcRequestItem	26
ArcSec::ArcRequestTuple	27
ArcSec::ArcRule	28
ArcSec::AttributeDesignator	29
ArcSec::AttributeSelector	30
ArcSHCLegacy::AuthUser	31
ArcSHCLegacy::AuthVO	32
ArcSHCLegacy::ConfigParser	33
ArcMCCTLS::ConfigTlsmcc	34
Arc::DataPointARC	35
Arc::DataPointFile	36
Arc::DataPointGFAL	37
Arc::DataPointGridFTP	38
Arc::DataPointHTTP	39
Arc::DataPointLDAP	40
Arc::DataPointLFC	41
Arc::DataPointRLS	42
Arc::DataPointSRM	43
Arc::DataPointXrootd	44
ArcMCCTLSec::DelegationCollector	45
ArcMCCTLSec::DelegationMultiSecAttr	46
ArcSec::DelegationPDP	47

ArcMCCTLSec::DelegationSecAttr	48
ArcSec::DelegationSH	49
ArcSec::DenyPDP	50
ArcSec::GACLEvaluator	51
ArcSec::GACLPDP	52
ArcSec::GACLPolicy	53
ArcSec::GACLRequest	54
Arc::LDAPQuery	55
ArcSHCLegacy::LegacyMap	56
ArcSHCLegacy::LegacyPDP	57
ArcSHCLegacy::LegacySecAttr	58
ArcSHCLegacy::LegacySecHandler	59
Arc::Lister	60
ArcMCCGSI::MCC_GSI_Client	61
ArcMCCGSI::MCC_GSI_Service	62
ArcMCCHTTP::MCC_HTTP	63
ArcMCCHTTP::MCC_HTTP_Client	64
ArcMCCHTTP::MCC_HTTP_Service	65
ArcMCCMsgValidator::MCC_MsgValidator	66
ArcMCCMsgValidator::MCC_MsgValidator_Service	67
ArcMCCSOAP::MCC_SOAP	68
ArcMCCSOAP::MCC_SOAP_Client	69
ArcMCCSOAP::MCC_SOAP_Service	70
ArcMCCTCP::MCC_TCP	71
ArcMCCTCP::MCC_TCP_Client	72
ArcMCCTCP::MCC_TCP_Service	73
ArcMCCTLS::MCC_TLS	74
ArcMCCTLS::MCC_TLS_Client	75
ArcMCCTLS::MCC_TLS_Service	76
ArcMCCGSI::PayloadGSISStream	77
ArcMCCHTTP::PayloadHTTP	78
ArcMCCTCP::PayloadTCPSToken	83
ArcMCCTLS::PayloadTLSStream	85
ArcMCCTLS::PayloadTSLMCC	84
ArcSec::PDPServletInvoker	87
ArcSec::SAML2SSO_AssertionConsumerSH	88
ArcSec::SAMLTokenSH	89
ArcSec::SimpleListPDP	90
ArcSHCLegacy::SimpleMap	91
Arc::SRMClient	103
Arc::SRM1Client	92
Arc::SRM22Client	99
Arc::SRMClientRequest	112
SRMFileInfo	113
Arc::SRMFileMetadata	114
SRMInfo	115
Arc::SRMInvalidRequestException	116
SRMURL	117
ArcSHCLegacy::UnixMap	119
ArcSec::UsernameTokenSH	120
ArcSHCLegacy::voms	121
ArcSHCLegacy::voms_attrs	122

ArcSec::X509TokenSH	123
ArcSec::XACMLAlgFactory	124
ArcSec::XACMLApply	125
ArcSec::XACMLAttributeFactory	126
ArcSec::XACMLAttributeProxy< TheAttribute >	127
ArcSec::XACMLCondition	128
ArcSec::XACMLEvaluationCtx	129
ArcSec::XACMLEvaluator	130
ArcSec::XACMLFnFactory	131
ArcSec::XACMLPDP	132
ArcSec::XACMLPolicy	133
ArcSec::XACMLRequest	134
ArcSec::XACMLRule	135
ArcSec::XACMLTarget	136
ArcSec::XACMLTargetMatch	137
ArcSec::XACMLTargetMatchGroup	138
ArcSec::XACMLTargetSection	139

Chapter 3

Data Structure Index

3.1 Data Structures

Here are the data structures with brief descriptions:

ArcSec::AllowPDP (This PDP always return true (allow))	15
ArcSec::ArcAlgFactory (Algorithm factory class for Arc)	16
ArcSec::ArcAttributeFactory (Attribute factory class for Arc specified attributes)	17
ArcSec::ArcAttributeProxy< TheAttribute > (Arc specific AttributeProxy class)	18
ArcSec::ArcAuthZ (Tests message against list of PDPs)	19
ArcSec::ArcEvaluationCtx (EvaluationCtx, in charge of storing some context information for evaluation, including Request, current time, etc)	20
ArcSec::ArcEvaluator (Execute the policy evaluation, based on the request and policy)	21
ArcSec::ArcFnFactory (Function factory class for Arc specified attributes)	22
ArcSec::ArcPDP (ArcPDP - PDP which can handle the Arc specific request and policy schema)	23
ArcSec::ArcPolicy (ArcPolicy class to parse and operate Arc specific <Policy> node)	24
ArcSec::ArcRequest	25
ArcSec::ArcRequestItem (Container, <Subjects, Actions, Objects, Contexts> tuple)	26
ArcSec::ArcRequestTuple (RequestTuple, container which includes the)	27
ArcSec::ArcRule (ArcRule class to parse Arc specific <Rule> node)	28
ArcSec::AttributeDesignator	29
ArcSec::AttributeSelector	30
ArcSHCLegacy::AuthUser	31
ArcSHCLegacy::AuthVO	32
ArcSHCLegacy::ConfigParser	33
ArcMCCTLS::ConfigTSMCC	34
Arc::DataPointARC	35
Arc::DataPointFile	36
Arc::DataPointGFAL	37
Arc::DataPointGridFTP	38
Arc::DataPointHTTP	39
Arc::DataPointLDAP	40
Arc::DataPointLFC	41
Arc::DataPointRLS	42
Arc::DataPointSRM	43
Arc::DataPointXrootd	44
ArcMCCTLSec::DelegationCollector	45
ArcMCCTLSec::DelegationMultiSecAttr	46

ArcSec::DelegationPDP	47
ArcMCCTLSec::DelegationSecAttr	48
ArcSec::DelegationSH	49
ArcSec::DenyPDP (This PDP always returns false (deny))	50
ArcSec::GACLEvaluator	51
ArcSec::GACLPDP	52
ArcSec::GACLPolicy	53
ArcSec::GACLRequest	54
Arc::LDAPQuery	55
ArcSHCLegacy::LegacyMap	56
ArcSHCLegacy::LegacyPDP	57
ArcSHCLegacy::LegacySecAttr	58
ArcSHCLegacy::LegacySecHandler	59
Arc::Lister	60
ArcMCCGSI::MCC_GSI_Client	61
ArcMCCGSI::MCC_GSI_Service	62
ArcMCCHTTP::MCC_HTTP (A base class for HTTP client and service MCCs)	63
ArcMCCHTTP::MCC_HTTP_Client	64
ArcMCCHTTP::MCC_HTTP_Service	65
ArcMCCMsgValidator::MCC_MsgValidator	66
ArcMCCMsgValidator::MCC_MsgValidator_Service	67
ArcMCCSOAP::MCC_SOAP (A base class for SOAP client and service MCCs)	68
ArcMCCSOAP::MCC_SOAP_Client	69
ArcMCCSOAP::MCC_SOAP_Service	70
ArcMCCTCP::MCC_TCP (A base class for TCP client and service MCCs)	71
ArcMCCTCP::MCC_TCP_Client	72
ArcMCCTCP::MCC_TCP_Service	73
ArcMCCTLS::MCC_TLS (A base class for TLS client and service MCCs)	74
ArcMCCTLS::MCC_TLS_Client	75
ArcMCCTLS::MCC_TLS_Service	76
ArcMCCGSI::PayloadGSISStream	77
ArcMCCHTTP::PayloadHTTP	78
ArcMCCTCP::PayloadTCPsSocket	83
ArcMCCTLS::PayloadTLSMCC	84
ArcMCCTLS::PayloadTLSSStream	85
ArcSec::PDPSERVICEInvoker (PDPSERVICEInvoker - client which will invoke pdpservice)	87
ArcSec::SAML2SSO_AssertionConsumerSH (Implement the functionality of the Service Provider in SAML2 SSO profile)	88
ArcSec::SAMLTokenSH (Adds WS-Security SAML Token into SOAP Header)	89
ArcSec::SimpleListPDP (Tests X509 subject against list of subjects in file)	90
ArcSHCLegacy::SimpleMap	91
Arc::SRM1Client	92
Arc::SRM22Client	99
Arc::SRMClient	103
Arc::SRMClientRequest (Class to represent a SRM request)	112
SRMFileInfo	113
Arc::SRMFileMetaData (SRM-related file metadata)	114
SRMInfo	115
Arc::SRMInvalidRequestException (General exception to represent a bad SRM request)	116
SRMURL	117
ArcSHCLegacy::UnixMap	119
ArcSec::UsernameTokenSH (Adds WS-Security Username Token into SOAP Header)	120
ArcSHCLegacy::voms	121
ArcSHCLegacy::voms_attrs	122

ArcSec::X509TokenSH (Adds WS-Security X509 Token into SOAP Header)	123
ArcSec::XACMLAlgFactory (Algorithm factory class for XACML)	124
ArcSec::XACMLApply	125
ArcSec::XACMLAttributeFactory (Attribute factory class for XACML specified attributes) . . .	126
ArcSec::XACMLAttributeProxy < TheAttribute > (XACML specific AttributeProxy class) . . .	127
ArcSec::XACMLCondition (XACMLCondition class to parse and operate XACML specific <Condition> node)	128
ArcSec::XACMLEvaluationCtx (EvaluationCtx, in charge of storing some context information for evaluation, including Request, current time, etc)	129
ArcSec::XACMLEvaluator (Execute the policy evaluation, based on the request and policy) . .	130
ArcSec::XACMLFnFactory (Function factory class for XACML specified attributes)	131
ArcSec::XACMLPDP (XACMLPDP - PDP which can handle the XACML specific request and policy schema)	132
ArcSec::XACMLPolicy (XACMLPolicy class to parse and operate XACML specific <Policy> node)	133
ArcSec::XACMLRequest	134
ArcSec::XACMLRule (XACMLRule class to parse XACML specific <Rule> node)	135
ArcSec::XACMLTarget (XACMLTarget class to parse and operate XACML specific <Target> node)	136
ArcSec::XACMLTargetMatch	137
ArcSec::XACMLTargetMatchGroup	138
ArcSec::XACMLTargetSection	139

Chapter 4

Namespace Documentation

4.1 ArcSec Namespace Reference

[ArcRequest](#), Parsing the specified Arc request format.

Data Structures

- class [AllowPDP](#)
This PDP always return true (allow).
- class [ArcAuthZ](#)
Tests message against list of PDPs.
- class [ArcAlgFactory](#)
Algorithm factory class for Arc.
- class [ArcAttributeFactory](#)
Attribute factory class for Arc specified attributes.
- class [ArcAttributeProxy](#)
Arc specific AttributeProxy class.
- class [ArcRequestTuple](#)
RequestTuple, container which includes the.
- class [ArcEvaluationCtx](#)
EvaluationCtx, in charge of storing some context information for evaluation, including Request, current time, etc.
- class [ArcEvaluator](#)
Execute the policy evaluation, based on the request and policy.
- class [ArcFnFactory](#)
Function factory class for Arc specified attributes.

- class [ArcPDP](#)
ArcPDP - PDP which can handle the Arc specific request and policy schema.
- class [ArcPolicy](#)
ArcPolicy class to parse and operate Arc specific <Policy> node.
- class [ArcRequest](#)
- class [ArcRequestItem](#)
Container, <Subjects, Actions, Objects, Contexts> tuple.
- class [ArcRule](#)
ArcRule class to parse Arc specific <Rule> node.
- class [DelegationPDP](#)
- class [DelegationSH](#)
- class [DenyPDP](#)
This PDP always returns false (deny).
- class [GACLEvaluator](#)
- class [GACLPDP](#)
- class [GACLPolicy](#)
- class [GACLRequest](#)
- class [PDPServiceInvoker](#)
PDPServiceInvoker - client which will invoke pdpservice.
- class [SAML2SSO_AssertionConsumerSH](#)
Implement the functionality of the Service Provider in SAML2 SSO profile.
- class [SAMLTokenSH](#)
Adds WS-Security SAML Token into SOAP Header.
- class [SimpleListPDP](#)
Tests X509 subject against list of subjects in file.
- class [UsernameTokenSH](#)
Adds WS-Security Username Token into SOAP Header.
- class [X509TokenSH](#)
Adds WS-Security X509 Token into SOAP Header.
- class [AttributeDesignator](#)
- class [AttributeSelector](#)
- class [XACMLAlgFactory](#)
Algorithm factory class for XACML.
- class [XACMLApply](#)
- class [XACMLAttributeFactory](#)
Attribute factory class for XACML specified attributes.
- class [XACMLAttributeProxy](#)

XACML specific AttributeProxy class.

- class [XACMLCondition](#)
XACMLCondition class to parse and operate XACML specific <Condition> node.
- class [XACMLEvaluationCtx](#)
EvaluationCtx, in charge of storing some context information for evaluation, including Request, current time, etc.
- class [XACMLEvaluator](#)
Execute the policy evaluation, based on the request and policy.
- class [XACMLFnFactory](#)
Function factory class for XACML specified attributes.
- class [XACMLPDP](#)
XACMLPDP - PDP which can handle the XACML specific request and policy schema.
- class [XACMLPolicy](#)
XACMLPolicy class to parse and operate XACML specific <Policy> node.
- class [XACMLRequest](#)
- class [XACMLRule](#)
XACMLRule class to parse XACML specific <Rule> node.
- class [XACMLTargetMatch](#)
- class [XACMLTargetMatchGroup](#)
- class [XACMLTargetSection](#)
- class [XACMLTarget](#)
XACMLTarget class to parse and operate XACML specific <Target> node.

Typedefs

- typedef std::pair< AttributeValue *, Function * > [Match](#)
- typedef std::list< [Match](#) > [AndList](#)
- typedef std::list< [AndList](#) > [OrList](#)

4.1.1 Detailed Description

[ArcRequest](#), Parsing the specified Arc request format. [XACMLRequest](#), Parsing the xacml request format.

4.1.2 Typedef Documentation

4.1.2.1 typedef std::list<Match> ArcSec::AndList

AndList - include items inside one <Subject> (or <Resource> <Action> <Condition>). "And" relationship means the request should satisfy all of the items <Subject> <SubFraction type="X500DN">/O=Grid/OU=KnowARC/CN=XYZ</SubFraction>

```

<SubFraction      type="ShibName">urn:mace:shibboleth:examples</SubFraction>      </Subject>
"Or" relationship   meant the request should satisfy any of the items <Subjects>
<Subject          type="X500DN">/O=Grid/OU=KnowARC/CN=ABC</Subject>              <Subject
type="VOMSAttribute">/vo.knowarc/usergroupA</Subject>                          <SubFraction
type="X500DN">/O=Grid/OU=KnowARC/CN=XYZ</SubFraction>                          <SubFraction
type="ShibName">urn:mace:shibboleth:examples</SubFraction>                      </Subject>      <GroupIdRef
location="/subjectgroup.xml">subgrpexample1</GroupIdRef> </Subjects>

```

4.1.2.2 typedef std::pair<AttributeValue*, Function*> ArcSec::Match

Pair Match include the AttributeValue object in <Rule> and the Function which is used to handle the AttributeValue, default function is "Equal", if some other function is used, it should be explicitly specified, e.g. Subject Type="string" Function="Match">/vo.knowarc/usergroupA</Subject> Subjects> example inside <Rule>: <Subjects> <Subject type="X500Name">/O=NorduGrid/OU=UIO/CN=test</Subject> <Subject type="string">/vo.knowarc/usergroupA</Subject> <Subject> <SubFraction type="string">/O=Grid/OU=KnowARC/CN=XYZ</SubFraction> <SubFraction type="string">urn:mace:shibboleth:examples</SubFraction> </Subject> <GroupIdRef location="/subjectgroup.xml">subgrpexample1</GroupIdRef> </Subjects>

Chapter 5

Data Structure Documentation

5.1 ArcSec::AllowPDP Class Reference

This PDP always return true (allow).

```
#include <AllowPDP.h>
```

5.1.1 Detailed Description

This PDP always return true (allow).

The documentation for this class was generated from the following file:

- AllowPDP.h

5.2 ArcSec::ArcAlgFactory Class Reference

Algorithm factory class for Arc.

```
#include <ArcAlgFactory.h>
```

Public Member Functions

- virtual CombiningAlg * [createAlg](#) (const std::string &type)

5.2.1 Detailed Description

Algorithm factory class for Arc.

5.2.2 Member Function Documentation

5.2.2.1 virtual CombiningAlg* ArcSec::ArcAlgFactory::createAlg (const std::string & type) [virtual]

return a Alg object according to the "CombiningAlg" attribute in the <Policy> node; The [ArcAlgFactory](#) itself will release the Alg objects

The documentation for this class was generated from the following file:

- ArcAlgFactory.h

5.3 ArcSec::ArcAttributeFactory Class Reference

Attribute factory class for Arc specified attributes.

```
#include <ArcAttributeFactory.h>
```

Public Member Functions

- virtual AttributeValue * [createValue](#) (const Arc::XMLNode &node, const std::string &type)

5.3.1 Detailed Description

Attribute factory class for Arc specified attributes.

5.3.2 Member Function Documentation

5.3.2.1 virtual AttributeValue* ArcSec::ArcAttributeFactory::createValue (const Arc::XMLNode & node, const std::string & type) [virtual]

creat a AttributeValue according to the value in the XML node and the type; It should be the caller to release the AttributeValue Object

The documentation for this class was generated from the following file:

- ArcAttributeFactory.h

5.4 ArcSec::ArcAttributeProxy< TheAttribute > Class Template Reference

Arc specific AttributeProxy class.

```
#include <ArcAttributeProxy.h>
```

Public Member Functions

- virtual AttributeValue * [getAttribute](#) (const Arc::XMLNode &node)

5.4.1 Detailed Description

```
template<class TheAttribute> class ArcSec::ArcAttributeProxy< TheAttribute >
```

Arc specific AttributeProxy class.

The documentation for this class was generated from the following file:

- ArcAttributeProxy.h

5.5 ArcSec::ArcAuthZ Class Reference

Tests message against list of PDPs.

```
#include <ArcAuthZ.h>
```

Data Structures

- class **PDPDesc**

Public Member Functions

- virtual bool [Handle](#) (Arc::Message *msg) const

Protected Member Functions

- bool [MakePDPs](#) (Arc::XMLNode cfg)

5.5.1 Detailed Description

Tests message against list of PDPs. This class implements SecHandler interface. It's [Handle\(\)](#) method runs provided Message instance against all PDPs specified in configuration. If any of PDPs returns positive result [Handle\(\)](#) return true, otherwise false. This class is the main entry for configuring authorization, and could include different PDP configured inside.

5.5.2 Member Function Documentation

5.5.2.1 virtual bool ArcSec::ArcAuthZ::Handle (Arc::Message * *msg*) const **[virtual]**

Get authorization decision

5.5.2.2 bool ArcSec::ArcAuthZ::MakePDPs (Arc::XMLNode *cfg*) **[protected]**

Create PDP according to conf info

The documentation for this class was generated from the following file:

- ArcAuthZ.h

5.6 ArcSec::ArcEvaluationCtx Class Reference

EvaluationCtx, in charge of storing some context information for evaluation, including Request, current time, etc.

```
#include <ArcEvaluationCtx.h>
```

Public Member Functions

- [ArcEvaluationCtx](#) (Request *request)
- virtual void [split](#) ()

5.6.1 Detailed Description

EvaluationCtx, in charge of storing some context information for evaluation, including Request, current time, etc.

5.6.2 Constructor & Destructor Documentation

5.6.2.1 ArcSec::ArcEvaluationCtx::ArcEvaluationCtx (Request * *request*)

Construct a new EvaluationCtx based on the given request

5.6.3 Member Function Documentation

5.6.3.1 virtual void ArcSec::ArcEvaluationCtx::split () [virtual]

Convert/split one RequestItem (one tuple <SubList, ResList, ActList, CtxList>) into a few <Subject, Resource, Action, Context> tuples. The purpose is for evaluation. The evaluator will evaluate each RequestTuple one by one, not the RequestItem because it includes some independent <Subject, Resource, Action, Context>s and the evaluator should deal with them independently.

The documentation for this class was generated from the following file:

- ArcEvaluationCtx.h

5.7 ArcSec::ArcEvaluator Class Reference

Execute the policy evaluation, based on the request and policy.

```
#include <ArcEvaluator.h>
```

Public Member Functions

- virtual Response * [evaluate](#) (Request *request)

5.7.1 Detailed Description

Execute the policy evaluation, based on the request and policy.

5.7.2 Member Function Documentation

5.7.2.1 virtual Response* ArcSec::ArcEvaluator::evaluate (Request * *request*) [virtual]

Evaluate the request based on the policy information inside PolicyStore

The documentation for this class was generated from the following file:

- ArcEvaluator.h

5.8 ArcSec::ArcFnFactory Class Reference

Function factory class for Arc specified attributes.

```
#include <ArcFnFactory.h>
```

Public Member Functions

- virtual Function * [createFn](#) (const std::string &type)

5.8.1 Detailed Description

Function factory class for Arc specified attributes.

5.8.2 Member Function Documentation

5.8.2.1 virtual Function* ArcSec::ArcFnFactory::createFn (const std::string & type) [virtual]

return a Function object according to the "Function" attribute in the XML node; The [ArcFnFactory](#) itself will release the Function objects

The documentation for this class was generated from the following file:

- ArcFnFactory.h

5.9 ArcSec::ArcPDP Class Reference

[ArcPDP](#) - PDP which can handle the Arc specific request and policy schema.

```
#include <ArcPDP.h>
```

5.9.1 Detailed Description

[ArcPDP](#) - PDP which can handle the Arc specific request and policy schema.

The documentation for this class was generated from the following file:

- ArcPDP.h

5.10 ArcSec::ArcPolicy Class Reference

[ArcPolicy](#) class to parse and operate Arc specific <Policy> node.

```
#include <ArcPolicy.h>
```

Public Member Functions

- [ArcPolicy](#) (Arc::PluginArgument *parg)
- [ArcPolicy](#) (const Arc::XMLNode node, Arc::PluginArgument *parg)
- [ArcPolicy](#) (const Arc::XMLNode node, EvaluatorContext *ctx, Arc::PluginArgument *parg)
- virtual void [make_policy](#) ()

5.10.1 Detailed Description

[ArcPolicy](#) class to parse and operate Arc specific <Policy> node.

5.10.2 Constructor & Destructor Documentation

5.10.2.1 ArcSec::ArcPolicy::ArcPolicy (Arc::PluginArgument * *parg*)

Constructor

5.10.2.2 ArcSec::ArcPolicy::ArcPolicy (const Arc::XMLNode *node*, Arc::PluginArgument * *parg*)

Constructor

5.10.2.3 ArcSec::ArcPolicy::ArcPolicy (const Arc::XMLNode *node*, EvaluatorContext * *ctx*, Arc::PluginArgument * *parg*)

Constructor

5.10.3 Member Function Documentation

5.10.3.1 virtual void ArcSec::ArcPolicy::make_policy () [virtual]

Parse XMLNode, and construct the low-level Rule object

The documentation for this class was generated from the following file:

- ArcPolicy.h

5.11 ArcSec::ArcRequest Class Reference

The documentation for this class was generated from the following file:

- ArcRequest.h

5.12 ArcSec::ArcRequestItem Class Reference

Container, <Subjects, Actions, Objects, Contexts> tuple.

```
#include <ArcRequestItem.h>
```

5.12.1 Detailed Description

Container, <Subjects, Actions, Objects, Contexts> tuple. Specified [ArcRequestItem](#) which can parse Arc request formate

The documentation for this class was generated from the following file:

- ArcRequestItem.h

5.13 ArcSec::ArcRequestTuple Class Reference

RequestTuple, container which includes the.

```
#include <ArcEvaluationCtx.h>
```

5.13.1 Detailed Description

RequestTuple, container which includes the.

The documentation for this class was generated from the following file:

- ArcEvaluationCtx.h

5.14 ArcSec::ArcRule Class Reference

[ArcRule](#) class to parse Arc specific <Rule> node.

```
#include <ArcRule.h>
```

5.14.1 Detailed Description

[ArcRule](#) class to parse Arc specific <Rule> node.

The documentation for this class was generated from the following file:

- ArcRule.h

5.15 ArcSec::AttributeDesignator Class Reference

The documentation for this class was generated from the following file:

- AttributeDesignator.h

5.16 ArcSec::AttributeSelector Class Reference

The documentation for this class was generated from the following file:

- AttributeSelector.h

5.17 ArcSHCLegacy::AuthUser Class Reference

Data Structures

- class **group_t**
- struct **source_t**

The documentation for this class was generated from the following file:

- `auth.h`

5.18 ArcSHCLegacy::AuthVO Class Reference

The documentation for this class was generated from the following file:

- auth.h

5.19 ArcSHCLegacy::ConfigParser Class Reference

The documentation for this class was generated from the following file:

- ConfigParser.h

5.20 ArcMCCTLS::ConfigTlSMCC Class Reference

The documentation for this class was generated from the following file:

- ConfigTlSMCC.h

5.21 Arc::DataPointARC Class Reference

```
#include <DataPointARC.h>
```

5.21.1 Detailed Description

Provides an interface to the Chelonia storage system developed by ARC.

This class is a loadable module and cannot be used directly. The DataHandle class loads modules at runtime and should be used instead of this.

The documentation for this class was generated from the following file:

- DataPointARC.h

5.22 Arc::DataPointFile Class Reference

```
#include <DataPointFile.h>
```

5.22.1 Detailed Description

This class allows access to the regular local filesystem through the same interface as is used for remote storage on the grid.

This class is a loadable module and cannot be used directly. The DataHandle class loads modules at runtime and should be used instead of this.

The documentation for this class was generated from the following file:

- DataPointFile.h

5.23 Arc::DataPointGFAL Class Reference

```
#include <DataPointGFAL.h>
```

5.23.1 Detailed Description

Provides access to the gLite Grid File Access Library through ARC's API. Only rfiio:// protocol is supported at the moment.

Notes on env variables:

- If LFC plugin is installed LFC_HOST must be set (lcgutils bug 322)
- If SRM is used LCG_GFAL_INFOSYS must be set to BDII host:port

This class is a loadable module and cannot be used directly. The DataHandle class loads modules at runtime and should be used instead of this.

The documentation for this class was generated from the following file:

- DataPointGFAL.h

5.24 Arc::DataPointGridFTP Class Reference

```
#include <DataPointGridFTP.h>
```

Data Structures

- class **CBAArg**

5.24.1 Detailed Description

GridFTP is essentially the FTP protocol with GSI security. This class uses libraries from the Globus Toolkit. It can also be used for regular FTP.

This class is a loadable module and cannot be used directly. The DataHandle class loads modules at runtime and should be used instead of this.

The documentation for this class was generated from the following file:

- DataPointGridFTP.h

5.25 Arc::DataPointHTTP Class Reference

```
#include <DataPointHTTP.h>
```

5.25.1 Detailed Description

This class allows access through HTTP to remote resources. HTTP over SSL (HTTPS) and HTTP over GSI (HTTPG) are also supported.

This class is a loadable module and cannot be used directly. The DataHandle class loads modules at runtime and should be used instead of this.

The documentation for this class was generated from the following file:

- DataPointHTTP.h

5.26 Arc::DataPointLDAP Class Reference

```
#include <DataPointLDAP.h>
```

5.26.1 Detailed Description

LDAP is used in grids mainly to store information about grid services or resources rather than to store data itself. This class allows access to LDAP data through the same interface as other grid resources.

This class is a loadable module and cannot be used directly. The DataHandle class loads modules at runtime and should be used instead of this.

The documentation for this class was generated from the following file:

- DataPointLDAP.h

5.27 Arc::DataPointLFC Class Reference

```
#include <DataPointLFC.h>
```

5.27.1 Detailed Description

The LCG File Catalog (LFC) is a replica catalog developed by CERN. It consists of a hierarchical namespace of grid files and each filename can be associated with one or more physical locations.

This class is a loadable module and cannot be used directly. The DataHandle class loads modules at runtime and should be used instead of this.

The documentation for this class was generated from the following file:

- DataPointLFC.h

5.28 Arc::DataPointRLS Class Reference

```
#include <DataPointRLS.h>
```

5.28.1 Detailed Description

The Replica Location Service (RLS) is a replica catalog developed by Globus. It maps filenames in a flat namespace to one or more physical locations, and can also store meta-information on each file. This class uses the Globus Toolkit libraries for accessing RLS.

This class is a loadable module and cannot be used directly. The DataHandle class loads modules at runtime and should be used instead of this.

The documentation for this class was generated from the following file:

- DataPointRLS.h

5.29 Arc::DataPointSRM Class Reference

```
#include <DataPointSRM.h>
```

5.29.1 Detailed Description

The Storage Resource Manager (SRM) protocol allows access to data distributed across physical storage through a unified namespace and management interface. PrepareReading() or PrepareWriting() must be used before reading or writing a physical file.

This class is a loadable module and cannot be used directly. The DataHandle class loads modules at runtime and should be used instead of this.

The documentation for this class was generated from the following file:

- DataPointSRM.h

5.30 Arc::DataPointXrootd Class Reference

```
#include <DataPointXrootd.h>
```

5.30.1 Detailed Description

xrootd is a protocol for data access across large scale storage clusters. More information can be found at <http://xrootd.slac.stanford.edu/>

This class is a loadable module and cannot be used directly. The DataHandle class loads modules at runtime and should be used instead of this.

The documentation for this class was generated from the following file:

- DataPointXrootd.h

5.31 ArcMCCTLSec::DelegationCollector Class Reference

The documentation for this class was generated from the following file:

- DelegationCollector.h

5.32 ArcMCCTLSec::DelegationMultiSecAttr Class Reference

The documentation for this class was generated from the following file:

- DelegationSecAttr.h

5.33 ArcSec::DelegationPDP Class Reference

```
#include <DelegationPDP.h>
```

5.33.1 Detailed Description

DeleagtionPDP - PDP which can handle the Arc specific request and policy provided as identity delegation policy.

The documentation for this class was generated from the following file:

- DelegationPDP.h

5.34 ArcMCCTLSec::DelegationSecAttr Class Reference

The documentation for this class was generated from the following file:

- DelegationSecAttr.h

5.35 ArcSec::DelegationSH Class Reference

The documentation for this class was generated from the following file:

- DelegationSH.h

5.36 ArcSec::DenyPDP Class Reference

This PDP always returns false (deny).

```
#include <DenyPDP.h>
```

5.36.1 Detailed Description

This PDP always returns false (deny).

The documentation for this class was generated from the following file:

- DenyPDP.h

5.37 ArcSec::GACLEvaluator Class Reference

Public Member Functions

- virtual Response * [evaluate](#) (Request *request)

5.37.1 Member Function Documentation

5.37.1.1 virtual Response* ArcSec::GACLEvaluator::evaluate (Request * *request*) [virtual]

Evaluate the request based on the policy information inside PolicyStore

The documentation for this class was generated from the following file:

- GACLEvaluator.h

5.38 ArcSec::GACLPDP Class Reference

The documentation for this class was generated from the following file:

- GACLPDP.h

5.39 ArcSec::GACLPolicy Class Reference

The documentation for this class was generated from the following file:

- GACLPolicy.h

5.40 ArcSec::GACLRequest Class Reference

The documentation for this class was generated from the following file:

- GACLRequest.h

5.41 Arc::LDAPQuery Class Reference

```
#include <LDAPQuery.h>
```

Public Member Functions

- [LDAPQuery](#) (const std::string &ldaphost, int ldapport, int timeout, bool anonymous=true, const std::string &usersn="")
- [~LDAPQuery](#) ()
- bool [Query](#) (const std::string &base, const std::string &filter="(objectclass=*)", const std::list< std::string > &attributes=std::list< std::string >(), URL::Scope scope=URL::subtree)
- bool [Result](#) (ldap_callback callback, void *ref)

5.41.1 Detailed Description

[LDAPQuery](#) class; querying of LDAP servers.

5.41.2 Constructor & Destructor Documentation

5.41.2.1 Arc::LDAPQuery::LDAPQuery (const std::string &ldaphost, int ldapport, int timeout, bool anonymous = true, const std::string &usersn = "")

Constructs a new [LDAPQuery](#) object and sets connection options. The connection is first established when calling [Query](#).

5.41.2.2 Arc::LDAPQuery::~~LDAPQuery ()

Destructor. Will disconnect from the ldapserver if still connected.

5.41.3 Member Function Documentation

5.41.3.1 bool Arc::LDAPQuery::Query (const std::string &base, const std::string &filter = "(objectclass=*)", const std::list< std::string > &attributes = std::list< std::string >(), URL::Scope scope = URL::subtree)

Queries the ldap server.

5.41.3.2 bool Arc::LDAPQuery::Result (ldap_callback callback, void *ref)

Retrieves the result of the query from the ldap-server.

The documentation for this class was generated from the following file:

- LDAPQuery.h

5.42 ArcSHCLegacy::LegacyMap Class Reference

Data Structures

- class `cfgfile`

The documentation for this class was generated from the following file:

- LegacyMap.h

5.43 ArcSHCLegacy::LegacyPDP Class Reference

Data Structures

- class `cfgfile`

The documentation for this class was generated from the following file:

- LegacyPDP.h

5.44 ArcSHCLegacy::LegacySecAttr Class Reference

The documentation for this class was generated from the following file:

- LegacySecAttr.h

5.45 ArcSHCLegacy::LegacySecHandler Class Reference

The documentation for this class was generated from the following file:

- LegacySecHandler.h

5.46 Arc::Lister Class Reference

The documentation for this class was generated from the following file:

- Lister.h

5.47 ArcMCCGSI::MCC_GSI_Client Class Reference

The documentation for this class was generated from the following file:

- MCCGSI.h

5.48 ArcMCCGSI::MCC_GSI_Service Class Reference


The documentation for this class was generated from the following file:

- MCCGSI.h

5.49 ArcMCCHTTP::MCC_HTTP Class Reference

A base class for HTTP client and service MCCs.

`#include <MCCHTTP.h>` Inheritance diagram for ArcMCCHTTP::MCC_HTTP::



5.49.1 Detailed Description


A base class for HTTP client and service MCCs. This is a base class for HTTP client and service MCCs. It provides some common functionality for them, i.e. so far only a logger.

The documentation for this class was generated from the following file:

- MCCHTTP.h

5.50 ArcMCCHTTP::MCC_HTTP_Client Class Reference

`#include <MCCHTTP.h>`Inheritance diagram for ArcMCCHTTP::MCC_HTTP_Client::



5.50.1 Detailed Description


This class is a client part of HTTP MCC. It accepts PayloadRawInterface payload and uses it as body to generate HTTP request. Request is passed to next MCC as PayloadRawInterface type of payload. Returned PayloadStreamInterface payload is parsed into HTTP response and it's body is passed back to calling MCC as PayloadRawInterface. Attributes of request/input message of type HTTP:name are translated into HTTP header with corresponding 'name's. Special attributes HTTP:METHORD and HTTP:ENDPOINT specify method and URL in HTTP request. If not present meathod and URL are taken from configuration. In output/response message following attributes are present: HTTP:CODE - response code of HTTP HTTP:REASON - reason string of HTTP response HTTP:name - all 'name' attributes of HTTP header.

The documentation for this class was generated from the following file:

- MCCHTTP.h

5.51 ArcMCCHTTP::MCC_HTTP_Service Class Reference

#include <MCCHTTP.h> Inheritance diagram for ArcMCCHTTP::MCC_HTTP_Service::



5.51.1 Detailed Description


This class implements MCC to processes HTTP request. On input payload with PayloadStreamInterface is expected. HTTP message is read from stream and its body is converted into PayloadRaw and passed to next MCC. Returned payload of PayloadRawInterface type is treated as body part of returning [PayloadHTTP](#). Generated HTTP response is sent through stream passed in input payload. During processing of request/input message following attributes are generated: HTTP:METHOD - HTTP method e.g. GET, PUT, POST, etc. HTTP:ENDPOINT - URL taken from HTTP request ENDPOINT - global attribute equal to HTTP:ENDPOINT HTTP:RANGESTART - start of requested byte range HTTP:RANGEEND - end of requested byte range (inclusive) HTTP:name - all 'name' attributes of HTTP header. Attributes of response message of HTTP:name type are translated into HTTP header with corresponding 'name's.

The documentation for this class was generated from the following file:

- MCCHTTP.h

5.52 ArcMCCMsgValidator::MCC_MsgValidator Class Reference

Inheritance diagram for ArcMCCMsgValidator::MCC_MsgValidator::




The documentation for this class was generated from the following file:

- MCCMsgValidator.h

5.53 ArcMCCMsgValidator::MCC_MsgValidator_Service Class Reference

Inheritance diagram for ArcMCCMsgValidator::MCC_MsgValidator_Service::




The documentation for this class was generated from the following file:

- MCCMsgValidator.h

5.54 ArcMCCSOAP::MCC_SOAP Class Reference

A base class for SOAP client and service MCCs.

#include <MCCSOAP.h> Inheritance diagram for ArcMCCSOAP::MCC_SOAP::



5.54.1 Detailed Description


A base class for SOAP client and service MCCs. This is a base class for SOAP client and service MCCs. It provides some common functionality for them, i.e. so far only a logger.

The documentation for this class was generated from the following file:

- MCCSOAP.h

5.55 ArcMCCSOAP::MCC_SOAP_Client Class Reference

Inheritance diagram for ArcMCCSOAP::MCC_SOAP_Client::




The documentation for this class was generated from the following file:

- MCCSOAP.h

5.56 ArcMCCSOAP::MCC_SOAP_Service Class Reference

`#include <MCCSOAP.h>`Inheritance diagram for ArcMCCSOAP::MCC_SOAP_Service::



5.56.1 Detailed Description

This MCC parses SOAP message from input payload. On input payload with PayloadRawInterface is expected. It's converted into PayloadSOAP and passed next MCC. Returned PayloadSOAP is converted into PayloadRaw and returned to calling MCC.


The documentation for this class was generated from the following file:

- MCCSOAP.h

5.57 ArcMCCTCP::MCC_TCP Class Reference

A base class for TCP client and service MCCs.

#include <MCCTCP.h> Inheritance diagram for ArcMCCTCP::MCC_TCP::



5.57.1 Detailed Description


A base class for TCP client and service MCCs. This is a base class for TCP client and service MCCs. It provides some common functionality for them, i.e. so far only a logger.

The documentation for this class was generated from the following file:

- MCCTCP.h

5.58 ArcMCCTCP::MCC_TCP_Client Class Reference

`#include <MCCTCP.h>`Inheritance diagram for ArcMCCTCP::MCC_TCP_Client::



5.58.1 Detailed Description


This class is MCC implementing TCP client. Upon creation it connects to specified TCP post at specified host. process() method accepts PayloadRawInterface type of payload. Content of payload is sent over TCP socket. It returns PayloadStreamInterface payload for previous MCC to read response.

The documentation for this class was generated from the following file:

- MCCTCP.h

5.59 ArcMCCTCP::MCC_TCP_Service Class Reference

#include <MCCTCP.h> Inheritance diagram for ArcMCCTCP::MCC_TCP_Service::



Data Structures

- class `mcc_tcp_exec_t`
- class `mcc_tcp_handle_t`

Public Member Functions

- [MCC_TCP_Service](#) (Config *cfg, PluginArgument *parg)

5.59.1 Detailed Description

This class is MCC implementing TCP server. Upon creation this object binds to specified TCP ports and listens for incoming TCP connections on dedicated thread. Each connection is accepted and dedicated thread is created. Then that thread is used to call process() method of next MCC in chain. That method is passed payload implementing PayloadStreamInterface. On response payload with PayloadRawInterface is expected. Alternatively called MCC may use provided PayloadStreamInterface to send it's response back directly. During processing of request this MCC generates following attributes: TCP:HOST - IP address of interface to which local TCP socket is bound TCP:PORT - port number to which local TCP socket is bound TCP:REMOTEHOST - IP address from which connection is accepted TCP:REMOTEPORT - TCP port from which connection is accepted TCP:ENDPOINT - URL-like representation of remote connection - `://HOST:PORT` ENDPOINT - global attribute equal to TCP:ENDPOINT

5.59.2 Constructor & Destructor Documentation

5.59.2.1 ArcMCCTCP::MCC_TCP_Service::MCC_TCP_Service (Config *cfg, PluginArgument *parg)

executing function for connection thread


The documentation for this class was generated from the following file:

- MCCTCP.h

5.60 ArcMCCTLS::MCC_TLS Class Reference

A base class for TLS client and service MCCs.

`#include <MCCTLS.h>`Inheritance diagram for ArcMCCTLS::MCC_TLS::



5.60.1 Detailed Description


A base class for TLS client and service MCCs. This is a base class for TLS client and service MCCs. It provides some common functionality for them.

The documentation for this class was generated from the following file:

- MCCTLS.h

5.61 ArcMCCTLS::MCC_TLS_Client Class Reference

`#include <MCCTLS.h>`Inheritance diagram for ArcMCCTLS::MCC_TLS_Client::



5.61.1 Detailed Description


This class is MCC implementing TLS client.

The documentation for this class was generated from the following file:

- MCCTLS.h

5.62 ArcMCCTLS::MCC_TLS_Service Class Reference

#include <MCCTLS.h> Inheritance diagram for ArcMCCTLS::MCC_TLS_Service::



5.62.1 Detailed Description

This MCC implements TLS server side functionality. Upon creation this object creates SSL_CTX object and configures SSL_CTX object with some environment information about credential. Because we cannot know the "socket" when the creation of MCC_TLS_Service/MCC_TLS_Client object (not like MCC_TCP_Client, which can creat socket in the constructor method by using information in configuration file), we can only creat "ssl" object which is binded to specified "socket", when MCC_HTTP_Client calls the process() method of [MCC_TLS_Client](#) object, or MCC_TCP_Service calls the process() method of [MCC_TLS_Service](#) object. The "ssl" object is embeded in a payload called PayloadTLSSocket.

The process() method of [MCC_TLS_Service](#) is passed payload implementing PayloadStreamInterface and the method returns empty PayloadRaw payload in "outmsg". The ssl object is created and bound to Stream payload when constructing the PayloadTLSSocket in the process() method.

During processing of message this MCC generates attribute TLS:PEERDN which contains Distinguished Name of remoote peer.

The documentation for this class was generated from the following file:

- MCCTLS.h

5.63 ArcMCCGSI::PayloadGSISStream Class Reference

The documentation for this class was generated from the following file:

- PayloadGSISStream.h

5.64 ArcMCCHTTP::PayloadHTTP Class Reference

```
#include <PayloadHTTP.h>
```

Public Member Functions

- [PayloadHTTP](#) (PayloadStreamInterface &stream, bool own=false)
- [PayloadHTTP](#) (const std::string &method, const std::string &url, PayloadStreamInterface &stream)
- [PayloadHTTP](#) (const std::string &method, const std::string &url)
- [PayloadHTTP](#) (int code, const std::string &reason, PayloadStreamInterface &stream, bool head_response=false)
- [PayloadHTTP](#) (int code, const std::string &reason, bool head_response=false)
- virtual const std::string & [Attribute](#) (const std::string &name)
- virtual const std::multimap< std::string, std::string > & [Attributes](#) (void)
- virtual void [Attribute](#) (const std::string &name, const std::string &value)
- virtual bool [Flush](#) (void)
- virtual void [Body](#) (PayloadRawInterface &body, bool ownership=true)

Protected Member Functions

- bool [readline](#) (std::string &line)
- bool [read](#) (char *buf, int64_t &size)
- bool [read_header](#) (void)
- bool [get_body](#) (void)

Protected Attributes

- PayloadStreamInterface * [stream_](#)
- bool [stream_own_](#)
- PayloadRawInterface * [rbody_](#)
- PayloadStreamInterface * [sbody_](#)
- bool [body_own_](#)
- std::string [uri_](#)
- int [version_major_](#)
- int [version_minor_](#)
- std::string [method_](#)
- int [code_](#)
- std::string [reason_](#)
- int64_t [length_](#)
- int64_t [end_](#)
- chunked_t [chunked_](#)
- int64_t [chunk_size_](#)
- std::multimap< std::string, std::string > [attributes_](#)

5.64.1 Detailed Description

This class implements parsing and generation of HTTP messages. It implements only subset of HTTP/1.1 and also provides an PayloadRawInterface for including as payload into Message passed through MCC chains.

5.64.2 Constructor & Destructor Documentation

5.64.2.1 ArcMCCHTTP::PayloadHTTP::PayloadHTTP (PayloadStreamInterface & *stream*, bool *own* = false)

Constructor - creates object by parsing HTTP request or response from stream. Supplied stream is associated with object for later use. If *own* is set to true then stream will be deleted in destructor. Because stream can be used by this object during whole lifetime it is important not to destroy stream till this object is deleted.

5.64.2.2 ArcMCCHTTP::PayloadHTTP::PayloadHTTP (const std::string & *method*, const std::string & *url*, PayloadStreamInterface & *stream*)

Constructor - creates HTTP request to be sent through stream. HTTP message is not sent yet.

5.64.2.3 ArcMCCHTTP::PayloadHTTP::PayloadHTTP (const std::string & *method*, const std::string & *url*)

Constructor - creates HTTP request to be rendered through Raw interface.

5.64.2.4 ArcMCCHTTP::PayloadHTTP::PayloadHTTP (int *code*, const std::string & *reason*, PayloadStreamInterface & *stream*, bool *head_response* = false)

Constructor - creates HTTP response to be sent through stream. HTTP message is not sent yet.

5.64.2.5 ArcMCCHTTP::PayloadHTTP::PayloadHTTP (int *code*, const std::string & *reason*, bool *head_response* = false)

Constructor - creates HTTP response to be rendered through Raw interface.

5.64.3 Member Function Documentation

5.64.3.1 virtual void ArcMCCHTTP::PayloadHTTP::Attribute (const std::string & *name*, const std::string & *value*) [virtual]

Adds HTTP header attribute 'name' = 'value'

5.64.3.2 virtual const std::string& ArcMCCHTTP::PayloadHTTP::Attribute (const std::string & *name*) [virtual]

Returns HTTP header attribute with specified name. Empty string if no such attribute.

5.64.3.3 virtual const std::multimap<std::string, std::string>& ArcMCCHTTP::PayloadHTTP::Attributes (void) [virtual]

Returns all HTTP header attributes.

5.64.3.4 **virtual void ArcMCCHTTP::PayloadHTTP::Body (PayloadRawInterface & *body*, bool *ownership* = true) [virtual]**

Assign HTTP body. Assigned object is not copied. Instead it is remembered and made available through Raw interface. If 'ownership' is true then passed object is treated as being owned by this instance and destroyed in destructor.

5.64.3.5 **virtual bool ArcMCCHTTP::PayloadHTTP::Flush (void) [virtual]**

Send created object through associated stream. If there is no stream associated then HTTP specific data is inserted into Raw buffers of this object. In last case this operation should not be repeated till content of buffer is completely rewritten.

5.64.3.6 **bool ArcMCCHTTP::PayloadHTTP::get_body (void) [protected]**

Read Body of HTTP message and attach it to inherited PayloadRaw object

5.64.3.7 **bool ArcMCCHTTP::PayloadHTTP::read (char * *buf*, int64_t & *size*) [protected]**

Read up to 'size' bytes from stream_

5.64.3.8 **bool ArcMCCHTTP::PayloadHTTP::read_header (void) [protected]**

Read HTTP header and fill internal variables

5.64.3.9 **bool ArcMCCHTTP::PayloadHTTP::readline (std::string & *line*) [protected]**

Read from stream till

5.64.4 **Field Documentation**

5.64.4.1 **std::multimap<std::string, std::string> ArcMCCHTTP::PayloadHTTP::attributes_ [protected]**

true if connection should not be closed after response

5.64.4.2 **bool ArcMCCHTTP::PayloadHTTP::body_own_ [protected]**

associated HTTP Body stream if any (to avoid copying to own buffer)

5.64.4.3 **int64_t ArcMCCHTTP::PayloadHTTP::chunk_size_ [protected]**

chunked encoding parsing state

5.64.4.4 **chunked_t ArcMCCHTTP::PayloadHTTP::chunked_ [protected]**

Logical end of content computed from Content-Range

5.64.4.5 int ArcMCCHTTP::PayloadHTTP::code_ [protected]

HTTP method being used or requested

5.64.4.6 int64_t ArcMCCHTTP::PayloadHTTP::end_ [protected]

Content-length of HTTP message

5.64.4.7 int64_t ArcMCCHTTP::PayloadHTTP::length_ [protected]

HTTP reason being sent or supplied

5.64.4.8 std::string ArcMCCHTTP::PayloadHTTP::method_ [protected]

minor number of HTTP version - must be 0 or 1

5.64.4.9 PayloadRawInterface* ArcMCCHTTP::PayloadHTTP::rbody_ [protected]

if true stream_ is owned by this

5.64.4.10 std::string ArcMCCHTTP::PayloadHTTP::reason_ [protected]

HTTP code being sent or supplied

5.64.4.11 PayloadStreamInterface* ArcMCCHTTP::PayloadHTTP::sbody_ [protected]

associated HTTP Body buffer if any (to avoid copying to own buffer)

5.64.4.12 PayloadStreamInterface* ArcMCCHTTP::PayloadHTTP::stream_ [protected]

true if whole content of HTTP body was fetched and stored in buffers. Otherwise only header was fetched and part of body in tbuf_ and rest is to be read through stream_.

5.64.4.13 bool ArcMCCHTTP::PayloadHTTP::stream_own_ [protected]

stream used to communicate to outside

5.64.4.14 std::string ArcMCCHTTP::PayloadHTTP::uri_ [protected]

if true body_ is owned by this

5.64.4.15 int ArcMCCHTTP::PayloadHTTP::version_major_ [protected]

URI being contacted

5.64.4.16 int ArcMCCHTTP::PayloadHTTP::version_minor_ [protected]

major number of HTTP version - must be 1

The documentation for this class was generated from the following file:

- PayloadHTTP.h

5.65 ArcMCCTCP::PayloadTCPSocket Class Reference

```
#include <PayloadTCPSocket.h>
```

Public Member Functions

- [PayloadTCPSocket](#) (const char *hostname, int port, int timeout, Logger &logger)
- [PayloadTCPSocket](#) (const std::string &endpoint, int timeout, Logger &logger)
- [PayloadTCPSocket](#) (int s, int timeout, Logger &logger)
- [PayloadTCPSocket](#) ([PayloadTCPSocket](#) &s)
- [PayloadTCPSocket](#) ([PayloadTCPSocket](#) &s, Logger &logger)

5.65.1 Detailed Description

This class extends PayloadStream with TCP socket specific features

5.65.2 Constructor & Destructor Documentation

5.65.2.1 ArcMCCTCP::PayloadTCPSocket::PayloadTCPSocket (const char * *hostname*, int *port*, int *timeout*, Logger & *logger*)

Constructor - connects to TCP server at specified hostname:port

5.65.2.2 ArcMCCTCP::PayloadTCPSocket::PayloadTCPSocket (const std::string & *endpoint*, int *timeout*, Logger & *logger*)

Constructor - connects to TCP server at specified endpoint - hostname:port

5.65.2.3 ArcMCCTCP::PayloadTCPSocket::PayloadTCPSocket (int *s*, int *timeout*, Logger & *logger*) [inline]

Constructor - creates object of already connected socket. Socket is NOT closed in destructor.

5.65.2.4 ArcMCCTCP::PayloadTCPSocket::PayloadTCPSocket (PayloadTCPSocket & *s*) [inline]

Copy constructor - inherits socket of copied object. Socket is NOT closed in destructor.

5.65.2.5 ArcMCCTCP::PayloadTCPSocket::PayloadTCPSocket (PayloadTCPSocket & *s*, Logger & *logger*) [inline]


Copy constructor - inherits handle of copied object. Handle is NOT closed in destructor.

The documentation for this class was generated from the following file:

- PayloadTCPSocket.h

5.66 ArcMCCTLS::PayloadTLMCC Class Reference

Inheritance diagram for ArcMCCTLS::PayloadTLMCC::



Public Member Functions

- [PayloadTLMCC](#) (MCCInterface *mcc, const [ConfigTLMCC](#) &cfg, Logger &logger)
- [PayloadTLMCC](#) (PayloadStreamInterface *stream, const [ConfigTLMCC](#) &cfg, Logger &logger)
- [PayloadTLMCC](#) ([PayloadTLMCC](#) &stream)

5.66.1 Constructor & Destructor Documentation

5.66.1.1 ArcMCCTLS::PayloadTLMCC::PayloadTLMCC (MCCInterface * *mcc*, const [ConfigTLMCC](#) & *cfg*, Logger & *logger*)

Constructor - creates ssl object which is bound to next MCC. This instance must be used on client side. It obtains Stream interface from next MCC dynamically.

5.66.1.2 ArcMCCTLS::PayloadTLMCC::PayloadTLMCC (PayloadStreamInterface * *stream*, const [ConfigTLMCC](#) & *cfg*, Logger & *logger*)

Constructor - creates ssl object which is bound to stream. This constructor to be used on server side. Provided stream is NOT destroyed in destructor.

5.66.1.3 ArcMCCTLS::PayloadTLMCC::PayloadTLMCC ([PayloadTLMCC](#) & *stream*)


Copy constructor with new logger. Created object shares same SSL objects but does not destroy them in destructor. Main instance must be destroyed after all copied ones.

The documentation for this class was generated from the following file:

- [PayloadTLMCC.h](#)

5.67 ArcMCCTLS::PayloadTLSStream Class Reference

#include <PayloadTLSStream.h> Inheritance diagram for ArcMCCTLS::PayloadTLSStream::



Public Member Functions

- [PayloadTLSStream](#) (Logger & logger, SSL *ssl=NULL)
- virtual [~PayloadTLSStream](#) (void)
- X509 * [GetPeerCert](#) (void)
- [STACK_OF](#) (X509)*GetPeerChain(void)
- X509 * [GetCert](#) (void)

Protected Attributes

- SSL * [ssl_](#)

5.67.1 Detailed Description

Implementation of PayloadStreamInterface for SSL handle.

5.67.2 Constructor & Destructor Documentation

5.67.2.1 ArcMCCTLS::PayloadTLSStream::PayloadTLSStream (Logger & *logger*, SSL * *ssl* = NULL)

Constructor. Attaches to already open handle. Handle is not managed by this class and must be closed by external code.

5.67.2.2 virtual ArcMCCTLS::PayloadTLSStream::~~PayloadTLSStream (void) [virtual]

Destructor.

5.67.3 Member Function Documentation

5.67.3.1 X509* ArcMCCTLS::PayloadTLSStream::GetCert (void)

Get local certificate from associated ssl. Obtained X509 object is owned by this instance and becomes invalid after destruction.

5.67.3.2 X509* ArcMCCTLS::PayloadTLSStream::GetPeerCert (void)

Get peer certificate from the established ssl. Obtained X509 object is owned by this instance and becomes invalid after destruction. Still obtained has to be freed at end of usage.

5.67.3.3 ArcMCCTLS::PayloadTLSStream::STACK_OF (X509)

Get chain of peer certificates from the established ssl. Obtained X509 object is owned by this instance and becomes invalid after destruction.

5.67.4 Field Documentation

5.67.4.1 SSL* ArcMCCTLS::PayloadTLSStream::ssl_ [protected]

Timeout for read/write operations

The documentation for this class was generated from the following file:

- PayloadTLSStream.h

5.68 ArcSec::PDPServiceInvoker Class Reference

[PDPServiceInvoker](#) - client which will invoke pdpservice.

```
#include <PDPServiceInvoker.h>
```

5.68.1 Detailed Description

[PDPServiceInvoker](#) - client which will invoke pdpservice.

The documentation for this class was generated from the following file:

- PDPServiceInvoker.h

5.69 ArcSec::SAML2SSO_AssertionConsumerSH Class Reference

Implement the functionality of the Service Provider in SAML2 SSO profile.

```
#include <SAML2SSO_AssertionConsumerSH.h>
```

5.69.1 Detailed Description

Implement the functionality of the Service Provider in SAML2 SSO profile.

The documentation for this class was generated from the following file:

- SAML2SSO_AssertionConsumerSH.h

5.70 ArcSec::SAMLTokenSH Class Reference

Adds WS-Security SAML Token into SOAP Header.

```
#include <SAMLTokenSH.h>
```

5.70.1 Detailed Description

Adds WS-Security SAML Token into SOAP Header.

The documentation for this class was generated from the following file:

- SAMLTokenSH.h

5.71 ArcSec::SimpleListPDP Class Reference

Tests X509 subject against list of subjects in file.

```
#include <SimpleListPDP.h>
```

5.71.1 Detailed Description

Tests X509 subject against list of subjects in file. This class implements PDP interface. It's isPermitted() method compares X509 subject of requestor obtained from TLS layer (TLS:PEERDN) to list of subjects (one per line) in external file. Location of file is defined by 'location' attribute of PDP configuration. Returns true if subject is present in list, otherwise false.

The documentation for this class was generated from the following file:

- SimpleListPDP.h


5.72 ArcSHCLegacy::SimpleMap Class Reference

The documentation for this class was generated from the following file:

- simplemap.h

5.73 Arc::SRM1Client Class Reference

Inheritance diagram for Arc::SRM1Client::



Public Member Functions

- SRMReturnCode [ping](#) (std::string &, bool=true)
- SRMReturnCode [getSpaceTokens](#) (std::list< std::string > &, const std::string &= "")
- SRMReturnCode [getRequestTokens](#) (std::list< std::string > &, const std::string &= "")
- SRMReturnCode [requestBringOnline](#) (SRMClientRequest &)
- SRMReturnCode [requestBringOnlineStatus](#) (SRMClientRequest &)
- SRMReturnCode [mkDir](#) (SRMClientRequest &)
- SRMReturnCode [checkPermissions](#) (SRMClientRequest &)
- SRMReturnCode [getTURLs](#) (SRMClientRequest &req, std::list< std::string > &urls)
- SRMReturnCode [getTURLsStatus](#) (SRMClientRequest &req, std::list< std::string > &urls)
- SRMReturnCode [putTURLs](#) (SRMClientRequest &req, std::list< std::string > &urls)
- SRMReturnCode [putTURLsStatus](#) (SRMClientRequest &req, std::list< std::string > &urls)
- SRMReturnCode [releaseGet](#) (SRMClientRequest &req)
- SRMReturnCode [releasePut](#) (SRMClientRequest &req)
- SRMReturnCode [release](#) (SRMClientRequest &req)
- SRMReturnCode [abort](#) (SRMClientRequest &req)
- SRMReturnCode [info](#) (SRMClientRequest &req, std::map< std::string, std::list< struct [SRMFileMetaData](#) > > &metadata)
- SRMReturnCode [info](#) (SRMClientRequest &req, std::list< struct [SRMFileMetaData](#) > &metadata)
- SRMReturnCode [remove](#) (SRMClientRequest &req)
- SRMReturnCode [copy](#) (SRMClientRequest &req, const std::string &source)

5.73.1 Member Function Documentation

5.73.1.1 SRMReturnCode Arc::SRM1Client::abort (SRMClientRequest &req) [virtual]

Called in the case of failure during transfer or releasePut. Releases all TURLs involved in the transfer.

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.2 SRMReturnCode Arc::SRM1Client::checkPermissions (SRMClientRequest & *req*) [inline, virtual]

Check permissions for the SURL in the request using the current credentials. *req* The request object

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.3 SRMReturnCode Arc::SRM1Client::copy (SRMClientRequest & *req*, const std::string & *source*) [virtual]

Copy a file between two SRM storages.

Parameters:

req The request object

source The source SURL

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.4 SRMReturnCode Arc::SRM1Client::getRequestTokens (std::list< std::string > & *tokens*, const std::string & *description* = "") [inline, virtual]

Returns a list of request tokens for the user calling the method which are still active requests, or the tokens corresponding to the token description, if given.

Parameters:

tokens The list filled by the service

description The user request description, which can be specified when the request is created

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.5 SRMReturnCode Arc::SRM1Client::getSpaceTokens (std::list< std::string > & *tokens*, const std::string & *description* = "") [inline, virtual]

Find the space tokens available to write to which correspond to the space token description, if given. The list of tokens is a list of numbers referring to the SRM internal definition of the spaces, not user-readable strings.

Parameters:

tokens The list filled by the service

description The space token description

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.6 SRMReturnCode Arc::SRM1Client::getTURLs (SRMClientRequest & req, std::list< std::string > & urls) [virtual]

If the user wishes to copy a file from somewhere, [getTURLs\(\)](#) is called to retrieve the transport URL(s) to copy the file from. It may be used synchronously or asynchronously, depending on the synchronous property of the request object. In the former case it will block until the TURLs are ready, in the latter case it will return after making the request and [getTURLsStatus\(\)](#) must be used to poll the request status if it was not completed.

Parameters:

req The request object

urls A list of TURLs filled by the method

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.7 SRMReturnCode Arc::SRM1Client::getTURLsStatus (SRMClientRequest & req, std::list< std::string > & urls) [inline, virtual]

In the case where [getTURLs](#) was called asynchronously and the request was not completed, this method should be called to poll the status of the request. [getTURLs](#) must be called before this method and the request object must have ongoing request status.

Parameters:

req The request object. Status must be ongoing.

urls A list of TURLs filled by the method if the request completed successfully

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.8 SRMReturnCode Arc::SRM1Client::info (SRMClientRequest & req, std::list< struct SRMFileMetaData > & metadata) [virtual]

Returns information on a file stored in an SRM, such as file size, checksum and estimated access latency. If a directory is listed with recursion ≥ 1 then the list in metadata will contain the content of the directory.

Parameters:

req The request object
metadata A list of structs filled with file information.

Returns:

SRMReturnCode specifying outcome of operation

See also:

[SRMFileMetaData](#)

Implements [Arc::SRMClient](#).

5.73.1.9 SRMReturnCode Arc::SRM1Client::info (SRMClientRequest & req, std::map< std::string, std::list< struct SRMFileMetaData > > & metadata) [virtual]

Returns information on a file or files (v2.2 and higher) stored in SRM, such as file size, checksum and estimated access latency. If a directory or directories is listed with recursion ≥ 1 then the list mapped to each SURL in metadata will contain the content of the directory or directories.

Parameters:

req The request object
metadata A map mapping each SURL in the request to a list of structs filled with file information. If a SURL is missing from the map it means there was some problem accessing it.

Returns:

SRMReturnCode specifying outcome of operation

See also:

[SRMFileMetaData](#)

Implements [Arc::SRMClient](#).

5.73.1.10 SRMReturnCode Arc::SRM1Client::mkDir (SRMClientRequest & req) [inline, virtual]

Make required directories for the SURL in the request

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.11 SRMReturnCode Arc::SRM1Client::ping (std::string & *version*, bool *report_error* = true) [inline, virtual]

Find out the version supported by the server this client is connected to. Since this method is used to determine which client version to instantiate, we may not want to report an error to the user, so setting *report_error* to false suppresses the error message.

Parameters:

version The version returned by the server
report_error Whether an error should be reported

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.12 SRMReturnCode Arc::SRM1Client::putURLs (SRMClientRequest & *req*, std::list< std::string > & *urls*) [virtual]

If the user wishes to copy a file to somewhere, [putURLs\(\)](#) is called to retrieve the transport URL(s) to copy the file to. It may be used synchronously or asynchronously, depending on the synchronous property of the request object. In the former case it will block until the TURLs are ready, in the latter case it will return after making the request and [putURLsStatus\(\)](#) must be used to poll the request status if it was not completed.

Parameters:

req The request object
urls A list of TURLs filled by the method

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.13 SRMReturnCode Arc::SRM1Client::putURLsStatus (SRMClientRequest & *req*, std::list< std::string > & *urls*) [inline, virtual]

In the case where [putURLs](#) was called asynchronously and the request was not completed, this method should be called to poll the status of the request. [putURLs](#) must be called before this method and the request object must have ongoing request status.

Parameters:

req The request object. Status must be ongoing.
urls A list of TURLs filled by the method if the request completed successfully

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.14 SRMReturnCode Arc::SRM1Client::release (SRMClientRequest & *req*) [virtual]

Used in SRM v1 only. Called to release files after successful transfer.

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.15 SRMReturnCode Arc::SRM1Client::releaseGet (SRMClientRequest & *req*) [virtual]

Should be called after a successful copy from SRM storage.

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.16 SRMReturnCode Arc::SRM1Client::releasePut (SRMClientRequest & *req*) [virtual]

Should be called after a successful copy to SRM storage.

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.17 SRMReturnCode Arc::SRM1Client::remove (SRMClientRequest & *req*) [virtual]

Delete a file physically from storage and the SRM namespace.

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.18 SRMReturnCode Arc::SRM1Client::requestBringOnline (SRMClientRequest & *req*) [inline, virtual]

Submit a request to bring online files. If the synchronous property of the request object is false, this operation is asynchronous and the status of the request can be checked by calling [requestBringOnlineStatus\(\)](#) with the request token in *req* which is assigned by this method. If the request is synchronous, this operation blocks until the file(s) are online or the timeout specified in the [SRMClient](#) constructor has passed.

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implements [Arc::SRMClient](#).

5.73.1.19 SRMReturnCode Arc::SRM1Client::requestBringOnlineStatus (SRMClientRequest & *req*) [inline, virtual]

Query the status of a request to bring files online. The URLs map of the request object is updated if the status of any files in the request has changed. [requestBringOnline\(\)](#) but be called before this method.

Parameters:

req The request object to query the status of

Returns:

SRMReturnCode specifying outcome of operation


Implements [Arc::SRMClient](#).

The documentation for this class was generated from the following file:

- SRM1Client.h

5.74 Arc::SRM22Client Class Reference

Inheritance diagram for Arc::SRM22Client::



Public Member Functions

- [SRM22Client](#) (const UserConfig &usercfg, const [SRMURL](#) &url)
- [~SRM22Client](#) ()
- SRMReturnCode [ping](#) (std::string &version, bool report_error=true)
- SRMReturnCode [getSpaceTokens](#) (std::list< std::string > &tokens, const std::string &description="")
- SRMReturnCode [getRequestTokens](#) (std::list< std::string > &tokens, const std::string &description="")
- SRMReturnCode [getTURLs](#) (SRMClientRequest &req, std::list< std::string > &urls)
- SRMReturnCode [getTURLsStatus](#) (SRMClientRequest &req, std::list< std::string > &urls)
- SRMReturnCode [putTURLs](#) (SRMClientRequest &req, std::list< std::string > &urls)
- SRMReturnCode [putTURLsStatus](#) (SRMClientRequest &req, std::list< std::string > &urls)
- SRMReturnCode [requestBringOnline](#) (SRMClientRequest &req)
- SRMReturnCode [requestBringOnlineStatus](#) (SRMClientRequest &req)
- SRMReturnCode [info](#) (SRMClientRequest &req, std::map< std::string, std::list< struct [SRMFileMetaData](#) > > &metadata)
- SRMReturnCode [info](#) (SRMClientRequest &req, std::list< struct [SRMFileMetaData](#) > &metadata)
- SRMReturnCode [releaseGet](#) (SRMClientRequest &req)
- SRMReturnCode [releasePut](#) (SRMClientRequest &req)
- SRMReturnCode [release](#) (SRMClientRequest &)
- SRMReturnCode [abort](#) (SRMClientRequest &req)
- SRMReturnCode [remove](#) (SRMClientRequest &req)
- SRMReturnCode [copy](#) (SRMClientRequest &req, const std::string &source)
- SRMReturnCode [mkDir](#) (SRMClientRequest &req)
- SRMReturnCode [checkPermissions](#) (SRMClientRequest &req)

5.74.1 Constructor & Destructor Documentation

5.74.1.1 Arc::SRM22Client::SRM22Client (const UserConfig & usercfg, const SRMURL & url)

Constructor

5.74.1.2 Arc::SRM22Client::~~SRM22Client ()

Destructor

5.74.2 Member Function Documentation

5.74.2.1 SRMReturnCode Arc::SRM22Client::abort (SRMClientRequest & *req*) [virtual]

Abort request. Called after any failure in the data transfer or putDone calls

Implements [Arc::SRMClient](#).

5.74.2.2 SRMReturnCode Arc::SRM22Client::checkPermissions (SRMClientRequest & *req*) [virtual]

Call srmCheckPermission

Implements [Arc::SRMClient](#).

5.74.2.3 SRMReturnCode Arc::SRM22Client::copy (SRMClientRequest & *req*, const std::string & *source*) [virtual]

Implemented in pull mode, ie the endpoint defined in the request object performs the copy.

Implements [Arc::SRMClient](#).

5.74.2.4 SRMReturnCode Arc::SRM22Client::getRequestTokens (std::list< std::string > & *tokens*, const std::string & *description* = "") [virtual]

Use srmGetRequestTokens to return a list of spaces available

Implements [Arc::SRMClient](#).

5.74.2.5 SRMReturnCode Arc::SRM22Client::getSpaceTokens (std::list< std::string > & *tokens*, const std::string & *description* = "") [virtual]

Use srmGetSpaceTokens to return a list of spaces available

Implements [Arc::SRMClient](#).

5.74.2.6 SRMReturnCode Arc::SRM22Client::getTURLs (SRMClientRequest & *req*, std::list< std::string > & *urls*) [virtual]

Get a list of TURLs for the given SURL. Uses srmPrepareToGet and waits until file is ready (online and pinned) if the request is synchronous. If not it returns after making the request. Although a list is returned, SRMv2.2 only returns one TURL per SURL.

Implements [Arc::SRMClient](#).

5.74.2.7 SRMReturnCode Arc::SRM22Client::getTURLsStatus (SRMClientRequest & *req*, std::list< std::string > & *urls*) [virtual]

Uses srmStatusOfGetRequest to query the status of the given request.

Implements [Arc::SRMClient](#).

5.74.2.8 SRMReturnCode Arc::SRM22Client::info (SRMClientRequest & req, std::list< struct SRMFileMetaData > & metadata) [virtual]

Use srmLs to get info on the given SURL. Info on each file or content of directory is put in a list of metadata structs

Implements [Arc::SRMClient](#).

5.74.2.9 SRMReturnCode Arc::SRM22Client::info (SRMClientRequest & req, std::map< std::string, std::list< struct SRMFileMetaData > > & metadata) [virtual]

Use srmLs to get info on the given SURLs. Info on each file or content of directory is put in a list of metadata structs.

Implements [Arc::SRMClient](#).

5.74.2.10 SRMReturnCode Arc::SRM22Client::mkDir (SRMClientRequest & req) [virtual]

Call srmMkDir

Implements [Arc::SRMClient](#).

5.74.2.11 SRMReturnCode Arc::SRM22Client::ping (std::string & version, bool report_error = true) [virtual]

Get the server version from srmPing

Implements [Arc::SRMClient](#).

5.74.2.12 SRMReturnCode Arc::SRM22Client::putTURLs (SRMClientRequest & req, std::list< std::string > & urls) [virtual]

Retrieve TURLs which a file can be written to. Uses srmPrepareToPut and waits until a suitable TURL has been assigned if the request is synchronous. If not it returns after making the request. Although a list is returned, SRMv2.2 only returns one TURL per SURL.

Implements [Arc::SRMClient](#).

5.74.2.13 SRMReturnCode Arc::SRM22Client::putTURLsStatus (SRMClientRequest & req, std::list< std::string > & urls) [virtual]

Uses srmStatusOfPutRequest to query the status of the given request.

Implements [Arc::SRMClient](#).

5.74.2.14 SRMReturnCode Arc::SRM22Client::release (SRMClientRequest &) [inline, virtual]

Not used in this version of SRM

Implements [Arc::SRMClient](#).

**5.74.2.15 SRMReturnCode Arc::SRM22Client::releaseGet (SRMClientRequest & *req*)
[virtual]**

Release files that have been pinned by srmPrepareToGet using srmReleaseFiles. Called after successful file transfer or failed prepareToGet.

Implements [Arc::SRMClient](#).

**5.74.2.16 SRMReturnCode Arc::SRM22Client::releasePut (SRMClientRequest & *req*)
[virtual]**

Mark a put request as finished. Called after successful file transfer or failed prepareToPut.

Implements [Arc::SRMClient](#).

5.74.2.17 SRMReturnCode Arc::SRM22Client::remove (SRMClientRequest & *req*) [virtual]

Delete by srmRm or srmRmDir

Implements [Arc::SRMClient](#).

**5.74.2.18 SRMReturnCode Arc::SRM22Client::requestBringOnline (SRMClientRequest & *req*)
[virtual]**

Call srmBringOnline with the URLs specified in req.

Implements [Arc::SRMClient](#).

5.74.2.19 SRMReturnCode Arc::SRM22Client::requestBringOnlineStatus (SRMClientRequest & *req*) [virtual]

Call srmStatusOfBringOnlineRequest and update req with any changes.


Implements [Arc::SRMClient](#).

The documentation for this class was generated from the following file:

- SRM22Client.h

5.75 Arc::SRMClient Class Reference

#include <SRMClient.h> Inheritance diagram for Arc::SRMClient::



Public Member Functions

- virtual `~SRMClient()`
- `std::string getVersion() const`
- virtual `SRMReturnCode ping(std::string &version, bool report_error=true)=0`
- virtual `SRMReturnCode getSpaceTokens(std::list< std::string > &tokens, const std::string &description="")=0`
- virtual `SRMReturnCode getRequestTokens(std::list< std::string > &tokens, const std::string &description="")=0`
- virtual `SRMReturnCode getURLs(SRMClientRequest &req, std::list< std::string > &urls)=0`
- virtual `SRMReturnCode getURLsStatus(SRMClientRequest &req, std::list< std::string > &urls)=0`
- virtual `SRMReturnCode requestBringOnline(SRMClientRequest &req)=0`
- virtual `SRMReturnCode requestBringOnlineStatus(SRMClientRequest &req)=0`
- virtual `SRMReturnCode putURLs(SRMClientRequest &req, std::list< std::string > &urls)=0`
- virtual `SRMReturnCode putURLsStatus(SRMClientRequest &req, std::list< std::string > &urls)=0`
- virtual `SRMReturnCode releaseGet(SRMClientRequest &req)=0`
- virtual `SRMReturnCode releasePut(SRMClientRequest &req)=0`
- virtual `SRMReturnCode release(SRMClientRequest &req)=0`
- virtual `SRMReturnCode abort(SRMClientRequest &req)=0`
- virtual `SRMReturnCode info(SRMClientRequest &req, std::map< std::string, std::list< struct SRMFileMetaData > > &metadata)=0`
- virtual `SRMReturnCode info(SRMClientRequest &req, std::list< struct SRMFileMetaData > &metadata)=0`
- virtual `SRMReturnCode remove(SRMClientRequest &req)=0`
- virtual `SRMReturnCode copy(SRMClientRequest &req, const std::string &source)=0`
- virtual `SRMReturnCode mkDir(SRMClientRequest &req)=0`
- virtual `SRMReturnCode checkPermissions(SRMClientRequest &req)=0`

Static Public Member Functions

- static `SRMClient * getInstance(const UserConfig &usercfg, const std::string &url, bool &timedout)`

Protected Member Functions

- `SRMClient(const UserConfig &usercfg, const SRMURL &url)`
- `SRMReturnCode process(const std::string &action, PayloadSOAP *request, PayloadSOAP **response)`

Protected Attributes

- std::string [service_endpoint](#)
- MCCCConfig [cfg](#)
- ClientSOAP * [client](#)
- NS [ns](#)
- SRMImplementation [implementation](#)
- time_t [user_timeout](#)
- std::string [version](#)

Static Protected Attributes

- static Logger [logger](#)

5.75.1 Detailed Description

A client interface to the SRM protocol. Instances of SRM clients are created by calling the [getInstance\(\)](#) factory method. One client instance can be used to make many requests to the same server (with the same protocol version), but not multiple servers.

5.75.2 Constructor & Destructor Documentation

5.75.2.1 virtual Arc::SRMClient::~~SRMClient () [virtual]

Destructor

5.75.3 Member Function Documentation

5.75.3.1 virtual SRMReturnCode Arc::SRMClient::abort (SRMClientRequest & *req*) [pure virtual]

Called in the case of failure during transfer or releasePut. Releases all TURLs involved in the transfer.

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.2 virtual SRMReturnCode Arc::SRMClient::checkPermissions (SRMClientRequest & *req*) [pure virtual]

Check permissions for the SURL in the request using the current credentials. *req* The request object

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.3 virtual SRMReturnCode Arc::SRMClient::copy (SRMClientRequest & *req*, const std::string & *source*) [pure virtual]

Copy a file between two SRM storages.

Parameters:

req The request object
source The source URL

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.4 static SRMClient* Arc::SRMClient::getInstance (const UserConfig & *usercfg*, const std::string & *url*, bool & *timedout*) [static]

Create an [SRMClient](#) instance. The instance will be a SRM v2.2 client unless another version is explicitly given in the url.

Parameters:

usercfg The user configuration.
url A URL. A client connects to the service host derived from this URL. All operations with a client instance must use URLs with the same host as this one.
timedout Whether the connection timed out

Returns:

A pointer to an instance of [SRMClient](#) is returned, or NULL if it was not possible to create one.

5.75.3.5 virtual SRMReturnCode Arc::SRMClient::getRequestTokens (std::list< std::string > & *tokens*, const std::string & *description* = "") [pure virtual]

Returns a list of request tokens for the user calling the method which are still active requests, or the tokens corresponding to the token description, if given.

Parameters:

tokens The list filled by the service
description The user request description, which can be specified when the request is created

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.6 **virtual SRMReturnCode Arc::SRMClient::getSpaceTokens (std::list< std::string > & tokens, const std::string & description = "") [pure virtual]**

Find the space tokens available to write to which correspond to the space token description, if given. The list of tokens is a list of numbers referring to the SRM internal definition of the spaces, not user-readable strings.

Parameters:

tokens The list filled by the service
description The space token description

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.7 **virtual SRMReturnCode Arc::SRMClient::getTURLs (SRMClientRequest & req, std::list< std::string > & urls) [pure virtual]**

If the user wishes to copy a file from somewhere, [getTURLs\(\)](#) is called to retrieve the transport URL(s) to copy the file from. It may be used synchronously or asynchronously, depending on the synchronous property of the request object. In the former case it will block until the TURLs are ready, in the latter case it will return after making the request and [getTURLsStatus\(\)](#) must be used to poll the request status if it was not completed.

Parameters:

req The request object
urls A list of TURLs filled by the method

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.8 **virtual SRMReturnCode Arc::SRMClient::getTURLsStatus (SRMClientRequest & req, std::list< std::string > & urls) [pure virtual]**

In the case where [getTURLs](#) was called asynchronously and the request was not completed, this method should be called to poll the status of the request. [getTURLs](#) must be called before this method and the request object must have ongoing request status.

Parameters:

req The request object. Status must be ongoing.
urls A list of TURLs filled by the method if the request completed successfully

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.9 `std::string Arc::SRMClient::getVersion () const [inline]`

Returns the version of the SRM protocol used by this instance

References version.

5.75.3.10 `virtual SRMReturnCode Arc::SRMClient::info (SRMClientRequest & req, std::list< struct SRMFileMetaData > & metadata) [pure virtual]`

Returns information on a file stored in an SRM, such as file size, checksum and estimated access latency. If a directory is listed with recursion ≥ 1 then the list in metadata will contain the content of the directory.

Parameters:

req The request object

metadata A list of structs filled with file information.

Returns:

SRMReturnCode specifying outcome of operation

See also:

[SRMFileMetaData](#)

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.11 `virtual SRMReturnCode Arc::SRMClient::info (SRMClientRequest & req, std::map< std::string, std::list< struct SRMFileMetaData > > & metadata) [pure virtual]`

Returns information on a file or files (v2.2 and higher) stored in SRM, such as file size, checksum and estimated access latency. If a directory or directories is listed with recursion ≥ 1 then the list mapped to each SURL in metadata will contain the content of the directory or directories.

Parameters:

req The request object

metadata A map mapping each SURL in the request to a list of structs filled with file information. If a SURL is missing from the map it means there was some problem accessing it.

Returns:

SRMReturnCode specifying outcome of operation

See also:

[SRMFileMetaData](#)

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.12 `virtual SRMReturnCode Arc::SRMClient::mkDir (SRMClientRequest & req) [pure virtual]`

Make required directories for the SURL in the request

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.13 **virtual SRMReturnCode Arc::SRMClient::ping (std::string & version, bool report_error = true) [pure virtual]**

Find out the version supported by the server this client is connected to. Since this method is used to determine which client version to instantiate, we may not want to report an error to the user, so setting report_error to false suppresses the error message.

Parameters:

version The version returned by the server

report_error Whether an error should be reported

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.14 **virtual SRMReturnCode Arc::SRMClient::putURLs (SRMClientRequest & req, std::list< std::string > & urls) [pure virtual]**

If the user wishes to copy a file to somewhere, [putURLs\(\)](#) is called to retrieve the transport URL(s) to copy the file to. It may be used synchronously or asynchronously, depending on the synchronous property of the request object. In the former case it will block until the TURLs are ready, in the latter case it will return after making the request and [putURLsStatus\(\)](#) must be used to poll the request status if it was not completed.

Parameters:

req The request object

urls A list of TURLs filled by the method

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.15 **virtual SRMReturnCode Arc::SRMClient::putURLsStatus (SRMClientRequest & req, std::list< std::string > & urls) [pure virtual]**

In the case where putURLs was called asynchronously and the request was not completed, this method should be called to poll the status of the request. putURLs must be called before this method and the request object must have ongoing request status.

Parameters:

req The request object. Status must be ongoing.

urls A list of TURLs filled by the method if the request completed successfully

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.16 virtual SRMReturnCode Arc::SRMClient::release (SRMClientRequest & req) [pure virtual]

Used in SRM v1 only. Called to release files after successful transfer.

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.17 virtual SRMReturnCode Arc::SRMClient::releaseGet (SRMClientRequest & req) [pure virtual]

Should be called after a successful copy from SRM storage.

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.18 virtual SRMReturnCode Arc::SRMClient::releasePut (SRMClientRequest & req) [pure virtual]

Should be called after a successful copy to SRM storage.

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.19 **virtual SRMReturnCode Arc::SRMClient::remove (SRMClientRequest & *req*) [pure virtual]**

Delete a file physically from storage and the SRM namespace.

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.20 **virtual SRMReturnCode Arc::SRMClient::requestBringOnline (SRMClientRequest & *req*) [pure virtual]**

Submit a request to bring online files. If the synchronous property of the request object is false, this operation is asynchronous and the status of the request can be checked by calling [requestBringOnlineStatus\(\)](#) with the request token in *req* which is assigned by this method. If the request is synchronous, this operation blocks until the file(s) are online or the timeout specified in the [SRMClient](#) constructor has passed.

Parameters:

req The request object

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.3.21 **virtual SRMReturnCode Arc::SRMClient::requestBringOnlineStatus (SRMClientRequest & *req*) [pure virtual]**

Query the status of a request to bring files online. The URLs map of the request object is updated if the status of any files in the request has changed. [requestBringOnline\(\)](#) but be called before this method.

Parameters:

req The request object to query the status of

Returns:

SRMReturnCode specifying outcome of operation

Implemented in [Arc::SRM1Client](#), and [Arc::SRM22Client](#).

5.75.4 Field Documentation

5.75.4.1 **std::string Arc::SRMClient::service_endpoint [protected]**

URL of the service endpoint, eg <http://srm.host.org:8443/srm/managerv2> All URLs passed to methods must correspond to this endpoint.

The documentation for this class was generated from the following file:

- SRMClient.h

5.76 Arc::SRMClientRequest Class Reference

Class to represent a SRM request.

```
#include <SRMClientRequest.h>
```

Public Member Functions

- [SRMClientRequest](#) (const std::list< std::string > &urls) throw (SRMInvalidRequestException)
- [SRMClientRequest](#) (const std::string &url="", const std::string &id="") throw (SRMInvalidRequestException)
- std::string [surl](#) () const
- int [waiting_time](#) () const
- void [finished_success](#) ()
- void [finished_partial_success](#) ()
- void [finished_error](#) ()
- void [finished_abort](#) ()
- void [wait](#) (int t=0)
- void [cancelled](#) ()
- SRMRequestStatus [status](#) () const

5.76.1 Detailed Description

Class to represent a SRM request. It may be used for multiple operations, for example calling getTURLs() sets the request token in the request object (for a v2.2 client) and then same object is passed to releaseGet().

5.76.2 Constructor & Destructor Documentation

5.76.2.1 Arc::SRMClientRequest::SRMClientRequest (const std::list< std::string > &urls) throw (SRMInvalidRequestException) [inline]

Creates a request object with multiple URLs. The URLs here are in the form srm://srm.host.org/path/to/file

5.76.2.2 Arc::SRMClientRequest::SRMClientRequest (const std::string &url = "", const std::string &id = "") throw (SRMInvalidRequestException) [inline]

Creates a request object with a single URL. The URL here is in the form srm://srm.host.org/path/to/file

5.76.3 Member Function Documentation

5.76.3.1 int Arc::SRMClientRequest::waiting_time () const [inline]

Get waiting time. A waiting time of zero means no estimate was given by the remote service.

The documentation for this class was generated from the following file:

- SRMClientRequest.h

5.77 SRMFileInfo Class Reference

```
#include <SRMInfo.h>
```

5.77.1 Detailed Description

Info about a particular entry in the SRM info file

The documentation for this class was generated from the following file:

- SRMInfo.h

5.78 Arc::SRMFileMetaData Struct Reference

SRM-related file metadata.

```
#include <SRMClient.h>
```

5.78.1 Detailed Description

SRM-related file metadata.

The documentation for this struct was generated from the following file:

- SRMClient.h

5.79 SRMInfo Class Reference

```
#include <SRMInfo.h>
```

5.79.1 Detailed Description

Represents SRM info stored in file. A combination of host and SRM version make a unique entry.

The documentation for this class was generated from the following file:

- SRMInfo.h

5.80 Arc::SRMInvalidRequestException Class Reference

General exception to represent a bad SRM request.

```
#include <SRMClientRequest.h>
```

5.80.1 Detailed Description

General exception to represent a bad SRM request.

The documentation for this class was generated from the following file:

- SRMClientRequest.h

5.81 SRMURL Class Reference

Public Member Functions

- [SRMURL](#) (std::string url)
- const std::string & [Endpoint](#) (void) const
- void [SetSRMVersion](#) (const std::string &version)
- std::string [FileName](#) (void) const
- std::string [ContactURL](#) (void) const
- std::string [BaseURL](#) (void) const
- std::string [ShortURL](#) (void) const
- std::string [FullURL](#) (void) const
- bool [PortDefined](#) ()

5.81.1 Constructor & Destructor Documentation

5.81.1.1 SRMURL::SRMURL (std::string url)

Examples shown for functions below assume the object was initiated with
srm://srm.ndgf.org/pnfs/ndgf.org/data/atlas/disk/user/user.mlassnig.dataset.1/dummyfile3

5.81.2 Member Function Documentation

5.81.2.1 std::string SRMURL::BaseURL (void) const

eg srm://srm.ndgf.org:8443/srm/managerv2?SFN=

5.81.2.2 std::string SRMURL::ContactURL (void) const

eg http://srm.ndgf.org:8443/srm/managerv2

5.81.2.3 const std::string& SRMURL::Endpoint (void) const `[inline]`

eg /srm/managerv2

5.81.2.4 std::string SRMURL::FileName (void) const `[inline]`

eg pnfs/ndgf.org/data/atlas/disk/user/user.mlassnig.dataset.1/dummyfile3

5.81.2.5 std::string SRMURL::FullURL (void) const

eg srm://srm.ndgf.org:8443/srm/managerv2?SFN=pnfs/ndgf.org/data/atlas/disk/user/user.mlassnig.dataset.1/dummyfile3

5.81.2.6 bool SRMURL::PortDefined () `[inline]`

Was the port number given in the constructor?

5.81.2.7 void SRMURL::SetSRMVersion (const std::string & *version*)

Possible values of version are "1" and "2.2"

5.81.2.8 std::string SRMURL::ShortURL (void) const

eg srm://srm.ndgf.org:8443/pnfs/ndgf.org/data/atlas/disk/user/user.mlassnig.dataset.1/dummyfile3

The documentation for this class was generated from the following file:

- SRMURL.h

5.82 ArcSHCLegacy::UnixMap Class Reference

Data Structures

- struct **source_t**
- class **unix_user_t**

The documentation for this class was generated from the following file:

- unixmap.h

5.83 ArcSec::UsernameTokenSH Class Reference

Adds WS-Security Username Token into SOAP Header.

```
#include <UsernameTokenSH.h>
```

5.83.1 Detailed Description

Adds WS-Security Username Token into SOAP Header.

The documentation for this class was generated from the following file:

- UsernameTokenSH.h

5.84 ArcSHCLegacy::voms Struct Reference

```
#include <auth.h>
```

Data Fields

- std::string [server](#)
- std::string [voname](#)
- std::vector< [voms_attrs](#) > [attrs](#)

5.84.1 Detailed Description

VOMS data

5.84.2 Field Documentation

5.84.2.1 std::vector<voms_attrs> ArcSHCLegacy::voms::attrs

User's characteristics

5.84.2.2 std::string ArcSHCLegacy::voms::server

The VOMS server DN, as from its certificate

5.84.2.3 std::string ArcSHCLegacy::voms::voname

The name of the VO to which the VOMS belongs

The documentation for this struct was generated from the following file:

- [auth.h](#)

5.85 ArcSHCLegacy::voms_attrs Struct Reference

```
#include <auth.h>
```

Data Fields

- std::string [group](#)
- std::string [role](#)
- std::string [cap](#)

5.85.1 Detailed Description

VOMS attributes

5.85.2 Field Documentation

5.85.2.1 std::string ArcSHCLegacy::voms_attrs::cap

user's capability

5.85.2.2 std::string ArcSHCLegacy::voms_attrs::group

user's group

5.85.2.3 std::string ArcSHCLegacy::voms_attrs::role

user's role

The documentation for this struct was generated from the following file:

- [auth.h](#)

5.86 ArcSec::X509TokenSH Class Reference

Adds WS-Security X509 Token into SOAP Header.

```
#include <X509TokenSH.h>
```

5.86.1 Detailed Description

Adds WS-Security X509 Token into SOAP Header.

The documentation for this class was generated from the following file:

- X509TokenSH.h

5.87 ArcSec::XACMLAlgFactory Class Reference

Algorithm factory class for XACML.

```
#include <XACMLAlgFactory.h>
```

Public Member Functions

- virtual CombiningAlg * [createAlg](#) (const std::string &type)

5.87.1 Detailed Description

Algorithm factory class for XACML.

5.87.2 Member Function Documentation

5.87.2.1 virtual CombiningAlg* ArcSec::XACMLAlgFactory::createAlg (const std::string & type) [virtual]

return a Alg object according to the "CombiningAlg" attribute in the <Policy> node; The [XACMLAlgFactory](#) itself will release the Alg objects

The documentation for this class was generated from the following file:

- XACMLAlgFactory.h

5.88 ArcSec::XACMLApply Class Reference

The documentation for this class was generated from the following file:

- XACMLApply.h

5.89 ArcSec::XACMLAttributeFactory Class Reference

Attribute factory class for XACML specified attributes.

```
#include <XACMLAttributeFactory.h>
```

Public Member Functions

- virtual AttributeValue * [createValue](#) (const Arc::XMLNode &node, const std::string &type)

5.89.1 Detailed Description

Attribute factory class for XACML specified attributes.

5.89.2 Member Function Documentation

5.89.2.1 virtual AttributeValue* ArcSec::XACMLAttributeFactory::createValue (const Arc::XMLNode & node, const std::string & type) [virtual]

creat a AttributeValue according to the value in the XML node and the type; It should be the caller to release the AttributeValue Object

The documentation for this class was generated from the following file:

- XACMLAttributeFactory.h

5.90 ArcSec::XACMLAttributeProxy< TheAttribute > Class Template Reference

XACML specific AttributeProxy class.

```
#include <XACMLAttributeProxy.h>
```

Public Member Functions

- virtual AttributeValue * [getAttribute](#) (const Arc::XMLNode &node)

5.90.1 Detailed Description

template<class TheAttribute> class ArcSec::XACMLAttributeProxy< TheAttribute >

XACML specific AttributeProxy class.

The documentation for this class was generated from the following file:

- XACMLAttributeProxy.h

5.91 ArcSec::XACMLCondition Class Reference

[XACMLCondition](#) class to parse and operate XACML specific <Condition> node.

```
#include <XACMLCondition.h>
```

Public Member Functions

- [XACMLCondition](#) (Arc::XMLNode &node, EvaluatorContext *ctx)

5.91.1 Detailed Description

[XACMLCondition](#) class to parse and operate XACML specific <Condition> node.

5.91.2 Constructor & Destructor Documentation

5.91.2.1 ArcSec::XACMLCondition::XACMLCondition (Arc::XMLNode & *node*, EvaluatorContext * *ctx*)

Constructor -

The documentation for this class was generated from the following file:

- XACMLCondition.h

5.92 ArcSec::XACMLEvaluationCtx Class Reference

EvaluationCtx, in charge of storing some context information for evaluation, including Request, current time, etc.

```
#include <XACMLEvaluationCtx.h>
```

Public Member Functions

- [XACMLEvaluationCtx](#) (Request *request)

5.92.1 Detailed Description

EvaluationCtx, in charge of storing some context information for evaluation, including Request, current time, etc.

5.92.2 Constructor & Destructor Documentation

5.92.2.1 ArcSec::XACMLEvaluationCtx::XACMLEvaluationCtx (Request * *request*)

Construct a new EvaluationCtx based on the given request

The documentation for this class was generated from the following file:

- XACMLEvaluationCtx.h

5.93 ArcSec::XACMLEvaluator Class Reference

Execute the policy evaluation, based on the request and policy.

```
#include <XACMLEvaluator.h>
```

Public Member Functions

- virtual Response * [evaluate](#) (Request *request)

5.93.1 Detailed Description

Execute the policy evaluation, based on the request and policy.

5.93.2 Member Function Documentation

5.93.2.1 virtual Response* ArcSec::XACMLEvaluator::evaluate (Request * *request*) [**virtual**]

Evaluate the request based on the policy information inside PolicyStore

The documentation for this class was generated from the following file:

- XACMLEvaluator.h

5.94 ArcSec::XACMLFnFactory Class Reference

Function factory class for XACML specified attributes.

```
#include <XACMLFnFactory.h>
```

Public Member Functions

- virtual Function * [createFn](#) (const std::string &type)

5.94.1 Detailed Description

Function factory class for XACML specified attributes.

5.94.2 Member Function Documentation

5.94.2.1 virtual Function* ArcSec::XACMLFnFactory::createFn (const std::string & *type*) [virtual]

return a Function object according to the "Function" attribute in the XML node; The [XACMLFnFactory](#) itself will release the Function objects

The documentation for this class was generated from the following file:

- XACMLFnFactory.h

5.95 ArcSec::XACMLPDP Class Reference

[XACMLPDP](#) - PDP which can handle the XACML specific request and policy schema.

```
#include <XACMLPDP.h>
```

5.95.1 Detailed Description

[XACMLPDP](#) - PDP which can handle the XACML specific request and policy schema.

The documentation for this class was generated from the following file:

- XACMLPDP.h

5.96 ArcSec::XACMLPolicy Class Reference

[XACMLPolicy](#) class to parse and operate XACML specific <Policy> node.

```
#include <XACMLPolicy.h>
```

Public Member Functions

- [XACMLPolicy](#) (Arc::PluginArgument *parg)
- [XACMLPolicy](#) (const Arc::XMLNode node, Arc::PluginArgument *parg)
- [XACMLPolicy](#) (const Arc::XMLNode node, EvaluatorContext *ctx, Arc::PluginArgument *parg)
- virtual void [make_policy](#) ()

5.96.1 Detailed Description

[XACMLPolicy](#) class to parse and operate XACML specific <Policy> node.

5.96.2 Constructor & Destructor Documentation

5.96.2.1 ArcSec::XACMLPolicy::XACMLPolicy (Arc::PluginArgument *parg)

Constructor

5.96.2.2 ArcSec::XACMLPolicy::XACMLPolicy (const Arc::XMLNode node, Arc::PluginArgument *parg)

Constructor

5.96.2.3 ArcSec::XACMLPolicy::XACMLPolicy (const Arc::XMLNode node, EvaluatorContext *ctx, Arc::PluginArgument *parg)

Constructor -

5.96.3 Member Function Documentation

5.96.3.1 virtual void ArcSec::XACMLPolicy::make_policy () [virtual]

Parse XMLNode, and construct the low-level Rule object

The documentation for this class was generated from the following file:

- XACMLPolicy.h

5.97 ArcSec::XACMLRequest Class Reference

Public Member Functions

- virtual const char * [getEvalName](#) () const
- virtual const char * [getName](#) () const

5.97.1 Member Function Documentation

5.97.1.1 virtual const char* ArcSec::XACMLRequest::getEvalName () const [inline, virtual]

Get the name of corresponding evaluator

5.97.1.2 virtual const char* ArcSec::XACMLRequest::getName (void) const [inline, virtual]

Get the name of this request

The documentation for this class was generated from the following file:

- XACMLRequest.h

5.98 ArcSec::XACMLRule Class Reference

[XACMLRule](#) class to parse XACML specific <Rule> node.

```
#include <XACMLRule.h>
```

5.98.1 Detailed Description

[XACMLRule](#) class to parse XACML specific <Rule> node.

The documentation for this class was generated from the following file:

- XACMLRule.h

5.99 ArcSec::XACMLTarget Class Reference

[XACMLTarget](#) class to parse and operate XACML specific <Target> node.

```
#include <XACMLTarget.h>
```

Public Member Functions

- [XACMLTarget](#) (Arc::XMLNode &node, EvaluatorContext *ctx)

5.99.1 Detailed Description

[XACMLTarget](#) class to parse and operate XACML specific <Target> node.

5.99.2 Constructor & Destructor Documentation

5.99.2.1 ArcSec::XACMLTarget::XACMLTarget (Arc::XMLNode & *node*, EvaluatorContext * *ctx*)

Constructor -

The documentation for this class was generated from the following file:

- XACMLTarget.h

5.100 ArcSec::XACMLTargetMatch Class Reference

The documentation for this class was generated from the following file:

- XACMLTarget.h

5.101 ArcSec::XACMLTargetMatchGroup Class Reference

The documentation for this class was generated from the following file:

- XACMLTarget.h

5.102 ArcSec::XACMLTargetSection Class Reference

The documentation for this class was generated from the following file:

- XACMLTarget.h

Index

- ~LDAPQuery
 - Arc::LDAPQuery, [55](#)
- ~PayloadTLSStream
 - ArcMCCTLS::PayloadTLSStream, [85](#)
- ~SRM22Client
 - Arc::SRM22Client, [99](#)
- ~SRMClient
 - Arc::SRMClient, [104](#)
- abort
 - Arc::SRM1Client, [92](#)
 - Arc::SRM22Client, [100](#)
 - Arc::SRMClient, [104](#)
- AndList
 - ArcSec, [13](#)
- Arc::DataPointARC, [35](#)
- Arc::DataPointFile, [36](#)
- Arc::DataPointGFAL, [37](#)
- Arc::DataPointGridFTP, [38](#)
- Arc::DataPointHTTP, [39](#)
- Arc::DataPointLDAP, [40](#)
- Arc::DataPointLFC, [41](#)
- Arc::DataPointRLS, [42](#)
- Arc::DataPointSRM, [43](#)
- Arc::DataPointXrootd, [44](#)
- Arc::LDAPQuery, [55](#)
 - ~LDAPQuery, [55](#)
 - LDAPQuery, [55](#)
 - Query, [55](#)
 - Result, [55](#)
- Arc::Lister, [60](#)
- Arc::SRM1Client, [92](#)
 - abort, [92](#)
 - checkPermissions, [92](#)
 - copy, [93](#)
 - getRequestTokens, [93](#)
 - getSpaceTokens, [93](#)
 - getURLs, [94](#)
 - getURLsStatus, [94](#)
 - info, [94](#), [95](#)
 - mkDir, [95](#)
 - ping, [95](#)
 - putURLs, [96](#)
 - putURLsStatus, [96](#)
 - release, [96](#)
 - releaseGet, [97](#)
 - releasePut, [97](#)
 - remove, [97](#)
 - requestBringOnline, [97](#)
 - requestBringOnlineStatus, [98](#)
- Arc::SRM22Client, [99](#)
 - ~SRM22Client, [99](#)
 - abort, [100](#)
 - checkPermissions, [100](#)
 - copy, [100](#)
 - getRequestTokens, [100](#)
 - getSpaceTokens, [100](#)
 - getURLs, [100](#)
 - getURLsStatus, [100](#)
 - info, [100](#), [101](#)
 - mkDir, [101](#)
 - ping, [101](#)
 - putURLs, [101](#)
 - putURLsStatus, [101](#)
 - release, [101](#)
 - releaseGet, [101](#)
 - releasePut, [102](#)
 - remove, [102](#)
 - requestBringOnline, [102](#)
 - requestBringOnlineStatus, [102](#)
 - SRM22Client, [99](#)
- Arc::SRMClient, [103](#)
 - ~SRMClient, [104](#)
 - abort, [104](#)
 - checkPermissions, [104](#)
 - copy, [104](#)
 - getInstance, [105](#)
 - getRequestTokens, [105](#)
 - getSpaceTokens, [105](#)
 - getURLs, [106](#)
 - getURLsStatus, [106](#)
 - getVersion, [106](#)
 - info, [107](#)
 - mkDir, [107](#)
 - ping, [108](#)
 - putURLs, [108](#)
 - putURLsStatus, [108](#)
 - release, [109](#)
 - releaseGet, [109](#)
 - releasePut, [109](#)

- remove, 109
- requestBringOnline, 110
- requestBringOnlineStatus, 110
- service_endpoint, 110
- Arc::SRMClientRequest, 112
 - SRMClientRequest, 112
 - waiting_time, 112
- Arc::SRMFileMetaData, 114
- Arc::SRMInvalidRequestException, 116
- ArcEvaluationCtx
 - ArcSec::ArcEvaluationCtx, 20
- ArcMCCGSI::MCC_GSI_Client, 61
- ArcMCCGSI::MCC_GSI_Service, 62
- ArcMCCGSI::PayloadGSISStream, 77
- ArcMCCHTTP::MCC_HTTP, 63
- ArcMCCHTTP::MCC_HTTP_Client, 64
- ArcMCCHTTP::MCC_HTTP_Service, 65
- ArcMCCHTTP::PayloadHTTP, 78
 - Attribute, 79
 - Attributes, 79
 - attributes_, 80
 - Body, 79
 - body_own_, 80
 - chunk_size_, 80
 - chunked_, 80
 - code_, 80
 - end_, 81
 - Flush, 80
 - get_body, 80
 - length_, 81
 - method_, 81
 - PayloadHTTP, 79
 - rbody_, 81
 - read, 80
 - read_header, 80
 - readline, 80
 - reason_, 81
 - sbody_, 81
 - stream_, 81
 - stream_own_, 81
 - uri_, 81
 - version_major_, 81
 - version_minor_, 81
- ArcMCCMsgValidator::MCC_MsgValidator, 66
- ArcMCCMsgValidator::MCC_MsgValidator_Service, 67
- ArcMCCSOAP::MCC_SOAP, 68
- ArcMCCSOAP::MCC_SOAP_Client, 69
- ArcMCCSOAP::MCC_SOAP_Service, 70
- ArcMCCTCP::MCC_TCP, 71
- ArcMCCTCP::MCC_TCP_Client, 72
- ArcMCCTCP::MCC_TCP_Service, 73
 - MCC_TCP_Service, 73
- ArcMCCTCP::PayloadTCPSocket, 83
 - PayloadTCPSocket, 83
- ArcMCCTLS::ConfigTLMCC, 34
- ArcMCCTLS::MCC_TLS, 74
- ArcMCCTLS::MCC_TLS_Client, 75
- ArcMCCTLS::MCC_TLS_Service, 76
- ArcMCCTLS::PayloadTLMCC, 84
 - PayloadTLMCC, 84
- ArcMCCTLS::PayloadTLSStream, 85
 - ~PayloadTLSStream, 85
 - GetCert, 85
 - GetPeerCert, 85
 - PayloadTLSStream, 85
 - ssl_, 86
 - STACK_OF, 86
- ArcMCCTLSec::DelegationCollector, 45
- ArcMCCTLSec::DelegationMultiSecAttr, 46
- ArcMCCTLSec::DelegationSecAttr, 48
- ArcPolicy
 - ArcSec::ArcPolicy, 24
- ArcSec, 11
 - AndList, 13
 - Match, 14
- ArcSec::AllowPDP, 15
- ArcSec::ArcAlgFactory, 16
 - createAlg, 16
- ArcSec::ArcAttributeFactory, 17
 - createValue, 17
- ArcSec::ArcAttributeProxy, 18
- ArcSec::ArcAuthZ, 19
 - Handle, 19
 - MakePDPs, 19
- ArcSec::ArcEvaluationCtx, 20
 - ArcEvaluationCtx, 20
 - split, 20
- ArcSec::ArcEvaluator, 21
 - evaluate, 21
- ArcSec::ArcFnFactory, 22
 - createFn, 22
- ArcSec::ArcPDP, 23
- ArcSec::ArcPolicy, 24
 - ArcPolicy, 24
 - make_policy, 24
- ArcSec::ArcRequest, 25
- ArcSec::ArcRequestItem, 26
- ArcSec::ArcRequestTuple, 27
- ArcSec::ArcRule, 28
- ArcSec::AttributeDesignator, 29
- ArcSec::AttributeSelector, 30
- ArcSec::DelegationPDP, 47
- ArcSec::DelegationSH, 49
- ArcSec::DenyPDP, 50
- ArcSec::GACLEvaluator, 51
 - evaluate, 51
- ArcSec::GACLPDP, 52

- ArcSec::GACLPolicy, [53](#)
- ArcSec::GACLRequest, [54](#)
- ArcSec::PDPServletInvoker, [87](#)
- ArcSec::SAML2SSO_AssertionConsumerSH, [88](#)
- ArcSec::SAMLTokenSH, [89](#)
- ArcSec::SimpleListPDP, [90](#)
- ArcSec::UsernameTokenSH, [120](#)
- ArcSec::X509TokenSH, [123](#)
- ArcSec::XACMLAlgFactory, [124](#)
 - createAlg, [124](#)
- ArcSec::XACMLApply, [125](#)
- ArcSec::XACMLAttributeFactory, [126](#)
 - createValue, [126](#)
- ArcSec::XACMLAttributeProxy, [127](#)
- ArcSec::XACMLCondition, [128](#)
 - XACMLCondition, [128](#)
- ArcSec::XACMLEvaluationCtx, [129](#)
 - XACMLEvaluationCtx, [129](#)
- ArcSec::XACMLEvaluator, [130](#)
 - evaluate, [130](#)
- ArcSec::XACMLFnFactory, [131](#)
 - createFn, [131](#)
- ArcSec::XACMLPDP, [132](#)
- ArcSec::XACMLPolicy, [133](#)
 - make_policy, [133](#)
 - XACMLPolicy, [133](#)
- ArcSec::XACMLRequest, [134](#)
 - getEvalName, [134](#)
 - getName, [134](#)
- ArcSec::XACMLRule, [135](#)
- ArcSec::XACMLTarget, [136](#)
 - XACMLTarget, [136](#)
- ArcSec::XACMLTargetMatch, [137](#)
- ArcSec::XACMLTargetMatchGroup, [138](#)
- ArcSec::XACMLTargetSection, [139](#)
- ArcSHCLegacy::AuthUser, [31](#)
- ArcSHCLegacy::AuthVO, [32](#)
- ArcSHCLegacy::ConfigParser, [33](#)
- ArcSHCLegacy::LegacyMap, [56](#)
- ArcSHCLegacy::LegacyPDP, [57](#)
- ArcSHCLegacy::LegacySecAttr, [58](#)
- ArcSHCLegacy::LegacySecHandler, [59](#)
- ArcSHCLegacy::SimpleMap, [91](#)
- ArcSHCLegacy::UnixMap, [119](#)
- ArcSHCLegacy::voms, [121](#)
 - attrs, [121](#)
 - server, [121](#)
 - voname, [121](#)
- ArcSHCLegacy::voms_attrs, [122](#)
 - cap, [122](#)
 - group, [122](#)
 - role, [122](#)
- Attribute
 - ArcMCCHTTP::PayloadHTTP, [79](#)
- Attributes
 - ArcMCCHTTP::PayloadHTTP, [79](#)
- attributes_
 - ArcMCCHTTP::PayloadHTTP, [80](#)
- attrs
 - ArcSHCLegacy::voms, [121](#)
- BaseURL
 - SRMURL, [117](#)
- Body
 - ArcMCCHTTP::PayloadHTTP, [79](#)
- body_own_
 - ArcMCCHTTP::PayloadHTTP, [80](#)
- cap
 - ArcSHCLegacy::voms_attrs, [122](#)
- checkPermissions
 - Arc::SRM1Client, [92](#)
 - Arc::SRM22Client, [100](#)
 - Arc::SRMClient, [104](#)
- chunk_size_
 - ArcMCCHTTP::PayloadHTTP, [80](#)
- chunked_
 - ArcMCCHTTP::PayloadHTTP, [80](#)
- code_
 - ArcMCCHTTP::PayloadHTTP, [80](#)
- ContactURL
 - SRMURL, [117](#)
- copy
 - Arc::SRM1Client, [93](#)
 - Arc::SRM22Client, [100](#)
 - Arc::SRMClient, [104](#)
- createAlg
 - ArcSec::ArcAlgFactory, [16](#)
 - ArcSec::XACMLAlgFactory, [124](#)
- createFn
 - ArcSec::ArcFnFactory, [22](#)
 - ArcSec::XACMLFnFactory, [131](#)
- createValue
 - ArcSec::ArcAttributeFactory, [17](#)
 - ArcSec::XACMLAttributeFactory, [126](#)
- end_
 - ArcMCCHTTP::PayloadHTTP, [81](#)
- Endpoint
 - SRMURL, [117](#)
- evaluate
 - ArcSec::ArcEvaluator, [21](#)
 - ArcSec::GACLEvaluator, [51](#)
 - ArcSec::XACMLEvaluator, [130](#)
- FileName
 - SRMURL, [117](#)
- Flush

- ArcMCCHTTP::PayloadHTTP, 80
- FullURL
 - SRMURL, 117
- get_body
 - ArcMCCHTTP::PayloadHTTP, 80
- GetCert
 - ArcMCCTLS::PayloadTLSStream, 85
- getEvalName
 - ArcSec::XACMLRequest, 134
- getInstance
 - Arc::SRMClient, 105
- getName
 - ArcSec::XACMLRequest, 134
- GetPeerCert
 - ArcMCCTLS::PayloadTLSStream, 85
- getRequestTokens
 - Arc::SRM1Client, 93
 - Arc::SRM22Client, 100
 - Arc::SRMClient, 105
- getSpaceTokens
 - Arc::SRM1Client, 93
 - Arc::SRM22Client, 100
 - Arc::SRMClient, 105
- getURLs
 - Arc::SRM1Client, 94
 - Arc::SRM22Client, 100
 - Arc::SRMClient, 106
- getURLsStatus
 - Arc::SRM1Client, 94
 - Arc::SRM22Client, 100
 - Arc::SRMClient, 106
- getVersion
 - Arc::SRMClient, 106
- group
 - ArcSHCLegacy::voms_attrs, 122
- Handle
 - ArcSec::ArcAuthZ, 19
- info
 - Arc::SRM1Client, 94, 95
 - Arc::SRM22Client, 100, 101
 - Arc::SRMClient, 107
- LDAPQuery
 - Arc::LDAPQuery, 55
- length_
 - ArcMCCHTTP::PayloadHTTP, 81
- make_policy
 - ArcSec::ArcPolicy, 24
 - ArcSec::XACMLPolicy, 133
- MakePDPs
 - ArcSec::ArcAuthZ, 19
- Match
 - ArcSec, 14
- MCC_TCP_Service
 - ArcMCCTCP::MCC_TCP_Service, 73
- method_
 - ArcMCCHTTP::PayloadHTTP, 81
- mkDir
 - Arc::SRM1Client, 95
 - Arc::SRM22Client, 101
 - Arc::SRMClient, 107
- PayloadHTTP
 - ArcMCCHTTP::PayloadHTTP, 79
- PayloadTCPSocket
 - ArcMCCTCP::PayloadTCPSocket, 83
- PayloadTLMCC
 - ArcMCCTLS::PayloadTLMCC, 84
- PayloadTLSStream
 - ArcMCCTLS::PayloadTLSStream, 85
- ping
 - Arc::SRM1Client, 95
 - Arc::SRM22Client, 101
 - Arc::SRMClient, 108
- PortDefined
 - SRMURL, 117
- putURLs
 - Arc::SRM1Client, 96
 - Arc::SRM22Client, 101
 - Arc::SRMClient, 108
- putURLsStatus
 - Arc::SRM1Client, 96
 - Arc::SRM22Client, 101
 - Arc::SRMClient, 108
- Query
 - Arc::LDAPQuery, 55
- rbody_
 - ArcMCCHTTP::PayloadHTTP, 81
- read
 - ArcMCCHTTP::PayloadHTTP, 80
- read_header
 - ArcMCCHTTP::PayloadHTTP, 80
- readline
 - ArcMCCHTTP::PayloadHTTP, 80
- reason_
 - ArcMCCHTTP::PayloadHTTP, 81
- release
 - Arc::SRM1Client, 96
 - Arc::SRM22Client, 101
 - Arc::SRMClient, 109
- releaseGet
 - Arc::SRM1Client, 97
 - Arc::SRM22Client, 101

- Arc::SRMClient, 109
- releasePut
 - Arc::SRM1Client, 97
 - Arc::SRM22Client, 102
 - Arc::SRMClient, 109
- remove
 - Arc::SRM1Client, 97
 - Arc::SRM22Client, 102
 - Arc::SRMClient, 109
- requestBringOnline
 - Arc::SRM1Client, 97
 - Arc::SRM22Client, 102
 - Arc::SRMClient, 110
- requestBringOnlineStatus
 - Arc::SRM1Client, 98
 - Arc::SRM22Client, 102
 - Arc::SRMClient, 110
- Result
 - Arc::LDAPQuery, 55
- role
 - ArcSHCLegacy::voms_attrs, 122
- sbody_
 - ArcMCCHTTP::PayloadHTTP, 81
- server
 - ArcSHCLegacy::voms, 121
- service_endpoint
 - Arc::SRMClient, 110
- SetSRMVersion
 - SRMURL, 117
- ShortURL
 - SRMURL, 118
- split
 - ArcSec::ArcEvaluationCtx, 20
- SRM22Client
 - Arc::SRM22Client, 99
- SRMClientRequest
 - Arc::SRMClientRequest, 112
- SRMFileInfo, 113
- SRMInfo, 115
- SRMURL, 117
 - BaseURL, 117
 - ContactURL, 117
 - Endpoint, 117
 - FileName, 117
 - FullURL, 117
 - PortDefined, 117
 - SetSRMVersion, 117
 - ShortURL, 118
 - SRMURL, 117
- ssl_
 - ArcMCCTLS::PayloadTLSSStream, 86
- STACK_OF
 - ArcMCCTLS::PayloadTLSSStream, 86
- stream_
 - ArcMCCHTTP::PayloadHTTP, 81
- stream_own_
 - ArcMCCHTTP::PayloadHTTP, 81
- uri_
 - ArcMCCHTTP::PayloadHTTP, 81
- version_major_
 - ArcMCCHTTP::PayloadHTTP, 81
- version_minor_
 - ArcMCCHTTP::PayloadHTTP, 81
- voname
 - ArcSHCLegacy::voms, 121
- waiting_time
 - Arc::SRMClientRequest, 112
- XACMLCondition
 - ArcSec::XACMLCondition, 128
- XACMLEvaluationCtx
 - ArcSec::XACMLEvaluationCtx, 129
- XACMLPolicy
 - ArcSec::XACMLPolicy, 133
- XACMLTarget
 - ArcSec::XACMLTarget, 136