

globus rsl assist
2.2

Generated by Doxygen 1.6.1

Wed Jul 21 14:47:05 2010

Contents

1 RSL Helper Functions	1
2 Module Index	1
2.1 Modules	1
3 Module Documentation	1
3.1 RSL Helper Functions	1
3.1.1 Detailed Description	1
3.1.2 Function Documentation	1

1 RSL Helper Functions

[RSL Helper Functions](#)

2 Module Index

2.1 Modules

Here is a list of all modules:

RSL Helper Functions	1
--------------------------------------	---

3 Module Documentation

3.1 RSL Helper Functions

Functions

- int [globus_rsl_assist_attributes_canonicalize](#) ([globus_rsl_t](#) **rsl*)
- void [globus_rsl_assist_string_canonicalize](#) (char **ptr*)

3.1.1 Detailed Description

The *rsl_assist* library provide a set of functions to canonicalize RSL parse trees or strings.

3.1.2 Function Documentation

3.1.2.1 int [globus_rsl_assist_attributes_canonicalize](#) ([globus_rsl_t](#) * *rsl*)

Canonicalize all attribute names in an RSL parse tree. The [globus_rsl_assist_attributes_canonicalize\(\)](#) function performs an in-place canonicalization of the RSL parse tree pointed to by its *rsl* parameter. All relation attribute names will be changed so that they lower-case, with all internal underscore characters removed.

Parameters:

rsl Pointer to the RSL parse tree to canonicalize.

Returns:

If [globus_rsl_assist_attributes_canonicalize\(\)](#) is successful, it will ensure that all attribute names in the given RSL will be in canonical form and return GLOBUS_SUCCESS. If an error occurs, it will return GLOBUS_FAILURE.

Return values:

GLOBUS_SUCCESS Success

GLOBUS_FAILURE Failure

3.1.2.2 void [globus_rsl_assist_string_canonicalize \(char *ptr\)](#)

Canonicalize an attribute name. The [globus_rsl_assist_string_canonicalize\(\)](#) function modifies the NULL-terminated string pointed to by its *ptr* parameter so that it is in canonical form. The canonical form is all lower-case with all underscore characters removed.

Parameters:

ptr Pointer to the RSL string to modify in place.

Returns:

void

Index

globus_rsl_assist
 globus_rsl_assist_attributes_canonicalize, [1](#)
 globus_rsl_assist_string_canonicalize, [1](#)

globus_rsl_assist_attributes_canonicalize

 globus_rsl_assist, [1](#)

globus_rsl_assist_string_canonicalize

 globus_rsl_assist, [1](#)

RSL Helper Functions, [1](#)