

globus rsl assist Reference Manual

2.2

Generated by Doxygen 1.4.4

Wed Jul 21 14:07:09 2010

Contents

1 RSL Helper Functions	1
2 globus_rsl_assist Module Index	1
3 globus_rsl_assist Module Documentation	1

1 RSL Helper Functions

2 globus_rsl_assist Module Index

2.1 globus_rsl_assist Modules

Here is a list of all modules:

RSL Helper Functions	1
--------------------------------------	-------------------

3 globus_rsl_assist Module Documentation

3.1 RSL Helper Functions

Functions

- [int globus_rsl_assist_attributes_canonicalize](#) (globus_rsl_t *rsl)
- [void globus_rsl_assist_string_canonicalize](#) (char *ptr)

3.1.1 Detailed Description

The rsl_assist library provide a set of functions to canonicalize RSL parse trees or strings.

3.1.2 Function Documentation

3.1.2.1 int globus_rsl_assist_attributes_canonicalize (globus_rsl_t * rsl)

Canonicalize all attribute names in an RSL parse tree.

The [globus_rsl_assist_attributes_canonicalize\(\)](#) function performs an in-place canonicalization of the RSL parse tree pointed to by its *rsl* parameter. All relation attribute names will be changed so that they lower-case, with all internal underscore characters removed.

Parameters:

rsl Pointer to the RSL parse tree to canonicalize.

Returns:

If [globus_rsl_assist_attributes_canonicalize\(\)](#) is successful, it will ensure that all attribute names in the given RSL will be in canonical form and return GLOBUS_SUCCESS. If an error occurs, it will return GLOBUS_FAILURE.

Return values:

GLOBUS_SUCCESS Success

GLOBUS_FAILURE Failure

3.1.2.2 void globus_rsl_assist_string_canonicalize (char * *ptr*)

Canonicalize an attribute name.

The [globus_rsl_assist_string_canonicalize\(\)](#) function modifies the NULL-terminated string pointed to by its *ptr* parameter so that it is in canonical form. The canonical form is all lower-case with all underscore characters removed.

Parameters:

ptr Pointer to the RSL string to modify in place.

Returns:

void

Index

globus_rsl_assist
 globus_rsl_assist_attributes_canonicalize, [1](#)
 globus_rsl_assist_string_canonicalize, [2](#)
globus_rsl_assist_attributes_canonicalize
 globus_rsl_assist, [1](#)
globus_rsl_assist_string_canonicalize
 globus_rsl_assist, [2](#)

RSL Helper Functions, [1](#)